

Your Project Calculations



Project Name: Burnt Peak

S3D Model Link:

https://platform.skyciv.com/structural?preload_name=Burnt%20Peak&preload_path=Shared%20Enterprise%20Folder/MT_Solar_Projects/9_2023

Public Model Link:

https://platform.skyciv.com/structural-viewer?project_id=uRcO3TGOqBFbXnxosqV82Omgi4JRZRPpYcDghnb0f3AEsnbGsEoYwHgVnRnxDPp

Array Specification

Product:	Beam
Unique ID:	1P-0-6TOP-XD-45-L-4Hx3W-D27L
Duty Classification:	XD
Module Width:	40.00 in
Module Length:	65.00in
Number of Rows:	4
Number of Columns:	3
Total Number of Modules:	12
Desired Tilt Angle:	30
Front Edge Clearance:	2
Total Array Height at Tilt:	8.71 ft
Total Frame Length:	15.00 ft
Frame Weight:	734 lbs
Array Dimensions N/S:	13.50 ft
Array Dimensions E/W:	16.50 ft
Rail Length:	162.00 in
Rail Spacing:	2.71 ft
Rail Check:	Not Checked

Support Specifications


Pole Size:	6in Pipe Sch 40
Pole Length above Grade:	5.38 ft
Number of Poles:	1
Pole Spacing:	0

Foundation Specifications

Foundation Type:	Square
Foundation Dimensions:	48 x 48 in
Foundation Depth (below grade):	Pile 1: 5.50 ft
Foundation Volume:	3.259 y ³
Foundation Result:	PASSED
Mount Twist:	0.000005 kip

Site Info

Risk Category:	I
Exposure:	C
Soil Classification:	sand
Site Location:	MCMF+5J Lake Hughes, CA, USA
Wind Speed:	101 mph
Snow Load:	80 psf
Design Uplift Pressure:	Multiple pressures
Design Downforce Pressure:	Multiple pressures
Design Snow Pressure:	0.035188 ksf



Design Disclaimer


This software should be used for preliminary designs and should not be used as a final design unless reviewed, verified and designed by a qualified structural engineer.




AutoDesigner Input


```
{
  "product_type": "Beam",
  "project_id": "Burnt Peak",
  "site_address": "MCMF+5J Lake Hughes, CA, USA",
  "module_width": 40,
  "module_length": 65,
  "number_rows": 4,
  "number_columns": 3,
  "pole_mount_section": "4_40",
  "core_pipe_width": 65,
  "core_pipe_section": "2_40",
  "adjuster_section": "2_40",
  "core_beam_height": 65,
  "core_beam_section": "HSS3x2x1/8",
  "main_pipe_section": "2_12GA",
  "pole_spacing": 15,
  "tilt_angle": 30,
  "ground_clearance": 2,
  "risk_category": "I",
  "exposure_category": "C",
  "frame_duty_override": "auto",
  "pole_override": "auto",
  "soil_type": "sand",
  "customer_foundation_override": "48_Square",
  "foundation_type": "Square",
  "foundation_size": 48,
  "check_rails": false,
  "wind_speed_override": 101,
  "snow_load_override": 80,
  "direct_snow_load": false
}
```

Design Notes:



- AISC Deflection checks are set to L/1 due to structure design intent
- Foundation Design and Sizing is approximate only










FEM Results (Envelope Worst Case for each member)





Reaction Forces for Foundation 1 (Node ID#1), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	0.0000	1.8051	0.0000	0.0000	-0.0000	0.0291
ULS: 2. D + L	0.0000	1.8051	0.0000	0.0000	-0.0000	0.0291
ULS: 3. D + (S or Lr or R)	0.0000	7.9761	0.0000	0.0000	-0.0000	0.0633
ULS: 3. D + (S or Lr or R)	0.0000	1.8051	0.0000	0.0000	-0.0000	0.0291
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0000	6.4333	0.0000	0.0000	-0.0000	0.0547
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0000	1.8051	0.0000	0.0000	-0.0000	0.0291
ULS: 5b. D + 0.7E	0.0000	1.8051	0.0000	0.0000	-0.0000	0.0291
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	0.0000	6.4333	0.0000	0.0000	-0.0000	0.0547
ULS: 8. 0.6D + 0.7E	0.0000	1.0831	0.0000	0.0000	-0.0000	0.0175
ULS: 5a. D + 0.6W_Wind downforce Case A only	-2.7332	6.5392	0.0000	0.0000	-0.0000	14.9205
ULS: 5a. D + 0.6W_Wind downforce Case B only	-2.7332	6.5392	0.0000	0.0000	-0.0000	14.9205
ULS: 5a. D + 0.6W_Wind uplift Case A only	2.3428	-2.2527	0.0000	0.0000	-0.0000	-12.4206
ULS: 5a. D + 0.6W_Wind uplift Case B only	1.9523	-1.5764	0.0000	0.0000	-0.0000	-19.9882
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-2.0499	9.9839	0.0000	0.0000	-0.0000	11.2232
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-2.0499	9.9839	0.0000	0.0000	-0.0000	11.2232
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.7571	3.3900	0.0000	0.0000	-0.0000	-9.2825
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.4642	3.8972	0.0000	0.0000	-0.0000	-14.9583
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-2.0499	5.3557	0.0000	0.0000	-0.0000	11.1976
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-2.0499	5.3557	0.0000	0.0000	-0.0000	11.1976
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.7571	-1.2383	0.0000	0.0000	-0.0000	-9.3082
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.4642	-0.7310	0.0000	0.0000	-0.0000	-14.9839
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-2.7332	5.8172	0.0000	0.0000	-0.0000	14.9088
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-2.7332	5.8172	0.0000	0.0000	-0.0000	14.9088
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	2.3428	-2.9747	0.0000	0.0000	-0.0000	-12.4322
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	1.9523	-2.2984	0.0000	0.0000	-0.0000	-19.9999

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	15.9848
Shear X	-4.5554
Shear Z	0.0000
Moment X	-0.0000
Moment Y (Twist)	0.0000
Moment Z	33.7104

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	9.9839
Shear X	-2.7332
Shear Z	0.0000
Moment X	0.0000
Moment Y (Twist)	0.0000
Moment Z	19.9999

Project Details

Design Code: AISC 360-16 LRFD
 Provision: LRFD
 Country: United States
 User Name: sales@mtsolar.us
 Unit System: imperial



Design Input Information


Design Factors			
Φ_t	Φ_c	Φ_b	Φ_v
0.9	0.9	0.9	0.9

Design Materials			
ID	E (ksi)	F_y (ksi)	F_u (ksi)
1	29000	50	65

Section Dimensions							

ID	Name	d (in)	t_w (in)				
3	2in Pipe Sch 120	2.38	0.25				
6	4in Pipe Sch 120	4.50	0.44				
7	6in Pipe Sch 40	6.63	0.28				

ID	Name	d (in)	b (in)	t_w (in)	t_b (in)	r (in)	
17	HSS5x3x1/4	5.00	3.00	0.23	0.23	0.23	

ID	Name	d (in)	b (in)	t _w (in)	t _b (in)	r (in)		
17	HSS5x3x1/4	5.00	3.00	0.23	0.23	0.23		
								
ID	Name	d (in)	t _w (in)	b _t (in)	b _b (in)	t _t (in)	t _b (in)	r (in)
20	W10x12	9.87	0.19	3.96	3.96	0.21	0.21	0.30

Section Properties								
ID	Name	A (in ²)	J (in ⁴)	I_{yp} (in ⁴)	I_{zp} (in ⁴)	I_w (in ⁶)	S_{yp} (in ³)	S_{zp} (in ³)
3	2in Pipe Sch 120	1.67	1.91	0.96	0.96	0.00	1.13	1.13
6	4in Pipe Sch 120	5.58	23.29	11.64	11.64	0.00	7.24	7.24
7	6in Pipe Sch 40	5.58	56.28	28.14	28.14	0.00	11.28	11.28

11	159.30	55.15	46.90	6.46	56.26	44.91
12	251.01	248.88	27.16	27.16	75.30	75.30
13	159.30	116.35	31.78	6.46	56.26	44.91
14	159.30	116.35	31.17	6.46	56.26	44.91
15	159.30	55.15	46.90	6.46	56.26	44.91
16	159.30	55.15	46.90	6.46	56.26	44.91


Design Ratio

Member ID	P	M _z	M _y	V _y	V _z	(P,M _z ,M _y)	Worst LC	KL/r	δ	Status
1	0.083	0.797	0.000	0.060	0.000	0.799	#32	0.302	Not Required	Pass
2	0.003	0.482	0.170	0.105	0.030	0.610	#21	0.036	Not Required	Pass
3	0.010	0.687	0.061	0.068	0.009	0.753	#21	0.046	Not Required	Pass
4	0.010	0.682	0.159	0.068	0.035	0.793	#21	0.082	Not Required	Pass
5	0.010	0.426	0.163	0.068	0.042	0.468	#21	0.076	Not Required	Pass
6	0.010	0.687	0.061	0.068	0.009	0.753	#21	0.046	Not Required	Pass
7	0.010	0.426	0.163	0.068	0.042	0.468	#21	0.076	Not Required	Pass
8	0.000	0.073	0.210	0.032	0.016	0.283	#21	Not Required	Not Required	Pass
9	0.014	0.059	0.046	0.001	0.000	0.111	#21	0.206	Not Required	Pass
10	0.010	0.682	0.159	0.068	0.035	0.793	#21	0.082	Not Required	Pass
11	0.000	0.073	0.210	0.032	0.016	0.283	#21	Not Required	Not Required	Pass
12	0.003	0.482	0.170	0.105	0.030	0.610	#21	0.036	Not Required	Pass
13	0.008	0.253	0.453	0.048	0.024	0.684	#21	0.204	Not Required	Pass
14	0.009	0.256	0.453	0.048	0.024	0.684	#21	0.204	Not Required	Pass
15	0.000	0.073	0.210	0.032	0.016	0.283	#21	Not Required	Not Required	Pass
16	0.000	0.073	0.210	0.032	0.016	0.283	#21	Not Required	Not Required	Pass

Definitions

Φ_t	Safety factor for tensile
Φ_c	Safety factor for compression
Φ_b	Safety factor for flexure
Φ_v	Safety factor for shear
E	Modulus of elasticity
F _y	Specified minimum yield stress
F _u	Specified minimum tensile strength
A	Cross-sectional area
J	Torsional constant
I _{yp}	Moment of inertia about the Y axes
I _{zp}	Moment of inertia about the Z axes
I _w	Warping constant
S _{yp}	Plastic section modulus about the Y axis
S _{zp}	Plastic section modulus about the Z axis
KL	Effective length
C _b	Buckling modification factor (from all load combinations)
L _b	Length between braced points
LST	Limited slenderness for tension
LSC	Limited slenderness for compression
LD	Limited deflection
P _n	Nominal axial strength (tension/compression)
M _n	Nominal flexural strength (about Z/Y axis)
V _n	Nominal shear strength (along Z/Y axis)
P	Design ratio in case of axial force
M _z	Design ratio in case of bending about Z axis
M _y	Design ratio in case of bending about Y axis
V _y	Design ratio in case of shear along Y axis
V _z	Design ratio in case of shear along Z axis
(P,M _z ,M _y)	Design ratio in case of axial force and bending action
KL/r	Design ratio in case of section slenderness
δ	Design ratio in case of member deflection
OK	Capacity is provided
NG	Capacity is not provided

no capacity is not provided

REFERENCES	CALCULATIONS	RESULTS																										
	SkyCiv Foundation Design Pile Foundation Design Information : Design code : IBC 2021 (International Building Code) Unit System : Imperial																											
	Pile Input  Geometry Pile shape: rectangular b = 48 in - Pile width D = 48 in - Pile depth L = 5.5 ft - Total pile length h_1 = 0 ft - Lateral load height from the top of the pile, h_2 = 0 ft - Depth to resisting surface h_e = 0 ft - Length of pile above the ground Tabulation of Soil Parameters <table><thead><tr><th>Layer</th><th>Label</th><th>Allowable Bearing Pressure (q_a) (psf)</th><th>Allowable Lateral Pressure (R) (psf/ft)</th></tr></thead><tbody><tr><td>1</td><td>Sand, silty sand, clayey sand, silty gravel & clayey gravel</td><td>2000.000</td><td>150.000</td></tr></tbody></table> Tabulation of Loads <table><thead><tr><th>Load Component</th><th>ASD</th><th>LRFD</th></tr></thead><tbody><tr><td>P (kip)</td><td>9.984</td><td>15.985</td></tr><tr><td>V_x (kip)</td><td>-2.733</td><td>-4.555</td></tr><tr><td>V_z (kip)</td><td>0.000</td><td>0.000</td></tr><tr><td>M_x (kipft)</td><td>0.000</td><td>0.000</td></tr><tr><td>M_z (kipft)</td><td>20.000</td><td>33.710</td></tr></tbody></table> Material Properties f'_{ck} = 2.5 ksi - Concrete strength,	Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)	1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000	Load Component	ASD	LRFD	P (kip)	9.984	15.985	V_x (kip)	-2.733	-4.555	V_z (kip)	0.000	0.000	M_x (kipft)	0.000	0.000	M_z (kipft)	20.000	33.710	
Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)																									
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000																									
Load Component	ASD	LRFD																										
P (kip)	9.984	15.985																										
V_x (kip)	-2.733	-4.555																										
V_z (kip)	0.000	0.000																										
M_x (kipft)	0.000	0.000																										
M_z (kipft)	20.000	33.710																										
	Required depth to resist lateral loads (ASD) H - Point of application of the lateral load $H = h_1 + h_2 + h_e$ $H = (0\text{ ft}) + (0\text{ ft}) + (0\text{ ft})$ $H = 0\text{ ft}$ Considering x-direction: H_o - Lateral force per length of pile, $H_o = \frac{V_x}{1.57 D}$ $H_o = \frac{(-2.733\text{ kip})}{1.57 \times (48\text{ in})}$ $H_o = -0.43519\text{ kip/ft}$ M_o - Moment per length of pile, $M_o = \frac{M_z + (V_x H)}{1.57 D}$																											

	$M_o = \frac{(20 \text{ kipft}) + ((-2.733 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$ $M_o = 3.1847 \text{ kipft/ft}$ Required depth of embedment in earth: $L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$ Solving the cubic equation: $L_{e,x} = 4.9923 \text{ ft}$ - Required depth in x-direction, Considering z-direction: $L_{e,z} = 0 \text{ ft}$ - Required depth in z-direction, Minimum embedded depth required: $L_{e,req}$ - Depth of pile required, $L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$ $L_{e,req} = \text{MAX}[(4.9923 \text{ ft}), (0 \text{ ft})]$ $L_{e,req} = 4.992 \text{ ft}$ L_e - Actual embedded length of pile, $L_e = L - h_e - h_2$ $L_e = (5.5 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$ $L_e = 5.5 \text{ ft}$ <i>Ratio</i> - Embedded depth $\text{Ratio} = \frac{L_{e,req}}{L_e}$ $\text{Ratio} = \frac{(4.992 \text{ ft})}{(5.5 \text{ ft})}$ $\text{Ratio} = 0.90764$	Status: PASS Ratio: 0.910
	End-bearing Capacity (ASD) A - Pile cross-section area $A = b \ D$ $A = (48 \text{ in}) \times (48 \text{ in})$ $A = 16 \text{ ft}^2$ q - End-bearing pressure $q = \frac{P_v}{A}$ $q = \frac{(9.984 \text{ kip})}{(16 \text{ ft}^2)}$ $q = 0.624 \text{ kip/ft}^2$ Check bearing capacity ratio: <i>Ratio</i> - Capacity $\text{Ratio} = \frac{q}{q_a}$ $\text{Ratio} = \frac{(0.624 \text{ kip/ft}^2)}{(2000 \text{ psf})}$ $\text{Ratio} = 0.312$	Status: PASS Ratio: 0.310
Czerniak	Lateral Soil Pressure (ASD): L/D - Length to least lateral dimension ratio, $L/D = \frac{L}{D}$ $L/D = \frac{(5.5 \text{ ft})}{(48 \text{ in})}$	

$$L/D = 1.375$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.43519$ kip/ft - Lateral force per length of pile,

$M_o = 3.1847$ kipft/ft - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (3.1847 \text{ kipft/ft}) \times (5.5 \text{ ft})) + (3 \times (-0.43519 \text{ kip/ft}) \times (5.5 \text{ ft})^2)}{(6 \times (3.1847 \text{ kipft/ft})) + (4 \times (-0.43519 \text{ kip/ft}) \times (5.5 \text{ ft}))}$$

$$a = 3.8197 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^3 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 [(4 \times (3.1847 \text{ kipft/ft})) + (3 \times (-0.43519 \text{ kip/ft}) \times (5.5 \text{ ft}))]^2}{(5.5 \text{ ft})^3 [(3 \times (3.1847 \text{ kipft/ft})) + (2 \times (-0.43519 \text{ kip/ft}) \times (5.5 \text{ ft}))]}$$

$$p = 0.16068 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (3.1847 \text{ kipft/ft})) + ((-0.43519 \text{ kip/ft}) \times (5.5 \text{ ft}))]}{(5.5 \text{ ft})^2}$$

$$s = 0.7886 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(3.8197 \text{ ft})}{2}$$

$$p_a = 0.28647 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{p}{p_a}$$

$$\text{Ratio} = \frac{(0.16068 \text{ kip/ft}^2)}{(0.28647 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.56088$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (5.5 \text{ ft})$$

$$p_s = 0.825 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity


$$\text{Ratio} = \frac{s}{p_s}$$


$$\text{Ratio} = \frac{(0.7886 \text{ kip/ft}^2)}{(0.825 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.95588$$

Status: **PASS**
Ratio: **0.560**

Status: **PASS**
Ratio: **0.960**





Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-4.555 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.72532 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_x H)}{1.57 D}$$

$$M_o = \frac{(33.71 \text{ kipft}) + ((-4.555 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 5.3678 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(5.3678 \text{ kipft/ft})}{(-0.72532 \text{ kip/ft})}$$

$$E = 7.4007 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (5.3678 \text{ kipft/ft}) \times (5.5 \text{ ft})) + (3 \times (-0.72532 \text{ kip/ft}) \times (5.5 \text{ ft})^2)}{(6 \times (5.3678 \text{ kipft/ft})) + (4 \times (-0.72532 \text{ kip/ft}) \times (5.5 \text{ ft}))}$$

$$a = 3.8185 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.72532 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (7.4007 \text{ ft})}{(5.5 \text{ ft})} + 3 \right) \times \left(\frac{(3.8185 \text{ ft})}{(5.5 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (7.4007 \text{ ft})}{(5.5 \text{ ft})} + 2 \right) \times \left(\frac{(3.8185 \text{ ft})}{(5.5 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 8.8211 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.72532 \text{ kip/ft}) \times (48 \text{ in}) \times (5.5 \text{ ft})) \times \left[\left(\frac{(7.4007 \text{ ft})}{(5.5 \text{ ft})} + \frac{(3.8185 \text{ ft})}{2 \times (5.5 \text{ ft})} \right) - \left[\left(\frac{4 \times (7.4007 \text{ ft})}{(5.5 \text{ ft})} + 3 \right) \times \left(\frac{(3.8185 \text{ ft})}{2 \times (5.5 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (7.4007 \text{ ft})}{(5.5 \text{ ft})} + 2 \right) \times \left(\frac{(3.8185 \text{ ft})}{2 \times (5.5 \text{ ft})} \right)^4 \right] \right]$$

		$M_{max} = 22.814 \text{ kipft}$	

	Ties: #3(0.375 in) - 10 in	
22.4.2.2	Axial Compression Strength (ACI 318-19, LRFD) ϕP_N - Allowable axial compressive strength $\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_{yk} A_{st})]$ $\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (2.5 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$ $\phi P_N = 2675.2 \text{ kip}$ Ratio - Capacity $\text{Ratio} = \frac{P}{\phi P_N}$ $\text{Ratio} = \frac{(15.985 \text{ kip})}{(2675.2 \text{ kip})}$ $\text{Ratio} = 0.0059753$	Status: PASS Ratio: 0.010
22.5.2.2	Shear Strength (ACI 318-19, LRFD) Parameters: $b_w = 48 \text{ in}$ - Effective width, d - Effective depth $d = 0.80 D$ $d = 0.80 \times (48 \text{ in})$ $d = 38.4 \text{ in}$	
22.5.5.1.3	λ_s - size effect modification factor $\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$ $\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$ $\lambda_s = 0.64282$	
22.5.5.1.1	The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $V_{c,max}$ - Max shear strength of concrete $V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$ $V_{c,max} = 5 \times (0.64282) \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{c,max} = 296.21 \text{ kip}$	
22.5.5.1.1(a)	The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $P = 15.985 \text{ kip} \rightarrow 15985 \text{ lbf}$, $V_{c,a}$ - Shear strength of concrete (a) $V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck}} + \frac{P}{6 A_g} \right] b_w d$ $V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi})} + \frac{(15985 \text{ lbf})}{6 \times (2304 \text{ in}^2)} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{c,a} = 120.62 \text{ kip}$	
22.5.5.1.2	The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $V_{c,b}$ - Shear strength of concrete (b) $V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck}} + (0.05 f'_{ck}) \right] b_w d$ $V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi})} + (0.05 \times (2500 \text{ psi})) \right] \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{c,b} = 348.89 \text{ kip}$ V_c - Governing shear strength of concrete $V_c = \text{Min} [V_{c,max}, V_{c,a}, V_{c,b}]$ $V_c = \text{Min} [(296.21 \text{ kip}), (120.62 \text{ kip}), (348.89 \text{ kip})]$ $V_c = 120.62 \text{ kip}$	

22.5.1.2	The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $V_{s,a}$ - Shear strength of steel (a) $V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$ $V_{s,a} = 8 \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{s,a} = 737.28 \text{ kip}$ A_v - Ties rebar area, $A_v = \frac{\pi d_{ties}^2}{4}$ $A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$ $A_v = 0.11045 \text{ in}^2$ 22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b) $V_{s,b} = \frac{2 A_v f_{ywk} d}{s_{ties}}$ $V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$ $V_{s,b} = 50.894 \text{ kip}$ V_s - Governing shear strength of steel $V_s = MIN[V_{s,a}, V_{s,b}]$ $V_s = MIN[(737.28 \text{ kip}), (50.894 \text{ kip})]$ $V_s = 50.894 \text{ kip}$ 22.5.1.1 ϕV_n - Allowable shear strength $\phi V_n = \phi (V_c + V_s)$ $\phi V_n = (0.65) \times ((120.62 \text{ kip}) + (50.894 \text{ kip}))$ $\phi V_n = 111.48 \text{ kip}$ Considering x-direction: $V_{max} = 8.8211 \text{ kip}$ - Maximum shear force in the x-direction, $Ratio$ - Capacity $Ratio = \frac{V_{max}}{\phi V_n}$ $Ratio = \frac{(8.8211 \text{ kip})}{(111.48 \text{ kip})}$ $Ratio = 0.079126$	Status: PASS Ratio: 0.080
14.5.2.1b	Flexural Strength (ACI 318-19, LRFD) S_m - Section modulus $S_m = \frac{b D^2}{6}$ $S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$ $S_m = 18432 \text{ in}^3$ $\lambda = 1$ - Concrete modification factor (Normal concrete), Allowable flexural strength: M_n shall be the lesser of: $\phi M_{n,1}$ $\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$ $\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{(2.5 \text{ ksi})} \times 18432.001 \text{ in}^3$ $\phi M_{n,1} = 249.600 \text{ kip ft}$ $\phi M_{n,2}$ $\phi M_{n,2} = 0.85 f'_c S_m$	

