

Your Project Calculations



Project Name: HorseCanyon590CWL-JB-RevA

S3D Model Link:
https://platform.skyciv.com/structural?preload_name=HorseCanyon590CWL-JB-RevA&preload_path=Shared%20Enterprise%20Folder/MT_Solar_Projects/5_2023

Public Model Link:
https://platform.skyciv.com/structural-viewer?project_id=Tq4hZErnMNBGH04jRUGbvbYjGmicKCvBaI5GBpamVHu7OsrDSTa0MGcyr8CHYHo

Array Specification

Product:	Beam
Unique ID:	3P-17-8TOP-HD-45-L-5Hx7W-4CBG
Duty Classification:	HD
Module Width:	41.50 in
Module Length:	84.00in
Number of Rows:	5
Number of Columns:	7
Total Number of Modules:	35
Desired Tilt Angle:	45
Front Edge Clearance:	4
Total Array Height at Tilt:	16.30 ft
Total Frame Length:	49.00 ft
Frame Weight:	2496 lbs
Array Dimensions N/S:	17.50 ft
Array Dimensions E/W:	49.58 ft
Rail Length:	210.00 in
Rail Spacing:	3.54 ft
Rail Check:	FAIL (112% utilized)

Support Specifications

Pole Size:	8in Pipe Sch 40
Pole Length above Grade:	10.19 ft
Number of Poles:	3
Pole Spacing:	17 ft

Foundation Specifications

Foundation Type:	Square
Foundation Dimensions:	48 x 48 in
Foundation Depth (below grade):	Pile 1: 7.00 ft Pile 2: 7.00 ft Pile 3: 7.00 ft
Foundation Volume:	12.444 y ³
Foundation Result:	PASSED
Mount Twist:	0.191660 kip

Site Info

Risk Category:	I
Exposure:	C
Soil Classification:	sand
Site Location:	1562 Park St E, Castle Rock, CO 80109, USA
Wind Speed:	101 mph
Snow Load:	45 psf
Design Uplift Pressure:	Multiple pressures
Design Downforce Pressure:	Multiple pressures
Design Snow Pressure:	0.012371 ksf



Design Disclaimer


This software should be used for preliminary designs and should not be used as a final design unless reviewed, verified and designed by a qualified structural engineer.



AutoDesigner Input



```
{
  "wind_speed_override": null,
  "snow_load_override": null,
  "direct_snow_load": false,
  "product_type": "Beam",
  "project_id": "HorseCanyon590CWL-JB-RevA",
  "site_address": "1562 Park St E, Castle Rock, CO 80109, USA",
  "module_width": 41.5,
  "module_length": 84,
  "number_rows": 5,
  "number_columns": 7,
  "pole_mount_section": "4_40",
  "core_pipe_width": 65,
  "core_pipe_section": "2_40",
  "adjuster_section": "2_40",
  "core_beam_height": 65,
  "core_beam_section": "HSS3x2x1/8",
  "main_pipe_section": "2_12GA",
  "pole_spacing": 15,
  "tilt_angle": 45,
  "ground_clearance": 4,
  "risk_category": "I",
  "exposure_category": "C",
  "frame_duty_override": "auto",
  "pole_override": "auto",
  "soil_type": "sand",
  "foundation_type": "Square",
  "foundation_size": 48,
  "check_rails": true
}
```

Design Notes:

- AISC Deflection checks are set to L/1 due to structure design intent








Rail Design Check

Rail Length: 17.5 ft
Additional Restraints Required: None
Tributary Width: 3.541666666666665 ft
Material: Aluminium
Density: 169 lb/ft³
Elasticity Modulus: 10000 ksi
Fy: 34.5 ksi
Fu: 37 ksi
Snow (X): 0.0310 kip/ft
Snow (Y): -0.0310 kip/ft
Wind uplift Case A: 0.0817 kip/ft
Wind uplift Case A: 0.0817 kip/ft
Wind uplift Case B (X): 0.0000 kip/ft
Wind uplift Case B (Y): 0.1045 kip/ft





Result Check	Max Limit	Max Value	Utility	Status
Custom Stress Limit	34.5	38.56163812	1.118	FAIL
Material Yield	34.5	38.56163812	1.118	FAIL
Material Strength	37	38.56163812	1.042	FAIL



Member 1, ULS: 1.14D




FEM Results (Envelope Worst Case for each member)




Top Bending Stress Y (ksi)



Shear Stress Y (ksi)





Reaction Forces for Foundation 1 (Node ID#1), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	-0.0067	2.1036	-0.0034	-0.0072	0.0413	0.0826
ULS: 2. D + L	-0.0067	2.1036	-0.0034	-0.0072	0.0413	0.0826
ULS: 3. D + (S or Lr or R)	-0.0168	4.5648	-0.0084	-0.0175	0.1040	0.1820
ULS: 3. D + (S or Lr or R)	-0.0067	2.1036	-0.0034	-0.0072	0.0413	0.0826
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0143	3.9495	-0.0072	-0.0149	0.0883	0.1571
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0067	2.1036	-0.0034	-0.0072	0.0413	0.0826
ULS: 5b. D + 0.7E	-0.0067	2.1036	-0.0034	-0.0072	0.0413	0.0826
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	-0.0143	3.9495	-0.0072	-0.0149	0.0883	0.1571
ULS: 8. 0.6D + 0.7E	-0.0040	1.2622	-0.0020	-0.0043	0.0248	0.0496
ULS: 5a. D + 0.6W_Wind downforce Case A only	-3.6828	5.7737	-0.0176	-0.0457	0.0918	39.3801
ULS: 5a. D + 0.6W_Wind downforce Case B only	-3.6828	5.7737	-0.0176	-0.0457	0.0918	39.3801
ULS: 5a. D + 0.6W_Wind uplift Case A only	2.6516	-0.5509	0.0074	0.0221	0.0019	-25.9187
ULS: 5a. D + 0.6W_Wind uplift Case B only	2.3416	-0.2400	0.0045	0.0144	0.0141	-30.1742
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-2.7714	6.7021	-0.0178	-0.0437	0.1262	29.6302
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-2.7714	6.7021	-0.0178	-0.0437	0.1262	29.6302
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.9794	1.9587	0.0010	0.0071	0.0588	-19.3439
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.7469	2.1918	-0.0012	0.0013	0.0679	-22.5355
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-2.7638	4.8562	-0.0140	-0.0360	0.0792	29.5557
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-2.7638	4.8562	-0.0140	-0.0360	0.0792	29.5557
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.9870	0.1127	0.0047	0.0148	0.0118	-19.4184
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.7545	0.3459	0.0026	0.0090	0.0209	-22.6100
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-3.6801	4.9323	-0.0162	-0.0428	0.0753	39.3470
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-3.6801	4.9323	-0.0162	-0.0428	0.0753	39.3470
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	2.6543	-1.3923	0.0088	0.0250	-0.0146	-25.9518
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	2.3443	-1.0814	0.0059	0.0173	-0.0025	-30.2072

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	9.8721
Shear X	-6.1404
Shear Z	-0.0300
Moment X	-0.0775
Moment Y (Twist)	0.1917
Moment Z	66.3245

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	6.7021
Shear X	-3.6828
Shear Z	-0.0178
Moment X	-0.0457
Moment Y (Twist)	0.1262
Moment Z	39.3801

Reaction Forces for Foundation 2 (Node ID#101), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	0.0134	2.1796	-0.0000	0.0000	0.0000	-0.0976
ULS: 2. D + L	0.0134	2.1796	-0.0000	0.0000	0.0000	-0.0976
ULS: 3. D + (S or Lr or R)	0.0336	4.7581	-0.0000	0.0000	0.0000	-0.2721
ULS: 3. D + (S or Lr or R)	0.0134	2.1796	-0.0000	0.0000	0.0000	-0.0976
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0286	4.1135	-0.0000	0.0000	0.0000	-0.2285
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0134	2.1796	-0.0000	0.0000	0.0000	-0.0976
ULS: 5b. D + 0.7E	0.0134	2.1796	-0.0000	0.0000	0.0000	-0.0976

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	0.0286	4.1135	-0.0000	0.0000	0.0000	-0.2285
ULS: 8. 0.6D + 0.7E	0.0080	1.3077	-0.0000	0.0000	0.0000	-0.0585
ULS: 5a. D + 0.6W_Wind downforce Case A only	-3.7277	5.9325	-0.0000	0.0000	0.0000	39.8354
ULS: 5a. D + 0.6W_Wind downforce Case B only	-3.7277	5.9325	-0.0000	0.0000	0.0000	39.8354
ULS: 5a. D + 0.6W_Wind uplift Case A only	2.7217	-0.5364	-0.0000	0.0000	0.0000	-26.5289
ULS: 5a. D + 0.6W_Wind uplift Case B only	2.3976	-0.2141	-0.0000	0.0000	0.0000	-30.8030
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-2.7772	6.9282	-0.0000	0.0000	0.0000	29.7212
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-2.7772	6.9282	-0.0000	0.0000	0.0000	29.7212
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	2.0598	2.0765	-0.0000	0.0000	0.0000	-20.0520
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.8167	2.3183	-0.0000	0.0000	0.0000	-23.2576
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-2.7924	4.9943	-0.0000	0.0000	0.0000	29.8521
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-2.7924	4.9943	-0.0000	0.0000	0.0000	29.8521
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	2.0446	0.1426	-0.0000	0.0000	0.0000	-19.9211
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.8015	0.3843	-0.0000	0.0000	0.0000	-23.1267
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-3.7330	5.0607	-0.0000	0.0000	0.0000	39.8744
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-3.7330	5.0607	-0.0000	0.0000	0.0000	39.8744
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	2.7163	-1.4082	-0.0000	0.0000	0.0000	-26.4899
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	2.3922	-1.0859	-0.0000	0.0000	0.0000	-30.7640

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	10.1592
Shear X	-6.2351
Shear Z	-0.0000
Moment X	0.0001
Moment Y (Twist)	0.0002
Moment Z	67.0456

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	6.9282
Shear X	-3.7330
Shear Z	-0.0000
Moment X	0.0000
Moment Y (Twist)	0.0000
Moment Z	39.8744

Reaction Forces for Foundation 3 (Node ID#201), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	-0.0067	2.1036	0.0034	0.0072	-0.0413	0.0826
ULS: 2. D + L	-0.0067	2.1036	0.0034	0.0072	-0.0413	0.0826
ULS: 3. D + (S or Lr or R)	-0.0168	4.5648	0.0084	0.0175	-0.1040	0.1820
ULS: 3. D + (S or Lr or R)	-0.0067	2.1036	0.0034	0.0072	-0.0413	0.0826
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0143	3.9495	0.0072	0.0149	-0.0883	0.1571
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0067	2.1036	0.0034	0.0072	-0.0413	0.0826
ULS: 5b. D + 0.7E	-0.0067	2.1036	0.0034	0.0072	-0.0413	0.0826
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	-0.0143	3.9495	0.0072	0.0149	-0.0883	0.1571
ULS: 8. 0.6D + 0.7E	-0.0040	1.2622	0.0020	0.0043	-0.0248	0.0496
ULS: 5a. D + 0.6W_Wind downforce Case A only	-3.6828	5.7737	0.0176	0.0457	-0.0918	39.3801
ULS: 5a. D + 0.6W_Wind downforce Case B only	-3.6828	5.7737	0.0176	0.0457	-0.0918	39.3801
ULS: 5a. D + 0.6W_Wind uplift Case A only	2.6516	-0.5509	-0.0074	-0.0221	-0.0019	-25.9187
ULS: 5a. D + 0.6W_Wind uplift Case B only	2.3416	-0.2400	-0.0045	-0.0144	-0.0141	-30.1742
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-2.7714	6.7021	0.0178	0.0438	-0.1262	29.6302
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-2.7714	6.7021	0.0178	0.0438	-0.1262	29.6302
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.9794	1.9587	-0.0010	-0.0071	-0.0588	-19.3439
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.7469	2.1918	0.0012	-0.0013	-0.0679	-22.5355

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-2.7638	4.8562	0.0140	0.0361	-0.0792	29.5557
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-2.7638	4.8562	0.0140	0.0361	-0.0792	29.5557
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.9870	0.1127	-0.0047	-0.0148	-0.0118	-19.4184
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.7545	0.3459	-0.0025	-0.0090	-0.0209	-22.6100
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-3.6801	4.9323	0.0162	0.0428	-0.0753	39.3470
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-3.6801	4.9323	0.0162	0.0428	-0.0753	39.3470
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	2.6543	-1.3923	-0.0088	-0.0250	0.0146	-25.9518
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	2.3443	-1.0814	-0.0059	-0.0173	0.0025	-30.2072

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module. Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	9.8721
Shear X	-6.1404
Shear Z	0.0300
Moment X	0.0776
Moment Y (Twist)	0.1917
Moment Z	66.3256

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module. Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	6.7021
Shear X	-3.6828
Shear Z	0.0178
Moment X	0.0457
Moment Y (Twist)	0.1262
Moment Z	39.3801

Project Details

Design Code: AISC 360-16 LRFD
 Provision: LRFD
 Country: United States

User Name: sales@mtsolar.us
 Project Name: HorseCanyon590CWL-JB-RevA
 Unit System: imperial



Design Input Information

Design Factors			
Φ_t	Φ_c	Φ_b	Φ_v
0.9	0.9	0.9	0.9

Design Materials			
ID	E (ksi)	F _y (ksi)	F _u (ksi)
1	29000	50	65

Section Dimensions

ID	Name	d (in)	t _w (in)				
2	2in Pipe Sch 80	2.38	0.22				
5	4in Pipe Sch 80	4.50	0.34				
9	8in Pipe Sch 40	8.63	0.32				

ID	Name	d (in)	b (in)	t _w (in)	t _b (in)	r (in)	
16	HSS5x3x3/16	5.00	3.00	0.17	0.17	0.17	

ID	Name	d (in)	t _w (in)	b _t (in)	b _b (in)	t _t (in)	t _b (in)	r (in)
19	W8x10	7.89	0.17	3.94	3.94	0.20	0.20	0.30

Section Properties								
ID	Name	A (in ²)	J (in ⁴)	I _{yp} (in ⁴)	I _{zp} (in ⁴)	I _w (in ⁶)	S _{yp} (in ³)	S _{zp} (in ³)
2	2in Pipe Sch 80	1.48	1.74	0.87	0.87	0.00	1.02	1.02
5	4in Pipe Sch 80	4.41	19.22	9.61	9.61	0.00	5.85	5.85

Member Design Capacity


Member ID	$\Phi_t P_n$ (kip)	$\Phi_c P_n$ (kip)	$\Phi_b M_{zn}$ (k-ft)	$\Phi_b M_{yn}$ (k-ft)	$\Phi_v V_{yn}$ (kip)	$\Phi_v V_{zn}$ (kip)
1	377.97	216.26	83.29	83.29	113.39	113.39
2	198.33	196.72	21.95	21.95	59.50	59.50
3	116.10	115.41	15.79	11.10	42.08	23.28
4	116.10	111.33	15.79	11.10	42.08	23.28
5	116.10	114.23	15.79	11.10	42.08	23.28
6	116.10	115.41	15.79	11.10	42.08	23.28
7	116.10	114.23	15.79	11.10	42.08	23.28
8	133.20	126.01	32.87	6.12	40.24	43.62
9	66.48	58.89	3.82	3.82	19.94	19.94
10	116.10	111.33	15.79	11.10	42.08	23.28
11	133.20	126.01	32.87	6.12	40.24	43.62
12	198.33	196.72	21.95	21.95	59.50	59.50
13	133.20	104.94	25.44	6.12	40.24	43.62
14	133.20	104.94	24.06	6.12	40.24	43.62
15	133.20	52.83	32.87	6.12	40.24	43.62
16	133.20	52.83	32.87	6.12	40.24	43.62
101	377.97	216.26	83.29	83.29	113.39	113.39
102	198.33	196.72	21.95	21.95	59.50	59.50
103	116.10	115.41	15.79	11.10	42.08	23.28
104	116.10	111.33	15.79	11.10	42.08	23.28
105	116.10	114.23	15.79	11.10	42.08	23.28
106	116.10	115.41	15.79	11.10	42.08	23.28
107	116.10	114.23	15.79	11.10	42.08	23.28
108	133.20	126.01	32.87	6.12	40.24	43.62
109	66.48	58.89	3.82	3.82	19.94	19.94
110	116.10	111.33	15.79	11.10	42.08	23.28
111	133.20	126.01	32.87	6.12	40.24	43.62
112	198.33	196.72	21.95	21.95	59.50	59.50
113	133.20	104.94	23.14	6.12	40.24	43.62
114	133.20	104.94	23.60	6.12	40.24	43.62
115	133.20	93.89	25.33	6.12	40.24	43.62
116	133.20	93.89	24.64	6.12	40.24	43.62
201	377.97	216.26	83.29	83.29	113.39	113.39
202	198.33	196.72	21.95	21.95	59.50	59.50
203	116.10	115.41	15.79	11.10	42.08	23.28
204	116.10	111.33	15.79	11.10	42.08	23.28
205	116.10	114.23	15.79	11.10	42.08	23.28
206	116.10	115.41	15.79	11.10	42.08	23.28
207	116.10	114.23	15.79	11.10	42.08	23.28
208	133.20	52.83	32.87	6.12	40.24	43.62
209	66.48	58.89	3.82	3.82	19.94	19.94
210	116.10	111.33	15.79	11.10	42.08	23.28
211	133.20	52.83	32.87	6.12	40.24	43.62
212	198.33	196.72	21.95	21.95	59.50	59.50
213	133.20	104.94	25.44	6.12	40.24	43.62
214	133.20	104.94	23.83	6.12	40.24	43.62
215	133.20	93.89	26.48	6.12	40.24	43.62
216	133.20	93.89	26.02	6.12	40.24	43.62

Design Ratio

Member ID	P	M _z	M _y	V _y	V _z	(P,M _z ,M _y)	Worst LC	KL/r	δ	Status
1	0.046	0.796	0.003	0.054	0.000	0.820	#13	0.437	Not Required	Pass
2	0.002	0.368	0.273	0.081	0.052	0.642	#13	0.035	Not Required	Pass
3	0.009	0.694	0.061	0.070	0.013	0.731	#13	0.045	Not Required	Pass
4	0.009	0.625	0.125	0.063	0.027	0.672	#13	0.080	Not Required	Pass
5	0.009	0.430	0.129	0.069	0.031	0.446	#13	0.074	Not Required	Pass
6	0.009	0.684	0.064	0.068	0.013	0.721	#13	0.045	Not Required	Pass
7	0.009	0.425	0.125	0.068	0.032	0.442	#13	0.074	Not Required	Pass
8	0.000	0.058	0.086	0.039	0.014	0.132	#21	0.095	Not Required	Pass
9	0.007	0.050	0.053	0.001	0.000	0.105	#13	0.204	Not Required	Pass
10	0.009	0.614	0.123	0.061	0.027	0.667	#13	0.080	Not Required	Pass
11	0.000	0.064	0.084	0.044	0.014	0.133	#21	0.095	Not Required	Pass
12	0.002	0.358	0.266	0.080	0.051	0.624	#13	0.035	Not Required	Pass
13	0.005	0.224	0.318	0.059	0.019	0.478	#21	0.286	Not Required	Pass
14	0.006	0.208	0.318	0.053	0.019	0.468	#21	0.190	Not Required	Pass
15	0.000	0.076	0.148	0.033	0.011	0.206	#21	Not Required	Not Required	Pass
16	0.000	0.068	0.148	0.030	0.011	0.202	#21	Not Required	Not Required	Pass
101	0.047	0.805	0.000	0.055	0.000	0.828	#13	0.437	Not Required	Pass
102	0.001	0.370	0.270	0.082	0.052	0.640	#13	0.035	Not Required	Pass
103	0.010	0.704	0.070	0.070	0.017	0.745	#13	0.045	Not Required	Pass
104	0.010	0.635	0.116	0.064	0.026	0.686	#13	0.080	Not Required	Pass
105	0.010	0.437	0.118	0.070	0.029	0.452	#13	0.074	Not Required	Pass
106	0.010	0.704	0.070	0.070	0.017	0.745	#13	0.045	Not Required	Pass
107	0.010	0.437	0.118	0.070	0.029	0.452	#13	0.074	Not Required	Pass
108	0.000	0.069	0.087	0.036	0.014	0.139	#21	0.095	Not Required	Pass
109	0.005	0.044	0.049	0.001	0.000	0.095	#13	0.204	Not Required	Pass
110	0.010	0.635	0.116	0.064	0.026	0.686	#13	0.080	Not Required	Pass
111	0.000	0.077	0.086	0.040	0.014	0.141	#21	0.095	Not Required	Pass
112	0.001	0.370	0.270	0.082	0.052	0.640	#13	0.035	Not Required	Pass
113	0.005	0.159	0.284	0.055	0.019	0.394	#21	0.286	Not Required	Pass
114	0.006	0.152	0.283	0.050	0.019	0.385	#21	0.286	Not Required	Pass
115	0.000	0.139	0.161	0.040	0.014	0.267	#21	0.346	Not Required	Pass
116	0.000	0.126	0.162	0.036	0.014	0.262	#21	0.346	Not Required	Pass
201	0.046	0.796	0.003	0.054	0.000	0.820	#13	0.437	Not Required	Pass
202	0.002	0.358	0.266	0.080	0.051	0.624	#13	0.035	Not Required	Pass
203	0.009	0.684	0.064	0.068	0.013	0.721	#13	0.045	Not Required	Pass
204	0.009	0.614	0.123	0.061	0.027	0.667	#13	0.080	Not Required	Pass
205	0.009	0.425	0.125	0.068	0.032	0.442	#13	0.074	Not Required	Pass
206	0.009	0.694	0.061	0.070	0.013	0.731	#13	0.045	Not Required	Pass
207	0.009	0.430	0.129	0.069	0.031	0.446	#13	0.074	Not Required	Pass
208	0.000	0.068	0.148	0.030	0.011	0.202	#21	Not Required	Not Required	Pass
209	0.007	0.050	0.053	0.001	0.000	0.105	#13	0.204	Not Required	Pass
210	0.009	0.625	0.125	0.063	0.027	0.672	#13	0.080	Not Required	Pass
211	0.000	0.076	0.148	0.033	0.011	0.206	#21	Not Required	Not Required	Pass
212	0.002	0.368	0.273	0.081	0.052	0.642	#13	0.035	Not Required	Pass
213	0.005	0.224	0.318	0.059	0.019	0.478	#21	0.190	Not Required	Pass
214	0.006	0.208	0.318	0.053	0.019	0.468	#21	0.286	Not Required	Pass
215	0.000	0.134	0.161	0.044	0.014	0.263	#21	0.346	Not Required	Pass
216	0.000	0.121	0.162	0.039	0.014	0.258	#21	0.346	Not Required	Pass

Definitions

Φ_t	Safety factor for tensile
Φ_c	Safety factor for compression
Φ_b	Safety factor for flexure
Φ_v	Safety factor for shear
E	Modulus of elasticity
F_y	Specified minimum yield stress
F_u	Specified minimum tensile strength
A	Cross-sectional area
J	Torsional constant
I_{yp}	Moment of inertia about the Y axes
I_{zp}	Moment of inertia about the Z axes
I_w	Warping constant
S_{yp}	Plastic section modulus about the Y axis
S_{zp}	Plastic section modulus about the Z axis
KL	Effective length
C_b	Buckling modification factor (from all load combinations)
L_b	Length between braced points
LST	Limited slenderness for tension
LSC	Limited slenderness for compression
LD	Limited deflection
P_n	Nominal axial strength (tension/compression)
M_n	Nominal flexural strength (about Z/Y axis)
V_n	Nominal shear strength (along Z/Y axis)
P	Design ratio in case of axial force
M_z	Design ratio in case of bending about Z axis
M_y	Design ratio in case of bending about Y axis
V_y	Design ratio in case of shear along Y axis
V_z	Design ratio in case of shear along Z axis
(P, M_z, M_y)	Design ratio in case of axial force and bending action
KL/r	Design ratio in case of section slenderness
δ	Design ratio in case of member deflection
OK	Capacity is provided
NG	Capacity is not provided

REFERENCES	CALCULATIONS	RESULTS																										
	<p>SkyCiv Foundation Design Pile Foundation</p> <p>Design Information : Design code : IBC 2021 (International Building Code) Unit System : Imperial</p>																											
	<p>Pile Input</p>  <p>Geometry Pile shape: rectangular $b = 48$ in - Pile width $D = 48$ in - Pile depth $L = 7$ ft - Total pile length $h_1 = 0$ ft - Lateral load height from the top of the pile, $h_2 = 0$ ft - Depth to resting surface $h_e = 0$ ft - Length of pile above the ground</p> <p>Tabulation of Soil Parameters</p> <table border="1" data-bbox="416 1102 1193 1191"> <thead> <tr> <th>Layer</th> <th>Label</th> <th>Allowable Bearing Pressure (q_a) (psf)</th> <th>Allowable Lateral Pressure (R) (psf/ft)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Sand, silty sand, clayey sand, silty gravel & clayey gravel</td> <td>2000.000</td> <td>150.000</td> </tr> </tbody> </table> <p>Tabulation of Loads</p> <table border="1" data-bbox="676 1285 935 1458"> <thead> <tr> <th>Load Component</th> <th>ASD</th> <th>LRFD</th> </tr> </thead> <tbody> <tr> <td>P (kip)</td> <td>6.702</td> <td>9.872</td> </tr> <tr> <td>V_x (kip)</td> <td>-3.683</td> <td>-6.140</td> </tr> <tr> <td>V_z (kip)</td> <td>-0.018</td> <td>-0.030</td> </tr> <tr> <td>M_x (kipft)</td> <td>-0.046</td> <td>-0.078</td> </tr> <tr> <td>M_z (kipft)</td> <td>39.380</td> <td>66.325</td> </tr> </tbody> </table> <p>Material Properties $f'_{ck} = 3$ ksi - Concrete strength,</p>	Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)	1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000	Load Component	ASD	LRFD	P (kip)	6.702	9.872	V_x (kip)	-3.683	-6.140	V_z (kip)	-0.018	-0.030	M_x (kipft)	-0.046	-0.078	M_z (kipft)	39.380	66.325	
Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)																									
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000																									
Load Component	ASD	LRFD																										
P (kip)	6.702	9.872																										
V_x (kip)	-3.683	-6.140																										
V_z (kip)	-0.018	-0.030																										
M_x (kipft)	-0.046	-0.078																										
M_z (kipft)	39.380	66.325																										
	<p>Required depth to resist lateral loads (ASD) H - Point of application of the lateral load</p> $H = h_1 + h_2 + h_e$ $H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$ $H = 0 \text{ ft}$ <p>Considering x-direction: H_o - Lateral force per length of pile,</p> $H_o = \frac{V_x}{1.57 D}$ $H_o = \frac{(-3.683 \text{ kip})}{1.57 \times (48 \text{ in})}$ $H_o = -0.58646 \text{ kip/ft}$ <p>M_o - Moment per length of pile,</p> $M_o = \frac{M_z + (V_x H)}{1.57 D}$																											

$$M_o = \frac{(39.38 \text{ kipft}) + ((-3.683 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 6.2707 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$$

Solving the cubic equation:

$L_{e,x} = 6.4896 \text{ ft}$ - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.018 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.0028662 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.046 \text{ kipft}) + ((-0.018 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.0073248 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$$

Solving the cubic equation:

$L_{e,z} = 0.76819 \text{ ft}$ - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = \text{MAX}[(6.4896 \text{ ft}), (0.76819 \text{ ft})]$$

$$L_{e,req} = 6.49 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_c - h_2$$

$$L_e = (7 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 7 \text{ ft}$$

Ratio - Embedded depth

$$\text{Ratio} = \frac{L_{e,req}}{L_e}$$

$$\text{Ratio} = \frac{(6.49 \text{ ft})}{(7 \text{ ft})}$$

$$\text{Ratio} = 0.92714$$

Status: **PASS**
Ratio: **0.930**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_c}{A}$$

$$q = \frac{(6.702 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.418875 \text{ kip/ft}^2$$

$$q = 0.41887 \text{ kip/ft}^2$$

Check bearing capacity ratio:

Ratio - Capacity

$$Ratio = \frac{q}{q_a}$$

$$Ratio = \frac{(0.41887 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$Ratio = 0.20944$$

Status: **PASS**
Ratio: **0.210**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(7 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1.75$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.58646 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 6.2707 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (6.2707 \text{ kipft/ft}) \times (7 \text{ ft})) + (3 \times (-0.58646 \text{ kip/ft}) \times (7 \text{ ft})^2)}{(6 \times (6.2707 \text{ kipft/ft})) + (4 \times (-0.58646 \text{ kip/ft}) \times (7 \text{ ft}))}$$

$$a = 4.8439 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (6.2707 \text{ kipft/ft})) + (3 \times (-0.58646 \text{ kip/ft}) \times (7 \text{ ft}))]^2}{(7 \text{ ft})^2 \times [(3 \times (6.2707 \text{ kipft/ft})) + (2 \times (-0.58646 \text{ kip/ft}) \times (7 \text{ ft}))]}$$

$$p = 0.23533 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (6.2707 \text{ kipft/ft})) + ((-0.58646 \text{ kip/ft}) \times (7 \text{ ft}))]}{(7 \text{ ft})^2}$$

$$s = 1.033 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(4.8439 \text{ ft})}{2}$$

$$p_a = 0.36329 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.23533 \text{ kip/ft}^2)}{(0.36329 \text{ kip/ft}^2)}$$

$$Ratio = 0.64776$$

p_s - Allowable lateral soil pressure at depth L_e ,


Status: **PASS**
Ratio: **0.650**

	$p_s = R L_e$ $p_s = (150 \text{ psf/ft}) \times (7 \text{ ft})$ $p_s = 1.05 \text{ kip/ft}^2$ <p>Ratio - Lateral soil capacity</p> $\text{Ratio} = \frac{s}{p_s}$ $\text{Ratio} = \frac{(1.033 \text{ kip/ft}^2)}{(1.05 \text{ kip/ft}^2)}$ $\text{Ratio} = 0.98381$	<p>Status: PASS Ratio: 0.980</p>
	<p>Considering z-direction:</p> <p>$H_o = -0.0028662 \text{ kip/ft}$ - Lateral force per length of pile, $M_o = 0.0073248 \text{ kipft/ft}$ - Overturning moment per length of pile, a - Distance from resting surface to pivot point,</p> $a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$ $a = \frac{(4 \times (0.0073248 \text{ kipft/ft}) \times (7 \text{ ft})) + (3 \times (-0.0028662 \text{ kip/ft}) \times (7 \text{ ft})^2)}{(6 \times (0.0073248 \text{ kipft/ft})) + (4 \times (-0.0028662 \text{ kip/ft}) \times (7 \text{ ft}))}$ $a = 5.0436 \text{ ft}$ <p>p - Earth pressure against the pile at distance $a/2$ from resting surface,</p> $p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$ $p = \frac{0.75 [(4 \times (0.0073248 \text{ kipft/ft})) + (3 \times (-0.0028662 \text{ kip/ft}) \times (7 \text{ ft}))]^2}{(7 \text{ ft})^2 \times [(3 \times (0.0073248 \text{ kipft/ft})) + (2 \times (-0.0028662 \text{ kip/ft}) \times (7 \text{ ft}))]}$ $p = -0.00080464 \text{ kip/ft}^2$ <p>s - Earth pressure against the pile at distance L_e,</p> $s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$ $s = \frac{6 \times [(2 \times (0.0073248 \text{ kipft/ft})) + ((-0.0028662 \text{ kip/ft}) \times (7 \text{ ft}))]}{(7 \text{ ft})^2}$ $s = -0.00066294 \text{ kip/ft}^2$ <p>Check lateral soil pressure capacity:</p> <p>p_a - Allowable lateral soil pressure at depth $a/2$,</p> $p_a = R \frac{a}{2}$ $p_a = (150 \text{ psf/ft}) \times \frac{(5.0436 \text{ ft})}{2}$ $p_a = 0.37827 \text{ kip/ft}^2$ <p>Ratio - Lateral soil capacity</p> $\text{Ratio} = \frac{p}{p_a}$ $\text{Ratio} = \frac{(-0.00080464 \text{ kip/ft}^2)}{(0.37827 \text{ kip/ft}^2)}$ $\text{Ratio} = -0.0021272$ <p>p_s - Allowable lateral soil pressure at depth L_e,</p> $p_s = R L_e$ $p_s = (150 \text{ psf/ft}) \times (7 \text{ ft})$ $p_s = 1.05 \text{ kip/ft}^2$ <p>Ratio - Lateral soil capacity</p> $\text{Ratio} = \frac{s}{p_s}$	<p>Status: PASS Ratio: 0.000</p>

$$\text{Ratio} = \frac{(-0.00066294 \text{ kip/ft}^2)}{(1.05 \text{ kip/ft}^2)}$$

$$\text{Ratio} = -0.00063137$$

Status: **PASS**
Ratio: **0.000**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-6.14 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.97771 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(66.325 \text{ kipft}) + ((-6.14 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 10.561 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(10.561 \text{ kipft/ft})}{(-0.97771 \text{ kip/ft})}$$

$$E = 10.802 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_c) + (3 H_o L_c^2)}{(6 M_o) + (4 H_o L_c)}$$

$$a = \frac{(4 \times (10.561 \text{ kipft/ft}) \times (7 \text{ ft})) + (3 \times (-0.97771 \text{ kip/ft}) \times (7 \text{ ft})^2)}{(6 \times (10.561 \text{ kipft/ft})) + (4 \times (-0.97771 \text{ kip/ft}) \times (7 \text{ ft}))}$$

$$a = 4.8426 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4 E}{L_c} + 3 \right) \left(\frac{a}{L_c} \right)^2 \right] + \left[4 \left(\frac{3 E}{L_c} + 2 \right) \left(\frac{a}{L_c} \right)^3 \right] \right]$$

$$V_{max} = ((-0.97771 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (10.802 \text{ ft})}{(7 \text{ ft})} + 3 \right) \times \left(\frac{(4.8426 \text{ ft})}{(7 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (10.802 \text{ ft})}{(7 \text{ ft})} + 2 \right) \times \left(\frac{(4.8426 \text{ ft})}{(7 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 13.258 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.97771 \text{ kip/ft}) \times (48 \text{ in}) \times (7 \text{ ft})) \times \left[\left(\frac{(10.802 \text{ ft})}{(7 \text{ ft})} + \frac{(4.8426 \text{ ft})}{2 \times (7 \text{ ft})} \right) - \left[\left(\frac{4 \times (10.802 \text{ ft})}{(7 \text{ ft})} + 3 \right) \times \left(\frac{(4.8426 \text{ ft})}{2 \times (7 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (10.802 \text{ ft})}{(7 \text{ ft})} + 2 \right) \times \left(\frac{(4.8426 \text{ ft})}{2 \times (7 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 43.92 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.03 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.0047771 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.078 \text{ kipft}) + ((-0.03 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.01242 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.01242 \text{ kipft/ft})}{(-0.0047771 \text{ kip/ft})}$$

$$E = 2.6 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.01242 \text{ kipft/ft}) \times (7 \text{ ft})) + (3 \times (-0.0047771 \text{ kip/ft}) \times (7 \text{ ft})^2)}{(6 \times (0.01242 \text{ kipft/ft})) + (4 \times (-0.0047771 \text{ kip/ft}) \times (7 \text{ ft}))}$$

$$a = 5.0413 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.0047771 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (2.6 \text{ ft})}{(7 \text{ ft})} + 3 \right) \times \left(\frac{(5.0413 \text{ ft})}{(7 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (2.6 \text{ ft})}{(7 \text{ ft})} + 2 \right) \times \left(\frac{(5.0413 \text{ ft})}{(7 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.025349 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o b L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.0047771 \text{ kip/ft}) \times (48 \text{ in}) \times (7 \text{ ft})) \times \left[\left(\frac{(2.6 \text{ ft})}{(7 \text{ ft})} + \frac{(5.0413 \text{ ft})}{2 \times (7 \text{ ft})} \right) - \left[\left(\frac{4 \times (2.6 \text{ ft})}{(7 \text{ ft})} + 3 \right) \times \left(\frac{(5.0413 \text{ ft})}{2 \times (7 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (2.6 \text{ ft})}{(7 \text{ ft})} + 2 \right) \times \left(\frac{(5.0413 \text{ ft})}{2 \times (7 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 0.076835 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 3 \text{ ksi}$ - Concrete strength,
 $f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,
 $\phi = 0.65$ - Reduction factor for axial strength,
 $\alpha = 0.8$ - Alpha factor for axial strength,
 $A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Table 22.4.2.1

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

22.4.2.2, 10.6.1.1

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(0.872 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (3 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (3 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -101.94 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-101.94 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

$$\text{Ratio} = 0.96556$$

25.2.3

s_{rebar} - Minimum spacing of reinforcement,

$$s_{rebar} = \text{Max} [1.5, (1.5 d_{bar})]$$

$$s_{rebar} = \text{Max} [1.5, (1.5 \times (0.625 \text{ in}))]$$

$$s_{rebar} = 1.5 \text{ in}$$

Ties:

25.7.2.2 Since longitudinal reinforcement is \leq No. 10: Use #3(0.375 in)

25.7.2.1 s_{ties} - Maximum spacing of ties,

$$s_{ties} = \text{Min} [(16 d_{bar}), (48 d_{ties}), \text{Min} (D, b)]$$

$$s_{ties} = \text{Min} [(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), \text{Min} ((48 \text{ in}), (48 \text{ in}))]$$

$$s_{ties} = 10 \text{ in}$$

Summary:

Main reinforcement: 14 - #5 (0.625 in)

Status: **PASS**
Ratio: **0.970**

Ties: #3(0.375 in) - 10 in

Axial Compression Strength (ACI 318-19, LRFD)

22.4.2.2

ϕP_N - Allowable axial compressive strength

$$\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_{yk} A_{st})]$$

$$\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (3 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$$

$$\phi P_N = 3183.4 \text{ kip}$$

Ratio - Capacity

$$\text{Ratio} = \frac{P}{\phi P_N}$$

$$\text{Ratio} = \frac{(9.872 \text{ kip})}{(3183.4 \text{ kip})}$$

$$\text{Ratio} = 0.0031011$$

Status: **PASS**
Ratio: **0.000**

Shear Strength (ACI 318-19, LRFD)

Parameters:

22.5.2.2

$b_w = 48 \text{ in}$ - Effective width,
 d - Effective depth

$$d = 0.80 D$$

$$d = 0.80 \times (48 \text{ in})$$

$$d = 38.4 \text{ in}$$

22.5.5.1.3

λ_s - size effect modification factor

$$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$$

$$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$$

$$\lambda_s = 0.64282$$

22.5.5.1.1

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$,
 $V_{c,max}$ - Max shear strength of concrete

$$V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$$

$$V_{c,max} = 5 \times (0.64282) \times \sqrt{(3000 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,max} = 324.49 \text{ kip}$$

22.5.5.1.1(a)

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$, $P = 9.872 \text{ kip} \rightarrow 9872 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck}} + \frac{P}{6 A_g} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(3000 \text{ psi})} + \frac{(9872 \text{ lbf})}{6 \times (2304 \text{ in}^2)} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 131.11 \text{ kip}$$

22.5.5.1.2

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck}} + (0.05 f'_{ck}) \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(3000 \text{ psi})} + (0.05 \times (3000 \text{ psi})) \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 406.27 \text{ kip}$$

V_c - Governing shear strength of concrete


$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(324.49 \text{ kip}), (131.11 \text{ kip}), (406.27 \text{ kip})]$$

$$V_c = 131.11 \text{ kip}$$

<p>22.5.1.2</p>	<p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$, $V_{s,a}$ - Shear strength of steel (a)</p> $V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$ $V_{s,a} = 8 \times \sqrt{(3000 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{s,a} = 807.65 \text{ kip}$ <p>A_v - Ties rebar area,</p> $A_v = \frac{\pi d_{ties}^2}{4}$ $A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$ $A_v = 0.11045 \text{ in}^2$ <p>22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)</p> $V_{s,b} = \frac{2 A_v f_{yties} d}{s_{ties}}$ $V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$ $V_{s,b} = 50.894 \text{ kip}$ <p>V_s - Governing shear strength of steel</p> $V_s = \text{MIN}[V_{s,a}, V_{s,b}]$ $V_s = \text{MIN}[(807.65 \text{ kip}), (50.894 \text{ kip})]$ $V_s = 50.894 \text{ kip}$ <p>22.5.1.1 ϕV_n - Allowable shear strength</p> $\phi V_n = \phi (V_c + V_s)$ $\phi V_n = (0.65) \times ((131.11 \text{ kip}) + (50.894 \text{ kip}))$ $\phi V_n = 118.3 \text{ kip}$ <p>Considering x-direction:</p> <p>$V_{max} = 13.258 \text{ kip}$ - Maximum shear force in the x-direction, Ratio - Capacity</p> $\text{Ratio} = \frac{V_{max}}{\phi V_n}$ $\text{Ratio} = \frac{(13.258 \text{ kip})}{(118.3 \text{ kip})}$ $\text{Ratio} = 0.11207$ <p>Considering z-direction:</p> <p>$V_{max} = 0.025349 \text{ kip}$ - Maximum shear force in the z-direction, Ratio - Capacity</p> $\text{Ratio} = \frac{V_{max}}{\phi V_n}$ $\text{Ratio} = \frac{(0.025349 \text{ kip})}{(118.3 \text{ kip})}$ $\text{Ratio} = 0.00021427$	<p>Status: PASS Ratio: 0.110</p> <p>Status: PASS Ratio: 0.000</p>
	<p>Flexural Strength (ACI 318-19, LRFD)</p> <p>S_m - Section modulus</p> $S_m = \frac{b D^2}{6}$ $S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$ $S_m = 18432 \text{ in}^3$	

<p>14.5.2.1b</p>	<p>$\lambda = 1$ - Concrete modification factor (Normal concrete), Allowable flexural strength: M_n shall be the lesser of: $\phi M_{n,1}$</p> $\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$ $\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{3ksi} \times 18432.001 in^3$ $\phi M_{n,1} = 273.423 kipft$ <p>$\phi M_{n,2}$</p> $\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$ $\phi M_{n,2} = (0.65) \times 0.85 \times (3 ksi) \times (18432 in^3)$ $\phi M_{n,2} = 2545.9 kipft$ <p>Therefore, ϕM_n - Allowable flexural strength,</p> $\phi M_n = MIN[\phi M_{n,1}, \phi M_{n,2}]$ $\phi M_n = MIN[(273.42 kipft), (2545.9 kipft)]$ $\phi M_n = 273.42 kipft$ <p>Considering x-direction: $M_{max} = 43.92 kipft$ - Maximum moment in the x-direction, Ratio - Capacity</p> $Ratio = \frac{M_{max}}{\phi M_n}$ $Ratio = \frac{(43.92 kipft)}{(273.42 kipft)}$ $Ratio = 0.16063$	<p>Status: PASS Ratio: 0.160</p>
	<p>Considering z-direction: $M_{max} = 0.076835 kipft$ - Maximum moment in the z-direction, Ratio - Capacity</p> $Ratio = \frac{M_{max}}{\phi M_n}$ $Ratio = \frac{(0.076835 kipft)}{(273.42 kipft)}$ $Ratio = 0.00028101$	<p>Status: PASS Ratio: 0.000</p>

REFERENCES	CALCULATIONS	RESULTS																										
	<p>SkyCiv Foundation Design Pile Foundation</p> <p>Design Information : Design code : IBC 2021 (International Building Code) Unit System : Imperial</p>																											
	<p>Pile Input</p>  <p>Geometry Pile shape: rectangular $b = 48$ in - Pile width $D = 48$ in - Pile depth $L = 7$ ft - Total pile length $h_1 = 0$ ft - Lateral load height from the top of the pile, $h_2 = 0$ ft - Depth to resting surface $h_e = 0$ ft - Length of pile above the ground</p> <p>Tabulation of Soil Parameters</p> <table border="1" data-bbox="416 1102 1193 1193"> <thead> <tr> <th>Layer</th> <th>Label</th> <th>Allowable Bearing Pressure (q_a) (psf)</th> <th>Allowable Lateral Pressure (R) (psf/ft)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Sand, silty sand, clayey sand, silty gravel & clayey gravel</td> <td>2000.000</td> <td>150.000</td> </tr> </tbody> </table> <p>Tabulation of Loads</p> <table border="1" data-bbox="676 1288 935 1458"> <thead> <tr> <th>Load Component</th> <th>ASD</th> <th>LRFD</th> </tr> </thead> <tbody> <tr> <td>P (kip)</td> <td>6.928</td> <td>10.159</td> </tr> <tr> <td>V_x (kip)</td> <td>-3.733</td> <td>-6.235</td> </tr> <tr> <td>V_z (kip)</td> <td>0.000</td> <td>0.000</td> </tr> <tr> <td>M_x (kipft)</td> <td>0.000</td> <td>0.000</td> </tr> <tr> <td>M_z (kipft)</td> <td>39.874</td> <td>67.046</td> </tr> </tbody> </table> <p>Material Properties $f'_{ck} = 3$ ksi - Concrete strength,</p>	Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)	1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000	Load Component	ASD	LRFD	P (kip)	6.928	10.159	V_x (kip)	-3.733	-6.235	V_z (kip)	0.000	0.000	M_x (kipft)	0.000	0.000	M_z (kipft)	39.874	67.046	
Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)																									
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000																									
Load Component	ASD	LRFD																										
P (kip)	6.928	10.159																										
V_x (kip)	-3.733	-6.235																										
V_z (kip)	0.000	0.000																										
M_x (kipft)	0.000	0.000																										
M_z (kipft)	39.874	67.046																										
	<p>Required depth to resist lateral loads (ASD) H - Point of application of the lateral load</p> $H = h_1 + h_2 + h_e$ $H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$ $H = 0 \text{ ft}$ <p>Considering x-direction: H_o - Lateral force per length of pile,</p> $H_o = \frac{V_x}{1.57 D}$ $H_o = \frac{(-3.733 \text{ kip})}{1.57 \times (48 \text{ in})}$ $H_o = -0.59443 \text{ kip/ft}$ <p>M_o - Moment per length of pile,</p> $M_o = \frac{M_z + (V_x H)}{1.57 D}$																											

	$M_o = \frac{(39.874 \text{ kipft}) + ((-3.733 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$ $M_o = 6.3494 \text{ kipft/ft}$ <p>Required depth of embedment in earth:</p> $L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$ <p>Solving the cubic equation: $L_{e,x} = 6.5092 \text{ ft}$ - Required depth in x-direction,</p> <p>Considering z-direction: $L_{e,z} = 0 \text{ ft}$ - Required depth in z-direction,</p> <p>Minimum embedded depth required: $L_{e,req}$ - Depth of pile required,</p> $L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$ $L_{e,req} = \text{MAX}[(6.5092 \text{ ft}), (0 \text{ ft})]$ $L_{e,req} = 6.509 \text{ ft}$ <p>L_e - Actual embedded length of pile,</p> $L_e = L - h_e - h_2$ $L_e = (7 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$ $L_e = 7 \text{ ft}$ <p><i>Ratio</i> - Embedded depth</p> $\text{Ratio} = \frac{L_{e,req}}{L_e}$ $\text{Ratio} = \frac{(6.509 \text{ ft})}{(7 \text{ ft})}$ $\text{Ratio} = 0.92986$	<p>Status: PASS Ratio: 0.930</p>
	<p>End-bearing Capacity (ASD) A - Pile cross-section area</p> $A = b D$ $A = (48 \text{ in}) \times (48 \text{ in})$ $A = 16 \text{ ft}^2$ <p>q - End-bearing pressure</p> $q = \frac{P_u}{A}$ $q = \frac{(6.928 \text{ kip})}{(16 \text{ ft}^2)}$ $q = 0.433 \text{ kip/ft}^2$ <p>Check bearing capacity ratio: <i>Ratio</i> - Capacity</p> $\text{Ratio} = \frac{q}{q_o}$ $\text{Ratio} = \frac{(0.433 \text{ kip/ft}^2)}{(2000 \text{ psf})}$ $\text{Ratio} = 0.2165$	<p>Status: PASS Ratio: 0.220</p>
<p>Czerniak</p>	<p>Lateral Soil Pressure (ASD): L/D - Length to least lateral dimension ratio,</p> $L/D = \frac{L}{D}$ $L/D = \frac{(7 \text{ ft})}{(48 \text{ in})}$	

$$L/D = 1.75$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.59443$ kip/ft - Lateral force per length of pile,

$M_o = 6.3494$ kipft/ft - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (6.3494 \text{ kipft/ft}) \times (7 \text{ ft})) + (3 \times (-0.59443 \text{ kip/ft}) \times (7 \text{ ft})^2)}{(6 \times (6.3494 \text{ kipft/ft})) + (4 \times (-0.59443 \text{ kip/ft}) \times (7 \text{ ft}))}$$

$$a = 4.844 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (6.3494 \text{ kipft/ft})) + (3 \times (-0.59443 \text{ kip/ft}) \times (7 \text{ ft}))]^2}{(7 \text{ ft})^2 \times [(3 \times (6.3494 \text{ kipft/ft})) + (2 \times (-0.59443 \text{ kip/ft}) \times (7 \text{ ft}))]}$$

$$p = 0.238 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (6.3494 \text{ kipft/ft})) + ((-0.59443 \text{ kip/ft}) \times (7 \text{ ft}))]}{(7 \text{ ft})^2}$$

$$s = 1.0454 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{q}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(4.844 \text{ ft})}{2}$$

$$p_a = 0.3633 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{p}{p_a}$$

$$\text{Ratio} = \frac{(0.238 \text{ kip/ft}^2)}{(0.3633 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.6551$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (7 \text{ ft})$$

$$p_s = 1.05 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity


$$\text{Ratio} = \frac{s}{p_s}$$


$$\text{Ratio} = \frac{(1.0454 \text{ kip/ft}^2)}{(1.05 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.99565$$

Status: **PASS**
Ratio: **0.660**

Status: **PASS**
Ratio: **1.000**





Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-6.235 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.99283 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_x H)}{1.57 D}$$

$$M_o = \frac{(67.046 \text{ kipft}) + ((-6.235 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 10.676 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(10.676 \text{ kipft/ft})}{(-0.99283 \text{ kip/ft})}$$

$$E = 10.753 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_c) + (3 H_o L_c^2)}{(6 M_o) + (4 H_o L_c)}$$

$$a = \frac{(4 \times (10.676 \text{ kipft/ft}) \times (7 \text{ ft})) + (3 \times (-0.99283 \text{ kip/ft}) \times (7 \text{ ft})^2)}{(6 \times (10.676 \text{ kipft/ft})) + (4 \times (-0.99283 \text{ kip/ft}) \times (7 \text{ ft}))}$$

$$a = 4.8432 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4 E}{L_c} + 3 \right) \left(\frac{a}{L_c} \right)^2 \right] + \left[4 \left(\frac{3 E}{L_c} + 2 \right) \left(\frac{a}{L_c} \right)^3 \right] \right]$$

$$V_{max} = ((-0.99283 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (10.753 \text{ ft})}{(7 \text{ ft})} + 3 \right) \times \left(\frac{(4.8432 \text{ ft})}{(7 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (10.753 \text{ ft})}{(7 \text{ ft})} + 2 \right) \times \left(\frac{(4.8432 \text{ ft})}{(7 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 13.414 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o D L_c) \left[\left(\frac{E}{L_c} + \frac{a}{2 L_c} \right) - \left[\left(\frac{4 E}{L_c} + 3 \right) \left(\frac{a}{2 L_c} \right)^3 \right] + \left[\left(\frac{3 E}{L_c} + 2 \right) \left(\frac{a}{2 L_c} \right)^4 \right] \right]$$

$$M_{max} = ((-0.99283 \text{ kip/ft}) \times (48 \text{ in}) \times (7 \text{ ft})) \times \left[\left(\frac{(10.753 \text{ ft})}{(7 \text{ ft})} + \frac{(4.8432 \text{ ft})}{2 \times (7 \text{ ft})} \right) - \left[\left(\frac{4 \times (10.753 \text{ ft})}{(7 \text{ ft})} + 3 \right) \times \left(\frac{(4.8432 \text{ ft})}{2 \times (7 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (10.753 \text{ ft})}{(7 \text{ ft})} + 2 \right) \times \left(\frac{(4.8432 \text{ ft})}{2 \times (7 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 44.428 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 3 \text{ ksi}$ - Concrete strength,
 $f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,
 $\phi = 0.65$ - Reduction factor for axial strength,
 $\alpha = 0.8$ - Alpha factor for axial strength,
 $A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Table 22.4.2.1

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

22.4.2.2, 10.6.1.1

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(10.159 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (3 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (3 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -101.93 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-101.93 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

$$\text{Ratio} = 0.96556$$

Status: **PASS**
Ratio: **0.970**

25.2.3

s_{rebar} - Minimum spacing of reinforcement,

$$s_{rebar} = \text{Max} [1.5, (1.5 d_{bar})]$$

$$s_{rebar} = \text{Max} [1.5, (1.5 \times (0.625 \text{ in}))]$$

$$s_{rebar} = 1.5 \text{ in}$$

Ties:

25.7.2.2 Since longitudinal reinforcement is \leq No. 10: Use #3(0.375 in)

25.7.2.1

s_{ties} - Maximum spacing of ties,

$$s_{ties} = \text{Min} [(16 d_{bar}), (48 d_{ties}), \text{Min} (D, b)]$$

$$s_{ties} = \text{Min} [(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), \text{Min} ((48 \text{ in}), (48 \text{ in}))]$$

$$s_{ties} = 10 \text{ in}$$

Summary:

Main reinforcement: **14 - #5 (0.625 in)**

Axial Compression Strength (ACI 318-19, LRFD)22.4.2.2 ϕP_N - Allowable axial compressive strength

$$\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_{yk} A_{st})]$$

$$\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (3 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$$

$$\phi P_N = 3183.4 \text{ kip}$$

Ratio - Capacity

$$\text{Ratio} = \frac{P}{\phi P_N}$$

$$\text{Ratio} = \frac{(10.159 \text{ kip})}{(3183.4 \text{ kip})}$$

$$\text{Ratio} = 0.0031912$$

Status: **PASS**
Ratio: **0.000****Shear Strength (ACI 318-19, LRFD)****Parameters:** $b_w = 48 \text{ in}$ - Effective width,22.5.2.2 d - Effective depth

$$d = 0.80 D$$

$$d = 0.80 \times (48 \text{ in})$$

$$d = 38.4 \text{ in}$$

22.5.5.1.3 λ_s - size effect modification factor

$$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$$

$$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$$

$$\lambda_s = 0.64282$$

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$,22.5.5.1.1 $V_{c,max}$ - Max shear strength of concrete

$$V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$$

$$V_{c,max} = 5 \times (0.64282) \times \sqrt{(3000 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,max} = 324.49 \text{ kip}$$

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$, $P = 10.159 \text{ kip} \rightarrow 10159 \text{ lbf}$,22.5.5.1.1(a) $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck}} + \frac{P}{6 A_g} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(3000 \text{ psi})} + \frac{(10159 \text{ lbf})}{6 \times (2304 \text{ in}^2)} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 131.15 \text{ kip}$$

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$,22.5.5.1.2 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck}} + (0.05 f'_{ck}) \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(3000 \text{ psi})} + (0.05 \times (3000 \text{ psi})) \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 406.27 \text{ kip}$$

 V_c - Governing shear strength of concrete

$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(324.49 \text{ kip}), (131.15 \text{ kip}), (406.27 \text{ kip})]$$

$$V_c = 131.15 \text{ kip}$$

<p>22.5.1.2</p>	<p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$.</p> <p>$V_{s,a}$ - Shear strength of steel (a)</p> $V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$ $V_{s,a} = 8 \times \sqrt{(3000 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{s,a} = 807.65 \text{ kip}$ <p>A_v - Ties rebar area,</p> $A_v = \frac{\pi d_{ties}^2}{4}$ $A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$ $A_v = 0.11045 \text{ in}^2$ <p>22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)</p> $V_{s,b} = \frac{2 A_v f_{ywk} d}{s_{ties}}$ $V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$ $V_{s,b} = 50.894 \text{ kip}$ <p>V_s - Governing shear strength of steel</p> $V_s = \text{MIN}[V_{s,a}, V_{s,b}]$ $V_s = \text{MIN}[(807.65 \text{ kip}), (50.894 \text{ kip})]$ $V_s = 50.894 \text{ kip}$ <p>22.5.1.1 ϕV_n - Allowable shear strength</p> $\phi V_n = \phi (V_c + V_s)$ $\phi V_n = (0.65) \times ((131.15 \text{ kip}) + (50.894 \text{ kip}))$ $\phi V_n = 118.33 \text{ kip}$ <p>Considering x-direction:</p> <p>$V_{max} = 13.414 \text{ kip}$ - Maximum shear force in the x-direction, Ratio - Capacity</p> $\text{Ratio} = \frac{V_{max}}{\phi V_n}$ $\text{Ratio} = \frac{(13.414 \text{ kip})}{(118.33 \text{ kip})}$ $\text{Ratio} = 0.11336$	<p>Status: PASS Ratio: 0.110</p>
<p>14.5.2.1b</p>	<p>Flexural Strength (ACI 318-19, LRFD)</p> <p>S_m - Section modulus</p> $S_m = \frac{b D^2}{6}$ $S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$ $S_m = 18432 \text{ in}^3$ <p>$\lambda = 1$ - Concrete modification factor (Normal concrete), Allowable flexural strength: M_n shall be the lesser of:</p> <p>$\phi M_{n,1}$</p> $\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$ $\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{(3 \text{ ksi})} \times 18432.001 \text{ in}^3$ $\phi M_{n,1} = 273.423 \text{ kip ft}$ <p>$\phi M_{n,2}$</p> $\phi M_{n,2} = 0.85 f'_c S_m$	

$$\phi M_{n,z} = \phi S_x F_y$$

$$\phi M_{n,z} = (0.65) \times 0.85 \times (3 \text{ ksi}) \times (18432 \text{ in}^3)$$

$$\phi M_{n,z} = 2545.9 \text{ kipft}$$

Therefore,
 ϕM_n - Allowable flexural strength,

$$\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$$

$$\phi M_n = \text{MIN}[(273.42 \text{ kipft}), (2545.9 \text{ kipft})]$$

$$\phi M_n = 273.42 \text{ kipft}$$

Considering x-direction:

$M_{max} = 44.428 \text{ kipft}$ - Maximum moment in the x-direction,


Ratio - Capacity

$$\text{Ratio} = \frac{M_{max}}{\phi M_n}$$

$$\text{Ratio} = \frac{(44.428 \text{ kipft})}{(273.42 \text{ kipft})}$$

$$\text{Ratio} = 0.16249$$

Status: **PASS**
Ratio: **0.160**

REFERENCES	CALCULATIONS	RESULTS																										
	<p>SkyCiv Foundation Design Pile Foundation</p> <p>Design Information : Design code : IBC 2021 (International Building Code) Unit System : Imperial</p>																											
	<p>Pile Input</p>  <p>Geometry Pile shape: rectangular $b = 48$ in - Pile width $D = 48$ in - Pile depth $L = 7$ ft - Total pile length $h_1 = 0$ ft - Lateral load height from the top of the pile, $h_2 = 0$ ft - Depth to resting surface $h_e = 0$ ft - Length of pile above the ground</p> <p>Tabulation of Soil Parameters</p> <table border="1" data-bbox="416 1102 1193 1191"> <thead> <tr> <th>Layer</th> <th>Label</th> <th>Allowable Bearing Pressure (q_a) (psf)</th> <th>Allowable Lateral Pressure (R) (psf/ft)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Sand, silty sand, clayey sand, silty gravel & clayey gravel</td> <td>2000.000</td> <td>150.000</td> </tr> </tbody> </table> <p>Tabulation of Loads</p> <table border="1" data-bbox="676 1288 935 1458"> <thead> <tr> <th>Load Component</th> <th>ASD</th> <th>LRFD</th> </tr> </thead> <tbody> <tr> <td>P (kip)</td> <td>6.702</td> <td>9.872</td> </tr> <tr> <td>V_x (kip)</td> <td>-3.683</td> <td>-6.140</td> </tr> <tr> <td>V_z (kip)</td> <td>0.018</td> <td>0.030</td> </tr> <tr> <td>M_x (kipft)</td> <td>0.046</td> <td>0.078</td> </tr> <tr> <td>M_z (kipft)</td> <td>39.380</td> <td>66.326</td> </tr> </tbody> </table> <p>Material Properties $f'_{ck} = 3$ ksi - Concrete strength,</p>	Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)	1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000	Load Component	ASD	LRFD	P (kip)	6.702	9.872	V_x (kip)	-3.683	-6.140	V_z (kip)	0.018	0.030	M_x (kipft)	0.046	0.078	M_z (kipft)	39.380	66.326	
Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)																									
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000																									
Load Component	ASD	LRFD																										
P (kip)	6.702	9.872																										
V_x (kip)	-3.683	-6.140																										
V_z (kip)	0.018	0.030																										
M_x (kipft)	0.046	0.078																										
M_z (kipft)	39.380	66.326																										
	<p>Required depth to resist lateral loads (ASD) H - Point of application of the lateral load</p> $H = h_1 + h_2 + h_e$ $H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$ $H = 0 \text{ ft}$ <p>Considering x-direction: H_o - Lateral force per length of pile,</p> $H_o = \frac{V_x}{1.57 D}$ $H_o = \frac{(-3.683 \text{ kip})}{1.57 \times (48 \text{ in})}$ $H_o = -0.58646 \text{ kip/ft}$ <p>M_o - Moment per length of pile,</p> $M_o = \frac{M_z + (V_x H)}{1.57 D}$																											

$$M_o = \frac{(39.38 \text{ kipft}) + ((-3.683 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 6.2707 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$$

Solving the cubic equation:

$L_{e,x} = 6.4896 \text{ ft}$ - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.018 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.0028662 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.046 \text{ kipft}) + ((0.018 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.0073248 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$$

Solving the cubic equation:

$L_{e,z} = 0.9051 \text{ ft}$ - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = \text{MAX}[(6.4896 \text{ ft}), (0.9051 \text{ ft})]$$

$$L_{e,req} = 6.49 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_c - h_2$$

$$L_e = (7 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 7 \text{ ft}$$

Ratio - Embedded depth

$$\text{Ratio} = \frac{L_{e,req}}{L_e}$$

$$\text{Ratio} = \frac{(6.49 \text{ ft})}{(7 \text{ ft})}$$

$$\text{Ratio} = 0.92714$$

Status: **PASS**
Ratio: **0.930**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_c}{A}$$

$$q = \frac{(6.702 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.418875 \text{ kip/ft}^2$$

$$q = 0.41887 \text{ kip/ft}^2$$

Check bearing capacity ratio:

Ratio - Capacity

$$Ratio = \frac{q}{q_a}$$

$$Ratio = \frac{(0.41887 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$Ratio = 0.20944$$

Status: **PASS**
Ratio: **0.210**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(7 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1.75$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.58646 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 6.2707 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (6.2707 \text{ kipft/ft}) \times (7 \text{ ft})) + (3 \times (-0.58646 \text{ kip/ft}) \times (7 \text{ ft})^2)}{(6 \times (6.2707 \text{ kipft/ft})) + (4 \times (-0.58646 \text{ kip/ft}) \times (7 \text{ ft}))}$$

$$a = 4.8439 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (6.2707 \text{ kipft/ft})) + (3 \times (-0.58646 \text{ kip/ft}) \times (7 \text{ ft}))]^2}{(7 \text{ ft})^2 \times [(3 \times (6.2707 \text{ kipft/ft})) + (2 \times (-0.58646 \text{ kip/ft}) \times (7 \text{ ft}))]}$$

$$p = 0.23533 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (6.2707 \text{ kipft/ft})) + ((-0.58646 \text{ kip/ft}) \times (7 \text{ ft}))]}{(7 \text{ ft})^2}$$

$$s = 1.033 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(4.8439 \text{ ft})}{2}$$

$$p_a = 0.36329 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.23533 \text{ kip/ft}^2)}{(0.36329 \text{ kip/ft}^2)}$$

$$Ratio = 0.64776$$

p_s - Allowable lateral soil pressure at depth L_e ,

Status: **PASS**
Ratio: **0.650**

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (7 \text{ ft})$$

$$p_s = 1.05 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{s}{p_s}$$

$$\text{Ratio} = \frac{(1.033 \text{ kip/ft}^2)}{(1.05 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.98381$$

Status: **PASS**
Ratio: **0.980**

Considering z-direction:

$H_o = 0.0028662 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.0073248 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.0073248 \text{ kipft/ft}) \times (7 \text{ ft})) + (3 \times (0.0028662 \text{ kip/ft}) \times (7 \text{ ft})^2)}{(6 \times (0.0073248 \text{ kipft/ft})) + (4 \times (0.0028662 \text{ kip/ft}) \times (7 \text{ ft}))}$$

$$a = 5.0436 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (0.0073248 \text{ kipft/ft})) + (3 \times (0.0028662 \text{ kip/ft}) \times (7 \text{ ft}))]^2}{(7 \text{ ft})^2 \times [(3 \times (0.0073248 \text{ kipft/ft})) + (2 \times (0.0028662 \text{ kip/ft}) \times (7 \text{ ft}))]}$$

$$p = 0.0019738 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.0073248 \text{ kipft/ft})) + ((0.0028662 \text{ kip/ft}) \times (7 \text{ ft}))]}{(7 \text{ ft})^2}$$

$$s = 0.0042506 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(5.0436 \text{ ft})}{2}$$

$$p_a = 0.37827 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{p}{p_a}$$

$$\text{Ratio} = \frac{(0.0019738 \text{ kip/ft}^2)}{(0.37827 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.0052181$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (7 \text{ ft})$$

$$p_s = 1.05 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity


$$\text{Ratio} = \frac{s}{p_s}$$

Status: **PASS**
Ratio: **0.010**

$$Ratio = \frac{(0.0042506 \text{ kip/ft}^2)}{(1.05 \text{ kip/ft}^2)}$$

$$Ratio = 0.0040482$$

Status: **PASS**
Ratio: **0.000**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-6.14 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.97771 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(66.326 \text{ kipft}) + ((-6.14 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 10.561 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(10.561 \text{ kipft/ft})}{(-0.97771 \text{ kip/ft})}$$

$$E = 10.802 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_c) + (3 H_o L_c^2)}{(6 M_o) + (4 H_o L_c)}$$

$$a = \frac{(4 \times (10.561 \text{ kipft/ft}) \times (7 \text{ ft})) + (3 \times (-0.97771 \text{ kip/ft}) \times (7 \text{ ft})^2)}{(6 \times (10.561 \text{ kipft/ft})) + (4 \times (-0.97771 \text{ kip/ft}) \times (7 \text{ ft}))}$$

$$a = 4.8426 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4 E}{L_c} + 3 \right) \left(\frac{a}{L_c} \right)^2 \right] + \left[4 \left(\frac{3 E}{L_c} + 2 \right) \left(\frac{a}{L_c} \right)^3 \right] \right]$$

$$V_{max} = ((-0.97771 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (10.802 \text{ ft})}{(7 \text{ ft})} + 3 \right) \times \left(\frac{(4.8426 \text{ ft})}{(7 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (10.802 \text{ ft})}{(7 \text{ ft})} + 2 \right) \times \left(\frac{(4.8426 \text{ ft})}{(7 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 13.258 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.97771 \text{ kip/ft}) \times (48 \text{ in}) \times (7 \text{ ft})) \times \left[\left(\frac{(10.802 \text{ ft})}{(7 \text{ ft})} + \frac{(4.8426 \text{ ft})}{2 \times (7 \text{ ft})} \right) - \left[\left(\frac{4 \times (10.802 \text{ ft})}{(7 \text{ ft})} + 3 \right) \times \left(\frac{(4.8426 \text{ ft})}{2 \times (7 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (10.802 \text{ ft})}{(7 \text{ ft})} + 2 \right) \times \left(\frac{(4.8426 \text{ ft})}{2 \times (7 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 43.921 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.03 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.0047771 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.078 \text{ kipft}) + ((0.03 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.01242 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.01242 \text{ kipft/ft})}{(0.0047771 \text{ kip/ft})}$$

$$E = 2.6 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.01242 \text{ kipft/ft}) \times (7 \text{ ft})) + (3 \times (0.0047771 \text{ kip/ft}) \times (7 \text{ ft})^2)}{(6 \times (0.01242 \text{ kipft/ft})) + (4 \times (0.0047771 \text{ kip/ft}) \times (7 \text{ ft}))}$$

$$a = 5.0413 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((0.0047771 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (2.6 \text{ ft})}{(7 \text{ ft})} + 3 \right) \times \left(\frac{(5.0413 \text{ ft})}{(7 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (2.6 \text{ ft})}{(7 \text{ ft})} + 2 \right) \times \left(\frac{(5.0413 \text{ ft})}{(7 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.025349 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o b L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((0.0047771 \text{ kip/ft}) \times (48 \text{ in}) \times (7 \text{ ft})) \times \left[\left(\frac{(2.6 \text{ ft})}{(7 \text{ ft})} + \frac{(5.0413 \text{ ft})}{2 \times (7 \text{ ft})} \right) - \left[\left(\frac{4 \times (2.6 \text{ ft})}{(7 \text{ ft})} + 3 \right) \times \left(\frac{(5.0413 \text{ ft})}{2 \times (7 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (2.6 \text{ ft})}{(7 \text{ ft})} + 2 \right) \times \left(\frac{(5.0413 \text{ ft})}{2 \times (7 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 0.076835 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 3 \text{ ksi}$ - Concrete strength,
 $f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,
 $\phi = 0.65$ - Reduction factor for axial strength,
 $\alpha = 0.8$ - Alpha factor for axial strength,
 $A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Table 22.4.2.1

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

22.4.2.2, 10.6.1.1

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(0.872 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (3 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (3 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -101.94 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-101.94 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

$$\text{Ratio} = 0.96556$$

Status: **PASS**
Ratio: **0.970**

25.2.3

s_{rebar} - Minimum spacing of reinforcement,

$$s_{rebar} = \text{Max} [1.5, (1.5 d_{bar})]$$

$$s_{rebar} = \text{Max} [1.5, (1.5 \times (0.625 \text{ in}))]$$

$$s_{rebar} = 1.5 \text{ in}$$

Ties:

25.7.2.2

Since longitudinal reinforcement is \leq No. 10: Use #3(0.375 in)

25.7.2.1

s_{ties} - Maximum spacing of ties,

$$s_{ties} = \text{Min} [(16 d_{bar}), (48 d_{ties}), \text{Min} (D, b)]$$

$$s_{ties} = \text{Min} [(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), \text{Min} ((48 \text{ in}), (48 \text{ in}))]$$

$$s_{ties} = 10 \text{ in}$$

Summary:

Main reinforcement: **14 - #5 (0.625 in)**

Ties: #3(0.375 in) - 10 in

Axial Compression Strength (ACI 318-19, LRFD)

22.4.2.2

ϕP_N - Allowable axial compressive strength

$$\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_{yk} A_{st})]$$

$$\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (3 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$$

$$\phi P_N = 3183.4 \text{ kip}$$

Ratio - Capacity

$$\text{Ratio} = \frac{P}{\phi P_N}$$

$$\text{Ratio} = \frac{(9.872 \text{ kip})}{(3183.4 \text{ kip})}$$

$$\text{Ratio} = 0.0031011$$

Status: **PASS**
Ratio: **0.000**

Shear Strength (ACI 318-19, LRFD)

Parameters:

22.5.2.2

$b_w = 48 \text{ in}$ - Effective width,
 d - Effective depth

$$d = 0.80 D$$

$$d = 0.80 \times (48 \text{ in})$$

$$d = 38.4 \text{ in}$$

22.5.5.1.3

λ_s - size effect modification factor

$$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$$

$$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$$

$$\lambda_s = 0.64282$$

22.5.5.1.1

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$,
 $V_{c,max}$ - Max shear strength of concrete

$$V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$$

$$V_{c,max} = 5 \times (0.64282) \times \sqrt{(3000 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,max} = 324.49 \text{ kip}$$

22.5.5.1.1(a)

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$, $P = 9.872 \text{ kip} \rightarrow 9872 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck}} + \frac{P}{6 A_g} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(3000 \text{ psi})} + \frac{(9872 \text{ lbf})}{6 \times (2304 \text{ in}^2)} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 131.11 \text{ kip}$$

22.5.5.1.2

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck}} + (0.05 f'_{ck}) \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(3000 \text{ psi})} + (0.05 \times (3000 \text{ psi})) \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 406.27 \text{ kip}$$

V_c - Governing shear strength of concrete

$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(324.49 \text{ kip}), (131.11 \text{ kip}), (406.27 \text{ kip})]$$

$$V_c = 131.11 \text{ kip}$$

<p>22.5.1.2</p>	<p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$, $V_{s,a}$ - Shear strength of steel (a)</p> $V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$ $V_{s,a} = 8 \times \sqrt{(3000 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{s,a} = 807.65 \text{ kip}$ <p>A_v - Ties rebar area,</p> $A_v = \frac{\pi d_{ties}^2}{4}$ $A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$ $A_v = 0.11045 \text{ in}^2$ <p>22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)</p> $V_{s,b} = \frac{2 A_v f_{yt} d}{s_{ties}}$ $V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$ $V_{s,b} = 50.894 \text{ kip}$ <p>V_s - Governing shear strength of steel</p> $V_s = \text{MIN}[V_{s,a}, V_{s,b}]$ $V_s = \text{MIN}[(807.65 \text{ kip}), (50.894 \text{ kip})]$ $V_s = 50.894 \text{ kip}$ <p>22.5.1.1 ϕV_n - Allowable shear strength</p> $\phi V_n = \phi (V_c + V_s)$ $\phi V_n = (0.65) \times ((131.11 \text{ kip}) + (50.894 \text{ kip}))$ $\phi V_n = 118.3 \text{ kip}$ <p>Considering x-direction:</p> <p>$V_{max} = 13.258 \text{ kip}$ - Maximum shear force in the x-direction, Ratio - Capacity</p> $\text{Ratio} = \frac{V_{max}}{\phi V_n}$ $\text{Ratio} = \frac{(13.258 \text{ kip})}{(118.3 \text{ kip})}$ $\text{Ratio} = 0.11207$ <p>Considering z-direction:</p> <p>$V_{max} = 0.025349 \text{ kip}$ - Maximum shear force in the z-direction, Ratio - Capacity</p> $\text{Ratio} = \frac{V_{max}}{\phi V_n}$ $\text{Ratio} = \frac{(0.025349 \text{ kip})}{(118.3 \text{ kip})}$ $\text{Ratio} = 0.00021427$	<p>Status: PASS Ratio: 0.110</p> <p>Status: PASS Ratio: 0.000</p>
	<p>Flexural Strength (ACI 318-19, LFRD)</p> <p>S_m - Section modulus</p> $S_m = \frac{b D^2}{6}$ $S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$ $S_m = 18432 \text{ in}^3$	

<p>14.5.2.1b</p>	<p>$\lambda = 1$ - Concrete modification factor (Normal concrete), Allowable flexural strength: M_n shall be the lesser of: $\phi M_{n,1}$</p> $\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$ $\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{3ksi} \times 18432.001 in^3$ $\phi M_{n,1} = 273.423 kipft$ <p>$\phi M_{n,2}$</p> $\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$ $\phi M_{n,2} = (0.65) \times 0.85 \times (3 ksi) \times (18432 in^3)$ $\phi M_{n,2} = 2545.9 kipft$ <p>Therefore, ϕM_n - Allowable flexural strength,</p> $\phi M_n = MIN[\phi M_{n,1}, \phi M_{n,2}]$ $\phi M_n = MIN[(273.42 kipft), (2545.9 kipft)]$ $\phi M_n = 273.42 kipft$ <p>Considering x-direction: $M_{max} = 43.921 kipft$ - Maximum moment in the x-direction, Ratio - Capacity</p> $Ratio = \frac{M_{max}}{\phi M_n}$ $Ratio = \frac{(43.921 kipft)}{(273.42 kipft)}$ $Ratio = 0.16063$	<p>Status: PASS Ratio: 0.160</p>
	<p>Considering z-direction: $M_{max} = 0.076835 kipft$ - Maximum moment in the z-direction, Ratio - Capacity</p> $Ratio = \frac{M_{max}}{\phi M_n}$ $Ratio = \frac{(0.076835 kipft)}{(273.42 kipft)}$ $Ratio = 0.00028101$	<p>Status: PASS Ratio: 0.000</p>