

Project Name: MTSOLAR_EDCKCB9K0434 **Date:** Thu Oct 31 2024
Location: Grand Rapids, MI, USA **Number of Modules:** 60
Unique ID: 4P-19.75-8TOP-XD-45-L-5Hx12W-2ELA **Number of Poles:** 4
Dealer: _____ **Date Sold:** _____



Array Dimensions N/S	17.29 ft
Array Dimensions E/W	76.00 ft
Winter Tilt Angle	15
Front Edge Clearance	12 ft


MT Solar Bill of Materials (4P-19.75-8TOP-XD-45-L-5Hx12W-2ELA)

Part	Short Description	BOM Qty
MTS-PC-8	8IN Pole Cap Assembly	4
MTS-HF-XD	H-Frame Assembly-XD	4
MTS-XD-Wing-45	45IN XD Wing	4
MTS-XD-Splice-90	90IN XD Splice	6
MTS-XD-Splice-57	57IN XD Splice	6
MTS-CLAMP-ANGLE-4PK	Angle Clamp	12

Rail Bill of Materials

Part	Qty
Rails (205in)	24
Rail Attachment	96
Module Mid Clamp	96
Module End Clamp	48
Ground Lug	12

Site Details:



Site Address: Grand Rapids, MI, USA

Array Specification

Duty Classification:	XD
Module Width:	41.00 in
Module Length:	75.00in
Number of Rows:	5
Number of Columns:	12
Total Number of Modules:	60
Winter Tilt Angle:	15
Front Edge Clearance:	12
Total Array Height at Tilt:	16.48 ft
Total Frame Length:	74.25 ft
Frame Weight:	5668 lbs
Array Dimensions N/S:	17.29 ft
Array Dimensions E/W:	76.00 ft
Rail Length:	207.50 in
Rail Spacing:	3.17 ft

Support Specifications

Pole Size:	8in Pipe Sch 40
Pole Length above Grade:	14.24 ft
Number of Poles:	4
Pole Spacing:	19.75 ft

Foundation Specifications

Foundation Type:	Square
Foundation Dimensions:	48 x 48 in
Foundation Depth (below grade):	Pile 1: 6.25 ft Pile 2: 6.25 ft Pile 3: 6.25 ft Pile 4: 6.25 ft
Foundation Volume:	14.815 y ³

Site Info

Risk Category:	I
Exposure:	C
Soil Classification:	sand
Site Location:	Grand Rapids, MI, USA
Wind Speed:	101 mph

Snow Load:

35 psf

Design Disclaimer



This software should be used for preliminary designs and should not be used as a final design unless reviewed, verified and designed by a qualified structural engineer.



AutoDesigner Input

```
{ "wind_speed_override": null, "snow_load_override": null, "direct_snow_load": false, "add_angle_brace": false, "product_type": "Beam", "designer_name": "", "designer_email": "lws6@calvin.edu", "designer_phone": "", "project_id": "MTSOLAR_EDCKCB9K0434", "site_address": "Grand Rapids, MI, USA", "module_width": 41, "module_length": 75, "number_rows": 5, "number_columns": 12, "pole_mount_section": "4_40", "core_pipe_width": 65, "core_pipe_section": "2_40", "adjuster_section": "2_40", "core_beam_height": 65, "core_beam_section": "HSS3x2x1/8", "main_pipe_section": "2_12GA", "pole_spacing": 15, "tilt_angle": 15, "ground_clearance": 12, "risk_category": "I", "exposure_category": "C", "frame_duty_override": "auto", "pole_override": "auto", "soil_type": "sand", "customer_foundation_override": "48_Square", "foundation_type": "Square", "foundation_size": 48, "check_rails": false }
```


Design Notes:



- AISC Deflection checks are set to L/1 due to structure design intent
- Foundation Soil Parameters used in this Autodesign are all estimates, proper geotechnical reports are required to confirm soil profiles
- Wind speeds, snow loads and other site specific results are based on ASCE 7 2016
- Steel frame design checks are based on AISC 360 2016 (LRFD)
- Foundation Design and Sizing is approximate only






FEM Results (Envelope Worst Case for each member)







Reaction Forces for Foundation 1 (Node ID#1), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	0.0045	2.4730	0.0206	0.0928	-0.0008	-0.0267
ULS: 2. D + L	0.0045	2.4730	0.0206	0.0928	-0.0008	-0.0267
ULS: 3. D + (S or Lr or R)	0.0198	8.5419	0.0908	0.4105	-0.0041	-0.2097
ULS: 3. D + (S or Lr or R)	0.0045	2.4730	0.0206	0.0928	-0.0008	-0.0267
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0160	7.0247	0.0733	0.3311	-0.0033	-0.1639
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0045	2.4730	0.0206	0.0928	-0.0008	-0.0267
ULS: 5b. D + 0.7E	0.0045	2.4730	0.0206	0.0928	-0.0008	-0.0267
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	0.0160	7.0247	0.0733	0.3311	-0.0033	-0.1639
ULS: 8. 0.6D + 0.7E	0.0027	1.4838	0.0123	0.0557	-0.0005	-0.0160
ULS: 5a. D + 0.6W_Wind downforce Case A only	-1.0901	6.4756	0.0791	0.3525	-0.0795	17.8651
ULS: 5a. D + 0.6W_Wind downforce Case B only	-1.0901	6.4756	0.0791	0.3525	-0.0795	17.8651
ULS: 5a. D + 0.6W_Wind uplift Case A only	0.8271	-0.5594	-0.0191	-0.0826	0.0497	-9.4287
ULS: 5a. D + 0.6W_Wind uplift Case B only	0.7357	-0.1565	-0.0256	-0.1107	0.0670	-20.3114
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.8050	10.0267	0.1172	0.5258	-0.0624	13.2549
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.8050	10.0267	0.1172	0.5258	-0.0624	13.2549
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.6329	4.7504	0.0435	0.1995	0.0345	-7.2154
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.5644	5.0526	0.0386	0.1785	0.0475	-15.3774
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.8165	5.4750	0.0645	0.2876	-0.0598	13.3921
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.8165	5.4750	0.0645	0.2876	-0.0598	13.3921
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.6215	0.1987	-0.0092	-0.0388	0.0371	-7.0782
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.5529	0.5009	-0.0141	-0.0598	0.0501	-15.2402
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-1.0919	5.4864	0.0709	0.3153	-0.0792	17.8757
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-1.0919	5.4864	0.0709	0.3153	-0.0792	17.8757
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	0.8253	-1.5486	-0.0274	-0.1198	0.0500	-9.4180
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	0.7339	-1.1457	-0.0338	-0.1478	0.0673	-20.3007

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.

Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	16.0146
Shear X	-1.8244
Shear Z	0.1879
Moment X	0.8484
Moment Y (Twist)	0.1370
Moment Z	35.1813

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.

Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	10.0267
Shear X	-1.0919
Shear Z	0.1172
Moment X	0.5258
Moment Y (Twist)	0.0795
Moment Z	20.3114

Reaction Forces for Foundation 2 (Node ID#101), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	-0.0045	2.7649	-0.0012	-0.0055	0.0007	0.0920
ULS: 2. D + L	-0.0045	2.7649	-0.0012	-0.0055	0.0007	0.0920
ULS: 3. D + (S or Lr or R)	-0.0198	9.8218	-0.0054	-0.0245	0.0030	0.3222
ULS: 3. D + (S or Lr or R)	-0.0045	2.7649	-0.0012	-0.0055	0.0007	0.0920
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0160	8.0575	-0.0043	-0.0198	0.0024	0.2647

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0045	2.7649	-0.0012	-0.0055	0.0007	0.0920
ULS: 5b. D + 0.7E	-0.0045	2.7649	-0.0012	-0.0055	0.0007	0.0920
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	-0.0160	8.0575	-0.0043	-0.0198	0.0024	0.2647
ULS: 8. 0.6D + 0.7E	-0.0027	1.6589	-0.0007	-0.0033	0.0004	0.0552
ULS: 5a. D + 0.6W_Wind downforce Case A only	-1.2254	7.4039	0.0030	0.0120	-0.0168	19.9697
ULS: 5a. D + 0.6W_Wind downforce Case B only	-1.2254	7.4039	0.0030	0.0120	-0.0168	19.9697
ULS: 5a. D + 0.6W_Wind uplift Case A only	0.9295	-0.7585	-0.0017	-0.0073	0.0072	-10.4432
ULS: 5a. D + 0.6W_Wind uplift Case B only	0.7814	-0.2674	-0.0083	-0.0359	0.0239	-22.0395
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.9317	11.5369	-0.0012	-0.0066	-0.0107	15.1730
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.9317	11.5369	-0.0012	-0.0066	-0.0107	15.1730
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.6845	5.4150	-0.0047	-0.0211	0.0073	-7.6367
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.5734	5.7833	-0.0097	-0.0426	0.0198	-16.3339
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.9202	6.2442	0.0019	0.0076	-0.0125	15.0003
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.9202	6.2442	0.0019	0.0076	-0.0125	15.0003
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.6960	0.1223	-0.0016	-0.0069	0.0056	-7.8094
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.5849	0.4907	-0.0065	-0.0283	0.0181	-16.5066
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-1.2236	6.2980	0.0034	0.0142	-0.0171	19.9329
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-1.2236	6.2980	0.0034	0.0142	-0.0171	19.9329
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	0.9313	-1.8645	-0.0012	-0.0051	0.0069	-10.4800
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	0.7832	-1.3734	-0.0078	-0.0337	0.0237	-22.0763

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	18.4736
Shear X	-2.0452
Shear Z	-0.0164
Moment X	-0.0713
Moment Y (Twist)	0.0435
Moment Z	38.1010

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	11.5369
Shear X	-1.2254
Shear Z	-0.0097
Moment X	-0.0426
Moment Y (Twist)	0.0239
Moment Z	22.0763

Reaction Forces for Foundation 3 (Node ID#201), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	-0.0045	2.7649	0.0012	0.0055	-0.0007	0.0920
ULS: 2. D + L	-0.0045	2.7649	0.0012	0.0055	-0.0007	0.0920
ULS: 3. D + (S or Lr or R)	-0.0198	9.8218	0.0054	0.0245	-0.0029	0.3222
ULS: 3. D + (S or Lr or R)	-0.0045	2.7649	0.0012	0.0055	-0.0007	0.0920
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0160	8.0575	0.0043	0.0198	-0.0024	0.2647
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0045	2.7649	0.0012	0.0055	-0.0007	0.0920
ULS: 5b. D + 0.7E	-0.0045	2.7649	0.0012	0.0055	-0.0007	0.0920
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	-0.0160	8.0575	0.0043	0.0198	-0.0024	0.2647
ULS: 8. 0.6D + 0.7E	-0.0027	1.6589	0.0007	0.0033	-0.0004	0.0552
ULS: 5a. D + 0.6W_Wind downforce Case A only	-1.2254	7.4039	-0.0030	-0.0120	0.0168	19.9697
ULS: 5a. D + 0.6W_Wind downforce Case B only	-1.2254	7.4039	-0.0030	-0.0120	0.0168	19.9697
ULS: 5a. D + 0.6W_Wind uplift Case A only	0.9295	-0.7585	0.0017	0.0073	-0.0072	-10.4432
ULS: 5a. D + 0.6W_Wind uplift Case B only	0.7814	-0.2674	0.0083	0.0359	-0.0239	-22.0395

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.9317	11.5369	0.0012	0.0066	0.0108	15.1730
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.9317	11.5369	0.0012	0.0066	0.0108	15.1730
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.6845	5.4150	0.0047	0.0211	-0.0072	-7.6367
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.5734	5.7833	0.0097	0.0426	-0.0198	-16.3339
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.9202	6.2442	-0.0019	-0.0076	0.0125	15.0003
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.9202	6.2442	-0.0019	-0.0076	0.0125	15.0003
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.6960	0.1223	0.0016	0.0069	-0.0056	-7.8094
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.5849	0.4907	0.0065	0.0283	-0.0181	-16.5066
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-1.2236	6.2980	-0.0034	-0.0142	0.0171	19.9329
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-1.2236	6.2980	-0.0034	-0.0142	0.0171	19.9329
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	0.9313	-1.8645	0.0012	0.0051	-0.0069	-10.4800
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	0.7832	-1.3734	0.0078	0.0337	-0.0237	-22.0763

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	18.4736
Shear X	-2.0452
Shear Z	0.0164
Moment X	0.0716
Moment Y (Twist)	0.0434
Moment Z	38.1011

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	11.5369
Shear X	-1.2254
Shear Z	0.0097
Moment X	0.0426
Moment Y (Twist)	0.0239
Moment Z	22.0763

Reaction Forces for Foundation 4 (Node ID#301), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	0.0045	2.4730	-0.0206	-0.0928	0.0008	-0.0266
ULS: 2. D + L	0.0045	2.4730	-0.0206	-0.0928	0.0008	-0.0266
ULS: 3. D + (S or Lr or R)	0.0198	8.5419	-0.0908	-0.4105	0.0042	-0.2096
ULS: 3. D + (S or Lr or R)	0.0045	2.4730	-0.0206	-0.0928	0.0008	-0.0266
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0160	7.0247	-0.0733	-0.3311	0.0033	-0.1639
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0045	2.4730	-0.0206	-0.0928	0.0008	-0.0266
ULS: 5b. D + 0.7E	0.0045	2.4730	-0.0206	-0.0928	0.0008	-0.0266
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	0.0160	7.0247	-0.0733	-0.3311	0.0033	-0.1639
ULS: 8. 0.6D + 0.7E	0.0027	1.4838	-0.0123	-0.0557	0.0005	-0.0160
ULS: 5a. D + 0.6W_Wind downforce Case A only	-1.0901	6.4756	-0.0791	-0.3525	0.0795	17.8651
ULS: 5a. D + 0.6W_Wind downforce Case B only	-1.0901	6.4756	-0.0791	-0.3525	0.0795	17.8651
ULS: 5a. D + 0.6W_Wind uplift Case A only	0.8271	-0.5594	0.0191	0.0826	-0.0497	-9.4287
ULS: 5a. D + 0.6W_Wind uplift Case B only	0.7357	-0.1565	0.0256	0.1107	-0.0670	-20.3114
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.8050	10.0267	-0.1172	-0.5258	0.0624	13.2549
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.8050	10.0267	-0.1172	-0.5258	0.0624	13.2549
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.6329	4.7504	-0.0435	-0.1995	-0.0345	-7.2154
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.5644	5.0526	-0.0386	-0.1785	-0.0475	-15.3774
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.8165	5.4750	-0.0645	-0.2876	0.0598	13.3921
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.8165	5.4750	-0.0645	-0.2876	0.0598	13.3921
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.6215	0.1987	0.0092	0.0388	-0.0371	-7.0782
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.5529	0.5009	0.0141	0.0598	-0.0501	-15.2402

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-1.0919	5.4864	-0.0709	-0.3153	0.0792	17.8757
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-1.0919	5.4864	-0.0709	-0.3153	0.0792	17.8757
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	0.8253	-1.5486	0.0274	0.1198	-0.0500	-9.4180
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	0.7339	-1.1457	0.0338	0.1478	-0.0673	-20.3007

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
 Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	16.0146
Shear X	-1.8244
Shear Z	-0.1879
Moment X	-0.8483
Moment Y (Twist)	0.1370
Moment Z	35.1818

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
 Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	10.0267
Shear X	-1.0919
Shear Z	-0.1172
Moment X	-0.5258
Moment Y (Twist)	0.0795
Moment Z	20.3114

Project Details

Design Code: AISC 360-16 LRFD
 Provision: LRFD
 Country: United States
 User Name: sales@mtsolar.us
 Unit System: imperial




Design Input Information


Design Factors			
Φ_t	Φ_c	Φ_b	Φ_v
0.9	0.9	0.9	0.9

Design Materials			
ID	E (ksi)	F_y (ksi)	F_u (ksi)
1	29000	50	65


Section Dimensions



ID	Name	d (in)	t_w (in)				
3	2in Pipe Sch 120	2.38	0.25				
6	4in Pipe Sch 120	4.50	0.44				
9	8in Pipe Sch 40	8.63	0.32				



ID	Name	d (in)	b (in)	t_w (in)	t_b (in)	r (in)	
17	HSS5x3x1/4	5.00	3.00	0.23	0.23	0.23	



ID	Name	d (in)	t_w (in)	b_t (in)	b_b (in)	t_t (in)	t_b (in)	r (in)
20	W10x12	9.87	0.19	3.96	3.96	0.21	0.21	0.30

Section Properties

ID	Name	A (in ²)	J (in ⁴)	I_{yp} (in ⁴)	I_{zp} (in ⁴)	I_w (in ⁶)	S_{yp} (in ³)	S_{zp} (in ³)
----	------	----------------------	----------------------	-----------------------------	-----------------------------	--------------------------	-----------------------------	-----------------------------

113	20	4.88	4.00	7.50	1.04,1.04,1.04,1.04,1.04,1.04,1.05,1.05,1.09,1.21,1.05,1.05,1.05,1.07,1.05,1.05,1.04,1.04,1.05,1.05,2.5 1,1.15,1.05,1.05,1.05,1.06	300	200	1
114	20	4.88	4.00	7.50	1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.09,1.08,1.05,1.05,1.05,1.45,1.04,1.04,1.04,1.04,1.04,1.04,1.0 5,1.11,1.05,1.05,1.05,1.90	300	200	1
115	20	6.63	6.63	10.20	1.15,1.15,1.15,1.15,1.15,1.15,1.14,1.14,1.21,1.10,1.14,1.14,1.14,1.12,1.15,1.15,1.15,1.17,1.14,1.14,1.0 8,1.11,1.14,1.14,1.14,1.12	300	200	1
116	20	6.63	6.63	10.20	1.15,1.15,1.15,1.15,1.15,1.15,1.16,1.16,1.15,1.13,1.16,1.16,1.15,1.11,1.15,1.15,1.15,1.15,1.16,1.16,1.1 5,1.13,1.16,1.16,1.15,1.10	300	200	1
201	9	29.90	29.90	14.24	-	300	200	1
202	6	1.30	1.30	2.00	-	300	200	1
203	17	0.92	0.92	1.42	1.19,1.18,1.19,1.18,1.18,1.19,1.18,1.18,1.20,1.17,1.18,1.18,1.17,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.9 7,1.17,1.18,1.18,1.17,1.18	300	200	1
204	17	2.44	2.44	3.75	1.69,1.67,1.69,1.67,1.68,1.69,1.67,1.67,1.63,1.68,1.67,1.67,1.66,1.69,1.67,1.67,1.67,1.67,1.67,1.67,1.6 2,1.69,1.67,1.67,1.66,1.69	300	200	1
205	17	1.52	1.52	2.33	1.68,1.67,1.68,1.67,1.67,1.68,1.67,1.67,1.70,1.66,1.67,1.67,1.66,1.66,1.67,1.67,1.67,1.67,1.67,1.1 1,1.66,1.67,1.67,1.66,1.66	300	200	1
206	17	0.92	0.92	1.42	1.19,1.18,1.19,1.18,1.18,1.19,1.18,1.18,1.20,1.17,1.18,1.18,1.17,1.17,1.18,1.18,1.18,1.18,1.18,1.6 6,1.17,1.18,1.18,1.17,1.18	300	200	1
207	17	1.52	1.52	2.33	1.68,1.67,1.68,1.67,1.67,1.68,1.67,1.67,1.70,1.66,1.67,1.67,1.65,1.66,1.67,1.67,1.67,1.67,1.67,1.4 7,1.66,1.67,1.67,1.66,1.66	300	200	1
208	20	1.33	1.33	2.05	2.07,2.07,2.07,2.07,2.07,2.07,2.08,2.08,2.06,1.85,2.08,2.08,2.07,1.57,2.07,2.07,2.07,2.06,2.08,2.08,2.0 7,1.79,2.08,2.08,2.07,1.47	300	200	1
209	3	2.60	2.60	4.00	-	300	200	1
210	17	2.44	2.44	3.75	1.69,1.67,1.69,1.67,1.68,1.69,1.67,1.67,1.63,1.68,1.67,1.67,1.66,1.69,1.67,1.67,1.67,1.67,1.67,1.6 2,1.69,1.67,1.67,1.66,1.69	300	200	1
211	20	1.33	1.33	2.05	2.07,2.07,2.07,2.07,2.07,2.07,1.94,1.94,2.28,1.49,1.89,1.89,1.85,1.68,2.06,2.06,2.07,2.10,1.94,1.94,1.0 7,1.56,1.88,1.88,1.90,1.70	300	200	1
212	6	1.30	1.30	2.00	-	300	200	1
213	20	4.88	4.00	7.50	1.04,1.04,1.04,1.04,1.04,1.04,1.05,1.05,1.09,1.21,1.05,1.05,1.05,1.07,1.05,1.05,1.04,1.04,1.05,1.05,2.5 1,1.15,1.05,1.05,1.05,1.06	300	200	1
214	20	4.88	4.00	7.50	1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.09,1.08,1.04,1.04,1.05,1.45,1.04,1.04,1.04,1.04,1.04,1.04,1.0 5,1.11,1.05,1.05,1.05,1.90	300	200	1
215	20	6.63	6.63	10.20	1.16,1.16,1.16,1.16,1.16,1.16,1.15,1.15,1.23,1.12,1.14,1.14,1.14,1.13,1.15,1.15,1.16,1.17,1.15,1.15,1.0 5,1.12,1.14,1.14,1.14,1.13	300	200	1
216	20	6.63	6.63	10.20	1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.15,1.14,1.16,1.16,1.16,1.13,1.16,1.16,1.16,1.15,1.16,1.16,1.1 6,1.14,1.16,1.16,1.16,1.12	300	200	1
301	9	29.90	29.90	14.24	-	300	200	1
302	6	1.30	1.30	2.00	-	300	200	1
303	17	0.92	0.92	1.42	1.19,1.18,1.19,1.18,1.19,1.19,1.18,1.18,1.21,1.18,1.18,1.18,1.17,1.18,1.18,1.18,1.18,1.18,1.18,1.18,2.0 2,1.17,1.18,1.18,1.17,1.18	300	200	1
304	17	2.44	2.44	3.75	1.69,1.68,1.69,1.67,1.68,1.69,1.67,1.67,1.63,1.68,1.67,1.67,1.66,1.69,1.67,1.67,1.67,1.67,1.68,1.68,1.6 2,1.69,1.67,1.67,1.66,1.69	300	200	1
305	17	1.52	1.52	2.33	1.68,1.67,1.68,1.67,1.68,1.68,1.67,1.67,1.71,1.66,1.67,1.67,1.65,1.66,1.67,1.67,1.67,1.67,1.67,1.1 8,1.66,1.67,1.67,1.66,1.66	300	200	1
306	17	0.92	0.92	1.42	1.19,1.18,1.19,1.18,1.18,1.19,1.18,1.18,1.21,1.17,1.18,1.18,1.16,1.17,1.18,1.18,1.18,1.18,1.18,1.18,1.5 7,1.16,1.18,1.18,1.17,1.17	300	200	1
307	17	1.52	1.52	2.33	1.68,1.67,1.68,1.67,1.68,1.68,1.67,1.67,1.70,1.66,1.67,1.67,1.65,1.66,1.67,1.67,1.67,1.67,1.67,2.5 8,1.65,1.67,1.67,1.66,1.66	300	200	1
308	20	7.88	7.88	3.75	2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.3 3,2.33,2.33,2.33,2.33,2.33	300	200	1
309	3	2.60	2.60	4.00	-	300	200	1
310	17	2.44	2.44	3.75	1.69,1.68,1.69,1.67,1.68,1.69,1.67,1.67,1.62,1.68,1.67,1.67,1.65,1.69,1.67,1.67,1.67,1.67,1.68,1.68,1.6 1,1.69,1.67,1.67,1.66,1.69	300	200	1
311	20	7.88	7.88	3.75	2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.3 3,2.33,2.33,2.33,2.33,2.33	300	200	1
312	6	1.30	1.30	2.00	-	300	200	1
313	20	4.88	4.00	7.50	1.12,1.12,1.12,1.12,1.12,1.12,1.11,1.11,1.22,1.14,1.11,1.11,1.10,1.12,1.12,1.12,1.12,1.12,1.11,1.11,1.1 1,1.12,1.11,1.11,1.10,1.12	300	200	1
314	20	4.88	4.00	7.50	1.11,1.12,1.11,1.12,1.12,1.11,1.11,1.11,1.14,1.15,1.11,1.11,1.12,1.30,1.11,1.11,1.11,1.12,1.11,1.11,1.1 3,1.16,1.11,1.11,1.12,1.48	300	200	1

212	251.01	248.88	27.10	27.10	75.30	75.30
213	159.30	97.43	31.75	6.46	56.26	44.91
214	159.30	97.43	31.86	6.46	56.26	44.91
215	159.30	75.13	20.31	6.46	56.26	44.91
216	159.30	75.13	21.58	6.46	56.26	44.91
301	377.97	127.21	83.29	83.29	113.39	113.39
302	251.01	248.88	27.16	27.16	75.30	75.30
303	151.65	150.70	20.17	14.14	54.12	28.95
304	151.65	145.15	20.17	14.14	54.12	28.95
305	151.65	149.10	20.17	14.14	54.12	28.95
306	151.65	150.70	20.17	14.14	54.12	28.95
307	151.65	149.10	20.17	14.14	54.12	28.95
308	159.30	55.15	46.90	6.46	56.26	44.91
309	75.10	66.32	4.25	4.25	22.53	22.53
310	151.65	145.15	20.17	14.14	54.12	28.95
311	159.30	55.15	46.90	6.46	56.26	44.91
312	251.01	248.88	27.16	27.16	75.30	75.30
313	159.30	97.43	33.55	6.46	56.26	44.91
314	159.30	97.43	33.95	6.46	56.26	44.91
315	159.30	75.13	21.33	6.46	56.26	44.91
316	159.30	75.13	21.43	6.46	56.26	44.91

Design Ratio

Member ID	P	M _z	M _y	V _y	V _z	(P,M _z ,M _y)	Worst LC	KL/r	δ	Status
1	0.126	0.422	0.022	0.016	0.002	0.430	#16	0.611	Not Required	Pass
2	0.002	0.457	0.069	0.098	0.012	0.515	#21	0.036	Not Required	Pass
3	0.005	0.686	0.020	0.068	0.002	0.708	#21	0.046	Not Required	Pass
4	0.004	0.651	0.077	0.065	0.017	0.709	#21	0.082	Not Required	Pass
5	0.005	0.426	0.074	0.068	0.019	0.442	#21	0.076	Not Required	Pass
6	0.006	0.753	0.046	0.076	0.009	0.802	#21	0.046	Not Required	Pass
7	0.006	0.467	0.108	0.075	0.028	0.495	#21	0.076	Not Required	Pass
8	0.001	0.083	0.113	0.044	0.012	0.132	#21	0.102	Not Required	Pass
9	0.008	0.078	0.039	0.001	0.001	0.120	#21	0.206	Not Required	Pass
10	0.006	0.708	0.101	0.071	0.022	0.767	#21	0.082	Not Required	Pass
11	0.002	0.085	0.116	0.047	0.012	0.132	#21	0.102	Not Required	Pass
12	0.001	0.524	0.074	0.108	0.013	0.585	#21	0.054	Not Required	Pass
13	0.003	0.224	0.288	0.061	0.016	0.434	#21	0.306	Not Required	Pass
14	0.005	0.215	0.285	0.057	0.016	0.413	#21	0.204	Not Required	Pass
15	0.000	0.067	0.097	0.030	0.007	0.164	#21	Not Required	Not Required	Pass
16	0.000	0.064	0.097	0.028	0.007	0.161	#21	Not Required	Not Required	Pass
101	0.145	0.457	0.002	0.018	0.000	0.472	#13	0.611	Not Required	Pass
102	0.002	0.569	0.082	0.120	0.013	0.639	#21	0.036	Not Required	Pass
103	0.006	0.831	0.037	0.083	0.005	0.871	#21	0.046	Not Required	Pass
104	0.006	0.795	0.105	0.079	0.023	0.867	#21	0.082	Not Required	Pass
105	0.006	0.516	0.109	0.082	0.028	0.543	#21	0.076	Not Required	Pass
106	0.006	0.832	0.037	0.083	0.006	0.870	#21	0.046	Not Required	Pass
107	0.006	0.517	0.103	0.082	0.027	0.544	#21	0.076	Not Required	Pass
108	0.001	0.054	0.106	0.046	0.012	0.147	#21	0.102	Not Required	Pass
109	0.010	0.080	0.029	0.001	0.000	0.113	#21	0.206	Not Required	Pass
110	0.006	0.791	0.099	0.079	0.022	0.860	#21	0.082	Not Required	Pass

111	0.002	0.062	0.108	0.048	0.012	0.145	#21	0.102	Not Required	Pass
112	0.002	0.568	0.083	0.119	0.014	0.638	#21	0.036	Not Required	Pass
113	0.004	0.250	0.295	0.063	0.016	0.514	#21	0.306	Not Required	Pass
114	0.006	0.254	0.294	0.061	0.016	0.513	#21	0.306	Not Required	Pass
115	0.003	0.334	0.153	0.050	0.013	0.490	#21	0.507	Not Required	Pass
116	0.001	0.316	0.154	0.048	0.013	0.469	#21	0.507	Not Required	Pass
201	0.145	0.457	0.002	0.018	0.000	0.472	#13	0.611	Not Required	Pass
202	0.002	0.568	0.083	0.119	0.014	0.638	#21	0.036	Not Required	Pass
203	0.006	0.832	0.037	0.083	0.006	0.870	#21	0.046	Not Required	Pass
204	0.006	0.791	0.099	0.079	0.022	0.859	#21	0.082	Not Required	Pass
205	0.006	0.517	0.103	0.082	0.027	0.544	#21	0.076	Not Required	Pass
206	0.006	0.831	0.037	0.083	0.005	0.871	#21	0.046	Not Required	Pass
207	0.006	0.516	0.109	0.082	0.028	0.543	#21	0.076	Not Required	Pass
208	0.001	0.065	0.120	0.048	0.013	0.154	#21	0.102	Not Required	Pass
209	0.010	0.080	0.029	0.001	0.000	0.113	#21	0.206	Not Required	Pass
210	0.006	0.795	0.105	0.079	0.023	0.867	#21	0.082	Not Required	Pass
211	0.002	0.073	0.122	0.050	0.013	0.152	#21	0.102	Not Required	Pass
212	0.002	0.569	0.082	0.120	0.013	0.639	#21	0.036	Not Required	Pass
213	0.004	0.250	0.295	0.063	0.016	0.514	#21	0.306	Not Required	Pass
214	0.006	0.254	0.294	0.061	0.016	0.513	#21	0.306	Not Required	Pass
215	0.004	0.297	0.153	0.048	0.012	0.452	#21	0.507	Not Required	Pass
216	0.002	0.271	0.153	0.046	0.012	0.424	#21	0.507	Not Required	Pass
301	0.126	0.422	0.022	0.016	0.002	0.430	#16	0.611	Not Required	Pass
302	0.001	0.524	0.074	0.108	0.013	0.585	#21	0.054	Not Required	Pass
303	0.006	0.753	0.046	0.076	0.009	0.802	#21	0.046	Not Required	Pass
304	0.006	0.708	0.101	0.071	0.022	0.767	#21	0.082	Not Required	Pass
305	0.006	0.467	0.108	0.075	0.028	0.495	#21	0.076	Not Required	Pass
306	0.005	0.686	0.020	0.068	0.002	0.708	#21	0.046	Not Required	Pass
307	0.005	0.426	0.074	0.068	0.019	0.442	#21	0.076	Not Required	Pass
308	0.000	0.064	0.097	0.028	0.007	0.161	#21	Not Required	Not Required	Pass
309	0.008	0.078	0.039	0.001	0.001	0.120	#21	0.206	Not Required	Pass
310	0.004	0.651	0.077	0.065	0.017	0.709	#21	0.082	Not Required	Pass
311	0.000	0.067	0.097	0.030	0.007	0.164	#21	Not Required	Not Required	Pass
312	0.002	0.457	0.069	0.098	0.012	0.515	#21	0.036	Not Required	Pass
313	0.003	0.224	0.288	0.061	0.016	0.434	#21	0.204	Not Required	Pass
314	0.005	0.215	0.285	0.057	0.016	0.413	#21	0.306	Not Required	Pass
315	0.003	0.342	0.153	0.047	0.012	0.494	#21	0.507	Not Required	Pass
316	0.001	0.324	0.153	0.044	0.012	0.477	#21	0.507	Not Required	Pass

Definitions

Φ_t	Safety factor for tensile
Φ_c	Safety factor for compression
Φ_b	Safety factor for flexure
Φ_v	Safety factor for shear
E	Modulus of elasticity
F_y	Specified minimum yield stress
F_u	Specified minimum tensile strength
A	Cross-sectional area
J	Torsional constant
I_{yp}	Moment of inertia about the Y axes
I_{zp}	Moment of inertia about the Z axes
I_w	Warping constant
S_{yp}	Plastic section modulus about the Y axis
S_{zp}	Plastic section modulus about the Z axis

KL	Effective length
C_b	Buckling modification factor (from all load combinations)
L_b	Length between braced points
LST	Limited slenderness for tension
LSC	Limited slenderness for compression
LD	Limited deflection
P_n	Nominal axial strength (tension/compression)
M_n	Nominal flexural strength (about Z/Y axis)
V_n	Nominal shear strength (along Z/Y axis)
P	Design ratio in case of axial force
M_z	Design ratio in case of bending about Z axis
M_y	Design ratio in case of bending about Y axis
V_y	Design ratio in case of shear along Y axis
V_z	Design ratio in case of shear along Z axis
(P, M_z , M_y)	Design ratio in case of axial force and bending action
KL/r	Design ratio in case of section slenderness
δ	Design ratio in case of member deflection
OK	Capacity is provided
NG	Capacity is not provided

REFERENCES	CALCULATIONS	RESULTS
------------	--------------	---------


SkyCiv Foundation Design

Pile Foundation

Design Information :

Design code : IBC 2021 (International Building Code)
Unit System : Imperial

Pile Input



Geometry

Pile shape: rectangular

$b = 48$ in - Pile width

$D = 48$ in - Pile depth

$L = 6.25$ ft - Total pile length

$h_1 = 0$ ft - Lateral load height from the top of the pile,

$h_2 = 0$ ft - Depth to resisting surface

$h_e = 0$ ft - Length of pile above the ground

Tabulation of Soil Parameters

Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000

Tabulation of Loads

Load Component	ASD	LRFD
P (kip)	10.027	16.015
V_x (kip)	-1.092	-1.824
V_z (kip)	0.117	0.188
M_x (kipft)	0.526	0.848
M_z (kipft)	20.311	35.181

Material Properties

$f'_{ck} = 2.5$ ksi - Concrete strength.

Required depth to resist lateral loads (ASD)

H - Point of application of the lateral load

$$H = h_1 + h_2 + h_e$$

$$H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$$

$$H = 0 \text{ ft}$$

Considering x-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-1.092 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.17389 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(20.311 \text{ kipft}) + ((-1.092 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 3.2342 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,x} = 5.8278 \text{ ft}$ - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.117 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.018631 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.526 \text{ kipft}) + ((0.117 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.083758 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,z} = 2.0823 \text{ ft}$ - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = MAX[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = MAX[(5.8278 \text{ ft}), (2.0823 \text{ ft})]$$

$$L_{e,req} = 5.828 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_e - h_2$$

$$L_e = (6.25 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 6.25 \text{ ft}$$

Ratio - Embedded depth

$$Ratio = \frac{L_{e,req}}{L_e}$$

$$Ratio = \frac{(5.828 \text{ ft})}{(6.25 \text{ ft})}$$

$$Ratio = 0.93248$$

Status: **PASS**
Ratio: **0.930**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_v}{A}$$

$$q = \frac{(10.027 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.62669 \text{ kip/ft}^2$$

Check bearing capacity ratio:

Ratio - Capacity

$$\text{Ratio} = \frac{q}{q_a}$$

$$\text{Ratio} = \frac{(0.62669 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$\text{Ratio} = 0.31334$$

Status: **PASS**
Ratio: **0.310**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(6.25 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1.5625$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.17389 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 3.2342 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (3.2342 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (-0.17389 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (3.2342 \text{ kipft/ft})) + (4 \times (-0.17389 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.262 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (3.2342 \text{ kipft/ft})) + (3 \times (-0.17389 \text{ kip/ft}) \times (6.25 \text{ ft}))]^2}{(6.25 \text{ ft})^2 \times [(3 \times (3.2342 \text{ kipft/ft})) + (2 \times (-0.17389 \text{ kip/ft}) \times (6.25 \text{ ft}))]}$$

$$p = 0.23878 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (3.2342 \text{ kipft/ft})) + ((-0.17389 \text{ kip/ft}) \times (6.25 \text{ ft}))]}{(6.25 \text{ ft})^2}$$

$$s = 0.82663 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(4.262 \text{ ft})}{2}$$

$$p_a = 0.31965 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{p}{p_a}$$

$$\text{Ratio} = \frac{(0.23878 \text{ kip/ft}^2)}{(0.31965 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.74701$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (6.25 \text{ ft})$$

$$p_s = 0.9375 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{s}{p_s}$$

$$\text{Ratio} = \frac{(0.82663 \text{ kip/ft}^2)}{(0.9375 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.88174$$

Status: **PASS**
Ratio: **0.750**

Status: **PASS**
Ratio: **0.880**

Considering z-direction:

$H_o = 0.018631 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.083758 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.083758 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (0.018631 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (0.083758 \text{ kipft/ft})) + (4 \times (0.018631 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.4172 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (0.083758 \text{ kipft/ft})) + (3 \times (0.018631 \text{ kip/ft}) \times (6.25 \text{ ft}))]^2}{(6.25 \text{ ft})^2 \times [(3 \times (0.083758 \text{ kipft/ft})) + (2 \times (0.018631 \text{ kip/ft}) \times (6.25 \text{ ft}))]}$$

$$p = 0.018573 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.083758 \text{ kipft/ft})) + ((0.018631 \text{ kip/ft}) \times (6.25 \text{ ft}))]}{(6.25 \text{ ft})^2}$$

$$s = 0.043616 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(4.4172 \text{ ft})}{2}$$

$$p_a = 0.33129 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{p}{p_a}$$

$$\text{Ratio} = \frac{(0.018573 \text{ kip/ft}^2)}{(0.33129 \text{ kip/ft}^2)}$$

$$Ratio = 0.056062$$

p_s - Allowable lateral soil pressure at depth L_e .

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (6.25 \text{ ft})$$

$$p_s = 0.9375 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.043616 \text{ kip/ft}^2)}{(0.9375 \text{ kip/ft}^2)}$$

$$Ratio = 0.046524$$

Status: **PASS**
Ratio: **0.060**

Status: **PASS**
Ratio: **0.050**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-1.824 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.29045 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(35.181 \text{ kipft}) + ((-1.824 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 5.6021 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(5.6021 \text{ kipft/ft})}{(-0.29045 \text{ kip/ft})}$$

$$E = 19.288 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (5.6021 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (-0.29045 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (5.6021 \text{ kipft/ft})) + (4 \times (-0.29045 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = \frac{(-0.29045 \text{ kip/ft}) \times (48 \text{ in})}{(6 \times (5.6021 \text{ kipft/ft})) + (4 \times (-0.29045 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.2592 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.29045 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (19.288 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.2592 \text{ ft})}{(6.25 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (19.288 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.2592 \text{ ft})}{(6.25 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 7.117 \text{ kip}$$

M_{max} - Max bending moment located at depth a/2,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.29045 \text{ kip/ft}) \times (48 \text{ in}) \times (6.25 \text{ ft})) \times \left[\left(\frac{(19.288 \text{ ft})}{(6.25 \text{ ft})} + \frac{(4.2592 \text{ ft})}{2 \times (6.25 \text{ ft})} \right) - \left[\left(\frac{4 \times (19.288 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.2592 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (19.288 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.2592 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 21.577 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.188 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.029936 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.848 \text{ kipft}) + ((0.188 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.13503 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.13503 \text{ kipft/ft})}{(0.029936 \text{ kip/ft})}$$

$$E = 4.5106 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.13503 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (0.029936 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (0.13503 \text{ kipft/ft})) + (4 \times (0.029936 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.4168 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((0.029936 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (4.5106 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.4168 \text{ ft})}{(6.25 \text{ ft})} \right)^2 \right] \right. \\ \left. + \left[4 \times \left(\frac{3 \times (4.5106 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.4168 \text{ ft})}{(6.25 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.23229 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o \cdot b \cdot L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) \right. \\ \left. - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((0.029936 \text{ kip/ft}) \times (48 \text{ in}) \times (6.25 \text{ ft})) \times \left[\left(\frac{(4.5106 \text{ ft})}{(6.25 \text{ ft})} + \frac{(4.4168 \text{ ft})}{2 \times (6.25 \text{ ft})} \right) \right. \\ \left. - \left[\left(\frac{4 \times (4.5106 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.4168 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (4.5106 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.4168 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 0.6588 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 2.5 \text{ ksi}$ - Concrete strength,

$f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,

$\phi = 0.65$ - Reduction factor for axial strength,

$\alpha = 0.8$ - Alpha factor for axial strength,

$A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(16.015 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (2.5 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (2.5 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -84.064 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-84.064 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

Table 22.4.2.1

22.4.2.2, 10.6.1.1

<p>25.2.3</p> <p>25.7.2.2</p> <p>25.7.2.1</p>	<p style="text-align: center;">$Ratio = 0.96556$</p> <p>$s_{rebar} = Max[1.5, (1.5 d_{bar})]$</p> <p>$s_{rebar} = Max[1.5, (1.5 \times (0.625 \text{ in}))]$</p> <p>$s_{rebar} = 1.5 \text{ in}$</p> <p>Ties:</p> <p>Since longitudinal reinforcement is \leq No. 10: Use #3(0.375 in)</p> <p>$s_{ties} = Min[(16 d_{bar}), (48 d_{ties}), Min(D, b)]$</p> <p>$s_{ties} = Min[(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), Min((48 \text{ in}), (48 \text{ in}))]$</p> <p>$s_{ties} = 10 \text{ in}$</p> <p>Summary:</p> <p style="text-align: center;">Main reinforcement: 14 - #5 (0.625 in) Ties: #3(0.375 in) - 10 in</p>	<p>Status: PASS Ratio: 0.970</p>
<p>22.4.2.2</p>	<p>Axial Compression Strength (ACI 318-19, LRFD)</p> <p>ϕP_N - Allowable axial compressive strength</p> <p style="text-align: center;">$\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_y A_{st})]$</p> <p style="text-align: center;">$\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (2.5 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$</p> <p style="text-align: center;">$\phi P_N = 2675.2 \text{ kip}$</p> <p>Ratio - Capacity</p> <p style="text-align: center;">$Ratio = \frac{P}{\phi P_N}$</p> <p style="text-align: center;">$Ratio = \frac{(16.015 \text{ kip})}{(2675.2 \text{ kip})}$</p> <p style="text-align: center;">$Ratio = 0.0059865$</p>	<p>Status: PASS Ratio: 0.010</p>
<p>22.5.2.2</p> <p>22.5.5.1.3</p> <p>22.5.5.1.1</p>	<p>Shear Strength (ACI 318-19, LRFD)</p> <p>Parameters:</p> <p>$b_w = 48 \text{ in}$ - Effective width, d - Effective depth</p> <p style="text-align: center;">$d = 0.80 D$</p> <p style="text-align: center;">$d = 0.80 \times (48 \text{ in})$</p> <p style="text-align: center;">$d = 38.4 \text{ in}$</p> <p>λ_s - size effect modification factor</p> <p style="text-align: center;">$\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = 0.64282$</p> <p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,</p> <p>$V_{c,max}$ - Max shear strength of concrete</p> <p style="text-align: center;">$V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$</p> <p style="text-align: center;">$V_{c,max} = 5 \times (0.64282) \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$</p>	

$$V_{c,max} = 296.21 \text{ kip}$$

22.5.5.1.1(a) The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $P = 16.015 \text{ kip} \rightarrow 16015 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck} + \frac{P}{6 A_g}} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + \frac{(16015 \text{ lbf})}{6 \times (2304 \text{ in}^2)}} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 120.62 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck} + (0.05 f'_{ck})} \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + (0.05 \times (2500 \text{ psi}))} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 348.89 \text{ kip}$$

V_c - Governing shear strength of concrete

$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(296.21 \text{ kip}), (120.62 \text{ kip}), (348.89 \text{ kip})]$$

$$V_c = 120.62 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{s,a}$ - Shear strength of steel (a)

$$V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$$

$$V_{s,a} = 8 \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{s,a} = 737.28 \text{ kip}$$

A_v - Ties rebar area,

$$A_v = \frac{\pi d_{ties}^2}{4}$$

$$A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$$

$$A_v = 0.11045 \text{ in}^2$$

22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)

$$V_{s,b} = \frac{2 A_v f_{yw} d}{s_{ties}}$$

$$V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$$

$$V_{s,b} = 50.894 \text{ kip}$$

V_s - Governing shear strength of steel

$$V_s = \text{MIN}[V_{s,a}, V_{s,b}]$$

$$V_s = \text{MIN}[(737.28 \text{ kip}), (50.894 \text{ kip})]$$

$$V_s = 50.894 \text{ kip}$$

22.5.1.1 ϕV_n - Allowable shear strength

$$\phi V_n = \phi (V_c + V_s)$$

$$\phi V_n = (0.65) \times ((120.62 \text{ kip}) + (50.894 \text{ kip}))$$

$$\phi V_n = 111.48 \text{ kip}$$

Considering x-direction:

$V_{max} = 7.117 \text{ kip}$ - Maximum shear force in the x-direction,

Ratio - Capacity

$$\text{Ratio} = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(7.117 \text{ kip})}{(111.48 \text{ kip})}$$

$$Ratio = 0.063838$$

Status: **PASS**
Ratio: **0.060**

Considering z-direction:

$V_{max} = 0.23229 \text{ kip}$ - Maximum shear force in the z-direction,

Ratio - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(0.23229 \text{ kip})}{(111.48 \text{ kip})}$$

$$Ratio = 0.0020836$$

Status: **PASS**
Ratio: **0.000**

Flexural Strength (ACI 318-19, LRFD)

S_m - Section modulus

$$S_m = \frac{b D^2}{6}$$

$$S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$$

$$S_m = 18432 \text{ in}^3$$

$\lambda = 1$ - Concrete modification factor (Normal concrete),

Allowable flexural strength:

M_n shall be the lesser of:

$\phi M_{n,1}$

$$\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$$

$$\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{(2.5 \text{ ksi})} \times 18432.001 \text{ in}^3$$

$$\phi M_{n,1} = 249.600 \text{ kipft}$$

14.5.2.1b

$\phi M_{n,2}$

$$\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$$

$$\phi M_{n,2} = (0.65) \times 0.85 \times (2.5 \text{ ksi}) \times (18432 \text{ in}^3)$$

$$\phi M_{n,2} = 2121.6 \text{ kipft}$$

Therefore,

ϕM_n - Allowable flexural strength,

$$\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$$

$$\phi M_n = \text{MIN}[(249.6 \text{ kipft}), (2121.6 \text{ kipft})]$$

$$\phi M_n = 249.6 \text{ kipft}$$

Considering x-direction:

$M_{max} = 21.577 \text{ kipft}$ - Maximum moment in the x-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(21.577 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.086445$$

Status: **PASS**
Ratio: **0.090**

Considering z-direction:

$M_{max} = 0.6588 \text{ kipft}$ - Maximum moment in the z-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(0.6588 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.0026394$$

Status: **PASS**
Ratio: **0.000**

REFERENCES	CALCULATIONS	RESULTS
------------	--------------	---------


SkyCiv Foundation Design

Pile Foundation

Design Information :

Design code : IBC 2021 (International Building Code)
Unit System : Imperial

Pile Input



Geometry

Pile shape: rectangular

$b = 48$ in - Pile width

$D = 48$ in - Pile depth

$L = 6.25$ ft - Total pile length

$h_1 = 0$ ft - Lateral load height from the top of the pile,

$h_2 = 0$ ft - Depth to resisting surface

$h_e = 0$ ft - Length of pile above the ground

Tabulation of Soil Parameters

Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000

Tabulation of Loads

Load Component	ASD	LRFD
P (kip)	11.537	18.474
V_x (kip)	-1.225	-2.045
V_z (kip)	-0.010	-0.016
M_x (kipft)	-0.043	-0.071
M_z (kipft)	22.076	38.101

Material Properties

$f'_{ck} = 2.5$ ksi - Concrete strength.

Required depth to resist lateral loads (ASD)

H - Point of application of the lateral load

$$H = h_1 + h_2 + h_e$$

$$H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$$

$$H = 0 \text{ ft}$$

Considering x-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-1.225 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.19506 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(22.076 \text{ kipft}) + ((-1.225 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 3.5153 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,x} = 5.958 \text{ ft}$ - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.01 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.0015924 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.043 \text{ kipft}) + ((-0.01 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.0068471 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,z} = 0.7795 \text{ ft}$ - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = \text{MAX}[(5.958 \text{ ft}), (0.7795 \text{ ft})]$$

$$L_{e,req} = 5.958 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_e - h_2$$

$$L_e = (6.25 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 6.25 \text{ ft}$$

Ratio - Embedded depth

$$\text{Ratio} = \frac{L_{e,req}}{L_e}$$

$$\text{Ratio} = \frac{(5.958 \text{ ft})}{(6.25 \text{ ft})}$$

$$\text{Ratio} = 0.95328$$

Status: **PASS**
Ratio: **0.950**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_v}{A}$$

$$q = \frac{(11.537 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.72106 \text{ kip/ft}^2$$

Check bearing capacity ratio:

Ratio - Capacity

$$\text{Ratio} = \frac{q}{q_a}$$

$$\text{Ratio} = \frac{(0.72106 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$\text{Ratio} = 0.36053$$

Status: **PASS**
Ratio: **0.360**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(6.25 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1.5625$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.19506 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 3.5153 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (3.5153 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (-0.19506 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (3.5153 \text{ kipft/ft})) + (4 \times (-0.19506 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.2645 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (3.5153 \text{ kipft/ft})) + (3 \times (-0.19506 \text{ kip/ft}) \times (6.25 \text{ ft}))]^2}{(6.25 \text{ ft})^2 \times [(3 \times (3.5153 \text{ kipft/ft})) + (2 \times (-0.19506 \text{ kip/ft}) \times (6.25 \text{ ft}))]}$$

$$p = 0.25632 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (3.5153 \text{ kipft/ft})) + ((-0.19506 \text{ kip/ft}) \times (6.25 \text{ ft}))]}{(6.25 \text{ ft})^2}$$

$$s = 0.89263 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(4.2645 \text{ ft})}{2}$$

$$p_a = 0.31984 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.25632 \text{ kip/ft}^2)}{(0.31984 \text{ kip/ft}^2)}$$

$$Ratio = 0.80142$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (6.25 \text{ ft})$$

$$p_s = 0.9375 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.89263 \text{ kip/ft}^2)}{(0.9375 \text{ kip/ft}^2)}$$

$$Ratio = 0.95214$$

Status: **PASS**
Ratio: **0.800**

Status: **PASS**
Ratio: **0.950**

Considering z-direction:

$H_o = -0.0015924 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.0068471 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.0068471 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (-0.0015924 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (0.0068471 \text{ kipft/ft})) + (4 \times (-0.0015924 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.423 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 [(4 \times (0.0068471 \text{ kipft/ft})) + (3 \times (-0.0015924 \text{ kip/ft}) \times (6.25 \text{ ft}))]^2}{(6.25 \text{ ft})^2 [(3 \times (0.0068471 \text{ kipft/ft})) + (2 \times (-0.0015924 \text{ kip/ft}) \times (6.25 \text{ ft}))]}$$

$$p = 0.00018363 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 [(2 \times (0.0068471 \text{ kipft/ft})) + ((-0.0015924 \text{ kip/ft}) \times (6.25 \text{ ft}))]}{(6.25 \text{ ft})^2}$$

$$s = 0.00057478 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(4.423 \text{ ft})}{2}$$

$$p_a = 0.33172 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.00018363 \text{ kip/ft}^2)}{(0.33172 \text{ kip/ft}^2)}$$

$$Ratio = 0.00055357$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (6.25 \text{ ft})$$

$$p_s = 0.9375 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.00057478 \text{ kip/ft}^2)}{(0.9375 \text{ kip/ft}^2)}$$

$$Ratio = 0.0006131$$

Status: **PASS**
Ratio: **0.000**

Status: **PASS**
Ratio: **0.000**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-2.045 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.32564 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(38.101 \text{ kipft}) + ((-2.045 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 6.067 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(6.067 \text{ kipft/ft})}{(-0.32564 \text{ kip/ft})}$$

$$E = 18.631 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (6.067 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (-0.32564 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times 6.067) + (4 \times (-0.32564) \times 6.25)}$$

$$a = \frac{(-0.32564 \text{ kip/ft}) \times (48 \text{ in})}{(6 \times (6.067 \text{ kip/ft})) + (4 \times (-0.32564 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.2619 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.32564 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (18.631 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.2619 \text{ ft})}{(6.25 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (18.631 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.2619 \text{ ft})}{(6.25 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 7.7364 \text{ kip}$$

M_{max} - Max bending moment located at depth a/2,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.32564 \text{ kip/ft}) \times (48 \text{ in}) \times (6.25 \text{ ft})) \times \left[\left(\frac{(18.631 \text{ ft})}{(6.25 \text{ ft})} + \frac{(4.2619 \text{ ft})}{2 \times (6.25 \text{ ft})} \right) - \left[\left(\frac{4 \times (18.631 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.2619 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (18.631 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.2619 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 23.432 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.016 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.0025478 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.071 \text{ kipft}) + ((-0.016 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.011306 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.011306 \text{ kipft/ft})}{(-0.0025478 \text{ kip/ft})}$$

$$E = 4.4375 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.011306 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (-0.0025478 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (0.011306 \text{ kipft/ft})) + (4 \times (-0.0025478 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.4189 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.0025478 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (4.4375 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.4189 \text{ ft})}{(6.25 \text{ ft})} \right)^2 \right] \right. \\ \left. + \left[4 \times \left(\frac{3 \times (4.4375 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.4189 \text{ ft})}{(6.25 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.01956 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o \ b \ L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) \right. \\ \left. - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.0025478 \text{ kip/ft}) \times (48 \text{ in}) \times (6.25 \text{ ft})) \times \left[\left(\frac{(4.4375 \text{ ft})}{(6.25 \text{ ft})} + \frac{(4.4189 \text{ ft})}{2 \times (6.25 \text{ ft})} \right) \right. \\ \left. - \left[\left(\frac{4 \times (4.4375 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.4189 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (4.4375 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.4189 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 0.055415 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 2.5 \text{ ksi}$ - Concrete strength,

$f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,

$\phi = 0.65$ - Reduction factor for axial strength,

$\alpha = 0.8$ - Alpha factor for axial strength,

$A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(18.474 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (2.5 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (2.5 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -83.982 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-83.982 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

Table 22.4.2.1

22.4.2.2, 10.6.1.1

<p>25.2.3</p> <p>25.7.2.2</p> <p>25.7.2.1</p>	<p style="text-align: center;">$Ratio = 0.96556$</p> <p>$s_{rebar} = Max[1.5, (1.5 d_{bar})]$</p> <p>$s_{rebar} = Max[1.5, (1.5 \times (0.625 \text{ in}))]$</p> <p>$s_{rebar} = 1.5 \text{ in}$</p> <p>Ties:</p> <p>Since longitudinal reinforcement is \leq No. 10: Use #3(0.375 in)</p> <p>$s_{ties} = Min[(16 d_{bar}), (48 d_{ties}), Min(D, b)]$</p> <p>$s_{ties} = Min[(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), Min((48 \text{ in}), (48 \text{ in}))]$</p> <p>$s_{ties} = 10 \text{ in}$</p> <p>Summary:</p> <p style="text-align: center;">Main reinforcement: 14 - #5 (0.625 in) Ties: #3(0.375 in) - 10 in</p>	<p>Status: PASS Ratio: 0.970</p>
<p>22.4.2.2</p>	<p>Axial Compression Strength (ACI 318-19, LRFD)</p> <p>ϕP_N - Allowable axial compressive strength</p> <p style="text-align: center;">$\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_y A_{st})]$</p> <p style="text-align: center;">$\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (2.5 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$</p> <p style="text-align: center;">$\phi P_N = 2675.2 \text{ kip}$</p> <p>Ratio - Capacity</p> <p style="text-align: center;">$Ratio = \frac{P}{\phi P_N}$</p> <p style="text-align: center;">$Ratio = \frac{(18.474 \text{ kip})}{(2675.2 \text{ kip})}$</p> <p style="text-align: center;">$Ratio = 0.0069057$</p>	<p>Status: PASS Ratio: 0.010</p>
<p>22.5.2.2</p> <p>22.5.5.1.3</p> <p>22.5.5.1.1</p>	<p>Shear Strength (ACI 318-19, LRFD)</p> <p>Parameters:</p> <p>$b_w = 48 \text{ in}$ - Effective width, d - Effective depth</p> <p style="text-align: center;">$d = 0.80 D$</p> <p style="text-align: center;">$d = 0.80 \times (48 \text{ in})$</p> <p style="text-align: center;">$d = 38.4 \text{ in}$</p> <p>λ_s - size effect modification factor</p> <p style="text-align: center;">$\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = 0.64282$</p> <p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,</p> <p>$V_{c,max}$ - Max shear strength of concrete</p> <p style="text-align: center;">$V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$</p> <p style="text-align: center;">$V_{c,max} = 5 \times (0.64282) \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$</p>	

$$V_{c,max} = 296.21 \text{ kip}$$

22.5.5.1.1(a) The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $P = 18.474 \text{ kip} \rightarrow 18474 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck} + \frac{P}{6 A_g}} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + \frac{(18474 \text{ lbf})}{6 \times (2304 \text{ in}^2)}} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 120.95 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck} + (0.05 f'_{ck})} \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + (0.05 \times (2500 \text{ psi}))} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 348.89 \text{ kip}$$

V_c - Governing shear strength of concrete

$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(296.21 \text{ kip}), (120.95 \text{ kip}), (348.89 \text{ kip})]$$

$$V_c = 120.95 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{s,a}$ - Shear strength of steel (a)

$$V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$$

$$V_{s,a} = 8 \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{s,a} = 737.28 \text{ kip}$$

A_v - Ties rebar area,

$$A_v = \frac{\pi d_{ties}^2}{4}$$

$$A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$$

$$A_v = 0.11045 \text{ in}^2$$

22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)

$$V_{s,b} = \frac{2 A_v f_{yw} d}{s_{ties}}$$

$$V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$$

$$V_{s,b} = 50.894 \text{ kip}$$

V_s - Governing shear strength of steel

$$V_s = \text{MIN}[V_{s,a}, V_{s,b}]$$

$$V_s = \text{MIN}[(737.28 \text{ kip}), (50.894 \text{ kip})]$$

$$V_s = 50.894 \text{ kip}$$

22.5.1.1 ϕV_n - Allowable shear strength

$$\phi V_n = \phi (V_c + V_s)$$

$$\phi V_n = (0.65) \times ((120.95 \text{ kip}) + (50.894 \text{ kip}))$$

$$\phi V_n = 111.7 \text{ kip}$$

Considering x-direction:

$V_{max} = 7.7364 \text{ kip}$ - Maximum shear force in the x-direction,

Ratio - Capacity

$$\text{Ratio} = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(7.7364 \text{ kip})}{(111.7 \text{ kip})}$$

$$Ratio = 0.069262$$

Status: **PASS**
Ratio: **0.070**

Considering z-direction:

$V_{max} = 0.01956 \text{ kip}$ - Maximum shear force in the z-direction,

Ratio - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(0.01956 \text{ kip})}{(111.7 \text{ kip})}$$

$$Ratio = 0.00017511$$

Status: **PASS**
Ratio: **0.000**

Flexural Strength (ACI 318-19, LRFD)

S_m - Section modulus

$$S_m = \frac{b D^2}{6}$$

$$S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$$

$$S_m = 18432 \text{ in}^3$$

$\lambda = 1$ - Concrete modification factor (Normal concrete),

Allowable flexural strength:

M_n shall be the lesser of:

$\phi M_{n,1}$

$$\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$$

$$\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{(2.5 \text{ ksi})} \times 18432.001 \text{ in}^3$$

$$\phi M_{n,1} = 249.600 \text{ kipft}$$

14.5.2.1b

$\phi M_{n,2}$

$$\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$$

$$\phi M_{n,2} = (0.65) \times 0.85 \times (2.5 \text{ ksi}) \times (18432 \text{ in}^3)$$

$$\phi M_{n,2} = 2121.6 \text{ kipft}$$

Therefore,

ϕM_n - Allowable flexural strength,

$$\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$$

$$\phi M_n = \text{MIN}[(249.6 \text{ kipft}), (2121.6 \text{ kipft})]$$

$$\phi M_n = 249.6 \text{ kipft}$$

Considering x-direction:

$M_{max} = 23.432 \text{ kipft}$ - Maximum moment in the x-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(23.432 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.093879$$

Status: **PASS**
Ratio: **0.090**

Considering z-direction:

$M_{max} = 0.055415 \text{ kipft}$ - Maximum moment in the z-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$\text{Ratio} = \frac{(0.055415 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$\text{Ratio} = 0.00022201$$

Status: **PASS**
Ratio: **0.000**

REFERENCES	CALCULATIONS	RESULTS
------------	--------------	---------


SkyCiv Foundation Design

Pile Foundation

Design Information :

Design code : IBC 2021 (International Building Code)
Unit System : Imperial

Pile Input



Geometry

Pile shape: rectangular

$b = 48$ in - Pile width

$D = 48$ in - Pile depth

$L = 6.25$ ft - Total pile length

$h_1 = 0$ ft - Lateral load height from the top of the pile,

$h_2 = 0$ ft - Depth to resisting surface

$h_e = 0$ ft - Length of pile above the ground

Tabulation of Soil Parameters

Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000

Tabulation of Loads

Load Component	ASD	LRFD
P (kip)	11.537	18.474
V_x (kip)	-1.225	-2.045
V_z (kip)	0.010	0.016
M_x (kipft)	0.043	0.072
M_z (kipft)	22.076	38.101

Material Properties

$f'_{ck} = 2.5$ ksi - Concrete strength.

Required depth to resist lateral loads (ASD)

H - Point of application of the lateral load

$$H = h_1 + h_2 + h_e$$

$$H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$$

$$H = 0 \text{ ft}$$

Considering x-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-1.225 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.19506 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(22.076 \text{ kipft}) + ((-1.225 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 3.5153 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_e^3 - \left(14.14 \times \frac{H_o \times L_x}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,x} = 5.958 \text{ ft}$ - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.01 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.0015924 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.043 \text{ kipft}) + ((0.01 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.0068471 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_e^3 - \left(14.14 \times \frac{H_o \times L_z}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,z} = 0.85716 \text{ ft}$ - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = \text{MAX}[(5.958 \text{ ft}), (0.85716 \text{ ft})]$$

$$L_{e,req} = 5.958 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_e - h_2$$

$$L_e = (6.25 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 6.25 \text{ ft}$$

Ratio - Embedded depth

$$\text{Ratio} = \frac{L_{e,req}}{L_e}$$

$$\text{Ratio} = \frac{(5.958 \text{ ft})}{(6.25 \text{ ft})}$$

$$\text{Ratio} = 0.95328$$

Status: **PASS**
Ratio: **0.950**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_v}{A}$$

$$q = \frac{(11.537 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.72106 \text{ kip/ft}^2$$

Check bearing capacity ratio:

Ratio - Capacity

$$\text{Ratio} = \frac{q}{q_a}$$

$$\text{Ratio} = \frac{(0.72106 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$\text{Ratio} = 0.36053$$

Status: **PASS**
Ratio: **0.360**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(6.25 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1.5625$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.19506 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 3.5153 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (3.5153 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (-0.19506 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (3.5153 \text{ kipft/ft})) + (4 \times (-0.19506 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.2645 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (3.5153 \text{ kipft/ft})) + (3 \times (-0.19506 \text{ kip/ft}) \times (6.25 \text{ ft}))]^2}{(6.25 \text{ ft})^2 \times [(3 \times (3.5153 \text{ kipft/ft})) + (2 \times (-0.19506 \text{ kip/ft}) \times (6.25 \text{ ft}))]}$$

$$p = 0.25632 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (3.5153 \text{ kipft/ft})) + ((-0.19506 \text{ kip/ft}) \times (6.25 \text{ ft}))]}{(6.25 \text{ ft})^2}$$

$$s = 0.89263 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(4.2645 \text{ ft})}{2}$$

$$p_a = 0.31984 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.25632 \text{ kip/ft}^2)}{(0.31984 \text{ kip/ft}^2)}$$

$$Ratio = 0.80142$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (6.25 \text{ ft})$$

$$p_s = 0.9375 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.89263 \text{ kip/ft}^2)}{(0.9375 \text{ kip/ft}^2)}$$

$$Ratio = 0.95214$$

Status: **PASS**
Ratio: **0.800**

Status: **PASS**
Ratio: **0.950**

Considering z-direction:

$H_o = 0.0015924 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.0068471 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.0068471 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (0.0015924 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (0.0068471 \text{ kipft/ft})) + (4 \times (0.0015924 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.423 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (0.0068471 \text{ kipft/ft})) + (3 \times (0.0015924 \text{ kip/ft}) \times (6.25 \text{ ft}))]^2}{(6.25 \text{ ft})^2 \times [(3 \times (0.0068471 \text{ kipft/ft})) + (2 \times (0.0015924 \text{ kip/ft}) \times (6.25 \text{ ft}))]}$$

$$p = 0.0015556 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.0068471 \text{ kipft/ft})) + ((0.0015924 \text{ kip/ft}) \times (6.25 \text{ ft}))]}{(6.25 \text{ ft})^2}$$

$$s = 0.0036321 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(4.423 \text{ ft})}{2}$$

$$p_a = 0.33172 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.0015556 \text{ kip/ft}^2)}{(0.33172 \text{ kip/ft}^2)}$$

$$Ratio = 0.0046895$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (6.25 \text{ ft})$$

$$p_s = 0.9375 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.0036321 \text{ kip/ft}^2)}{(0.9375 \text{ kip/ft}^2)}$$

$$Ratio = 0.0038742$$

Status: **PASS**
Ratio: **0.000**

Status: **PASS**
Ratio: **0.000**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-2.045 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.32564 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(38.101 \text{ kipft}) + ((-2.045 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 6.067 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(6.067 \text{ kipft/ft})}{(-0.32564 \text{ kip/ft})}$$

$$E = 18.631 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (6.067 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (-0.32564 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times 6.067) + (4 \times (-0.32564) \times 6.25)}$$

$$a = \frac{(-0.32564 \text{ kip/ft}) \times (48 \text{ in})}{(6 \times (0.067 \text{ kip/ft})) + (4 \times (-0.32564 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.2619 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.32564 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (18.631 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.2619 \text{ ft})}{(6.25 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (18.631 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.2619 \text{ ft})}{(6.25 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 7.7364 \text{ kip}$$

M_{max} - Max bending moment located at depth a/2,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.32564 \text{ kip/ft}) \times (48 \text{ in}) \times (6.25 \text{ ft})) \times \left[\left(\frac{(18.631 \text{ ft})}{(6.25 \text{ ft})} + \frac{(4.2619 \text{ ft})}{2 \times (6.25 \text{ ft})} \right) - \left[\left(\frac{4 \times (18.631 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.2619 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (18.631 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.2619 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 23.432 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.016 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.0025478 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.072 \text{ kipft}) + ((0.016 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.011465 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.011465 \text{ kipft/ft})}{(0.0025478 \text{ kip/ft})}$$

$$E = 4.5 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.011465 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (0.0025478 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (0.011465 \text{ kipft/ft})) + (4 \times (0.0025478 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.4171 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((0.0025478 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (4.5 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.4171 \text{ ft})}{(6.25 \text{ ft})} \right)^2 \right] \right. \\ \left. + \left[4 \times \left(\frac{3 \times (4.5 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.4171 \text{ ft})}{(6.25 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.019739 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o \ b \ L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) \right. \\ \left. - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((0.0025478 \text{ kip/ft}) \times (48 \text{ in}) \times (6.25 \text{ ft})) \times \left[\left(\frac{(4.5 \text{ ft})}{(6.25 \text{ ft})} + \frac{(4.4171 \text{ ft})}{2 \times (6.25 \text{ ft})} \right) \right. \\ \left. - \left[\left(\frac{4 \times (4.5 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.4171 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (4.5 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.4171 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 0.055973 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 2.5 \text{ ksi}$ - Concrete strength,

$f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,

$\phi = 0.65$ - Reduction factor for axial strength,

$\alpha = 0.8$ - Alpha factor for axial strength,

$A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(18.474 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (2.5 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (2.5 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -83.982 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-83.982 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

Table 22.4.2.1

22.4.2.2, 10.6.1.1

<p>25.2.3</p> <p>25.7.2.2</p> <p>25.7.2.1</p>	<p style="text-align: center;">$Ratio = 0.96556$</p> <p>$s_{rebar} = Minimum\ spacing\ of\ reinforcement,$</p> $s_{rebar} = Max[1.5, (1.5 d_{bar})]$ $s_{rebar} = Max[1.5, (1.5 \times (0.625\ in))]$ $s_{rebar} = 1.5\ in$ <p>Ties:</p> <p>Since longitudinal reinforcement is \leq No. 10: Use #3(0.375 in)</p> <p>s_{ties} - Maximum spacing of ties,</p> $s_{ties} = Min[(16 d_{bar}), (48 d_{ties}), Min(D, b)]$ $s_{ties} = Min[(16 \times (0.625\ in)), (48 \times (0.375\ in)), Min((48\ in), (48\ in))]$ $s_{ties} = 10\ in$ <p>Summary:</p> <p style="text-align: center;">Main reinforcement: 14 - #5 (0.625 in) Ties: #3(0.375 in) - 10 in</p>	<p>Status: PASS Ratio: 0.970</p>
<p>22.4.2.2</p>	<p>Axial Compression Strength (ACI 318-19, LRFD)</p> <p>ϕP_N - Allowable axial compressive strength</p> $\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_y A_{st})]$ $\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (2.5\ ksi) \times [(2304\ in^2) - (4.2951\ in^2)]) + ((60\ ksi) \times (4.2951\ in^2))]$ $\phi P_N = 2675.2\ kip$ <p>Ratio - Capacity</p> $Ratio = \frac{P}{\phi P_N}$ $Ratio = \frac{(18.474\ kip)}{(2675.2\ kip)}$ $Ratio = 0.0069057$	<p>Status: PASS Ratio: 0.010</p>
<p>22.5.2.2</p> <p>22.5.5.1.3</p> <p>22.5.5.1.1</p>	<p>Shear Strength (ACI 318-19, LRFD)</p> <p>Parameters:</p> <p>$b_w = 48\ in$ - Effective width, d - Effective depth</p> $d = 0.80 D$ $d = 0.80 \times (48\ in)$ $d = 38.4\ in$ <p>λ_s - size effect modification factor</p> $\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$ $\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{(38.4\ in)}{10}}}, 1 \right]$ $\lambda_s = 0.64282$ <p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5\ ksi \rightarrow 2500\ psi$,</p> <p>$V_{c,max}$ - Max shear strength of concrete</p> $V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$ $V_{c,max} = 5 \times (0.64282) \times \sqrt{(2500\ psi)} \times (48\ in) \times (38.4\ in)$	

$$V_{c,max} = 296.21 \text{ kip}$$

22.5.5.1.1(a) The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $P = 18.474 \text{ kip} \rightarrow 18474 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck} + \frac{P}{6 A_g}} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + \frac{(18474 \text{ lbf})}{6 \times (2304 \text{ in}^2)}} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 120.95 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck} + (0.05 f'_{ck})} \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + (0.05 \times (2500 \text{ psi}))} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 348.89 \text{ kip}$$

V_c - Governing shear strength of concrete

$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(296.21 \text{ kip}), (120.95 \text{ kip}), (348.89 \text{ kip})]$$

$$V_c = 120.95 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{s,a}$ - Shear strength of steel (a)

$$V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$$

$$V_{s,a} = 8 \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{s,a} = 737.28 \text{ kip}$$

A_v - Ties rebar area,

$$A_v = \frac{\pi d_{ties}^2}{4}$$

$$A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$$

$$A_v = 0.11045 \text{ in}^2$$

22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)

$$V_{s,b} = \frac{2 A_v f_{yw} d}{s_{ties}}$$

$$V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$$

$$V_{s,b} = 50.894 \text{ kip}$$

V_s - Governing shear strength of steel

$$V_s = \text{MIN}[V_{s,a}, V_{s,b}]$$

$$V_s = \text{MIN}[(737.28 \text{ kip}), (50.894 \text{ kip})]$$

$$V_s = 50.894 \text{ kip}$$

22.5.1.1 ϕV_n - Allowable shear strength

$$\phi V_n = \phi (V_c + V_s)$$

$$\phi V_n = (0.65) \times ((120.95 \text{ kip}) + (50.894 \text{ kip}))$$

$$\phi V_n = 111.7 \text{ kip}$$

Considering x-direction:

$V_{max} = 7.7364 \text{ kip}$ - Maximum shear force in the x-direction,

Ratio - Capacity

$$\text{Ratio} = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(7.7364 \text{ kip})}{(111.7 \text{ kip})}$$

$$Ratio = 0.069262$$

Considering z-direction:

$V_{max} = 0.019739 \text{ kip}$ - Maximum shear force in the z-direction,

Ratio - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(0.019739 \text{ kip})}{(111.7 \text{ kip})}$$

$$Ratio = 0.00017672$$

Status: **PASS**
Ratio: **0.070**

Status: **PASS**
Ratio: **0.000**

Flexural Strength (ACI 318-19, LRFD)

S_m - Section modulus

$$S_m = \frac{b D^2}{6}$$

$$S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$$

$$S_m = 18432 \text{ in}^3$$

$\lambda = 1$ - Concrete modification factor (Normal concrete),

Allowable flexural strength:

M_n shall be the lesser of:

$\phi M_{n,1}$

$$\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$$

$$\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{(2.5 \text{ ksi})} \times 18432.001 \text{ in}^3$$

$$\phi M_{n,1} = 249.600 \text{ kipft}$$

14.5.2.1b

$\phi M_{n,2}$

$$\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$$

$$\phi M_{n,2} = (0.65) \times 0.85 \times (2.5 \text{ ksi}) \times (18432 \text{ in}^3)$$

$$\phi M_{n,2} = 2121.6 \text{ kipft}$$

Therefore,

ϕM_n - Allowable flexural strength,

$$\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$$

$$\phi M_n = \text{MIN}[(249.6 \text{ kipft}), (2121.6 \text{ kipft})]$$

$$\phi M_n = 249.6 \text{ kipft}$$

Considering x-direction:

$M_{max} = 23.432 \text{ kipft}$ - Maximum moment in the x-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(23.432 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.093879$$

Status: **PASS**
Ratio: **0.090**

Considering z-direction:

$M_{max} = 0.055973 \text{ kipft}$ - Maximum moment in the z-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(0.055973 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.00022425$$

Status: **PASS**
Ratio: **0.000**

REFERENCES	CALCULATIONS	RESULTS
------------	--------------	---------


SkyCiv Foundation Design

Pile Foundation

Design Information :

Design code : IBC 2021 (International Building Code)
Unit System : Imperial

Pile Input



Geometry

Pile shape: rectangular

$b = 48$ in - Pile width

$D = 48$ in - Pile depth

$L = 6.25$ ft - Total pile length

$h_1 = 0$ ft - Lateral load height from the top of the pile,

$h_2 = 0$ ft - Depth to resisting surface

$h_e = 0$ ft - Length of pile above the ground

Tabulation of Soil Parameters

Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000

Tabulation of Loads

Load Component	ASD	LRFD
P (kip)	10.027	16.015
V_x (kip)	-1.092	-1.824
V_z (kip)	-0.117	-0.188
M_x (kipft)	-0.526	-0.848
M_z (kipft)	20.311	35.182

Material Properties

$f'_{ck} = 2.5$ ksi - Concrete strength.

Required depth to resist lateral loads (ASD)

H - Point of application of the lateral load

$$H = h_1 + h_2 + h_e$$

$$H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$$

$$H = 0 \text{ ft}$$

Considering x-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-1.092 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.17389 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(20.311 \text{ kipft}) + ((-1.092 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 3.2342 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,x} = 5.8278 \text{ ft}$ - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.117 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.018631 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.526 \text{ kipft}) + ((-0.117 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.083758 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,z} = 1.6884 \text{ ft}$ - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = \text{MAX}[(5.8278 \text{ ft}), (1.6884 \text{ ft})]$$

$$L_{e,req} = 5.828 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_e - h_2$$

$$L_e = (6.25 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 6.25 \text{ ft}$$

Ratio - Embedded depth

$$\text{Ratio} = \frac{L_{e,req}}{L_e}$$

$$\text{Ratio} = \frac{(5.828 \text{ ft})}{(6.25 \text{ ft})}$$

$$\text{Ratio} = 0.93248$$

Status: **PASS**
Ratio: **0.930**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_v}{A}$$

$$q = \frac{(10.027 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.62669 \text{ kip/ft}^2$$

Check bearing capacity ratio:

Ratio - Capacity

$$\text{Ratio} = \frac{q}{q_a}$$

$$\text{Ratio} = \frac{(0.62669 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$\text{Ratio} = 0.31334$$

Status: **PASS**
Ratio: **0.310**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(6.25 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1.5625$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.17389 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 3.2342 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (3.2342 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (-0.17389 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (3.2342 \text{ kipft/ft})) + (4 \times (-0.17389 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.262 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (3.2342 \text{ kipft/ft})) + (3 \times (-0.17389 \text{ kip/ft}) \times (6.25 \text{ ft}))]^2}{(6.25 \text{ ft})^2 \times [(3 \times (3.2342 \text{ kipft/ft})) + (2 \times (-0.17389 \text{ kip/ft}) \times (6.25 \text{ ft}))]}$$

$$p = 0.23878 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (3.2342 \text{ kipft/ft})) + ((-0.17389 \text{ kip/ft}) \times (6.25 \text{ ft}))]}{(6.25 \text{ ft})^2}$$

$$s = 0.82663 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(4.262 \text{ ft})}{2}$$

$$p_a = 0.31965 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{p}{p_a}$$

$$\text{Ratio} = \frac{(0.23878 \text{ kip/ft}^2)}{(0.31965 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.74701$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (6.25 \text{ ft})$$

$$p_s = 0.9375 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{s}{p_s}$$

$$\text{Ratio} = \frac{(0.82663 \text{ kip/ft}^2)}{(0.9375 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.88174$$

Status: **PASS**
Ratio: **0.750**

Status: **PASS**
Ratio: **0.880**

Considering z-direction:

$H_o = -0.018631 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.083758 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.083758 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (-0.018631 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (0.083758 \text{ kipft/ft})) + (4 \times (-0.018631 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.4172 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (0.083758 \text{ kipft/ft})) + (3 \times (-0.018631 \text{ kip/ft}) \times (6.25 \text{ ft}))]^2}{(6.25 \text{ ft})^2 \times [(3 \times (0.083758 \text{ kipft/ft})) + (2 \times (-0.018631 \text{ kip/ft}) \times (6.25 \text{ ft}))]}$$

$$p = 0.00021322 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.083758 \text{ kipft/ft})) + ((-0.018631 \text{ kip/ft}) \times (6.25 \text{ ft}))]}{(6.25 \text{ ft})^2}$$

$$s = 0.0078451 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(4.4172 \text{ ft})}{2}$$

$$p_a = 0.33129 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{p}{p_a}$$

$$\text{Ratio} = \frac{(0.00021322 \text{ kip/ft}^2)}{(0.33129 \text{ kip/ft}^2)}$$

$$Ratio = 0.00064361$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (6.25 \text{ ft})$$

$$p_s = 0.9375 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.0078451 \text{ kip/ft}^2)}{(0.9375 \text{ kip/ft}^2)}$$

$$Ratio = 0.0083681$$

Status: **PASS**
Ratio: **0.000**

Status: **PASS**
Ratio: **0.010**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-1.824 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.29045 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(35.182 \text{ kipft}) + ((-1.824 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 5.6022 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(5.6022 \text{ kipft/ft})}{(-0.29045 \text{ kip/ft})}$$

$$E = 19.288 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (5.6022 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (-0.29045 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (5.6022 \text{ kipft/ft})) + (4 \times (-0.29045 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = \frac{(-0.29045 \text{ kip/ft}) \times (48 \text{ in})}{(6 \times (5.6022 \text{ kipft/ft})) + (4 \times (-0.29045 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.2592 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.29045 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (19.288 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.2592 \text{ ft})}{(6.25 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (19.288 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.2592 \text{ ft})}{(6.25 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 7.1171 \text{ kip}$$

M_{max} - Max bending moment located at depth a/2,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.29045 \text{ kip/ft}) \times (48 \text{ in}) \times (6.25 \text{ ft})) \times \left[\left(\frac{(19.288 \text{ ft})}{(6.25 \text{ ft})} + \frac{(4.2592 \text{ ft})}{2 \times (6.25 \text{ ft})} \right) - \left[\left(\frac{4 \times (19.288 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.2592 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (19.288 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.2592 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 21.577 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.188 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.029936 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.848 \text{ kipft}) + ((-0.188 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.13503 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.13503 \text{ kipft/ft})}{(-0.029936 \text{ kip/ft})}$$

$$E = 4.5106 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.13503 \text{ kipft/ft}) \times (6.25 \text{ ft})) + (3 \times (-0.029936 \text{ kip/ft}) \times (6.25 \text{ ft})^2)}{(6 \times (0.13503 \text{ kipft/ft})) + (4 \times (-0.029936 \text{ kip/ft}) \times (6.25 \text{ ft}))}$$

$$a = 4.4168 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.029936 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (4.5106 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.4168 \text{ ft})}{(6.25 \text{ ft})} \right)^2 \right] \right. \\ \left. + \left[4 \times \left(\frac{3 \times (4.5106 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.4168 \text{ ft})}{(6.25 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.23229 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o \ b \ L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) \right. \\ \left. - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.029936 \text{ kip/ft}) \times (48 \text{ in}) \times (6.25 \text{ ft})) \times \left[\left(\frac{(4.5106 \text{ ft})}{(6.25 \text{ ft})} + \frac{(4.4168 \text{ ft})}{2 \times (6.25 \text{ ft})} \right) \right. \\ \left. - \left[\left(\frac{4 \times (4.5106 \text{ ft})}{(6.25 \text{ ft})} + 3 \right) \times \left(\frac{(4.4168 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (4.5106 \text{ ft})}{(6.25 \text{ ft})} + 2 \right) \times \left(\frac{(4.4168 \text{ ft})}{2 \times (6.25 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 0.6588 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 2.5 \text{ ksi}$ - Concrete strength,

$f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,

$\phi = 0.65$ - Reduction factor for axial strength,

$\alpha = 0.8$ - Alpha factor for axial strength,

$A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\left(\frac{16.015 \text{ kip}}{(0.65) \times (0.8)} \right) - (0.85 \times (2.5 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (2.5 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -84.064 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-84.064 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

Table 22.4.2.1

22.4.2.2, 10.6.1.1

<p>25.2.3</p> <p>25.7.2.2</p> <p>25.7.2.1</p>	<p style="text-align: center;">$Ratio = 0.96556$</p> <p>$s_{rebar} = \text{Max}[1.5, (1.5 d_{bar})]$</p> <p>$s_{rebar} = \text{Max}[1.5, (1.5 \times (0.625 \text{ in}))]$</p> <p>$s_{rebar} = 1.5 \text{ in}$</p> <p>Ties:</p> <p>Since longitudinal reinforcement is \leq No. 10: Use #3(0.375 in)</p> <p>$s_{ties} = \text{Min}[(16 d_{bar}), (48 d_{ties}), \text{Min}(D, b)]$</p> <p>$s_{ties} = \text{Min}[(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), \text{Min}((48 \text{ in}), (48 \text{ in}))]$</p> <p>$s_{ties} = 10 \text{ in}$</p> <p>Summary:</p> <p style="text-align: center;">Main reinforcement: 14 - #5 (0.625 in) Ties: #3(0.375 in) - 10 in</p>	<p>Status: PASS Ratio: 0.970</p>
<p>22.4.2.2</p>	<p>Axial Compression Strength (ACI 318-19, LRFD)</p> <p>ϕP_N - Allowable axial compressive strength</p> <p style="text-align: center;">$\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_{yk} A_{st})]$</p> <p style="text-align: center;">$\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (2.5 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$</p> <p style="text-align: center;">$\phi P_N = 2675.2 \text{ kip}$</p> <p>Ratio - Capacity</p> <p style="text-align: center;">$Ratio = \frac{P}{\phi P_N}$</p> <p style="text-align: center;">$Ratio = \frac{(16.015 \text{ kip})}{(2675.2 \text{ kip})}$</p> <p style="text-align: center;">$Ratio = 0.0059865$</p>	<p>Status: PASS Ratio: 0.010</p>
<p>22.5.2.2</p> <p>22.5.5.1.3</p> <p>22.5.5.1.1</p>	<p>Shear Strength (ACI 318-19, LRFD)</p> <p>Parameters:</p> <p>$b_w = 48 \text{ in}$ - Effective width, d - Effective depth</p> <p style="text-align: center;">$d = 0.80 D$</p> <p style="text-align: center;">$d = 0.80 \times (48 \text{ in})$</p> <p style="text-align: center;">$d = 38.4 \text{ in}$</p> <p>λ_s - size effect modification factor</p> <p style="text-align: center;">$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = 0.64282$</p> <p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,</p> <p>$V_{c,max}$ - Max shear strength of concrete</p> <p style="text-align: center;">$V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$</p> <p style="text-align: center;">$V_{c,max} = 5 \times (0.64282) \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$</p>	

$$V_{c,max} = 296.21 \text{ kip}$$

22.5.5.1.1(a) The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $P = 16.015 \text{ kip} \rightarrow 16015 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck} + \frac{P}{6 A_g}} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + \frac{(16015 \text{ lbf})}{6 \times (2304 \text{ in}^2)}} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 120.62 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck} + (0.05 f'_{ck})} \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + (0.05 \times (2500 \text{ psi}))} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 348.89 \text{ kip}$$

V_c - Governing shear strength of concrete

$$V_c = \text{Min} [V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min} [(296.21 \text{ kip}), (120.62 \text{ kip}), (348.89 \text{ kip})]$$

$$V_c = 120.62 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{s,a}$ - Shear strength of steel (a)

$$V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$$

$$V_{s,a} = 8 \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{s,a} = 737.28 \text{ kip}$$

A_v - Ties rebar area,

$$A_v = \frac{\pi d_{ties}^2}{4}$$

$$A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$$

$$A_v = 0.11045 \text{ in}^2$$

22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)

$$V_{s,b} = \frac{2 A_v f_{yw} d}{s_{ties}}$$

$$V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$$

$$V_{s,b} = 50.894 \text{ kip}$$

V_s - Governing shear strength of steel

$$V_s = \text{MIN} [V_{s,a}, V_{s,b}]$$

$$V_s = \text{MIN} [(737.28 \text{ kip}), (50.894 \text{ kip})]$$

$$V_s = 50.894 \text{ kip}$$

22.5.1.1 ϕV_n - Allowable shear strength

$$\phi V_n = \phi (V_c + V_s)$$

$$\phi V_n = (0.65) \times ((120.62 \text{ kip}) + (50.894 \text{ kip}))$$

$$\phi V_n = 111.48 \text{ kip}$$

Considering x-direction:

$V_{max} = 7.1171 \text{ kip}$ - Maximum shear force in the x-direction,

$Ratio$ - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(7.1171 \text{ kip})}{(111.48 \text{ kip})}$$

$$Ratio = 0.06384$$

Considering z-direction:

$V_{max} = 0.23229 \text{ kip}$ - Maximum shear force in the z-direction,

Ratio - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(0.23229 \text{ kip})}{(111.48 \text{ kip})}$$

$$Ratio = 0.0020836$$

Status: **PASS**
Ratio: **0.060**

Status: **PASS**
Ratio: **0.000**

Flexural Strength (ACI 318-19, LRFD)

S_m - Section modulus

$$S_m = \frac{b D^2}{6}$$

$$S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$$

$$S_m = 18432 \text{ in}^3$$

$\lambda = 1$ - Concrete modification factor (Normal concrete),

Allowable flexural strength:

M_n shall be the lesser of:

$\phi M_{n,1}$

$$\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$$

$$\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{(2.5 \text{ ksi})} \times 18432.001 \text{ in}^3$$

$$\phi M_{n,1} = 249.600 \text{ kipft}$$

14.5.2.1b

$\phi M_{n,2}$

$$\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$$

$$\phi M_{n,2} = (0.65) \times 0.85 \times (2.5 \text{ ksi}) \times (18432 \text{ in}^3)$$

$$\phi M_{n,2} = 2121.6 \text{ kipft}$$

Therefore,

ϕM_n - Allowable flexural strength,

$$\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$$

$$\phi M_n = \text{MIN}[(249.6 \text{ kipft}), (2121.6 \text{ kipft})]$$

$$\phi M_n = 249.6 \text{ kipft}$$

Considering x-direction:

$M_{max} = 21.577 \text{ kipft}$ - Maximum moment in the x-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(21.577 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.086447$$

Status: **PASS**
Ratio: **0.090**

Considering z-direction:

$M_{max} = 0.6588 \text{ kipft}$ - Maximum moment in the z-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(0.6588 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.0026394$$

Status: **PASS**
Ratio: **0.000**