

Project Name: MTSOLAR_A1EF25A583HI

Date: Sun Nov 09 2025

Location: 1200 Estrella Dr, Santa Barbara, CA 93110,

Number of Modules: 35


USA

Number of Poles: 2

Unique ID: 2P-22.5-6TOP-SD-57-L-5Hx7W-8518

Date Sold:

Dealer: _____



Array Dimensions N/S	18.96 ft
Array Dimensions E/W	40.25 ft
Winter Tilt Angle (Degrees)	55
Front Edge Clearance	2


MT Solar Bill of Materials (2P-22.5-6TOP-SD-57-L-5Hx7W-8518)

Part	Short Description	BOM Qty
MTS-PC-6	6IN Pole Cap Assembly	2
MTS-HF-SD	H-Frame Assembly-SD	2
MTS-SD-Wing-57	57IN SD Wing	4
MTS-SD-Splice-90	90IN SD Splice	4
MTS-CLAMP-ANGLE-4PK	Angle Clamp	7

Rail Bill of Materials

Part	Qty
Rails (228in Long)	14x
Rail Attachment	56x
Module Mid Clamp	56x
Module End Clamp	28x
Ground Lug	7x

Site Details:



Site Address: 1200 Estrella Dr, Santa Barbara, CA 93110, USA

Array Specifications

Duty Classification:	SD
Module Width:	45.00 in
Module Length:	68.00 in
Number of Rows:	5
Number of Columns:	7
Total Number of Modules:	35
Winter Tilt Angle:	55
Front Edge Clearance:	2
Total Array Height at Tilt:	17.53 ft
Total Frame Length:	39.50 ft
Module Info/Notes:	
Array Dimensions N/S:	18.96 ft
Array Dimensions E/W:	40.25 ft
Rail Length:	227.50 in
Rail Spacing:	2.88 ft

Support Specifications

Pole Size:	6in Pipe Sch 40
Pole Length above Grade:	9.76 ft
Number of Poles:	2
Pole Spacing:	22.5 ft

Foundation Specifications

Foundation Type:	rectangular
Foundation Dimensions:	48x48 in
Foundation Depth (below grade):	5.8 ft
Foundation Volume:	92.00 ft ³

Site Info

Risk Category:	I
Exposure:	B
Soil Classification:	sand
Site Location:	1200 Estrella Dr, Santa Barbara, CA 93110, USA
Wind Speed:	88 mph

Snow Load:

0 psf

Design Disclaimer



This software should be used for preliminary designs and should not be used as a final design unless reviewed, verified and designed by a qualified structural engineer.

AutoDesigner Input



```
{ "wind_speed_override": null, "snow_load_override": null, "direct_snow_load": false, "add_angle_brace": false, "product_type": "Beam", "designer_name": "Emmanuel Stapf", "designer_email": "manu@stapf.org", "designer_phone": "", "project_id": "MTSOLAR_A1EF25A583HI", "site_address": "1200 Estrella Dr, Santa Barbara, CA 93110, USA", "module_info": "", "module_width": 45, "module_length": 68, "number_rows": 5, "number_columns": 7, "pole_mount_section": "4_40", "core_pipe_width": 65, "core_pipe_section": "2_40", "adjuster_section": "2_40", "core_beam_height": 65, "core_beam_section": "HSS3x2x1/8", "main_pipe_section": "2_12GA", "pole_spacing": "15", "tilt_angle": 55, "ground_clearance": 2, "risk_category": "I", "exposure_category": "B", "frame_duty_override": "auto", "pole_override": "auto", "soil_type": "sand", "customer_foundation_override": "48_Square", "foundation_type": "Square", "foundation_size": 48, "check_rails": false }
```



Design Notes:

- Deflection checks are set to L/1 due to manufacturer structural design intent
- Foundation Soil Parameters used in this Autodesign are all estimates, proper geotechnical reports are required to confirm soil profiles
- Wind speeds, snow loads and other site specific results are based on ASCE 7-16
- Steel frame design checks are based on AISC 360-16 LRFD
- Design / analysis of fixings and connections are not carried out by this module.
- Impacts of eccentrically applied, partial or pattern loading are not considered by this module.
- Foundation Design and Sizing is approximate only



FEM Results (Envelope Worst Case)





Reaction Forces for Foundation 1 (Node ID#1), (kip, kip-ft)

LRFD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. 1.4D	0.0000	3.4020	0.0710	0.2161	-0.0727	0.0329
ULS: 2. 1.2D + 1.6L + 0.5(S or Lr or R)	0.0000	2.9160	0.0608	0.1851	-0.0623	0.0262
ULS: 2. 1.2D + 1.6L + 0.5(S or Lr or R)	0.0000	2.9160	0.0608	0.1851	-0.0623	0.0262
ULS: 3. 1.2D + 1.6(S or Lr or R) + L	0.0000	2.9160	0.0608	0.1851	-0.0623	0.0262
ULS: 5. 1.2D + E + L + 0.2S	0.0000	2.9160	0.0608	0.1851	-0.0623	0.0262
ULS: 7. 0.9D + 1.0E	0.0000	2.1870	0.0456	0.1386	-0.0467	0.0174
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind downforce Case A only	-3.4344	5.3208	0.1614	0.4744	-0.4582	34.6362
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind downforce Case B only	0.0000	2.9160	0.0608	0.1851	-0.0623	0.0262
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind uplift Case A only	3.4344	0.5112	-0.0396	-0.1030	0.3335	-33.6408
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind uplift Case B only	0.0000	2.9160	0.0608	0.1851	-0.0623	0.0262
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind downforce Case A only	-3.4344	5.3208	0.1614	0.4744	-0.4582	34.6362
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind downforce Case B only	0.0000	2.9160	0.0608	0.1851	-0.0623	0.0262
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind uplift Case A only	3.4344	0.5112	-0.0396	-0.1030	0.3335	-33.6408
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind uplift Case B only	0.0000	2.9160	0.0608	0.1851	-0.0623	0.0262
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind downforce Case A only	-1.7172	4.1184	0.1111	0.3296	-0.2602	17.2104
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind downforce Case B only	0.0000	2.9160	0.0608	0.1851	-0.0623	0.0262
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind uplift Case A only	1.7172	1.7136	0.0106	0.0409	0.1356	-16.9223
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind uplift Case B only	0.0000	2.9160	0.0608	0.1851	-0.0623	0.0262
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind downforce Case A only	-1.7172	4.1184	0.1111	0.3296	-0.2602	17.2104
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind downforce Case B only	0.0000	2.9160	0.0608	0.1851	-0.0623	0.0262
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind uplift Case A only	1.7172	1.7136	0.0106	0.0409	0.1356	-16.9223
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind uplift Case B only	0.0000	2.9160	0.0608	0.1851	-0.0623	0.0262
ULS: 6. 0.9D + 1.0W_Wind downforce Case A only	-3.4344	4.5918	0.1462	0.4280	-0.4430	34.4715
ULS: 6. 0.9D + 1.0W_Wind downforce Case B only	0.0000	2.1870	0.0456	0.1386	-0.0467	0.0174
ULS: 6. 0.9D + 1.0W_Wind uplift Case A only	3.4344	-0.2178	-0.0548	-0.1495	0.3494	-33.5035
ULS: 6. 0.9D + 1.0W_Wind uplift Case B only	0.0000	2.1870	0.0456	0.1386	-0.0467	0.0174

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201
ULS: 2. D + L	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201
ULS: 3. D + (S or Lr or R)	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201
ULS: 3. D + (S or Lr or R)	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201
ULS: 5b. D + 0.7E	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201
ULS: 8. 0.6D + 0.7E	0.0000	1.4580	0.0304	0.0923	-0.0311	0.0101
ULS: 5a. D + 0.6W_Wind downforce Case A only	-2.0607	3.8729	0.1110	0.3276	-0.2896	20.6083
ULS: 5a. D + 0.6W_Wind downforce Case B only	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201
ULS: 5a. D + 0.6W_Wind uplift Case A only	2.0607	0.9871	-0.0096	-0.0190	0.1857	-20.2310
ULS: 5a. D + 0.6W_Wind uplift Case B only	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-1.5455	3.5122	0.0959	0.2842	-0.2302	15.4291
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.5455	1.3478	0.0054	0.0243	0.1263	-15.1992
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-1.5455	3.5122	0.0959	0.2842	-0.2302	15.4291
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.5455	1.3478	0.0054	0.0243	0.1263	-15.1992
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.0000	2.4300	0.0507	0.1541	-0.0519	0.0201
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-2.0607	2.9009	0.0908	0.2658	-0.2691	20.4763
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	0.0000	1.4580	0.0304	0.0923	-0.0311	0.0101
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	2.0607	0.0151	-0.0299	-0.0808	0.2068	-20.1237
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	0.0000	1.4580	0.0304	0.0923	-0.0311	0.0101

Worst Case Reactions (LRFD)

Note: Downforce / downwind wind load cases are assumed to govern.

Result	Value (kip, kip-ft)
Axial	5.3208
Shear X	-3.4344
Shear Z	0.1614
Moment X	0.4744
Moment Y (Twist)	0.4582
Moment Z	34.6362

Worst Case Reactions (ASD)

Note: Downforce / downwind wind load cases are assumed to govern.

Result	Value (kip, kip-ft)
Axial	3.8729
Shear X	-2.0607
Shear Z	0.1110
Moment X	0.3276
Moment Y (Twist)	0.2896
Moment Z	20.6083

Reaction Forces for Foundation 2 (Node ID#101), (kip, kip-ft)

LRFD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. 1.4D	-0.0000	3.4020	-0.0710	-0.2162	0.0728	0.0330
ULS: 2. 1.2D + 1.6L + 0.5(S or Lr or R)	-0.0000	2.9160	-0.0608	-0.1851	0.0624	0.0262
ULS: 2. 1.2D + 1.6L + 0.5(S or Lr or R)	-0.0000	2.9160	-0.0608	-0.1851	0.0624	0.0262
ULS: 3. 1.2D + 1.6(S or Lr or R) + L	-0.0000	2.9160	-0.0608	-0.1851	0.0624	0.0262
ULS: 5. 1.2D + E + L + 0.2S	-0.0000	2.9160	-0.0608	-0.1851	0.0624	0.0262
ULS: 7. 0.9D + 1.0E	-0.0000	2.1870	-0.0456	-0.1386	0.0468	0.0174
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind downforce Case A only	-3.4344	5.3208	-0.1614	-0.4747	0.4581	34.6370
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind downforce Case B only	-0.0000	2.9160	-0.0608	-0.1851	0.0624	0.0262
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind uplift Case A only	3.4344	0.5112	0.0396	0.1032	-0.3333	-33.6414
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind uplift Case B only	-0.0000	2.9160	-0.0608	-0.1851	0.0624	0.0262
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind downforce Case A only	-3.4344	5.3208	-0.1614	-0.4747	0.4581	34.6370
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind downforce Case B only	-0.0000	2.9160	-0.0608	-0.1851	0.0624	0.0262
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind uplift Case A only	3.4344	0.5112	0.0396	0.1032	-0.3333	-33.6414
ULS: 4. 1.2D + W + L + 0.5(S or Lr or R)_Wind uplift Case B only	-0.0000	2.9160	-0.0608	-0.1851	0.0624	0.0262
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind downforce Case A only	-1.7172	4.1184	-0.1111	-0.3297	0.2602	17.2108
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind downforce Case B only	-0.0000	2.9160	-0.0608	-0.1851	0.0624	0.0262
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind uplift Case A only	1.7172	1.7136	-0.0106	-0.0408	-0.1355	-16.9226
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind uplift Case B only	-0.0000	2.9160	-0.0608	-0.1851	0.0624	0.0262
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind downforce Case A only	-1.7172	4.1184	-0.1111	-0.3297	0.2602	17.2108
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind downforce Case B only	-0.0000	2.9160	-0.0608	-0.1851	0.0624	0.0262
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind uplift Case A only	1.7172	1.7136	-0.0106	-0.0408	-0.1355	-16.9226
ULS: 3. 1.2D + 1.6(S or Lr or R) + 0.5W_Wind uplift Case B only	-0.0000	2.9160	-0.0608	-0.1851	0.0624	0.0262
ULS: 6. 0.9D + 1.0W_Wind downforce Case A only	-3.4344	4.5918	-0.1462	-0.4282	0.4429	34.4721
ULS: 6. 0.9D + 1.0W_Wind downforce Case B only	-0.0000	2.1870	-0.0456	-0.1386	0.0468	0.0174
ULS: 6. 0.9D + 1.0W_Wind uplift Case A only	3.4344	-0.2178	0.0548	0.1497	-0.3493	-33.5040
ULS: 6. 0.9D + 1.0W_Wind uplift Case B only	-0.0000	2.1870	-0.0456	-0.1386	0.0468	0.0174

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 2. D + L	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 3. D + (S or Lr or R)	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 3. D + (S or Lr or R)	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 5b. D + 0.7E	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 8. 0.6D + 0.7E	-0.0000	1.4580	-0.0304	-0.0923	0.0312	0.0101
ULS: 5a. D + 0.6W_Wind downforce Case A only	-2.0607	3.8729	-0.1110	-0.3277	0.2896	20.6087
ULS: 5a. D + 0.6W_Wind downforce Case B only	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 5a. D + 0.6W_Wind uplift Case A only	2.0607	0.9871	0.0096	0.0190	-0.1856	-20.2313
ULS: 5a. D + 0.6W_Wind uplift Case B only	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-1.5455	3.5122	-0.0959	-0.2843	0.2302	15.4294
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.5455	1.3478	-0.0054	-0.0242	-0.1262	-15.1995
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-1.5455	3.5122	-0.0959	-0.2843	0.2302	15.4294
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.5455	1.3478	-0.0054	-0.0242	-0.1262	-15.1995
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	-0.0000	2.4300	-0.0507	-0.1541	0.0520	0.0202
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-2.0607	2.9009	-0.0908	-0.2659	0.2691	20.4765
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-0.0000	1.4580	-0.0304	-0.0923	0.0312	0.0101
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	2.0607	0.0151	0.0299	0.0808	-0.2067	-20.1239
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	-0.0000	1.4580	-0.0304	-0.0923	0.0312	0.0101

Worst Case Reactions (LRFD)

Note: Downforce / downwind wind load cases are assumed to govern.

Result	Value (kip, kip-ft)
Axial	5.3208
Shear X	-3.4344
Shear Z	-0.1614
Moment X	-0.4747
Moment Y (Twist)	0.4581
Moment Z	34.6370

Worst Case Reactions (ASD)

Note: Downforce / downwind wind load cases are assumed to govern.

Result	Value (kip, kip-ft)
Axial	3.8729
Shear X	-2.0607
Shear Z	-0.1110
Moment X	-0.3277
Moment Y (Twist)	0.2896
Moment Z	20.6087

Project Details

Design Code: AISC 360-16 LRFD
 Provision: LRFD
 Country: United States
 User Name: sales@mtsolar.us
 Unit System: imperial



Design Input Information

Design Factors			
Φ_t	Φ_c	Φ_b	Φ_v
0.9	0.9	0.9	0.9

Design Materials			
ID	E (ksi)	F _y (ksi)	F _u (ksi)
1	29000	50	65
2	29000	46	62
4	29000	50	62

Section Dimensions

ID	Name	d (in)	t _w (in)				
1	2in Pipe Sch 40	2.38	0.15				
4	4in Pipe Sch 40	4.50	0.24				
7	6in Pipe Sch 40	6.63	0.28				

ID	Name	d (in)	b (in)	t _w (in)	t _b (in)	r (in)	
15	HSS5x3x1/8	5.00	3.00	0.12	0.12	0.12	

ID	Name	d (in)	t _w (in)	b _t (in)	b _b (in)	t _t (in)	t _b (in)	r (in)
18	W6x9	5.90	0.17	3.94	3.94	0.21	0.21	0.25

Section Properties

106	79.65	74.89	10.99	6.26	29.14	16.61
107	79.65	74.30	10.99	6.26	29.14	16.61
108	120.60	34.69	23.36	6.45	30.09	45.74
109	44.49	40.02	2.63	2.63	13.35	13.35
110	79.65	72.84	10.99	6.26	29.14	16.61
111	120.60	34.69	23.36	6.45	30.09	45.74
112	131.41	130.46	14.87	14.87	39.42	39.42
113	120.60	84.03	19.03	6.45	30.09	45.74
114	120.60	84.03	19.00	6.45	30.09	45.74
115	120.60	48.60	11.10	6.45	30.09	45.74
116	120.60	48.60	11.10	6.45	30.09	45.74

Design Ratio

Member ID	P	M _z	M _y	V _y	V _z	(P,M _z ,M _y)	Worst LC	KL/r	δ	Status
1	0.025	0.890	0.028	0.050	0.002	0.915	#13	0.170	Not Required	Pass
2	0.003	0.237	0.222	0.057	0.042	0.461	#13	0.034	Not Required	Pass
3	0.007	0.458	0.039	0.045	0.001	0.487	#13	0.044	Not Required	Pass
4	0.006	0.455	0.146	0.046	0.024	0.555	#13	0.078	Not Required	Pass
5	0.007	0.284	0.148	0.046	0.030	0.316	#13	0.073	Not Required	Pass
6	0.009	0.523	0.073	0.053	0.009	0.593	#13	0.044	Not Required	Pass
7	0.010	0.324	0.201	0.052	0.040	0.372	#13	0.073	Not Required	Pass
8	0.002	0.054	0.117	0.036	0.010	0.128	#13	0.088	Not Required	Pass
9	0.013	0.037	0.071	0.002	0.002	0.103	#13	0.198	Not Required	Pass
10	0.009	0.521	0.185	0.052	0.031	0.613	#13	0.078	Not Required	Pass
11	0.002	0.053	0.120	0.036	0.010	0.132	#13	0.088	Not Required	Pass
12	0.003	0.311	0.253	0.072	0.047	0.565	#13	0.034	Not Required	Pass
13	0.004	0.168	0.258	0.044	0.012	0.366	#13	0.265	Not Required	Pass
14	0.005	0.171	0.255	0.044	0.012	0.362	#13	0.177	Not Required	Pass
15	0.000	0.069	0.106	0.023	0.006	0.160	#13	Not Required	Not Required	Pass
16	0.000	0.069	0.106	0.023	0.006	0.160	#13	Not Required	Not Required	Pass
101	0.025	0.890	0.028	0.050	0.002	0.915	#13	0.170	Not Required	Pass
102	0.003	0.311	0.253	0.072	0.047	0.565	#13	0.034	Not Required	Pass
103	0.009	0.523	0.073	0.053	0.009	0.593	#13	0.044	Not Required	Pass
104	0.009	0.521	0.185	0.052	0.031	0.613	#13	0.078	Not Required	Pass
105	0.010	0.324	0.201	0.052	0.040	0.372	#13	0.073	Not Required	Pass
106	0.007	0.458	0.039	0.045	0.001	0.487	#13	0.044	Not Required	Pass
107	0.007	0.284	0.148	0.046	0.030	0.316	#13	0.073	Not Required	Pass
108	0.000	0.069	0.106	0.023	0.006	0.160	#13	Not Required	Not Required	Pass
109	0.013	0.037	0.071	0.002	0.002	0.103	#13	0.198	Not Required	Pass
110	0.006	0.455	0.146	0.046	0.024	0.555	#13	0.078	Not Required	Pass
111	0.000	0.069	0.106	0.023	0.006	0.160	#13	Not Required	Not Required	Pass
112	0.003	0.237	0.222	0.057	0.042	0.461	#13	0.034	Not Required	Pass
113	0.004	0.168	0.258	0.044	0.012	0.366	#13	0.177	Not Required	Pass
114	0.005	0.171	0.255	0.044	0.012	0.362	#13	0.265	Not Required	Pass
115	0.004	0.299	0.145	0.036	0.010	0.424	#13	0.557	Not Required	Pass
116	0.002	0.300	0.146	0.036	0.010	0.426	#13	0.557	Not Required	Pass

Definitions

Φ_t	Safety factor for tensile
Φ_c	Safety factor for compression
Φ_b	Safety factor for flexure
Φ_v	Safety factor for shear
E	Modulus of elasticity
F_y	Specified minimum yield stress
F_u	Specified minimum tensile strength
A	Cross-sectional area
J	Torsional constant
I_{yp}	Moment of inertia about the Y axes
I_{zp}	Moment of inertia about the Z axes
I_w	Warping constant
S_{yp}	Plastic section modulus about the Y axis
S_{zp}	Plastic section modulus about the Z axis
KL	Effective length
C_b	Buckling modification factor (from all load combinations)
L_b	Length between braced points
LST	Limited slenderness for tension
LSC	Limited slenderness for compression
LD	Limited deflection
P_n	Nominal axial strength (tension/compression)
M_n	Nominal flexural strength (about Z/Y axis)
V_n	Nominal shear strength (along Z/Y axis)
P	Design ratio in case of axial force
M_z	Design ratio in case of bending about Z axis
M_y	Design ratio in case of bending about Y axis
V_y	Design ratio in case of shear along Y axis
V_z	Design ratio in case of shear along Z axis
(P, M_z, M_y)	Design ratio in case of axial force and bending action
KL/r	Design ratio in case of section slenderness
δ	Design ratio in case of member deflection
OK	Capacity is provided
NG	Capacity is not provided

IBC 2018 Pile Design



Input	Description
Region	American Standard
Concrete design code	American Concrete Institute (ACI 318:2019)

Cross-section

Input	Description	Value
Shape	Cross-sectional shape	Square
b	Section width	48 in
D	Section depth	48 in

Material Properties


Input	Description	Value
f'_{ck}	Concrete compressive strength	2.5 ksi
f_{yk}	Yield strength of steel	60 ksi
d_b	Rebar diameter	#5 (0.625) in
cover	Concrete cover	3 in

Soil Parameters (IBC 1806)

Input	Description	Value
Soil type	Sand, silty sand, clayey sand, silty gravel & clayey gravel	
q_a	Allowable bearing pressure	2000 psf
R	Allowable lateral pressure	150 psf/ft

Loading

Load	ASD	LRFD
P	3.873 kip	5.321 kip
V _x	-2.061 kip	-3.434 kip
V _z	-0.111 kip	-0.161 kip
M _x	-0.328 kip-ft	-0.475 kip-ft
M _z	20.61 kip-ft	34.64 kip-ft



Required depth to resist lateral loads (ASD)

Allowable lateral pressure

$$R = 150 \text{ psf/ft}$$

Point of application of lateral load:

$$H = h_1 + h_2 + h_e = 0 + 0 + 0 = 0 \text{ ft}$$

Considering x-direction:

Lateral force per section length

$$H_o = \frac{V_x}{1.57 \times D} = \frac{-2.061}{1.57 \times 48} = -0.328 \frac{\text{kip}}{\text{ft}}$$

Moment per section length

$$M_o = \frac{M_z + (V_z \times H)}{1.57 \times D} = \frac{20.61 + (-2.061 \times 0)}{1.57 \times 48} = 3.282 \frac{\text{kip-ft}}{\text{ft}}$$

Required depth of embedment in earth:

$$L_e^3 - \left(9 \times \frac{H_o \times L_z}{R}\right) - \left(12 \times \frac{M_o}{R}\right) = 0$$

Solving the cubic equation:

$$L_{e,z} = 5.388 \text{ ft}$$

Considering z-direction:

Lateral force per section length

$$H_o = \frac{V_z}{1.57 \times b} = \frac{-0.111}{1.57 \times 48} = -0.018 \frac{\text{kip}}{\text{ft}}$$

Moment per section length

$$M_o = \frac{M_z + (V_z \times H)}{1.57 \times b} = \frac{-0.328 + (-0.111 \times 0)}{1.57 \times 48} = -0.052 \frac{\text{kip-ft}}{\text{ft}}$$

Required depth of embedment in earth:

$$L_e^3 - \left(9 \times \frac{H_o \times L_z}{R}\right) - \left(12 \times \frac{M_o}{R}\right) = 0$$

Solving the cubic equation:

$$L_{e,z} = -1.392 \text{ ft}$$

Minimum embedded depth

Depth of pile required

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}] = \text{MAX}[5.388, -1.392] = 5.388 \text{ ft}$$

Actual embedded length

$$L_e = L - h_2 - h_e = 5.75 - 0 - 0 = 5.75 \text{ ft}$$

Utilisation

$$\text{Ratio} = \frac{L_{e,req}}{L_e} = \frac{5.388}{5.75} = 0.937$$

UTILITY: 0.94

REFERENCES

CALCULATIONS

RESULTS

End-bearing Capacity (ASD)

Allowable bearing pressure
Unit weight of concrete

$q_a = 2000 \text{ psf}$
 $w_c = 0.15 \text{ kip/ft}^3$

Cross-sectional area:

$$A = b \times D = 48 \times 48 = 16 \text{ ft}^2$$

End-bearing pressure:

$$q = \frac{P}{A} = \frac{3.873}{16} = 242.1 \text{ psf}$$

Utilisation

$$\text{Ratio} = \frac{q}{q_a} = \frac{242.1}{2000} = 0.121$$

UTILITY: 0.12

Lateral Soil Pressure (ASD)

Allowable lateral pressure

$R = 150 \text{ psf/ft}$

Length to least lateral dimension ratio:

$$\frac{L}{\text{MIN}[b, D]} = \frac{5.75}{\text{MIN}[4, 4]} = 1.438$$

L/D ratio ≤ 10 . This pile is classified as a short pile.

Considering x-direction:

Distance from resting surface to pivot point:

$$a = \frac{(4 \times M_o \times L_e) + (3 \times H_o \times L_e^2)}{R}$$

$$(6 \times M_o) + (4 \times H_o \times L_e)$$

$$a = \frac{(4 \times 3.282 \times 5.75) + (3 \times 0.328 \times 5.75^2)}{(6 \times 3.282) + (4 \times 0.328 \times 5.75)} = 3.966 \text{ ft}$$

Earth pressure against the pile at a distance a/2 from the resting surface:

$$p = \frac{0.75 \times [(4 \times M_o) + (3 \times H_o \times L_e)]^2}{L_e^2 \times [(3 \times M_o) + (2 \times H_o \times L_e)]}$$

$$p = \frac{0.75 \times [(4 \times 3.282) + (3 \times -0.328 \times 5.75)]^2}{5.75^2 \times [(3 \times 3.282) + (2 \times -0.328 \times 5.75)]} = 0.208 \frac{\text{kip}}{\text{ft}^2}$$

Allowable lateral soil pressure at a depth of a/2:

$$p_a = R \times \frac{a}{2} = 0.15 \times \frac{3.966}{2} = 0.297 \frac{\text{kip}}{\text{ft}^2}$$

Utilisation - pressure at a depth of a/2

$$\text{Ratio} = \frac{p}{p_a} = \frac{0.208}{0.297} = 0.7$$

UTILITY: 0.70

Earth pressure against the pile at distance L_e :

$$s = \frac{6 \times [(2 \times M_o) + (H_o \times L_e)]}{L_e^2} = \frac{6 \times [(2 \times 3.282) + (-0.328 \times 5.75)]}{5.75^2} = 0.849 \frac{\text{kip}}{\text{ft}^2}$$

Allowable lateral soil pressure at a depth of L_e :

$$p_s = R \times L_e = 0.15 \times 5.75 = 0.862 \frac{\text{kip}}{\text{ft}^2}$$

Utilisation - pressure at a depth of L_e

$$\text{Ratio} = \frac{s}{p_s} = \frac{0.849}{0.862} = 0.984$$

UTILITY: 0.98

Considering z-direction:

Distance from resting surface to pivot point:

$$a = \frac{(4 \times M_o \times L_e) + (3 \times H_o \times L_e^2)}{(6 \times M_o) + (4 \times H_o \times L_e)}$$

$$a = \frac{(4 \times 0.052 \times 5.75) + (3 \times 0.018 \times 5.75^2)}{(6 \times 0.052) + (4 \times 0.018 \times 5.75)} = 4.104 \text{ ft}$$

Earth pressure against the pile at a distance a/2 from the resting surface:

$$p = \frac{0.75 \times [(4 \times M_o) + (3 \times H_o \times L_e)]^2}{L_e^2 \times [(3 \times M_o) + (2 \times H_o \times L_e)]}$$

$$p = \frac{0.75 \times [(4 \times -0.052) + (3 \times -0.018 \times 5.75)]^2}{5.75^2 \times [(3 \times -0.052) + (2 \times -0.018 \times 5.75)]} = -0.017 \frac{\text{kip}}{\text{ft}^2}$$

Allowable lateral soil pressure at a depth of a/2:

$$p_a = R \times \frac{a}{2} = 0.15 \times \frac{4.104}{2} = 0.308 \frac{\text{kip}}{\text{ft}^2}$$

Utilisation - pressure at a depth of a/2

$$\text{Ratio} = \frac{p}{p_a} = \frac{-0.017}{0.308} = -0.054$$

UTILITY: 0.05

Earth pressure against the pile at distance L_e :

$$s = \frac{6 \times [(2 \times M_o) + (H_o \times L_e)]}{L_e^2} = \frac{6 \times [(2 \times -0.052) + (-0.018 \times 5.75)]}{5.75^2} = -0.037 \frac{\text{kip}}{\text{ft}^2}$$

Allowable lateral soil pressure at a depth of L_e :

$$p_s = R \times L_e = 0.15 \times 5.75 = 0.862 \frac{\text{kip}}{\text{ft}^2}$$

Utilisation - pressure at a depth of L_e

$$\text{Ratio} = \frac{s}{p_s} = \frac{-0.037}{0.862} = -0.043$$

UTILITY: 0.04

REFERENCES

CALCULATIONS

RESULTS

Shear force and bending moment (LRFD)

Considering x-direction:

Lateral force per section length

$$H_o = \frac{V_z}{1.57 \times D} = \frac{-3.434}{1.57 \times 48} = -0.547 \frac{\text{kip}}{\text{ft}}$$

Moment per section length

$$M_o = \frac{M_z + (V_z \times H)}{1.57 \times D} = \frac{34.64 + (-3.434 \times 0)}{1.57 \times 48} = 5.515 \frac{\text{kip-ft}}{\text{ft}}$$

Distance from resting surface to pivot point:

$$a = \frac{(4 \times M_o \times L_e) + (3 \times H_o \times L_e^2)}{(6 \times M_o) + (4 \times H_o \times L_e)}$$

$$a = \frac{(4 \times 5.515 \times 5.75) + (3 \times 0.547 \times 5.75^2)}{(6 \times 5.515) + (4 \times 0.547 \times 5.75)} = 3.965 \text{ ft}$$

Max shear force located at depth a:

$$E = \frac{M_o}{H_o} = \frac{5.515}{-0.547} = 10.09 \text{ ft}$$

$$V_{max,x} = (H_o \times D) \times \left[1 - \left[3 \times \left(\frac{4 \times E}{L_e} + 3 \right) \times \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \times \left(\frac{3 \times E}{L_e} + 2 \right) \times \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max,x} = (-0.547 \times 48) \times \left[1 - \left[3 \times \left(\frac{4 \times 10.09}{5.75} + 3 \right) \times \left(\frac{3.965}{5.75} \right)^2 \right] + \left[4 \times \left(\frac{3 \times 10.09}{5.75} + 2 \right) \times \left(\frac{3.965}{5.75} \right)^3 \right] \right]$$

$$V_{max,x} = 8.232 \text{ kip}$$

Max bending moment located at a depth of a/2:

$$M_{max,x} = (H_o \times D \times L_e) \times \left[\left(\frac{E}{L_e} + \frac{a}{2 \times L_e} \right) - \left[\left(\frac{4 \times E}{L_e} + 3 \right) \times \left(\frac{a}{2 \times L_e} \right)^3 \right] + \left[\left(\frac{3 \times E}{L_e} + 2 \right) \times \left(\frac{a}{2 \times L_e} \right)^4 \right] \right]$$

$$M_{max,x} = (-0.547 \times 48 \times 5.75) \times \left[\left(\frac{10.09}{5.75} + \frac{3.965}{2 \times 5.75} \right) - \left[\left(\frac{4 \times 10.09}{5.75} + 3 \right) \times \left(\frac{3.965}{2 \times 5.75} \right)^3 \right] + \left[\left(\frac{3 \times 10.09}{5.75} + 2 \right) \times \left(\frac{3.965}{2 \times 5.75} \right)^4 \right] \right]$$

$$M_{max,x} = 22.53 \text{ kip-ft}$$

Considering z-direction:

Lateral force per section length

$$H_o = \frac{V_z}{1.57 \times b} = \frac{-0.161}{1.57 \times 48} = -0.026 \frac{\text{kip}}{\text{ft}}$$

Moment per section length

$$M_o = \frac{M_z + (V_z \times H)}{1.57 \times b} = \frac{-0.475 + (-0.161 \times 0)}{1.57 \times 48} = -0.076 \frac{\text{kip-ft}}{\text{ft}}$$

Distance from resting surface to pivot point:

$$a = \frac{(4 \times M_o \times L_e) + (3 \times H_o \times L_e^2)}{(6 \times M_o) + (4 \times H_o \times L_e)}$$

$$a = \frac{(4 \times 0.076 \times 5.75) + (3 \times 0.026 \times 5.75^2)}{(6 \times 0.076) + (4 \times 0.026 \times 5.75)} = 4.104 \text{ ft}$$

Max shear force located at depth a:

$$E = \frac{M_o}{H_o} = \frac{-0.076}{-0.026} = 2.941 \text{ ft}$$

$$V_{max,z} = (H_o \times b) \times \left[1 - \left[3 \times \left(\frac{4 \times E}{L_e} + 3 \right) \times \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \times \left(\frac{3 \times E}{L_e} + 2 \right) \times \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max,z} = (-0.026 \times 48) \times [1 - [3 \times \left(\frac{4 \times 2.941}{5.75} + 3\right) \times \left(\frac{4.104}{5.75}\right)^3] + [4 \times \left(\frac{3 \times 2.941}{5.75} + 2\right) \times \left(\frac{4.104}{5.75}\right)^4]$$


$$V_{max,z} = 0.162 \text{ kip}$$

Max bending moment located at a depth of a/2:

$$M_{max,z} = (H_o \times b \times L_e) \times \left[\left(\frac{E}{L_e} + \frac{a}{2 \times L_e} \right) - \left[\left(\frac{4 \times E}{L_e} + 3 \right) \times \left(\frac{a}{2 \times L_e} \right)^3 \right] + \left[\left(\frac{3 \times E}{L_e} + 2 \right) \times \left(\frac{a}{2 \times L_e} \right)^4 \right] \right]$$

$$M_{max,z} = (-0.026 \times 48 \times 5.75) \times \left[\left(\frac{2.941}{5.75} + \frac{4.104}{2 \times 5.75} \right) - \left[\left(\frac{4 \times 2.941}{5.75} + 3 \right) \times \left(\frac{4.104}{2 \times 5.75} \right)^3 \right] + \left[\left(\frac{3 \times 2.941}{5.75} + 2 \right) \times \left(\frac{4.104}{2 \times 5.75} \right)^4 \right] \right]$$

$$M_{max,z} = 0.412 \text{ kip-ft}$$



Minimum Reinforcement Check (LRFD)

Gross area of concrete:

$$A_g = b \times D = 48 \times 48 = 2304 \text{ in}^2$$

Main Reinforcement

22.4.2.2 Required reinforcement:

$$A_{st,req} = \frac{P - (0.85 \times f'_{ck} \times A_g)}{f_{yk} - (0.85 \times f'_{ck})} = \frac{5.321 - (0.85 \times 2.5 \times 2304)}{60 - (0.85 \times 2.5)} = -84.5 \text{ in}^2$$

10.6.1.1 Maximum reinforcement:

$$A_{st,max} = 0.08 \times A_g = 0.08 \times 2304 = 184.3 \text{ in}^2$$

7.6.1.1 Minimum reinforcement:

$$A_{st,min} = 0.0018 \times A_g = 0.0018 \times 2304 = 4.147 \text{ in}^2$$

Governing minimum reinforcement area:

$$(0.0018 \times A_g) \leq A_{st,req} \leq (0.08 \times A_g)$$

$$A_{min} = 4.147 \text{ in}^2$$

Minimum number of reinforcements:

$$A_{bar} = 0.307 \text{ in}^2$$

$$n_{min} = \frac{A_{min}}{A_{bar}} = \frac{4.147}{0.307} = 14$$

25.2.3 Minimum spacing:

$$s_{rebar} = \text{MAX}[1.5, 1.5 \times d_b] = \text{MAX}[1.5, (1.5 \times 0.625)] = 1.5 \text{ in}$$

Use: $n = 16$ pcs at 1.5 in minimum spacing

Total reinforcement area:

$$A_{st} = 16 \times 0.307 = 4.909 \text{ in}^2$$

Shear Reinforcement

25.7.2.2 For main reinforcement ≤ 1.41 in: Use #3(0.375 in)

Maximum spacing of shear Reinforcements:

$$s = \text{MIN}[16 \times d_b, 48 \times d_{b,ties}, \text{MIN}(b, D)] = \text{MIN}[(16 \times 0.625), (48 \times 0.375), \text{MIN}(48, 48)] = 10 \text{ in}$$

Detailing Summary

Main reinforcement

#5 (0.625 in) - 16pcs at 1.5 in min. spacing

Axial Compression Strength (LRFD)

22.4.2.2 Allowable axial compressive strength:

$$\phi P_N = \phi \times 0.8 \times [(0.85 \times f'_{ck} \times [A_g - A_{st}]) + (f_{yk} \times A_{st})]$$

$$\phi P_N = 0.65 \times 0.8 \times [(0.85 \times 2.5 \times [2304 - 4.909]) + (60 \times 4.909)] = 2694 \text{ kip}$$

Utilisation

$$\text{Ratio} = \frac{P}{\phi P_N} = \frac{5.321}{2694} = 0.002$$

UTILITY: 0.00

Shear Strength LRFD)

Effective shear width	$b_w = 48 \text{ in}$
Effective shear depth	$d = 44.31 \text{ in}$
Shear reinforcement area	$A_v = 0.221 \text{ in}^2$
Shear reinforcement spacing	$s = 10 \text{ in}$
Concrete type factor (Normal concrete)	$\lambda = 1$
Strength reduction factor for shear	$\phi = 0.75$
Maximum shear in the x-direction	$V_{max,x} = 8.232 \text{ kip}$
Maximum shear in the z-direction	$V_{max,z} = 0.162 \text{ kip}$

22.5.5.1.1 Max shear strength of concrete:

$$V_{c,max} = 5 \times \lambda \times \sqrt{f'_{ck}} \times b_w \times d = 5 \times 1 \times \sqrt{2.5} \times 48 \times 44.31 = 531.8 \text{ kip}$$

Table 22.5.5.1 Shear strength of concrete:

$$V_{c,a} = \left(2 \times \lambda \times \sqrt{f'_{ck}} + \text{MIN} \left[\frac{P}{6 \times A_g}, (0.05 \times f'_{ck}) \right] \right) \times (b_w \times d)$$

$$V_{c,a} = \left(2 \times 1 \times \sqrt{2.5} + \text{MIN} \left[\frac{5.321}{6 \times 2304}, (0.05 \times 2.5) \right] \right) \times (48 \times 44.31) = 213.5 \text{ kip}$$

Governing shear strength of concrete:

$$V_c = \text{MIN}[V_{c,max}, V_{c,a}] = \text{MIN}[531.8, 213.5] = 213.5 \text{ kip}$$

22.5.1.2 Shear strength of steel (a):

$$V_{s,a} = 8 \times \sqrt{f'_{ck}} \times b_w \times d = 8 \times \sqrt{2.5} \times 48 \times 44.31 = 850.8 \text{ kip}$$

22.5.8.5.3 Shear strength of steel (b):

$$V_{s,b} = \frac{A_v \times f_{yk} \times d}{s} = \frac{0.221 \times 60 \times 44.31}{10} = 58.73 \text{ kip}$$

Governing shear strength of steel:

$$V_s = \text{MIN}[V_{s,a}, V_{s,b}] = \text{MIN}[850.8, 58.73] = 58.73 \text{ kip}$$

22.5.1.1 Allowable shear strength:

$$\phi V_n = \phi \times (V_c + V_s) = 0.75 \times (213.5 + 58.73) = 204.2 \text{ kip}$$

$$V_{max} = \text{MAX}[8.232, 0.162] = 8.232 \text{ kip}$$

Utilisation

$$\text{Ratio} = \frac{V_{max}}{\phi V_n} = \frac{8.232}{204.2} = 0.04$$

UTILITY: 0.04

Flexural Strength (LRFD)

Concrete type factor (Normal concrete)	$\lambda = 1$
Strength reduction factor for flexure	$\phi = 0.65$
Modulus of steel reinforcement	$E_s = 200 \text{e}3 \text{ ksi}$
Maximum concrete strain	$\epsilon_c = 0.0030$
Yield strain of steel f_y/E_s	$\epsilon_y = 0.0003$
Section width	$b = 48 \text{ in}$
Distance to the compression rebar	$d_c = 3.688 \text{ in}$
Distance to the tension rebar	$d = 44.31 \text{ in}$
Total bar area	$A_s = 4.909 \text{ in}^2$
Maximum applied axial load	$P = 5.321 \text{ kip}$
Maximum moment in the x-direction	$M_{max,x} = 22.53 \text{ kip-ft}$
Maximum moment in the z-direction	$M_{max,z} = 0.412 \text{ kip-ft}$

Compressive force due to concrete:

$$\beta_1 = 0.85$$

$$C_{rc} = 0.85 \times \beta_1 \times f'_c \times b \times c$$

Compressive force due to bars in compression:

$$C_{rs} = f_1 \times A_{sc}$$

$$\epsilon_1 = (c - d_s) \times \frac{\epsilon_c}{c}$$

$$f_1 = E_s \times \epsilon_1 \quad (\epsilon_1 < \epsilon_{sy}), \quad f_1 = f_y \quad (\epsilon_1 \geq \epsilon_{sy})$$

Tensile force due to bars in tension:

$$T_{rs} = f_2 \times A_{st}$$

$$\epsilon_2 = (d - c) \times \frac{\epsilon_{cu}}{c}$$

$$f_2 = E_s \times \epsilon_2 \quad (\epsilon_2 < \epsilon_{sy}), \quad f_2 = \phi_s \times f_y \quad (\epsilon_2 \geq \epsilon_{sy})$$


Interaction Diagram Summary

Point	Case	M _r	P _r
P1	Pure Tension	0	-265.1
P2	Pure Bending	498.4	0
P3	Balanced Failure	1303	2402
P4	Decompression	1077	2629
P5	Compression Limit	982	2694
P6	Pure Compression	0	2694

Uniaxial Bending Check

$$M_f = \text{MAX}[22.53, 0.412] = 22.53 \text{ kip-ft}$$

Interaction Diagram



Segment	Signed Distance
P1 - P2	228.2
P2 - P3	452.9
P3 - P4	2598
P4 - P5	2760
P5 - P6	2688
Status	PASS: Point lies inside the curve

Utilisation

$$\text{Ratio} = \frac{a}{a + b} = \frac{23.15}{23.15 + 532.9} = 0.042$$

UTILITY: 0.04

Biaxial Bending Check

Maximum moment in the x-direction

$$M_{max,x} = 22.53 \text{ kip-ft}$$

Maximum moment in the z-direction

$$M_{max,z} = 0.412 \text{ kip-ft}$$

Nominal uniaxial moment strength about the x-axis

$$M_{nox} = 500.2 \text{ kip-ft}$$

Nominal uniaxial moment strength about the z-axis

$$M_{noz} = 500.2 \text{ kip-ft}$$

Interaction exponent

$$\alpha = 1$$

Bresler (1960)

According to Bresler (method B):

$$\left(\frac{M_{max,x}}{M_{nox}}\right)^\alpha + \left(\frac{M_{max,z}}{M_{noz}}\right)^\alpha = 1.0$$

$$\left(\frac{22.53}{500.2}\right)^1 + \left(\frac{0.412}{500.2}\right)^1 = 0.046$$

UTILITY: 0.05

REFERENCES

CALCULATIONS

RESULTS

Results Summary

Result Name	Results
PILE DETAILS	
Length of the pile	5.75 ft
Dimensions	48 x 48 in
Main bar reinforcement	#5-16pcs at 1.5 in min.
Shear reinforcement	#3 at 10 in max.
UTILISATIONS	
Required depth	0.94
End-bearing capacity	0.12
P _a	0.70
P _s	0.98
Axial compression strength	0.00
Shear strength	0.04
Uniaxial bending strength	0.04
Biaxial bending strength	0.05