

Your Project Calculations



Project Name: MTSOLAR_2CDA147LFL01F

S3D Model Link:

[https://platform.skyciv.com/structural?](https://platform.skyciv.com/structural?preload_name=MTSOLAR_2CDA147LFL01F&preload_path=Shared%20Enterprise%20Folder/MT_Solar_Projects/6_2023)

[preload_name=MTSOLAR_2CDA147LFL01F&preload_path=Shared%20Enterprise%20Folder/MT_Solar_Projects/6_2023](https://platform.skyciv.com/structural?preload_name=MTSOLAR_2CDA147LFL01F&preload_path=Shared%20Enterprise%20Folder/MT_Solar_Projects/6_2023)

Public Model Link:

https://platform.skyciv.com/structural-viewer?project_id=vSKIs1H1A5RsA4kVvEDnObLiYKPGMaOSqcKgYPHK5qRLuwDMZMu1tnWYOjmFPJrU

Array Specification

Product:	Beam
Unique ID:	2P-17-10TOP-XD-45-L-5Hx5W-HI4C
Duty Classification:	XD
Module Width:	39.45 in
Module Length:	79.06in
Number of Rows:	5
Number of Columns:	5
Total Number of Modules:	25
Desired Tilt Angle:	45
Front Edge Clearance:	5
Total Array Height at Tilt:	16.70 ft
Total Frame Length:	32.00 ft
Frame Weight:	3177 lbs
Array Dimensions N/S:	16.65 ft
Array Dimensions E/W:	33.36 ft
Rail Length:	199.75 in
Rail Spacing:	3.29 ft
Rail Check:	Not Checked

Support Specifications


Pole Size:	10in Pipe Sch 80
Pole Length above Grade:	10.89 ft
Number of Poles:	2
Pole Spacing:	17 ft

Foundation Specifications

Foundation Type:	Square
Foundation Dimensions:	48 x 48 in
Foundation Depth (below grade):	Pile 1: 7.50 ft Pile 2: 7.50 ft
Foundation Volume:	8.889 y ³
Foundation Result:	PASSED
Mount Twist:	0.502551 kip

Site Info

Risk Category:	I
Exposure:	C
Soil Classification:	sand
Site Location:	909 W Skyline Pkwy, Duluth, MN 55806, USA
Wind Speed:	99 mph
Snow Load:	60 psf
Design Uplift Pressure:	Multiple pressures
Design Downforce Pressure:	Multiple pressures
Design Snow Pressure:	0.016495 ksf



Design Disclaimer


This software should be used for preliminary designs and should not be used as a final design unless reviewed, verified and designed by a qualified structural engineer.



AutoDesigner Input

```
{"wind_speed_override":null,"snow_load_override":null,"direct_snow_load":false,"product_type":"Beam","project_id":"MTSOLAR_2CDA147LFL01F","site_address":"909 W Skyline Pkwy, Duluth, MN 55806, USA","module_width":39.45,"module_length":79.06,"number_rows":5,"number_columns":5,"pole_mount_section":"4_40","core_pipe_width":65,"core_pipe_section":"2_40","adjuster_section":"2_40","core_beam_height":65,"core_beam_section":"HSS3x2x1/8","main_pipe_section":"2_12GA","pole_spacing":15,"tilt_angle":45,"ground_clearance":5,"risk_category":"I","exposure_category":"C","frame_duty_override":"auto","pole_override":"auto","soil_type":"sand","foundation_type":"Square","foundation_size":48,"check_rails":false}
```



Design Notes:



- AISC Deflection checks are set to L/1 due to structure design intent
- Foundation Design and Sizing is approximate only






FEM Results (Envelope Worst Case for each member)







Reaction Forces for Foundation 1 (Node ID#1), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	0.0000	2.6175	-0.0025	-0.0012	0.0706	0.0246
ULS: 2. D + L	0.0000	2.6175	-0.0025	-0.0012	0.0706	0.0246
ULS: 3. D + (S or Lr or R)	0.0000	5.7239	-0.0069	-0.0022	0.2021	0.0345
ULS: 3. D + (S or Lr or R)	0.0000	2.6175	-0.0025	-0.0012	0.0706	0.0246
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0000	4.9473	-0.0058	-0.0020	0.1692	0.0320
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0000	2.6175	-0.0025	-0.0012	0.0706	0.0246
ULS: 5b. D + 0.7E	0.0000	2.6175	-0.0025	-0.0012	0.0706	0.0246
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	0.0000	4.9473	-0.0058	-0.0020	0.1692	0.0320
ULS: 8. 0.6D + 0.7E	0.0000	1.5705	-0.0015	-0.0007	0.0424	0.0148
ULS: 5a. D + 0.6W_Wind downforce Case A only	-4.0970	6.7145	-0.0348	-0.0628	0.2817	46.2647
ULS: 5a. D + 0.6W_Wind downforce Case B only	-4.0970	6.7145	-0.0348	-0.0628	0.2817	46.2647
ULS: 5a. D + 0.6W_Wind uplift Case A only	2.9638	-0.3462	0.0207	0.0432	-0.0819	-31.1903
ULS: 5a. D + 0.6W_Wind uplift Case B only	2.6151	0.0025	0.0181	0.0381	-0.0646	-35.7001
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-3.0727	8.0200	-0.0300	-0.0482	0.3275	34.7121
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-3.0727	8.0200	-0.0300	-0.0482	0.3275	34.7121
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	2.2228	2.7245	0.0116	0.0313	0.0548	-23.3792
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.9613	2.9860	0.0097	0.0275	0.0678	-26.7615
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-3.0727	5.6903	-0.0267	-0.0474	0.2289	34.7047
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-3.0727	5.6903	-0.0267	-0.0474	0.2289	34.7047
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	2.2228	0.3947	0.0149	0.0321	-0.0438	-23.3866
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.9613	0.6562	0.0130	0.0283	-0.0308	-26.7689
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-4.0970	5.6675	-0.0338	-0.0623	0.2535	46.2549
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-4.0970	5.6675	-0.0338	-0.0623	0.2535	46.2549
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	2.9638	-1.3932	0.0217	0.0436	-0.1101	-31.2002
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	2.6151	-1.0446	0.0191	0.0386	-0.0929	-35.7100

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	11.5253
Shear X	-6.8283
Shear Z	-0.0591
Moment X	-0.1045
Moment Y (Twist)	0.5028
Moment Z	77.4570

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	8.0200
Shear X	-4.0970
Shear Z	-0.0348
Moment X	-0.0628
Moment Y (Twist)	0.3275
Moment Z	46.2647

Reaction Forces for Foundation 2 (Node ID#101), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	-0.0000	2.6175	0.0025	0.0012	-0.0706	0.0246
ULS: 2. D + L	-0.0000	2.6175	0.0025	0.0012	-0.0706	0.0246
ULS: 3. D + (S or Lr or R)	-0.0000	5.7239	0.0069	0.0023	-0.2021	0.0345
ULS: 3. D + (S or Lr or R)	-0.0000	2.6175	0.0025	0.0012	-0.0706	0.0246
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0000	4.9473	0.0058	0.0020	-0.1692	0.0320
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0000	2.6175	0.0025	0.0012	-0.0706	0.0246
ULS: 5b. D + 0.7E	-0.0000	2.6175	0.0025	0.0012	-0.0706	0.0246

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	-0.0000	4.9473	0.0058	0.0020	-0.1692	0.0320
ULS: 8. 0.6D + 0.7E	-0.0000	1.5705	0.0015	0.0007	-0.0423	0.0148
ULS: 5a. D + 0.6W_Wind downforce Case A only	-4.0970	6.7145	0.0348	0.0628	-0.2817	46.2648
ULS: 5a. D + 0.6W_Wind downforce Case B only	-4.0970	6.7145	0.0348	0.0628	-0.2817	46.2648
ULS: 5a. D + 0.6W_Wind uplift Case A only	2.9638	-0.3462	-0.0207	-0.0431	0.0819	-31.1903
ULS: 5a. D + 0.6W_Wind uplift Case B only	2.6151	0.0025	-0.0181	-0.0381	0.0646	-35.7001
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-3.0727	8.0200	0.0300	0.0482	-0.3275	34.7121
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-3.0727	8.0200	0.0300	0.0482	-0.3275	34.7121
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	2.2228	2.7245	-0.0116	-0.0313	-0.0548	-23.3792
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.9613	2.9860	-0.0097	-0.0275	-0.0678	-26.7615
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-3.0727	5.6903	0.0267	0.0474	-0.2289	34.7047
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-3.0727	5.6903	0.0267	0.0474	-0.2289	34.7047
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	2.2228	0.3947	-0.0149	-0.0321	0.0438	-23.3866
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.9613	0.6562	-0.0130	-0.0283	0.0308	-26.7689
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-4.0970	5.6675	0.0338	0.0623	-0.2535	46.2549
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-4.0970	5.6675	0.0338	0.0623	-0.2535	46.2549
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	2.9638	-1.3932	-0.0217	-0.0436	0.1101	-31.2002
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	2.6151	-1.0446	-0.0191	-0.0386	0.0929	-35.7100

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	11.5254
Shear X	-6.8283
Shear Z	0.0591
Moment X	0.1049
Moment Y (Twist)	0.5026
Moment Z	77.4579

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	8.0200
Shear X	-4.0970
Shear Z	0.0348
Moment X	0.0628
Moment Y (Twist)	0.3275
Moment Z	46.2648

Project Details

Design Code: AISC 360-16 LRFD
 Provision: LRFD
 Country: United States
 User Name: sales@mtsolar.us
 Unit System: imperial



Design Input Information


Design Factors			
Φ_t	Φ_c	Φ_b	Φ_v
0.9	0.9	0.9	0.9

Design Materials			
ID	E (ksi)	F_y (ksi)	F_u (ksi)
1	29000	50	65

Section Dimensions



ID	Name	d (in)	t_w (in)				
3	2in Pipe Sch 120	2.38	0.25				
6	4in Pipe Sch 120	4.50	0.44				
12	10in Pipe Sch 80	10.75	0.59				



ID	Name	d (in)	b (in)	t_w (in)	t_b (in)	r (in)	
17	HSS5x3x1/4	5.00	3.00	0.23	0.23	0.23	



ID	Name	d (in)	t_w (in)	b_t (in)	b_b (in)	t_t (in)	t_b (in)	r (in)
20	W10x12	9.87	0.19	3.96	3.96	0.21	0.21	0.30

Section Properties

ID	Name	A (in ²)	J (in ⁴)	I_{yp} (in ⁴)	I_{zp} (in ⁴)	I_w (in ⁶)	S_{yp} (in ³)	S_{zp} (in ³)
3	2in Pipe Sch 120	1.67	1.91	0.96	0.96	0.00	1.13	1.13
6	4in Pipe Sch 120	5.58	23.29	11.64	11.64	0.00	7.24	7.24
12	10in Pipe Sch 80	18.92	489.69	244.84	244.84	0.00	61.25	61.25

115	159.30	104.63	32.89	6.46	56.26	44.91
116	159.30	104.63	32.89	6.46	56.26	44.91


Design Ratio

Member ID	P	M _z	M _y	V _y	V _z	(P,M _z ,M _y)	Worst LC	KL/r	δ	Status
1	0.021	0.337	0.002	0.027	0.000	0.348	#13	0.381	Not Required	Pass
2	0.002	0.334	0.248	0.072	0.047	0.582	#13	0.036	Not Required	Pass
3	0.008	0.612	0.057	0.061	0.012	0.645	#13	0.046	Not Required	Pass
4	0.008	0.552	0.122	0.055	0.027	0.593	#13	0.082	Not Required	Pass
5	0.008	0.379	0.125	0.061	0.031	0.394	#13	0.076	Not Required	Pass
6	0.009	0.587	0.059	0.058	0.012	0.620	#13	0.046	Not Required	Pass
7	0.009	0.365	0.119	0.058	0.031	0.380	#13	0.076	Not Required	Pass
8	0.000	0.041	0.095	0.030	0.016	0.128	#21	0.102	Not Required	Pass
9	0.008	0.045	0.048	0.001	0.000	0.095	#13	0.206	Not Required	Pass
10	0.009	0.528	0.118	0.053	0.027	0.578	#13	0.082	Not Required	Pass
11	0.000	0.045	0.093	0.034	0.016	0.129	#21	0.102	Not Required	Pass
12	0.002	0.314	0.230	0.070	0.044	0.544	#13	0.036	Not Required	Pass
13	0.006	0.193	0.359	0.046	0.022	0.498	#21	0.306	Not Required	Pass
14	0.007	0.180	0.359	0.042	0.022	0.491	#21	0.204	Not Required	Pass
15	0.000	0.060	0.167	0.027	0.013	0.214	#21	Not Required	Not Required	Pass
16	0.000	0.054	0.167	0.024	0.013	0.211	#21	Not Required	Not Required	Pass
101	0.021	0.337	0.002	0.027	0.000	0.348	#13	0.381	Not Required	Pass
102	0.002	0.314	0.230	0.070	0.044	0.544	#13	0.036	Not Required	Pass
103	0.009	0.587	0.059	0.058	0.012	0.620	#13	0.046	Not Required	Pass
104	0.009	0.528	0.118	0.053	0.027	0.578	#13	0.082	Not Required	Pass
105	0.009	0.365	0.119	0.058	0.031	0.380	#13	0.076	Not Required	Pass
106	0.008	0.612	0.057	0.061	0.012	0.646	#13	0.046	Not Required	Pass
107	0.008	0.379	0.125	0.061	0.031	0.394	#13	0.076	Not Required	Pass
108	0.000	0.054	0.167	0.024	0.013	0.211	#21	Not Required	Not Required	Pass
109	0.008	0.045	0.048	0.001	0.000	0.095	#13	0.206	Not Required	Pass
110	0.008	0.552	0.122	0.055	0.027	0.593	#13	0.082	Not Required	Pass
111	0.000	0.060	0.167	0.027	0.013	0.214	#21	Not Required	Not Required	Pass
112	0.002	0.334	0.248	0.072	0.047	0.582	#13	0.036	Not Required	Pass
113	0.006	0.193	0.359	0.046	0.022	0.498	#21	0.204	Not Required	Pass
114	0.007	0.180	0.359	0.042	0.022	0.491	#21	0.306	Not Required	Pass
115	0.000	0.100	0.180	0.034	0.016	0.259	#21	0.370	Not Required	Pass
116	0.000	0.091	0.181	0.030	0.016	0.255	#21	0.370	Not Required	Pass

Definitions

Φ_t	Safety factor for tensile
Φ_c	Safety factor for compression
Φ_b	Safety factor for flexure
Φ_v	Safety factor for shear
E	Modulus of elasticity
F _y	Specified minimum yield stress
F _u	Specified minimum tensile strength
A	Cross-sectional area
J	Torsional constant
I _{yp}	Moment of inertia about the Y axes
I _{zp}	Moment of inertia about the Z axes
I _w	Warping constant
S _{yp}	Plastic section modulus about the Y axis
S _{zp}	Plastic section modulus about the Z axis
KL	Effective length
C _b	Buckling modification factor (from all load combinations)
L _b	Length between braced points

L	Length between brace points
LST	Limited slenderness for tension
LSC	Limited slenderness for compression
LD	Limited deflection
P_n	Nominal axial strength (tension/compression)
M_n	Nominal flexural strength (about Z/Y axis)
V_n	Nominal shear strength (along Z/Y axis)
P	Design ratio in case of axial force
M_z	Design ratio in case of bending about Z axis
M_y	Design ratio in case of bending about Y axis
V_y	Design ratio in case of shear along Y axis
V_z	Design ratio in case of shear along Z axis
(P, M_z , M_y)	Design ratio in case of axial force and bending action
KL/r	Design ratio in case of section slenderness
δ	Design ratio in case of member deflection
OK	Capacity is provided
NG	Capacity is not provided

REFERENCES	CALCULATIONS	RESULTS																										
	<p>SkyCiv Foundation Design Pile Foundation</p> <p>Design Information : Design code : IBC 2021 (International Building Code) Unit System : Imperial</p>																											
	<p>Pile Input</p>  <p>Geometry Pile shape: rectangular $b = 48$ in - Pile width $D = 48$ in - Pile depth $L = 7.5$ ft - Total pile length $h_1 = 0$ ft - Lateral load height from the top of the pile, $h_2 = 0$ ft - Depth to resting surface $h_e = 0$ ft - Length of pile above the ground</p> <p>Tabulation of Soil Parameters</p> <table border="1" data-bbox="416 1102 1193 1191"> <thead> <tr> <th>Layer</th> <th>Label</th> <th>Allowable Bearing Pressure (q_a) (psf)</th> <th>Allowable Lateral Pressure (R) (psf/ft)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Sand, silty sand, clayey sand, silty gravel & clayey gravel</td> <td>2000.000</td> <td>150.000</td> </tr> </tbody> </table> <p>Tabulation of Loads</p> <table border="1" data-bbox="676 1285 935 1458"> <thead> <tr> <th>Load Component</th> <th>ASD</th> <th>LRFD</th> </tr> </thead> <tbody> <tr> <td>P (kip)</td> <td>8.020</td> <td>11.525</td> </tr> <tr> <td>V_x (kip)</td> <td>-4.097</td> <td>-6.828</td> </tr> <tr> <td>V_z (kip)</td> <td>-0.035</td> <td>-0.059</td> </tr> <tr> <td>M_x (kipft)</td> <td>-0.063</td> <td>-0.105</td> </tr> <tr> <td>M_z (kipft)</td> <td>46.265</td> <td>77.457</td> </tr> </tbody> </table> <p>Material Properties $f'_{ck} = 3$ ksi - Concrete strength,</p>	Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)	1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000	Load Component	ASD	LRFD	P (kip)	8.020	11.525	V_x (kip)	-4.097	-6.828	V_z (kip)	-0.035	-0.059	M_x (kipft)	-0.063	-0.105	M_z (kipft)	46.265	77.457	
Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)																									
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000																									
Load Component	ASD	LRFD																										
P (kip)	8.020	11.525																										
V_x (kip)	-4.097	-6.828																										
V_z (kip)	-0.035	-0.059																										
M_x (kipft)	-0.063	-0.105																										
M_z (kipft)	46.265	77.457																										
	<p>Required depth to resist lateral loads (ASD) H - Point of application of the lateral load</p> $H = h_1 + h_2 + h_e$ $H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$ $H = 0 \text{ ft}$ <p>Considering x-direction: H_o - Lateral force per length of pile,</p> $H_o = \frac{V_x}{1.57 D}$ $H_o = \frac{(-4.097 \text{ kip})}{1.57 \times (48 \text{ in})}$ $H_o = -0.65239 \text{ kip/ft}$ <p>M_o - Moment per length of pile,</p> $M_o = \frac{M_z + (V_x H)}{1.57 D}$																											

$$M_o = \frac{(46.265 \text{ kipft}) + ((-4.097 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 7.367 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$$

Solving the cubic equation:

$L_{e,x} = 6.849 \text{ ft}$ - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.035 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.0055732 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.063 \text{ kipft}) + ((-0.035 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.010032 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$$

Solving the cubic equation:

$L_{e,z} = 0.81011 \text{ ft}$ - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = \text{MAX}[(6.849 \text{ ft}), (0.81011 \text{ ft})]$$

$$L_{e,req} = 6.849 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_c - h_2$$

$$L_e = (7.5 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 7.5 \text{ ft}$$

Ratio - Embedded depth

$$\text{Ratio} = \frac{L_{e,req}}{L_e}$$

$$\text{Ratio} = \frac{(6.849 \text{ ft})}{(7.5 \text{ ft})}$$

$$\text{Ratio} = 0.9132$$

Status: **PASS**
Ratio: **0.910**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_c}{A}$$

$$q = \frac{(8.02 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.50125 \text{ kip/ft}^2$$

$$q = 0.00125 \text{ kip/ft}$$

Check bearing capacity ratio:

Ratio - Capacity

$$\text{Ratio} = \frac{q}{q_a}$$

$$\text{Ratio} = \frac{(0.50125 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$\text{Ratio} = 0.25062$$

Status: **PASS**
Ratio: **0.250**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(7.5 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1.875$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.65239 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 7.367 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (7.367 \text{ kipft/ft}) \times (7.5 \text{ ft})) + (3 \times (-0.65239 \text{ kip/ft}) \times (7.5 \text{ ft})^2)}{(6 \times (7.367 \text{ kipft/ft})) + (4 \times (-0.65239 \text{ kip/ft}) \times (7.5 \text{ ft}))}$$

$$a = 5.1918 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 [(4 \times (7.367 \text{ kipft/ft})) + (3 \times (-0.65239 \text{ kip/ft}) \times (7.5 \text{ ft}))]^2}{(7.5 \text{ ft})^2 [(3 \times (7.367 \text{ kipft/ft})) + (2 \times (-0.65239 \text{ kip/ft}) \times (7.5 \text{ ft}))]}$$

$$p = 0.23681 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (7.367 \text{ kipft/ft})) + ((-0.65239 \text{ kip/ft}) \times (7.5 \text{ ft}))]}{(7.5 \text{ ft})^2}$$

$$s = 1.0497 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(5.1918 \text{ ft})}{2}$$

$$p_a = 0.38939 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{p}{p_a}$$

$$\text{Ratio} = \frac{(0.23681 \text{ kip/ft}^2)}{(0.38939 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.60816$$

p_a - Allowable lateral soil pressure at depth L_e ,

Status: **PASS**
Ratio: **0.610**

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (7.5 \text{ ft})$$

$$p_s = 1.125 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{s}{p_s}$$

$$\text{Ratio} = \frac{(1.0497 \text{ kip/ft}^2)}{(1.125 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.93309$$

Status: **PASS**
Ratio: **0.930**

Considering z-direction:

$H_o = -0.0055732 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.010032 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.010032 \text{ kipft/ft}) \times (7.5 \text{ ft})) + (3 \times (-0.0055732 \text{ kip/ft}) \times (7.5 \text{ ft})^2)}{(6 \times (0.010032 \text{ kipft/ft})) + (4 \times (-0.0055732 \text{ kip/ft}) \times (7.5 \text{ ft}))}$$

$$a = 5.4596 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (0.010032 \text{ kipft/ft})) + (3 \times (-0.0055732 \text{ kip/ft}) \times (7.5 \text{ ft}))]^2}{(7.5 \text{ ft})^2 \times [(3 \times (0.010032 \text{ kipft/ft})) + (2 \times (-0.0055732 \text{ kip/ft}) \times (7.5 \text{ ft}))]}$$

$$p = -0.001812 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.010032 \text{ kipft/ft})) + ((-0.0055732 \text{ kip/ft}) \times (7.5 \text{ ft}))]}{(7.5 \text{ ft})^2}$$

$$s = -0.0023185 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(5.4596 \text{ ft})}{2}$$

$$p_a = 0.40947 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{p}{p_a}$$

$$\text{Ratio} = \frac{(-0.001812 \text{ kip/ft}^2)}{(0.40947 \text{ kip/ft}^2)}$$

$$\text{Ratio} = -0.0044253$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (7.5 \text{ ft})$$

$$p_s = 1.125 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity


$$\text{Ratio} = \frac{s}{p_s}$$

Status: **PASS**
Ratio: **0.000**

$$\text{Ratio} = \frac{(-0.0023185 \text{ kip/ft}^2)}{(1.125 \text{ kip/ft}^2)}$$

$$\text{Ratio} = -0.0020609$$

Status: **PASS**
Ratio: **0.000**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_e}{1.57 D}$$

$$H_o = \frac{(-6.828 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -1.0873 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(77.457 \text{ kipft}) + ((-6.828 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 12.334 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(12.334 \text{ kipft/ft})}{(-1.0873 \text{ kip/ft})}$$

$$E = 11.344 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_c) + (3 H_o L_c^2)}{(6 M_o) + (4 H_o L_c)}$$

$$a = \frac{(4 \times (12.334 \text{ kipft/ft}) \times (7.5 \text{ ft})) + (3 \times (-1.0873 \text{ kip/ft}) \times (7.5 \text{ ft})^2)}{(6 \times (12.334 \text{ kipft/ft})) + (4 \times (-1.0873 \text{ kip/ft}) \times (7.5 \text{ ft}))}$$

$$a = 5.1912 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4 E}{L_c} + 3 \right) \left(\frac{a}{L_c} \right)^2 \right] + \left[4 \left(\frac{3 E}{L_c} + 2 \right) \left(\frac{a}{L_c} \right)^3 \right] \right]$$

$$V_{max} = ((-1.0873 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (11.344 \text{ ft})}{(7.5 \text{ ft})} + 3 \right) \times \left(\frac{(5.1912 \text{ ft})}{(7.5 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (11.344 \text{ ft})}{(7.5 \text{ ft})} + 2 \right) \times \left(\frac{(5.1912 \text{ ft})}{(7.5 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 14.508 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right] \right]$$

$$M_{max} = ((-1.0873 \text{ kip/ft}) \times (48 \text{ in}) \times (7.5 \text{ ft})) \times \left[\left(\frac{(11.344 \text{ ft})}{(7.5 \text{ ft})} + \frac{(5.1912 \text{ ft})}{2 \times (7.5 \text{ ft})} \right) - \left[\left(\frac{4 \times (11.344 \text{ ft})}{(7.5 \text{ ft})} + 3 \right) \times \left(\frac{(5.1912 \text{ ft})}{2 \times (7.5 \text{ ft})} \right)^3 + \left[\left(\frac{3 \times (11.344 \text{ ft})}{(7.5 \text{ ft})} + 2 \right) \times \left(\frac{(5.1912 \text{ ft})}{2 \times (7.5 \text{ ft})} \right)^4 \right] \right] \right]$$

$$M_{max} = 51.447 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.059 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.009395 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.105 \text{ kipft}) + ((-0.059 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.01672 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.01672 \text{ kipft/ft})}{(-0.009395 \text{ kip/ft})}$$

$$E = 1.7797 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.01672 \text{ kipft/ft}) \times (7.5 \text{ ft})) + (3 \times (-0.009395 \text{ kip/ft}) \times (7.5 \text{ ft})^2)}{(6 \times (0.01672 \text{ kipft/ft})) + (4 \times (-0.009395 \text{ kip/ft}) \times (7.5 \text{ ft}))}$$

$$a = 5.4609 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 + 4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.009395 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (1.7797 \text{ ft})}{(7.5 \text{ ft})} + 3 \right) \times \left(\frac{(5.4609 \text{ ft})}{(7.5 \text{ ft})} \right)^2 + 4 \times \left(\frac{3 \times (1.7797 \text{ ft})}{(7.5 \text{ ft})} + 2 \right) \times \left(\frac{(5.4609 \text{ ft})}{(7.5 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.041101 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o b L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right] \right]$$

$$M_{max} = ((-0.009395 \text{ kip/ft}) \times (48 \text{ in}) \times (7.5 \text{ ft})) \times \left[\left(\frac{(1.7797 \text{ ft})}{(7.5 \text{ ft})} + \frac{(5.4609 \text{ ft})}{2 \times (7.5 \text{ ft})} \right) - \left[\left(\frac{4 \times (1.7797 \text{ ft})}{(7.5 \text{ ft})} + 3 \right) \times \left(\frac{(5.4609 \text{ ft})}{2 \times (7.5 \text{ ft})} \right)^3 + \left[\left(\frac{3 \times (1.7797 \text{ ft})}{(7.5 \text{ ft})} + 2 \right) \times \left(\frac{(5.4609 \text{ ft})}{2 \times (7.5 \text{ ft})} \right)^4 \right] \right] \right]$$

$$M_{max} = 0.12921 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 3 \text{ ksi}$ - Concrete strength,
 $f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,
 $\phi = 0.65$ - Reduction factor for axial strength,
 $\alpha = 0.8$ - Alpha factor for axial strength,
 $A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Table 22.4.2.1

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

22.4.2.2, 10.6.1.1

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(11.525 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (3 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (3 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -101.88 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-101.88 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

$$\text{Ratio} = 0.96556$$

25.2.3

s_{rebar} - Minimum spacing of reinforcement,

$$s_{rebar} = \text{Max} [1.5, (1.5 d_{bar})]$$

$$s_{rebar} = \text{Max} [1.5, (1.5 \times (0.625 \text{ in}))]$$

$$s_{rebar} = 1.5 \text{ in}$$

Ties:

25.7.2.2 Since longitudinal reinforcement is \leq No. 10: Use #3(0.375 in)

25.7.2.1 s_{ties} - Maximum spacing of ties,

$$s_{ties} = \text{Min} [(16 d_{bar}), (48 d_{ties}), \text{Min} (D, b)]$$

$$s_{ties} = \text{Min} [(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), \text{Min} ((48 \text{ in}), (48 \text{ in}))]$$

$$s_{ties} = 10 \text{ in}$$

Summary:

Main reinforcement: 14 - #5 (0.625 in)

Status: **PASS**
Ratio: **0.970**

Ties: #3(0.375 in) - 10 in

Axial Compression Strength (ACI 318-19, LRFD)

22.4.2.2

ϕP_N - Allowable axial compressive strength

$$\phi P_N = \phi 0.80 \left[(0.85 f'_{ck} [A_g - A_{st}]) + (f_{yk} A_{st}) \right]$$

$$\phi P_N = (0.65) \times 0.80 \times \left[(0.85 \times (3 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2)) \right]$$

$$\phi P_N = 3183.4 \text{ kip}$$

Ratio - Capacity

$$\text{Ratio} = \frac{P}{\phi P_N}$$

$$\text{Ratio} = \frac{(11.525 \text{ kip})}{(3183.4 \text{ kip})}$$

$$\text{Ratio} = 0.0036203$$

Status: **PASS**
Ratio: **0.000**

Shear Strength (ACI 318-19, LRFD)

Parameters:

22.5.2.2

$b_w = 48 \text{ in}$ - Effective width,
 d - Effective depth

$$d = 0.80 D$$

$$d = 0.80 \times (48 \text{ in})$$

$$d = 38.4 \text{ in}$$

22.5.5.1.3

λ_s - size effect modification factor

$$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$$

$$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$$

$$\lambda_s = 0.64282$$

22.5.5.1.1

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$,
 $V_{c,max}$ - Max shear strength of concrete

$$V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$$

$$V_{c,max} = 5 \times (0.64282) \times \sqrt{(3000 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,max} = 324.49 \text{ kip}$$

22.5.5.1.1(a)

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$, $P = 11.525 \text{ kip} \rightarrow 11525 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck}} + \frac{P}{6 A_g} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(3000 \text{ psi})} + \frac{(11525 \text{ lbf})}{6 \times (2304 \text{ in}^2)} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 131.33 \text{ kip}$$

22.5.5.1.2

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck}} + (0.05 f'_{ck}) \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(3000 \text{ psi})} + (0.05 \times (3000 \text{ psi})) \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 406.27 \text{ kip}$$

V_c - Governing shear strength of concrete


$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(324.49 \text{ kip}), (131.33 \text{ kip}), (406.27 \text{ kip})]$$

$$V_c = 131.33 \text{ kip}$$

<p>22.5.1.2</p>	<p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$, $V_{s,a}$ - Shear strength of steel (a)</p> $V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$ $V_{s,a} = 8 \times \sqrt{(3000 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{s,a} = 807.65 \text{ kip}$ <p>A_v - Ties rebar area,</p> $A_v = \frac{\pi d_{ties}^2}{4}$ $A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$ $A_v = 0.11045 \text{ in}^2$ <p>22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)</p> $V_{s,b} = \frac{2 A_v f_{yt} d}{s_{ties}}$ $V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$ $V_{s,b} = 50.894 \text{ kip}$ <p>V_s - Governing shear strength of steel</p> $V_s = \text{MIN}[V_{s,a}, V_{s,b}]$ $V_s = \text{MIN}[(807.65 \text{ kip}), (50.894 \text{ kip})]$ $V_s = 50.894 \text{ kip}$ <p>22.5.1.1 ϕV_n - Allowable shear strength</p> $\phi V_n = \phi (V_c + V_s)$ $\phi V_n = (0.65) \times ((131.33 \text{ kip}) + (50.894 \text{ kip}))$ $\phi V_n = 118.45 \text{ kip}$ <p>Considering x-direction:</p> <p>$V_{max} = 14.508 \text{ kip}$ - Maximum shear force in the x-direction, Ratio - Capacity</p> $\text{Ratio} = \frac{V_{max}}{\phi V_n}$ $\text{Ratio} = \frac{(14.508 \text{ kip})}{(118.45 \text{ kip})}$ $\text{Ratio} = 0.12248$ <p>Considering z-direction:</p> <p>$V_{max} = 0.041101 \text{ kip}$ - Maximum shear force in the z-direction, Ratio - Capacity</p> $\text{Ratio} = \frac{V_{max}}{\phi V_n}$ $\text{Ratio} = \frac{(0.041101 \text{ kip})}{(118.45 \text{ kip})}$ $\text{Ratio} = 0.000347$	<p>Status: PASS Ratio: 0.120</p> <p>Status: PASS Ratio: 0.000</p>
	<p>Flexural Strength (ACI 318-19, LRFD)</p> <p>S_m - Section modulus</p> $S_m = \frac{b D^2}{6}$ $S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$ $S_m = 18432 \text{ in}^3$	

<p>14.5.2.1b</p>	<p>$\lambda = 1$ - Concrete modification factor (Normal concrete), Allowable flexural strength: M_n shall be the lesser of: $\phi M_{n,1}$</p> $\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$ $\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{3\text{ksi}} \times 18432.001\text{in}^3$ $\phi M_{n,1} = 273.423\text{kipft}$ <p>$\phi M_{n,2}$</p> $\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$ $\phi M_{n,2} = (0.65) \times 0.85 \times (3\text{ksi}) \times (18432\text{in}^3)$ $\phi M_{n,2} = 2545.9\text{kipft}$ <p>Therefore, ϕM_n - Allowable flexural strength,</p> $\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$ $\phi M_n = \text{MIN}[(273.42\text{kipft}), (2545.9\text{kipft})]$ $\phi M_n = 273.42\text{kipft}$ <p>Considering x-direction: $M_{max} = 51.447\text{kipft}$ - Maximum moment in the x-direction, Ratio - Capacity</p> $\text{Ratio} = \frac{M_{max}}{\phi M_n}$ $\text{Ratio} = \frac{(51.447\text{kipft})}{(273.42\text{kipft})}$ $\text{Ratio} = 0.18816$	<p>Status: PASS Ratio: 0.190</p>
	<p>Considering z-direction: $M_{max} = 0.12921\text{kipft}$ - Maximum moment in the z-direction, Ratio - Capacity</p> $\text{Ratio} = \frac{M_{max}}{\phi M_n}$ $\text{Ratio} = \frac{(0.12921\text{kipft})}{(273.42\text{kipft})}$ $\text{Ratio} = 0.00047255$	<p>Status: PASS Ratio: 0.000</p>

REFERENCES	CALCULATIONS	RESULTS																										
	<p>SkyCiv Foundation Design Pile Foundation</p> <p>Design Information : Design code : IBC 2021 (International Building Code) Unit System : Imperial</p>																											
	<p>Pile Input</p>  <p>Geometry Pile shape: rectangular $b = 48$ in - Pile width $D = 48$ in - Pile depth $L = 7.5$ ft - Total pile length $h_1 = 0$ ft - Lateral load height from the top of the pile, $h_2 = 0$ ft - Depth to resting surface $h_e = 0$ ft - Length of pile above the ground</p> <p>Tabulation of Soil Parameters</p> <table border="1" data-bbox="416 1102 1193 1191"> <thead> <tr> <th>Layer</th> <th>Label</th> <th>Allowable Bearing Pressure (q_a) (psf)</th> <th>Allowable Lateral Pressure (R) (psf/ft)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Sand, silty sand, clayey sand, silty gravel & clayey gravel</td> <td>2000.000</td> <td>150.000</td> </tr> </tbody> </table> <p>Tabulation of Loads</p> <table border="1" data-bbox="676 1288 933 1458"> <thead> <tr> <th>Load Component</th> <th>ASD</th> <th>LRFD</th> </tr> </thead> <tbody> <tr> <td>P (kip)</td> <td>8.020</td> <td>11.525</td> </tr> <tr> <td>V_x (kip)</td> <td>-4.097</td> <td>-6.828</td> </tr> <tr> <td>V_z (kip)</td> <td>0.035</td> <td>0.059</td> </tr> <tr> <td>M_x (kipft)</td> <td>0.063</td> <td>0.105</td> </tr> <tr> <td>M_z (kipft)</td> <td>46.265</td> <td>77.458</td> </tr> </tbody> </table> <p>Material Properties $f'_{ck} = 3$ ksi - Concrete strength,</p>	Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)	1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000	Load Component	ASD	LRFD	P (kip)	8.020	11.525	V_x (kip)	-4.097	-6.828	V_z (kip)	0.035	0.059	M_x (kipft)	0.063	0.105	M_z (kipft)	46.265	77.458	
Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)																									
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000																									
Load Component	ASD	LRFD																										
P (kip)	8.020	11.525																										
V_x (kip)	-4.097	-6.828																										
V_z (kip)	0.035	0.059																										
M_x (kipft)	0.063	0.105																										
M_z (kipft)	46.265	77.458																										
	<p>Required depth to resist lateral loads (ASD) H - Point of application of the lateral load</p> $H = h_1 + h_2 + h_e$ $H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$ $H = 0 \text{ ft}$ <p>Considering x-direction: H_o - Lateral force per length of pile,</p> $H_o = \frac{V_x}{1.57 D}$ $H_o = \frac{(-4.097 \text{ kip})}{1.57 \times (48 \text{ in})}$ $H_o = -0.65239 \text{ kip/ft}$ <p>M_o - Moment per length of pile,</p> $M_o = \frac{M_z + (V_x H)}{1.57 D}$																											

$$M_o = \frac{(46.265 \text{ kipft}) + ((-4.097 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 7.367 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$$

Solving the cubic equation:

$L_{e,x}$ = 6.849 ft - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.035 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.0055732 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.063 \text{ kipft}) + ((0.035 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.010032 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$$

Solving the cubic equation:

$L_{e,z}$ = 1.0485 ft - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = \text{MAX}[(6.849 \text{ ft}), (1.0485 \text{ ft})]$$

$$L_{e,req} = 6.849 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_e - h_2$$

$$L_e = (7.5 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 7.5 \text{ ft}$$

Ratio - Embedded depth

$$\text{Ratio} = \frac{L_{e,req}}{L_e}$$

$$\text{Ratio} = \frac{(6.849 \text{ ft})}{(7.5 \text{ ft})}$$

$$\text{Ratio} = 0.9132$$

Status: **PASS**
Ratio: **0.910**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_c}{A}$$

$$q = \frac{(8.02 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.50125 \text{ kip/ft}^2$$

$$q = 0.00125 \text{ kip/ft}$$

Check bearing capacity ratio:

Ratio - Capacity

$$\text{Ratio} = \frac{q}{q_a}$$

$$\text{Ratio} = \frac{(0.50125 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$\text{Ratio} = 0.25062$$

Status: **PASS**
Ratio: **0.250**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(7.5 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1.875$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.65239 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 7.367 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (7.367 \text{ kipft/ft}) \times (7.5 \text{ ft})) + (3 \times (-0.65239 \text{ kip/ft}) \times (7.5 \text{ ft})^2)}{(6 \times (7.367 \text{ kipft/ft})) + (4 \times (-0.65239 \text{ kip/ft}) \times (7.5 \text{ ft}))}$$

$$a = 5.1918 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 [(4 \times (7.367 \text{ kipft/ft})) + (3 \times (-0.65239 \text{ kip/ft}) \times (7.5 \text{ ft}))]^2}{(7.5 \text{ ft})^2 [(3 \times (7.367 \text{ kipft/ft})) + (2 \times (-0.65239 \text{ kip/ft}) \times (7.5 \text{ ft}))]}$$

$$p = 0.23681 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 [(2 \times (7.367 \text{ kipft/ft})) + ((-0.65239 \text{ kip/ft}) \times (7.5 \text{ ft}))]}{(7.5 \text{ ft})^2}$$

$$s = 1.0497 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(5.1918 \text{ ft})}{2}$$

$$p_a = 0.38939 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{p}{p_a}$$

$$\text{Ratio} = \frac{(0.23681 \text{ kip/ft}^2)}{(0.38939 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.60816$$

p_a - Allowable lateral soil pressure at depth L_e ,

Status: **PASS**
Ratio: **0.610**

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (7.5 \text{ ft})$$

$$p_s = 1.125 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{s}{p_s}$$

$$\text{Ratio} = \frac{(1.0497 \text{ kip/ft}^2)}{(1.125 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.93309$$

Status: **PASS**
Ratio: **0.930**

Considering z-direction:

$H_o = 0.0055732 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.010032 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.010032 \text{ kipft/ft}) \times (7.5 \text{ ft})) + (3 \times (0.0055732 \text{ kip/ft}) \times (7.5 \text{ ft})^2)}{(6 \times (0.010032 \text{ kipft/ft})) + (4 \times (0.0055732 \text{ kip/ft}) \times (7.5 \text{ ft}))}$$

$$a = 5.4596 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (0.010032 \text{ kipft/ft})) + (3 \times (0.0055732 \text{ kip/ft}) \times (7.5 \text{ ft}))]^2}{(7.5 \text{ ft})^2 \times [(3 \times (0.010032 \text{ kipft/ft})) + (2 \times (0.0055732 \text{ kip/ft}) \times (7.5 \text{ ft}))]}$$

$$p = 0.0032131 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.010032 \text{ kipft/ft})) + ((0.0055732 \text{ kip/ft}) \times (7.5 \text{ ft}))]}{(7.5 \text{ ft})^2}$$

$$s = 0.0065987 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(5.4596 \text{ ft})}{2}$$

$$p_a = 0.40947 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{p}{p_a}$$

$$\text{Ratio} = \frac{(0.0032131 \text{ kip/ft}^2)}{(0.40947 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.0078471$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (7.5 \text{ ft})$$

$$p_s = 1.125 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity


$$\text{Ratio} = \frac{s}{p_s}$$

Status: **PASS**
Ratio: **0.010**

$$\text{Ratio} = \frac{(0.0065987 \text{ kip/ft}^2)}{(1.125 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.0058655$$

Status: **PASS**
Ratio: **0.010**



Shear force and Bending moment (x-direction, LRF)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_e}{1.57 D}$$

$$H_o = \frac{(-6.828 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -1.0873 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(77.458 \text{ kipft}) + ((-6.828 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 12.334 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(12.334 \text{ kipft/ft})}{(-1.0873 \text{ kip/ft})}$$

$$E = 11.344 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (12.334 \text{ kipft/ft}) \times (7.5 \text{ ft})) + (3 \times (-1.0873 \text{ kip/ft}) \times (7.5 \text{ ft})^2)}{(6 \times (12.334 \text{ kipft/ft})) + (4 \times (-1.0873 \text{ kip/ft}) \times (7.5 \text{ ft}))}$$

$$a = 5.1912 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-1.0873 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (11.344 \text{ ft})}{(7.5 \text{ ft})} + 3 \right) \times \left(\frac{(5.1912 \text{ ft})}{(7.5 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (11.344 \text{ ft})}{(7.5 \text{ ft})} + 2 \right) \times \left(\frac{(5.1912 \text{ ft})}{(7.5 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 14.508 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right] \right]$$

$$M_{max} = ((-1.0873 \text{ kip/ft}) \times (48 \text{ in}) \times (7.5 \text{ ft})) \times \left[\left(\frac{(11.344 \text{ ft})}{(7.5 \text{ ft})} + \frac{(5.1912 \text{ ft})}{2 \times (7.5 \text{ ft})} \right) - \left[\left(\frac{4 \times (11.344 \text{ ft})}{(7.5 \text{ ft})} + 3 \right) \times \left(\frac{(5.1912 \text{ ft})}{2 \times (7.5 \text{ ft})} \right)^3 + \left[\left(\frac{3 \times (11.344 \text{ ft})}{(7.5 \text{ ft})} + 2 \right) \times \left(\frac{(5.1912 \text{ ft})}{2 \times (7.5 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 51.448 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.059 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.009395 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.105 \text{ kipft}) + ((0.059 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.01672 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.01672 \text{ kipft/ft})}{(0.009395 \text{ kip/ft})}$$

$$E = 1.7797 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.01672 \text{ kipft/ft}) \times (7.5 \text{ ft})) + (3 \times (0.009395 \text{ kip/ft}) \times (7.5 \text{ ft})^2)}{(6 \times (0.01672 \text{ kipft/ft})) + (4 \times (0.009395 \text{ kip/ft}) \times (7.5 \text{ ft}))}$$

$$a = 5.4609 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 + 4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((0.009395 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (1.7797 \text{ ft})}{(7.5 \text{ ft})} + 3 \right) \times \left(\frac{(5.4609 \text{ ft})}{(7.5 \text{ ft})} \right)^2 + 4 \times \left(\frac{3 \times (1.7797 \text{ ft})}{(7.5 \text{ ft})} + 2 \right) \times \left(\frac{(5.4609 \text{ ft})}{(7.5 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.041101 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o b L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right] \right]$$

$$M_{max} = ((0.009395 \text{ kip/ft}) \times (48 \text{ in}) \times (7.5 \text{ ft})) \times \left[\left(\frac{(1.7797 \text{ ft})}{(7.5 \text{ ft})} + \frac{(5.4609 \text{ ft})}{2 \times (7.5 \text{ ft})} \right) - \left[\left(\frac{4 \times (1.7797 \text{ ft})}{(7.5 \text{ ft})} + 3 \right) \times \left(\frac{(5.4609 \text{ ft})}{2 \times (7.5 \text{ ft})} \right)^3 + \left[\left(\frac{3 \times (1.7797 \text{ ft})}{(7.5 \text{ ft})} + 2 \right) \times \left(\frac{(5.4609 \text{ ft})}{2 \times (7.5 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 0.12921 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 3 \text{ ksi}$ - Concrete strength,
 $f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,
 $\phi = 0.65$ - Reduction factor for axial strength,
 $\alpha = 0.8$ - Alpha factor for axial strength,
 $A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Table 22.4.2.1

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

22.4.2.2, 10.6.1.1

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(11.525 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (3 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (3 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -101.88 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-101.88 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

$$\text{Ratio} = 0.96556$$

Status: **PASS**
Ratio: **0.970**

25.2.3

s_{rebar} - Minimum spacing of reinforcement,

$$s_{rebar} = \text{Max} [1.5, (1.5 d_{bar})]$$

$$s_{rebar} = \text{Max} [1.5, (1.5 \times (0.625 \text{ in}))]$$

$$s_{rebar} = 1.5 \text{ in}$$

Ties:

25.7.2.2 Since longitudinal reinforcement is \leq No. 10: Use #3(0.375 in)

25.7.2.1 s_{ties} - Maximum spacing of ties,

$$s_{ties} = \text{Min} [(16 d_{bar}), (48 d_{ties}), \text{Min} (D, b)]$$

$$s_{ties} = \text{Min} [(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), \text{Min} ((48 \text{ in}), (48 \text{ in}))]$$

$$s_{ties} = 10 \text{ in}$$

Summary:

Main reinforcement: **14 - #5 (0.625 in)**

Ties: #3(0.375 in) - 10 in

Axial Compression Strength (ACI 318-19, LRFD)

22.4.2.2

ϕP_N - Allowable axial compressive strength

$$\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_{yk} A_{st})]$$

$$\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (3 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$$

$$\phi P_N = 3183.4 \text{ kip}$$

Ratio - Capacity

$$\text{Ratio} = \frac{P}{\phi P_N}$$

$$\text{Ratio} = \frac{(11.525 \text{ kip})}{(3183.4 \text{ kip})}$$

$$\text{Ratio} = 0.0036203$$

Status: **PASS**
Ratio: **0.000**

Shear Strength (ACI 318-19, LRFD)

Parameters:

22.5.2.2

$b_w = 48 \text{ in}$ - Effective width,
 d - Effective depth

$$d = 0.80 D$$

$$d = 0.80 \times (48 \text{ in})$$

$$d = 38.4 \text{ in}$$

22.5.5.1.3

λ_s - size effect modification factor

$$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$$

$$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$$

$$\lambda_s = 0.64282$$

22.5.5.1.1

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$,
 $V_{c,max}$ - Max shear strength of concrete

$$V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$$

$$V_{c,max} = 5 \times (0.64282) \times \sqrt{(3000 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,max} = 324.49 \text{ kip}$$

22.5.5.1.1(a)

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$, $P = 11.525 \text{ kip} \rightarrow 11525 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck}} + \frac{P}{6 A_g} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(3000 \text{ psi})} + \frac{(11525 \text{ lbf})}{6 \times (2304 \text{ in}^2)} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 131.33 \text{ kip}$$

22.5.5.1.2

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck}} + (0.05 f'_{ck}) \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(3000 \text{ psi})} + (0.05 \times (3000 \text{ psi})) \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 406.27 \text{ kip}$$

V_c - Governing shear strength of concrete

$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(324.49 \text{ kip}), (131.33 \text{ kip}), (406.27 \text{ kip})]$$

$$V_c = 131.33 \text{ kip}$$

<p>22.5.1.2</p>	<p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$, $V_{s,a}$ - Shear strength of steel (a)</p> $V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$ $V_{s,a} = 8 \times \sqrt{(3000 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{s,a} = 807.65 \text{ kip}$ <p>A_v - Ties rebar area,</p> $A_v = \frac{\pi d_{ties}^2}{4}$ $A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$ $A_v = 0.11045 \text{ in}^2$ <p>22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)</p> $V_{s,b} = \frac{2 A_v f_{yt} d}{s_{ties}}$ $V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$ $V_{s,b} = 50.894 \text{ kip}$ <p>V_s - Governing shear strength of steel</p> $V_s = \text{MIN}[V_{s,a}, V_{s,b}]$ $V_s = \text{MIN}[(807.65 \text{ kip}), (50.894 \text{ kip})]$ $V_s = 50.894 \text{ kip}$ <p>22.5.1.1 ϕV_n - Allowable shear strength</p> $\phi V_n = \phi (V_c + V_s)$ $\phi V_n = (0.65) \times ((131.33 \text{ kip}) + (50.894 \text{ kip}))$ $\phi V_n = 118.45 \text{ kip}$ <p>Considering x-direction:</p> <p>$V_{max} = 14.508 \text{ kip}$ - Maximum shear force in the x-direction, Ratio - Capacity</p> $\text{Ratio} = \frac{V_{max}}{\phi V_n}$ $\text{Ratio} = \frac{(14.508 \text{ kip})}{(118.45 \text{ kip})}$ $\text{Ratio} = 0.12248$ <p>Considering z-direction:</p> <p>$V_{max} = 0.041101 \text{ kip}$ - Maximum shear force in the z-direction, Ratio - Capacity</p> $\text{Ratio} = \frac{V_{max}}{\phi V_n}$ $\text{Ratio} = \frac{(0.041101 \text{ kip})}{(118.45 \text{ kip})}$ $\text{Ratio} = 0.000347$	<p>Status: PASS Ratio: 0.120</p> <p>Status: PASS Ratio: 0.000</p>
	<p>Flexural Strength (ACI 318-19, LRFD)</p> <p>S_m - Section modulus</p> $S_m = \frac{b D^2}{6}$ $S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$ $S_m = 18432 \text{ in}^3$	

<p>14.5.2.1b</p>	<p>$\lambda = 1$ - Concrete modification factor (Normal concrete), Allowable flexural strength: M_n shall be the lesser of: $\phi M_{n,1}$</p> $\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$ $\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{3\text{ksi}} \times 18432.001\text{in}^3$ $\phi M_{n,1} = 273.423\text{kipft}$ <p>$\phi M_{n,2}$</p> $\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$ $\phi M_{n,2} = (0.65) \times 0.85 \times (3\text{ksi}) \times (18432\text{in}^3)$ $\phi M_{n,2} = 2545.9\text{kipft}$ <p>Therefore, ϕM_n - Allowable flexural strength,</p> $\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$ $\phi M_n = \text{MIN}[(273.42\text{kipft}), (2545.9\text{kipft})]$ $\phi M_n = 273.42\text{kipft}$ <p>Considering x-direction: $M_{max} = 51.448\text{kipft}$ - Maximum moment in the x-direction, Ratio - Capacity</p> $\text{Ratio} = \frac{M_{max}}{\phi M_n}$ $\text{Ratio} = \frac{(51.448\text{kipft})}{(273.42\text{kipft})}$ $\text{Ratio} = 0.18816$	<p>Status: PASS Ratio: 0.190</p>
	<p>Considering z-direction: $M_{max} = 0.12921\text{kipft}$ - Maximum moment in the z-direction, Ratio - Capacity</p> $\text{Ratio} = \frac{M_{max}}{\phi M_n}$ $\text{Ratio} = \frac{(0.12921\text{kipft})}{(273.42\text{kipft})}$ $\text{Ratio} = 0.00047255$	<p>Status: PASS Ratio: 0.000</p>