


Project Details



Project Name: MTSOLAR_09F979EDFCK45 **Date:** Tue Nov 26 2024
Location: Rd 26.7 Lp, Colorado 81321, USA **Number of Modules:** 20
Unique ID: 2P-15-6TOP-SD-45-L-4Hx5W-5F3E **Number of Poles:** 2
Dealer: _____ **Date Sold:** _____



Array Dimensions N/S	13.87 ft
Array Dimensions E/W	31.25 ft
Winter Tilt Angle	50
Front Edge Clearance	5 ft


MT Solar Bill of Materials (2P-15-6TOP-SD-45-L-4Hx5W-5F3E)

Part	Short Description	BOM Qty
MTS-PC-6	6IN Pole Cap Assembly	2
MTS-HF-SD	H-Frame Assembly-SD	2
MTS-SD-Wing-45	45IN SD Wing	4
MTS-SD-Splice-90	90IN SD Splice	2
MTS-CLAMP-HOOK-4PK	Hook Clamp	5

Rail Bill of Materials

Part	Qty
Rails (164in)	10
Rail Attachment	20
Module Mid Clamp	30
Module End Clamp	20
Ground Lug	5

Site Details:



Site Address: Rd 26.7 Lp, Colorado 81321, USA

Array Specification

Duty Classification:	SD
Module Width:	41.10 in
Module Length:	74.00in
Number of Rows:	4
Number of Columns:	5
Total Number of Modules:	20
Winter Tilt Angle:	50
Front Edge Clearance:	5
Total Array Height at Tilt:	15.62 ft
Total Frame Length:	30.00 ft
Frame Weight:	1626 lbs
Array Dimensions N/S:	13.87 ft
Array Dimensions E/W:	31.25 ft
Rail Length:	166.40 in
Rail Spacing:	3.13 ft

Support Specifications

Pole Size:	6in Pipe Sch 40
Pole Length above Grade:	10.31 ft
Number of Poles:	2
Pole Spacing:	15 ft

Foundation Specifications

Foundation Type:	Square
Foundation Dimensions:	48 x 48 in
Foundation Depth (below grade):	Pile 1: 5.50 ft Pile 2: 5.50 ft
Foundation Volume:	6.519 y ³

Site Info

Risk Category:	I
Exposure:	C
Soil Classification:	sand
Site Location:	Rd 26.7 Lp, Colorado 81321, USA
Wind Speed:	98 mph
Snow Load:	30 psf

Design Disclaimer



This software should be used for preliminary designs and should not be used as a final design unless reviewed, verified and designed by a qualified structural engineer.



AutoDesigner Input


```
{ "wind_speed_override": null, "snow_load_override": null, "direct_snow_load": false, "add_angle_brace": false, "product_type": "Beam", "designer_name": "dusty bender", "designer_email": "dusty@shawsolar.com", "designer_phone": "9707991806", "project_id": "MTSOLAR_09F979EDFCK45", "site_address": "Rd 26.7 Lp, Colorado 81321, USA", "module_width": 41.1, "module_length": 74, "number_rows": 4, "number_columns": 5, "pole_mount_section": "4_40", "core_pipe_width": 65, "core_pipe_section": "2_40", "adjuster_section": "2_40", "core_beam_height": 65, "core_beam_section": "HSS3x2x1/8", "main_pipe_section": "2_12GA", "pole_spacing": "15", "tilt_angle": 50, "ground_clearance": 5, "risk_category": "I", "exposure_category": "C", "frame_duty_override": "auto", "pole_override": "auto", "soil_type": "sand", "customer_foundation_override": "48_Square", "foundation_type": "Square", "foundation_size": 48, "check_rails": false }
```

Design Notes:



- AISC Deflection checks are set to L/1 due to structure design intent
- Foundation Soil Parameters used in this Autodesign are all estimates, proper geotechnical reports are required to confirm soil profiles
- Wind speeds, snow loads and other site specific results are based on ASCE 7 2016
- Steel frame design checks are based on AISC 360 2016 (LRFD)
- Foundation Design and Sizing is approximate only










FEM Results (Envelope Worst Case for each member)







Reaction Forces for Foundation 1 (Node ID#1), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	0.0000	1.6343	-0.0263	-0.0834	0.0584	0.0154
ULS: 2. D + L	0.0000	1.6343	-0.0263	-0.0834	0.0584	0.0154
ULS: 3. D + (S or Lr or R)	0.0000	2.5164	-0.0442	-0.1402	0.0981	0.0169
ULS: 3. D + (S or Lr or R)	0.0000	1.6343	-0.0263	-0.0834	0.0584	0.0154
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0000	2.2958	-0.0398	-0.1260	0.0882	0.0165
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0000	1.6343	-0.0263	-0.0834	0.0584	0.0154
ULS: 5b. D + 0.7E	0.0000	1.6343	-0.0263	-0.0834	0.0584	0.0154
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	0.0000	2.2958	-0.0398	-0.1260	0.0882	0.0165
ULS: 8. 0.6D + 0.7E	0.0000	0.9806	-0.0158	-0.0501	0.0350	0.0093
ULS: 5a. D + 0.6W_Wind downforce Case A only	-1.6785	3.0427	-0.0836	-0.2610	0.2497	17.5815
ULS: 5a. D + 0.6W_Wind downforce Case B only	0.0000	1.6343	-0.0263	-0.0834	0.0584	0.0154
ULS: 5a. D + 0.6W_Wind uplift Case A only	1.6785	0.2258	0.0309	0.0936	-0.1332	-17.0422
ULS: 5a. D + 0.6W_Wind uplift Case B only	0.0000	1.6343	-0.0263	-0.0834	0.0584	0.0154
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-1.2589	3.3522	-0.0827	-0.2592	0.2316	13.1910
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	0.0000	2.2958	-0.0398	-0.1260	0.0882	0.0165
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.2589	1.2395	0.0032	0.0068	-0.0555	-12.7767
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.0000	2.2958	-0.0398	-0.1260	0.0882	0.0165
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-1.2589	2.6906	-0.0693	-0.2166	0.2019	13.1900
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	0.0000	1.6343	-0.0263	-0.0834	0.0584	0.0154
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.2589	0.5779	0.0166	0.0494	-0.0853	-12.7778
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.0000	1.6343	-0.0263	-0.0834	0.0584	0.0154
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-1.6785	2.3890	-0.0730	-0.2276	0.2263	17.5753
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	0.0000	0.9806	-0.0158	-0.0501	0.0350	0.0093
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	1.6785	-0.4279	0.0415	0.1270	-0.1566	-17.0484
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	0.0000	0.9806	-0.0158	-0.0501	0.0350	0.0093

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	4.7495
Shear X	-2.7975
Shear Z	-0.1359
Moment X	-0.4248
Moment Y (Twist)	0.4079
Moment Z	29.7809

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	3.3522
Shear X	-1.6785
Shear Z	-0.0836
Moment X	-0.2610
Moment Y (Twist)	0.2497
Moment Z	17.5815

Reaction Forces for Foundation 2 (Node ID#101), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	-0.0000	1.6343	0.0263	0.0835	-0.0584	0.0154
ULS: 2. D + L	-0.0000	1.6343	0.0263	0.0835	-0.0584	0.0154
ULS: 3. D + (S or Lr or R)	-0.0000	2.5164	0.0442	0.1402	-0.0981	0.0169
ULS: 3. D + (S or Lr or R)	-0.0000	1.6343	0.0263	0.0835	-0.0584	0.0154
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0000	2.2958	0.0398	0.1260	-0.0882	0.0165

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0000	1.6343	0.0263	0.0835	-0.0584	0.0154
ULS: 5b. D + 0.7E	-0.0000	1.6343	0.0263	0.0835	-0.0584	0.0154
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	-0.0000	2.2958	0.0398	0.1260	-0.0882	0.0165
ULS: 8. 0.6D + 0.7E	-0.0000	0.9806	0.0158	0.0501	-0.0350	0.0093
ULS: 5a. D + 0.6W_Wind downforce Case A only	-1.6785	3.0427	0.0836	0.2610	-0.2497	17.5815
ULS: 5a. D + 0.6W_Wind downforce Case B only	-0.0000	1.6343	0.0263	0.0835	-0.0584	0.0154
ULS: 5a. D + 0.6W_Wind uplift Case A only	1.6785	0.2258	-0.0309	-0.0936	0.1332	-17.0422
ULS: 5a. D + 0.6W_Wind uplift Case B only	-0.0000	1.6343	0.0263	0.0835	-0.0584	0.0154
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-1.2589	3.3522	0.0827	0.2592	-0.2316	13.1910
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.0000	2.2958	0.0398	0.1260	-0.0882	0.0165
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.2589	1.2395	-0.0032	-0.0068	0.0555	-12.7767
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	-0.0000	2.2958	0.0398	0.1260	-0.0882	0.0165
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-1.2589	2.6906	0.0693	0.2166	-0.2019	13.1900
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.0000	1.6343	0.0263	0.0835	-0.0584	0.0154
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.2589	0.5779	-0.0166	-0.0494	0.0853	-12.7778
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	-0.0000	1.6343	0.0263	0.0835	-0.0584	0.0154
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-1.6785	2.3890	0.0730	0.2276	-0.2263	17.5753
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-0.0000	0.9806	0.0158	0.0501	-0.0350	0.0093
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	1.6785	-0.4279	-0.0415	-0.1270	0.1566	-17.0484
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	-0.0000	0.9806	0.0158	0.0501	-0.0350	0.0093

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	4.7495
Shear X	-2.7975
Shear Z	0.1359
Moment X	0.4247
Moment Y (Twist)	0.4082
Moment Z	29.7815

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	3.3522
Shear X	-1.6785
Shear Z	0.0836
Moment X	0.2610
Moment Y (Twist)	0.2497
Moment Z	17.5815

Project Details

Design Code: AISC 360-16 LRFD
 Provision: LRFD
 Country: United States
 User Name: sales@mtsolar.us
 Unit System: imperial




Design Input Information


Design Factors			
Φ_t	Φ_c	Φ_b	Φ_v
0.9	0.9	0.9	0.9

Design Materials			
ID	E (ksi)	F_y (ksi)	F_u (ksi)
1	29000	50	65


Section Dimensions



ID	Name	d (in)	t_w (in)				
1	2in Pipe Sch 40	2.38	0.15				
4	4in Pipe Sch 40	4.50	0.24				
7	6in Pipe Sch 40	6.63	0.28				



ID	Name	d (in)	b (in)	t_w (in)	t_b (in)	r (in)	
15	HSS5x3x1/8	5.00	3.00	0.12	0.12	0.12	



ID	Name	d (in)	t_w (in)	b_t (in)	b_b (in)	t_t (in)	t_b (in)	r (in)
18	W6x9	5.90	0.17	3.94	3.94	0.21	0.21	0.25

Section Properties

ID	Name	A (in ²)	J (in ⁴)	I_{yp} (in ⁴)	I_{zp} (in ⁴)	I_w (in ⁶)	S_{yp} (in ³)	S_{zp} (in ³)
----	------	----------------------	----------------------	-----------------------------	-----------------------------	--------------------------	-----------------------------	-----------------------------

1	2in Pipe Sch 40	1.07	1.33	0.67	0.67	0.00	0.76	0.76
4	4in Pipe Sch 40	3.17	14.47	7.23	7.23	0.00	4.31	4.31
7	6in Pipe Sch 40	5.58	56.28	28.14	28.14	0.00	11.28	11.28
15	HSS5x3x1/8	1.77	6.02	2.75	6.03	0.51	2.07	2.93
18	W6x9	2.68	0.04	2.20	16.40	17.70	1.72	6.23

Member Properties									
Member ID	Section ID	K _z L (ft)	K _y L (ft)	L _b (ft)	C _b	LS T	LS C	L D	
1	7	21.65	21.65	10.31	-	30	20	0	1
2	4	2.00	1.30	2.00	-	30	20	0	1
3	15	0.92	0.92	1.42	1.19,1.19,1.19,1.18,1.19,1.19,1.18,1.19,1.18,1.19,1.18,1.19,1.18,1.19,1.18,1.27,1.18,1.18,1.19,1.17,1.19,1.18,1.19,1.18,1.19	30	20	0	1
4	15	2.44	2.44	3.75	1.68,1.68,1.68,1.68,1.68,1.68,1.67,1.68,1.66,1.68,1.67,1.68,1.66,1.68,1.67,1.68,1.66,1.68,1.67,1.68,1.87,1.68,1.67,1.68,1.65,1.68,1.67,1.68,1.66,1.68	30	20	0	1
5	15	1.52	1.52	2.33	1.68,1.67,1.68,1.67,1.68,1.68,1.67,1.67,1.66,1.67,1.67,1.68,1.66,1.68,1.67,1.67,1.81,1.67,1.67,1.68,1.66,1.68,1.67,1.68,1.66,1.68	30	20	0	1
6	15	0.92	0.92	1.42	1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.17,1.18,1.18,1.18,1.17,1.18,1.18,1.18,1.29,1.18,1.18,1.18,1.16,1.18,1.18,1.18,1.17,1.18	30	20	0	1
7	15	1.52	1.52	2.33	1.68,1.67,1.68,1.67,1.68,1.68,1.67,1.67,1.66,1.67,1.67,1.68,1.66,1.68,1.67,1.67,1.87,1.67,1.67,1.68,1.65,1.68,1.67,1.68,1.66,1.68	30	20	0	1
8	18	1.33	1.33	2.05	2.36,2.36,2.36,2.36,2.36,2.36,2.34,2.36,2.33,2.36,2.34,2.36,2.33,2.36,2.35,2.36,1.48,2.36,2.35,2.36,2.32,2.36,2.34,2.36,2.34,2.36	30	20	0	1
9	1	2.60	2.60	4.00	-	30	20	0	1
10	15	2.44	2.44	3.75	1.68,1.68,1.68,1.68,1.68,1.68,1.67,1.68,1.66,1.68,1.67,1.68,1.66,1.68,1.67,1.68,1.94,1.68,1.67,1.68,1.65,1.68,1.67,1.68,1.66,1.68	30	20	0	1
11	18	1.33	1.33	2.05	2.37,2.37,2.37,2.37,2.37,2.37,2.35,2.37,2.33,2.37,2.35,2.37,2.34,2.37,2.35,2.37,1.50,2.37,2.35,2.37,2.32,2.37,2.35,2.37,2.34,2.37	30	20	0	1
12	4	1.30	1.30	2.00	-	30	20	0	1
13	18	4.88	4.00	7.50	1.11,1.11,1.11,1.11,1.11,1.11,1.10,1.11,1.10,1.11,1.10,1.11,1.10,1.11,1.10,1.11,1.10,1.11,1.20,1.11,1.10,1.11,1.10,0.11,1.10,1.11,1.10,1.11	30	20	0	1
14	18	4.88	4.00	7.50	1.10,1.10,1.10,1.11,1.10,1.10,1.10,1.10,1.10,1.10,1.10,1.10,1.10,1.10,1.10,1.11,1.20,1.11,1.10,1.10,1.10,0.11,1.10,1.10,1.10,1.10	30	20	0	1
15	18	7.88	7.88	3.75	2.33,3.2,3.33,2.33,2.33,2.33,2.33	30	20	0	1
16	18	7.88	7.88	3.75	2.33,3.2,3.33,2.33,2.33,2.33,2.33	30	20	0	1
101	7	21.65	21.65	10.31	-	30	20	0	1
102	4	1.30	1.30	2.00	-	30	20	0	1
103	15	0.92	0.92	1.42	1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.17,1.18,1.18,1.18,1.17,1.18,1.18,1.18,1.29,1.18,1.18,1.18,1.16,1.18,1.18,1.18,1.17,1.18	30	20	0	1
104	15	2.44	2.44	3.75	1.68,1.68,1.68,1.68,1.68,1.68,1.67,1.68,1.66,1.68,1.67,1.68,1.66,1.68,1.67,1.68,1.95,1.68,1.67,1.68,1.65,1.68,1.67,1.68,1.66,1.68	30	20	0	1
105	15	1.52	1.52	2.33	1.68,1.67,1.68,1.67,1.68,1.68,1.67,1.67,1.66,1.67,1.67,1.68,1.66,1.68,1.67,1.67,1.87,1.67,1.67,1.68,1.65,1.68,1.67,1.68,1.66,1.68	30	20	0	1
106	15	0.92	0.92	1.42	1.19,1.19,1.19,1.18,1.19,1.19,1.18,1.19,1.18,1.19,1.18,1.19,1.18,1.19,1.18,1.18,1.28,1.18,1.18,1.19,1.17,1.19,1.18,1.19,1.18,1.19	30	20	0	1
107	15	1.52	1.52	2.33	1.68,1.67,1.68,1.67,1.68,1.68,1.67,1.67,1.66,1.67,1.67,1.68,1.66,1.68,1.67,1.67,1.81,1.67,1.67,1.68,1.65,1.68,1.67,1.68,1.66,1.68	30	20	0	1
108	18	7.88	7.88	3.75	2.33,3.2,3.33,2.33,2.33,2.33,2.33	30	20	0	1
109	1	2.60	2.60	4.00	-	30	20	0	1
110	15	2.44	2.44	3.75	1.68,1.68,1.68,1.68,1.68,1.68,1.67,1.68,1.66,1.68,1.67,1.68,1.66,1.68,1.67,1.68,1.87,1.68,1.67,1.68,1.65,1.68,1.67,1.68,1.66,1.68	30	20	0	1
111	18	7.88	7.88	3.75	2.33,3.2,3.33,2.33,2.33,2.33,2.33	30	20	0	1
112	4	2.00	1.30	2.00	-	30	20	0	1

5	0.009	0.283	0.123	0.045	0.023	0.301	#13	0.073	Not Required	Pass
6	0.008	0.400	0.056	0.040	0.010	0.437	#13	0.044	Not Required	Pass
7	0.007	0.248	0.083	0.040	0.016	0.261	#13	0.073	Not Required	Pass
8	0.001	0.030	0.051	0.020	0.006	0.058	#21	0.088	Not Required	Pass
9	0.003	0.034	0.049	0.001	0.001	0.084	#13	0.198	Not Required	Pass
10	0.007	0.397	0.094	0.040	0.018	0.465	#13	0.078	Not Required	Pass
11	0.001	0.029	0.051	0.020	0.006	0.059	#21	0.059	Not Required	Pass
12	0.001	0.200	0.163	0.048	0.031	0.363	#13	0.052	Not Required	Pass
13	0.003	0.131	0.177	0.030	0.009	0.274	#21	0.177	Not Required	Pass
14	0.004	0.134	0.177	0.030	0.009	0.274	#21	0.177	Not Required	Pass
15	0.000	0.049	0.082	0.020	0.006	0.120	#21	Not Required	Not Required	Pass
16	0.000	0.049	0.082	0.020	0.006	0.120	#21	Not Required	Not Required	Pass
101	0.050	0.704	0.023	0.037	0.002	0.739	#13	0.579	Not Required	Pass
102	0.001	0.200	0.163	0.048	0.031	0.363	#13	0.052	Not Required	Pass
103	0.008	0.400	0.056	0.040	0.010	0.438	#13	0.044	Not Required	Pass
104	0.007	0.397	0.094	0.040	0.018	0.465	#13	0.078	Not Required	Pass
105	0.007	0.248	0.083	0.040	0.016	0.261	#13	0.073	Not Required	Pass
106	0.009	0.458	0.079	0.046	0.017	0.517	#13	0.044	Not Required	Pass
107	0.009	0.283	0.123	0.045	0.023	0.301	#13	0.073	Not Required	Pass
108	0.000	0.049	0.082	0.020	0.006	0.120	#21	Not Required	Not Required	Pass
109	0.003	0.034	0.049	0.001	0.001	0.084	#13	0.198	Not Required	Pass
110	0.008	0.456	0.120	0.046	0.021	0.500	#13	0.078	Not Required	Pass
111	0.000	0.049	0.082	0.020	0.006	0.120	#21	Not Required	Not Required	Pass
112	0.001	0.260	0.188	0.057	0.035	0.448	#13	0.079	Not Required	Pass
113	0.003	0.131	0.177	0.030	0.009	0.274	#21	0.177	Not Required	Pass
114	0.004	0.134	0.177	0.030	0.009	0.274	#21	0.265	Not Required	Pass
115	0.001	0.029	0.067	0.020	0.006	0.083	#21	0.156	Not Required	Pass
116	0.001	0.030	0.067	0.020	0.006	0.082	#21	0.235	Not Required	Pass

Definitions

Φ_t	Safety factor for tensile
Φ_c	Safety factor for compression
Φ_b	Safety factor for flexure
Φ_v	Safety factor for shear
E	Modulus of elasticity
F_y	Specified minimum yield stress
F_u	Specified minimum tensile strength
A	Cross-sectional area
J	Torsional constant
I_{yp}	Moment of inertia about the Y axes
I_{zp}	Moment of inertia about the Z axes
I_w	Warping constant
S_{yp}	Plastic section modulus about the Y axis
S_{zp}	Plastic section modulus about the Z axis
KL	Effective length
C_b	Buckling modification factor (from all load combinations)
L_b	Length between braced points
LST	Limited slenderness for tension
LSC	Limited slenderness for compression
LD	Limited deflection
P_n	Nominal axial strength (tension/compression)
M_n	Nominal flexural strength (about Z/Y axis)
V_n	Nominal shear strength (along Z/Y axis)
P	Design ratio in case of axial force
M_z	Design ratio in case of bending about Z axis
M_y	Design ratio in case of bending about Y axis
V_y	Design ratio in case of shear along Y axis
V_z	Design ratio in case of shear along Z axis

(P,M _z ,M _y)	Design ratio in case of axial force and bending action
KL/r	Design ratio in case of section slenderness
δ	Design ratio in case of member deflection
OK	Capacity is provided
NG	Capacity is not provided

REFERENCES	CALCULATIONS	RESULTS
------------	--------------	---------


SkyCiv Foundation Design

Pile Foundation

Design Information :

Design code : IBC 2021 (International Building Code)
Unit System : Imperial

Pile Input



Geometry

Pile shape: rectangular

$b = 48$ in - Pile width

$D = 48$ in - Pile depth

$L = 5.5$ ft - Total pile length

$h_1 = 0$ ft - Lateral load height from the top of the pile,

$h_2 = 0$ ft - Depth to resisting surface

$h_e = 0$ ft - Length of pile above the ground

Tabulation of Soil Parameters

Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000

Tabulation of Loads

Load Component	ASD	LRFD
P (kip)	3.352	4.750
V_x (kip)	-1.678	-2.798
V_z (kip)	-0.084	-0.136
M_x (kipft)	-0.261	-0.425
M_z (kipft)	17.581	29.781

Material Properties

$f'_{ck} = 2.5$ ksi - Concrete strength.

Required depth to resist lateral loads (ASD)

H - Point of application of the lateral load

$$H = h_1 + h_2 + h_e$$

$$H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$$

$$H = 0 \text{ ft}$$

Considering x-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-1.678 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.2672 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(17.581 \text{ kipft}) + ((-1.678 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 2.7995 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,x} = 5.2 \text{ ft}$ - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.084 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.013376 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.261 \text{ kipft}) + ((-0.084 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.041561 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,z} = 1.3142 \text{ ft}$ - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = \text{MAX}[(5.2 \text{ ft}), (1.3142 \text{ ft})]$$

$$L_{e,req} = 5.2 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_e - h_2$$

$$L_e = (5.5 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 5.5 \text{ ft}$$

Ratio - Embedded depth

$$\text{Ratio} = \frac{L_{e,req}}{L_e}$$

$$\text{Ratio} = \frac{(5.2 \text{ ft})}{(5.5 \text{ ft})}$$

$$\text{Ratio} = 0.94545$$

Status: **PASS**
Ratio: **0.950**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_v}{A}$$

$$q = \frac{(3.352 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.2095 \text{ kip/ft}^2$$

Check bearing capacity ratio:

Ratio - Capacity

$$\text{Ratio} = \frac{q}{q_a}$$

$$\text{Ratio} = \frac{(0.2095 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$\text{Ratio} = 0.10475$$

Status: **PASS**
Ratio: **0.100**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(5.5 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1.375$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.2672 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 2.7995 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (2.7995 \text{ kipft/ft}) \times (5.5 \text{ ft})) + (3 \times (-0.2672 \text{ kip/ft}) \times (5.5 \text{ ft})^2)}{(6 \times (2.7995 \text{ kipft/ft})) + (4 \times (-0.2672 \text{ kip/ft}) \times (5.5 \text{ ft}))}$$

$$a = 3.7855 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (2.7995 \text{ kipft/ft})) + (3 \times (-0.2672 \text{ kip/ft}) \times (5.5 \text{ ft}))]^2}{(5.5 \text{ ft})^2 \times [(3 \times (2.7995 \text{ kipft/ft})) + (2 \times (-0.2672 \text{ kip/ft}) \times (5.5 \text{ ft}))]}$$

$$p = 0.20934 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (2.7995 \text{ kipft/ft})) + ((-0.2672 \text{ kip/ft}) \times (5.5 \text{ ft}))]}{(5.5 \text{ ft})^2}$$

$$s = 0.81907 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(3.7855 \text{ ft})}{2}$$

$$p_a = 0.28391 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.20934 \text{ kip/ft}^2)}{(0.28391 \text{ kip/ft}^2)}$$

$$Ratio = 0.73733$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (5.5 \text{ ft})$$

$$p_s = 0.825 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.81907 \text{ kip/ft}^2)}{(0.825 \text{ kip/ft}^2)}$$

$$Ratio = 0.99281$$

Status: **PASS**
Ratio: **0.740**

Status: **PASS**
Ratio: **0.990**

Considering z-direction:

$H_o = -0.013376 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.041561 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.041561 \text{ kipft/ft}) \times (5.5 \text{ ft})) + (3 \times (-0.013376 \text{ kip/ft}) \times (5.5 \text{ ft})^2)}{(6 \times (0.041561 \text{ kipft/ft})) + (4 \times (-0.013376 \text{ kip/ft}) \times (5.5 \text{ ft}))}$$

$$a = 3.9148 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (0.041561 \text{ kipft/ft})) + (3 \times (-0.013376 \text{ kip/ft}) \times (5.5 \text{ ft}))]^2}{(5.5 \text{ ft})^2 \times [(3 \times (0.041561 \text{ kipft/ft})) + (2 \times (-0.013376 \text{ kip/ft}) \times (5.5 \text{ ft}))]}$$

$$p = -0.003275 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.041561 \text{ kipft/ft})) + ((-0.013376 \text{ kip/ft}) \times (5.5 \text{ ft}))]}{(5.5 \text{ ft})^2}$$

$$s = 0.001895 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(3.9148 \text{ ft})}{2}$$

$$p_a = 0.29361 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(-0.003275 \text{ kip/ft}^2)}{(0.29361 \text{ kip/ft}^2)}$$

$$Ratio = -0.011154$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (5.5 \text{ ft})$$

$$p_s = 0.825 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity


$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.001895 \text{ kip/ft}^2)}{(0.825 \text{ kip/ft}^2)}$$

$$Ratio = 0.002297$$

Status: **PASS**
Ratio: **-0.010**

Status: **PASS**
Ratio: **0.000**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-2.798 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.44554 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(29.781 \text{ kipft}) + ((-2.798 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 4.7422 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(4.7422 \text{ kipft/ft})}{(-0.44554 \text{ kip/ft})}$$

$$E = 10.644 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (4.7422 \text{ kipft/ft}) \times (5.5 \text{ ft})) + (3 \times (-0.44554 \text{ kip/ft}) \times (5.5 \text{ ft})^2)}{(6 \times (4.7422 \text{ kipft/ft})) + (4 \times (-0.44554 \text{ kip/ft}) \times (5.5 \text{ ft}))}$$

$$a = \frac{(6 \times (4.7422 \text{ kipft/ft})) + (4 \times (-0.44554 \text{ kip/ft}) \times (5.5 \text{ ft}))}{(6 \times (4.7422 \text{ kipft/ft})) + (4 \times (-0.44554 \text{ kip/ft}) \times (5.5 \text{ ft}))}$$

$$a = 3.7841 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.44554 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (10.644 \text{ ft})}{(5.5 \text{ ft})} + 3 \right) \times \left(\frac{(3.7841 \text{ ft})}{(5.5 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (10.644 \text{ ft})}{(5.5 \text{ ft})} + 2 \right) \times \left(\frac{(3.7841 \text{ ft})}{(5.5 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 7.2791 \text{ kip}$$

M_{max} - Max bending moment located at depth a/2,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.44554 \text{ kip/ft}) \times (48 \text{ in}) \times (5.5 \text{ ft})) \times \left[\left(\frac{(10.644 \text{ ft})}{(5.5 \text{ ft})} + \frac{(3.7841 \text{ ft})}{2 \times (5.5 \text{ ft})} \right) - \left[\left(\frac{4 \times (10.644 \text{ ft})}{(5.5 \text{ ft})} + 3 \right) \times \left(\frac{(3.7841 \text{ ft})}{(2 \times (5.5 \text{ ft}))} \right)^3 \right] + \left[\left(\frac{3 \times (10.644 \text{ ft})}{(5.5 \text{ ft})} + 2 \right) \times \left(\frac{(3.7841 \text{ ft})}{(2 \times (5.5 \text{ ft}))} \right)^4 \right] \right]$$

$$M_{max} = 19.126 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.136 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.021656 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.425 \text{ kipft}) + ((-0.136 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.067675 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.067675 \text{ kipft/ft})}{(-0.021656 \text{ kip/ft})}$$

$$E = 3.125 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.067675 \text{ kipft/ft}) \times (5.5 \text{ ft})) + (3 \times (-0.021656 \text{ kip/ft}) \times (5.5 \text{ ft})^2)}{(6 \times (0.067675 \text{ kipft/ft})) + (4 \times (-0.021656 \text{ kip/ft}) \times (5.5 \text{ ft}))}$$

$$a = 3.9141 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.021656 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (3.125 \text{ ft})}{(5.5 \text{ ft})} + 3 \right) \times \left(\frac{(3.9141 \text{ ft})}{(5.5 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (3.125 \text{ ft})}{(5.5 \text{ ft})} + 2 \right) \times \left(\frac{(3.9141 \text{ ft})}{(5.5 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.1447 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o \ b \ L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.021656 \text{ kip/ft}) \times (48 \text{ in}) \times (5.5 \text{ ft})) \times \left[\left(\frac{(3.125 \text{ ft})}{(5.5 \text{ ft})} + \frac{(3.9141 \text{ ft})}{2 \times (5.5 \text{ ft})} \right) - \left[\left(\frac{4 \times (3.125 \text{ ft})}{(5.5 \text{ ft})} + 3 \right) \times \left(\frac{(3.9141 \text{ ft})}{2 \times (5.5 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (3.125 \text{ ft})}{(5.5 \text{ ft})} + 2 \right) \times \left(\frac{(3.9141 \text{ ft})}{2 \times (5.5 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 0.35535 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 2.5 \text{ ksi}$ - Concrete strength,

$f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,

$\phi = 0.65$ - Reduction factor for axial strength,

$\alpha = 0.8$ - Alpha factor for axial strength,

$A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(4.75 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (2.5 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (2.5 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -84.438 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-84.438 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

Table 22.4.2.1

22.4.2.2, 10.6.1.1

<p>25.2.3</p> <p>25.7.2.2</p> <p>25.7.2.1</p>	<p style="text-align: center;">$Ratio = 0.96556$</p> <p>$s_{rebar} = \text{Min spacing of reinforcement,}$</p> $s_{rebar} = \text{Max}[1.5, (1.5 d_{bar})]$ $s_{rebar} = \text{Max}[1.5, (1.5 \times (0.625 \text{ in}))]$ $s_{rebar} = 1.5 \text{ in}$ <p>Ties:</p> <p>Since longitudinal reinforcement is \leq No. 10ø: Use #3(0.375 in)</p> <p>s_{ties} - Maximum spacing of ties,</p> $s_{ties} = \text{Min}[(16 d_{bar}), (48 d_{ties}), \text{Min}(D, b)]$ $s_{ties} = \text{Min}[(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), \text{Min}((48 \text{ in}), (48 \text{ in}))]$ $s_{ties} = 10 \text{ in}$ <p>Summary:</p> <p style="text-align: center;">Main reinforcement: 14 - #5 (0.625 in) Ties: #3(0.375 in) - 10 in</p>	<p>Status: PASS Ratio: 0.970</p>
<p>22.4.2.2</p>	<p>Axial Compression Strength (ACI 318-19, LRFD)</p> <p>ϕP_N - Allowable axial compressive strength</p> $\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_{yk} A_{st})]$ $\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (2.5 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$ $\phi P_N = 2675.2 \text{ kip}$ <p><i>Ratio</i> - Capacity</p> $Ratio = \frac{P}{\phi P_N}$ $Ratio = \frac{(4.75 \text{ kip})}{(2675.2 \text{ kip})}$ $Ratio = 0.0017756$	<p>Status: PASS Ratio: 0.000</p>
<p>22.5.2.2</p> <p>22.5.5.1.3</p> <p>22.5.5.1.1</p>	<p>Shear Strength (ACI 318-19, LRFD)</p> <p>Parameters:</p> <p>$b_w = 48 \text{ in}$ - Effective width, d - Effective depth</p> $d = 0.80 D$ $d = 0.80 \times (48 \text{ in})$ $d = 38.4 \text{ in}$ <p>λ_s - size effect modification factor</p> $\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$ $\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$ $\lambda_s = 0.64282$ <p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,</p> <p>$V_{c,max}$ - Max shear strength of concrete</p> $V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$ $V_{c,max} = 5 \times (0.64282) \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$	

$$V_{c,max} = 296.21 \text{ kip}$$

22.5.5.1.1(a) The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $P = 4.75 \text{ kip} \rightarrow 4750 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck} + \frac{P}{6 A_g}} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + \frac{(4750 \text{ lbf})}{6 \times (2304 \text{ in}^2)}} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 119.12 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck} + (0.05 f'_{ck})} \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + (0.05 \times (2500 \text{ psi}))} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 348.89 \text{ kip}$$

V_c - Governing shear strength of concrete

$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(296.21 \text{ kip}), (119.12 \text{ kip}), (348.89 \text{ kip})]$$

$$V_c = 119.12 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{s,a}$ - Shear strength of steel (a)

$$V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$$

$$V_{s,a} = 8 \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{s,a} = 737.28 \text{ kip}$$

A_v - Ties rebar area,

$$A_v = \frac{\pi d_{ties}^2}{4}$$

$$A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$$

$$A_v = 0.11045 \text{ in}^2$$

22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)

$$V_{s,b} = \frac{2 A_v f_{yw} d}{s_{ties}}$$

$$V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$$

$$V_{s,b} = 50.894 \text{ kip}$$

V_s - Governing shear strength of steel

$$V_s = \text{MIN}[V_{s,a}, V_{s,b}]$$

$$V_s = \text{MIN}[(737.28 \text{ kip}), (50.894 \text{ kip})]$$

$$V_s = 50.894 \text{ kip}$$

22.5.1.1 ϕV_n - Allowable shear strength

$$\phi V_n = \phi (V_c + V_s)$$

$$\phi V_n = (0.65) \times ((119.12 \text{ kip}) + (50.894 \text{ kip}))$$

$$\phi V_n = 110.51 \text{ kip}$$

Considering x-direction:

$V_{max} = 7.2791 \text{ kip}$ - Maximum shear force in the x-direction,

$Ratio$ - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(7.2791 \text{ kip})}{(110.51 \text{ kip})}$$

$$Ratio = 0.065869$$

Status: **PASS**
Ratio: **0.070**

Considering z-direction:

$V_{max} = 0.1447 \text{ kip}$ - Maximum shear force in the z-direction,
Ratio - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(0.1447 \text{ kip})}{(110.51 \text{ kip})}$$

$$Ratio = 0.0013094$$

Status: **PASS**
Ratio: **0.000**

Flexural Strength (ACI 318-19, LRFD)

S_m - Section modulus

$$S_m = \frac{b D^2}{6}$$

$$S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$$

$$S_m = 18432 \text{ in}^3$$

$\lambda = 1$ - Concrete modification factor (Normal concrete),

Allowable flexural strength:

M_n shall be the lesser of:

$\phi M_{n,1}$

$$\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$$

$$\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{(2.5 \text{ ksi})} \times 18432.001 \text{ in}^3$$

$$\phi M_{n,1} = 249.600 \text{ kipft}$$

14.5.2.1b $\phi M_{n,2}$

$$\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$$

$$\phi M_{n,2} = (0.65) \times 0.85 \times (2.5 \text{ ksi}) \times (18432 \text{ in}^3)$$

$$\phi M_{n,2} = 2121.6 \text{ kipft}$$

Therefore,

ϕM_n - Allowable flexural strength,

$$\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$$

$$\phi M_n = \text{MIN}[(249.6 \text{ kipft}), (2121.6 \text{ kipft})]$$

$$\phi M_n = 249.6 \text{ kipft}$$

Considering x-direction:

$M_{max} = 19.126 \text{ kipft}$ - Maximum moment in the x-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(19.126 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.076627$$

Status: **PASS**
Ratio: **0.080**

Considering z-direction:

$M_{max} = 0.35535 \text{ kipft}$ - Maximum moment in the z-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(0.35535 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.0014237$$

Status: **PASS**
Ratio: **0.000**

REFERENCES	CALCULATIONS	RESULTS
------------	--------------	---------


SkyCiv Foundation Design

Pile Foundation

Design Information :

Design code : IBC 2021 (International Building Code)
Unit System : Imperial

Pile Input



Geometry

Pile shape: rectangular

$b = 48$ in - Pile width

$D = 48$ in - Pile depth

$L = 5.5$ ft - Total pile length

$h_1 = 0$ ft - Lateral load height from the top of the pile,

$h_2 = 0$ ft - Depth to resisting surface

$h_e = 0$ ft - Length of pile above the ground

Tabulation of Soil Parameters

Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000

Tabulation of Loads

Load Component	ASD	LRFD
P (kip)	3.352	4.750
V_x (kip)	-1.678	-2.797
V_z (kip)	0.084	0.136
M_x (kipft)	0.261	0.425
M_z (kipft)	17.581	29.781

Material Properties

$f'_{ck} = 2.5$ ksi - Concrete strength.

Required depth to resist lateral loads (ASD)

H - Point of application of the lateral load

$$H = h_1 + h_2 + h_e$$

$$H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$$

$$H = 0 \text{ ft}$$

Considering x-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-1.678 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.2672 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(17.581 \text{ kipft}) + ((-1.678 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 2.7995 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,x} = 5.2 \text{ ft}$ - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.084 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.013376 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.261 \text{ kipft}) + ((0.084 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.041561 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,z} = 1.6711 \text{ ft}$ - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = \text{MAX}[(5.2 \text{ ft}), (1.6711 \text{ ft})]$$

$$L_{e,req} = 5.2 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_e - h_2$$

$$L_e = (5.5 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 5.5 \text{ ft}$$

Ratio - Embedded depth

$$\text{Ratio} = \frac{L_{e,req}}{L_e}$$

$$\text{Ratio} = \frac{(5.2 \text{ ft})}{(5.5 \text{ ft})}$$

$$\text{Ratio} = 0.94545$$

Status: **PASS**
Ratio: **0.950**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_v}{A}$$

$$q = \frac{(3.352 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.2095 \text{ kip/ft}^2$$

Check bearing capacity ratio:

Ratio - Capacity

$$\text{Ratio} = \frac{q}{q_a}$$

$$\text{Ratio} = \frac{(0.2095 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$\text{Ratio} = 0.10475$$

Status: **PASS**
Ratio: **0.100**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(5.5 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1.375$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.2672 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 2.7995 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (2.7995 \text{ kipft/ft}) \times (5.5 \text{ ft})) + (3 \times (-0.2672 \text{ kip/ft}) \times (5.5 \text{ ft})^2)}{(6 \times (2.7995 \text{ kipft/ft})) + (4 \times (-0.2672 \text{ kip/ft}) \times (5.5 \text{ ft}))}$$

$$a = 3.7855 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (2.7995 \text{ kipft/ft})) + (3 \times (-0.2672 \text{ kip/ft}) \times (5.5 \text{ ft}))]^2}{(5.5 \text{ ft})^2 \times [(3 \times (2.7995 \text{ kipft/ft})) + (2 \times (-0.2672 \text{ kip/ft}) \times (5.5 \text{ ft}))]}$$

$$p = 0.20934 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (2.7995 \text{ kipft/ft})) + ((-0.2672 \text{ kip/ft}) \times (5.5 \text{ ft}))]}{(5.5 \text{ ft})^2}$$

$$s = 0.81907 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(3.7855 \text{ ft})}{2}$$

$$p_a = 0.28391 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.20934 \text{ kip/ft}^2)}{(0.28391 \text{ kip/ft}^2)}$$

$$Ratio = 0.73733$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (5.5 \text{ ft})$$

$$p_s = 0.825 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.81907 \text{ kip/ft}^2)}{(0.825 \text{ kip/ft}^2)}$$

$$Ratio = 0.99281$$

Status: **PASS**
Ratio: **0.740**

Status: **PASS**
Ratio: **0.990**

Considering z-direction:

$H_o = 0.013376 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.041561 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.041561 \text{ kipft/ft}) \times (5.5 \text{ ft})) + (3 \times (0.013376 \text{ kip/ft}) \times (5.5 \text{ ft})^2)}{(6 \times (0.041561 \text{ kipft/ft})) + (4 \times (0.013376 \text{ kip/ft}) \times (5.5 \text{ ft}))}$$

$$a = 3.9148 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 [(4 \times (0.041561 \text{ kipft/ft})) + (3 \times (0.013376 \text{ kip/ft}) \times (5.5 \text{ ft}))]^2}{(5.5 \text{ ft})^2 [(3 \times (0.041561 \text{ kipft/ft})) + (2 \times (0.013376 \text{ kip/ft}) \times (5.5 \text{ ft}))]}$$

$$p = 0.013657 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 [(2 \times (0.041561 \text{ kipft/ft})) + ((0.013376 \text{ kip/ft}) \times (5.5 \text{ ft}))]}{(5.5 \text{ ft})^2}$$

$$s = 0.031079 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(3.9148 \text{ ft})}{2}$$

$$p_a = 0.29361 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.013657 \text{ kip/ft}^2)}{(0.29361 \text{ kip/ft}^2)}$$

$$Ratio = 0.046515$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (5.5 \text{ ft})$$

$$p_s = 0.825 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity


$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.031079 \text{ kip/ft}^2)}{(0.825 \text{ kip/ft}^2)}$$

$$Ratio = 0.037671$$

Status: **PASS**
Ratio: **0.050**

Status: **PASS**
Ratio: **0.040**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-2.797 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.44538 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(29.781 \text{ kipft}) + ((-2.797 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 4.7422 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(4.7422 \text{ kipft/ft})}{(-0.44538 \text{ kip/ft})}$$

$$E = 10.647 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (4.7422 \text{ kipft/ft}) \times (5.5 \text{ ft})) + (3 \times (-0.44538 \text{ kip/ft}) \times (5.5 \text{ ft})^2)}{(6 \times (4.7422 \text{ kipft/ft})) + (4 \times (-0.44538 \text{ kip/ft}) \times (5.5 \text{ ft}))}$$

$$a = \frac{(6 \times (4.7422 \text{ kipft/ft})) + (4 \times (-0.44538 \text{ kip/ft}) \times (5.5 \text{ ft}))}{}$$

$$a = 3.7841 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.44538 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (10.647 \text{ ft})}{(5.5 \text{ ft})} + 3 \right) \times \left(\frac{(3.7841 \text{ ft})}{(5.5 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (10.647 \text{ ft})}{(5.5 \text{ ft})} + 2 \right) \times \left(\frac{(3.7841 \text{ ft})}{(5.5 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 7.2787 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.44538 \text{ kip/ft}) \times (48 \text{ in}) \times (5.5 \text{ ft})) \times \left[\left(\frac{(10.647 \text{ ft})}{(5.5 \text{ ft})} + \frac{(3.7841 \text{ ft})}{2 \times (5.5 \text{ ft})} \right) - \left[\left(\frac{4 \times (10.647 \text{ ft})}{(5.5 \text{ ft})} + 3 \right) \times \left(\frac{(3.7841 \text{ ft})}{(2 \times (5.5 \text{ ft}))} \right)^3 \right] + \left[\left(\frac{3 \times (10.647 \text{ ft})}{(5.5 \text{ ft})} + 2 \right) \times \left(\frac{(3.7841 \text{ ft})}{(2 \times (5.5 \text{ ft}))} \right)^4 \right] \right]$$

$$M_{max} = 19.125 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.136 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.021656 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.425 \text{ kipft}) + ((0.136 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.067675 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.067675 \text{ kipft/ft})}{(0.021656 \text{ kip/ft})}$$

$$E = 3.125 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.067675 \text{ kipft/ft}) \times (5.5 \text{ ft})) + (3 \times (0.021656 \text{ kip/ft}) \times (5.5 \text{ ft})^2)}{(6 \times (0.067675 \text{ kipft/ft})) + (4 \times (0.021656 \text{ kip/ft}) \times (5.5 \text{ ft}))}$$

$$a = 3.9141 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((0.021656 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (3.125 \text{ ft})}{(5.5 \text{ ft})} + 3 \right) \times \left(\frac{(3.9141 \text{ ft})}{(5.5 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (3.125 \text{ ft})}{(5.5 \text{ ft})} + 2 \right) \times \left(\frac{(3.9141 \text{ ft})}{(5.5 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.1447 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o \cdot b \cdot L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((0.021656 \text{ kip/ft}) \times (48 \text{ in}) \times (5.5 \text{ ft})) \times \left[\left(\frac{(3.125 \text{ ft})}{(5.5 \text{ ft})} + \frac{(3.9141 \text{ ft})}{2 \times (5.5 \text{ ft})} \right) - \left[\left(\frac{4 \times (3.125 \text{ ft})}{(5.5 \text{ ft})} + 3 \right) \times \left(\frac{(3.9141 \text{ ft})}{2 \times (5.5 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (3.125 \text{ ft})}{(5.5 \text{ ft})} + 2 \right) \times \left(\frac{(3.9141 \text{ ft})}{2 \times (5.5 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 0.35535 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 2.5 \text{ ksi}$ - Concrete strength,

$f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,

$\phi = 0.65$ - Reduction factor for axial strength,

$\alpha = 0.8$ - Alpha factor for axial strength,

$A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(4.75 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (2.5 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (2.5 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -84.438 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-84.438 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

Table 22.4.2.1

22.4.2.2, 10.6.1.1

<p>25.2.3</p> <p>25.7.2.2</p> <p>25.7.2.1</p>	<p style="text-align: center;">$Ratio = 0.96556$</p> <p>$s_{rebar} = Max[1.5, (1.5 d_{bar})]$</p> <p>$s_{rebar} = Max[1.5, (1.5 \times (0.625 \text{ in}))]$</p> <p>$s_{rebar} = 1.5 \text{ in}$</p> <p>Ties:</p> <p>Since longitudinal reinforcement is \leq No. 10ø: Use #3(0.375 in)</p> <p>$s_{ties} = Min[(16 d_{bar}), (48 d_{ties}), Min(D, b)]$</p> <p>$s_{ties} = Min[(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), Min((48 \text{ in}), (48 \text{ in}))]$</p> <p>$s_{ties} = 10 \text{ in}$</p> <p>Summary:</p> <p style="text-align: center;">Main reinforcement: 14 - #5 (0.625 in) Ties: #3(0.375 in) - 10 in</p>	<p>Status: PASS Ratio: 0.970</p>
<p>22.4.2.2</p>	<p>Axial Compression Strength (ACI 318-19, LRFD)</p> <p>ϕP_N - Allowable axial compressive strength</p> <p style="text-align: center;">$\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_{yk} A_{st})]$</p> <p style="text-align: center;">$\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (2.5 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$</p> <p style="text-align: center;">$\phi P_N = 2675.2 \text{ kip}$</p> <p>Ratio - Capacity</p> <p style="text-align: center;">$Ratio = \frac{P}{\phi P_N}$</p> <p style="text-align: center;">$Ratio = \frac{(4.75 \text{ kip})}{(2675.2 \text{ kip})}$</p> <p style="text-align: center;">$Ratio = 0.0017756$</p>	<p>Status: PASS Ratio: 0.000</p>
<p>22.5.2.2</p> <p>22.5.5.1.3</p> <p>22.5.5.1.1</p>	<p>Shear Strength (ACI 318-19, LRFD)</p> <p>Parameters:</p> <p>$b_w = 48 \text{ in}$ - Effective width, d - Effective depth</p> <p style="text-align: center;">$d = 0.80 D$</p> <p style="text-align: center;">$d = 0.80 \times (48 \text{ in})$</p> <p style="text-align: center;">$d = 38.4 \text{ in}$</p> <p>λ_s - size effect modification factor</p> <p style="text-align: center;">$\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = 0.64282$</p> <p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,</p> <p>$V_{c,max}$ - Max shear strength of concrete</p> <p style="text-align: center;">$V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$</p> <p style="text-align: center;">$V_{c,max} = 5 \times (0.64282) \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$</p>	

$$V_{c,max} = 296.21 \text{ kip}$$

22.5.5.1.1(a) The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $P = 4.75 \text{ kip} \rightarrow 4750 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck} + \frac{P}{6 A_g}} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + \frac{(4750 \text{ lbf})}{6 \times (2304 \text{ in}^2)}} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 119.12 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck} + (0.05 f'_{ck})} \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + (0.05 \times (2500 \text{ psi}))} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 348.89 \text{ kip}$$

V_c - Governing shear strength of concrete

$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(296.21 \text{ kip}), (119.12 \text{ kip}), (348.89 \text{ kip})]$$

$$V_c = 119.12 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{s,a}$ - Shear strength of steel (a)

$$V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$$

$$V_{s,a} = 8 \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{s,a} = 737.28 \text{ kip}$$

A_v - Ties rebar area,

$$A_v = \frac{\pi d_{ties}^2}{4}$$

$$A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$$

$$A_v = 0.11045 \text{ in}^2$$

22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)

$$V_{s,b} = \frac{2 A_v f_{yw} d}{s_{ties}}$$

$$V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$$

$$V_{s,b} = 50.894 \text{ kip}$$

V_s - Governing shear strength of steel

$$V_s = \text{MIN}[V_{s,a}, V_{s,b}]$$

$$V_s = \text{MIN}[(737.28 \text{ kip}), (50.894 \text{ kip})]$$

$$V_s = 50.894 \text{ kip}$$

22.5.1.1 ϕV_n - Allowable shear strength

$$\phi V_n = \phi (V_c + V_s)$$

$$\phi V_n = (0.65) \times ((119.12 \text{ kip}) + (50.894 \text{ kip}))$$

$$\phi V_n = 110.51 \text{ kip}$$

Considering x-direction:

$V_{max} = 7.2787 \text{ kip}$ - Maximum shear force in the x-direction,

$Ratio$ - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(7.2787 \text{ kip})}{(110.51 \text{ kip})}$$

$$Ratio = 0.065865$$

Considering z-direction:

$V_{max} = 0.1447 \text{ kip}$ - Maximum shear force in the z-direction,
Ratio - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(0.1447 \text{ kip})}{(110.51 \text{ kip})}$$

$$Ratio = 0.0013094$$

Status: **PASS**
 Ratio: **0.070**

Status: **PASS**
 Ratio: **0.000**

Flexural Strength (ACI 318-19, LRFD)

S_m - Section modulus

$$S_m = \frac{b D^2}{6}$$

$$S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$$

$$S_m = 18432 \text{ in}^3$$

$\lambda = 1$ - Concrete modification factor (Normal concrete),

Allowable flexural strength:

M_n shall be the lesser of:

$\phi M_{n,1}$

$$\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$$

$$\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{(2.5 \text{ ksi})} \times 18432.001 \text{ in}^3$$

$$\phi M_{n,1} = 249.600 \text{ kipft}$$

14.5.2.1b

$\phi M_{n,2}$

$$\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$$

$$\phi M_{n,2} = (0.65) \times 0.85 \times (2.5 \text{ ksi}) \times (18432 \text{ in}^3)$$

$$\phi M_{n,2} = 2121.6 \text{ kipft}$$

Therefore,

ϕM_n - Allowable flexural strength,

$$\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$$

$$\phi M_n = \text{MIN}[(249.6 \text{ kipft}), (2121.6 \text{ kipft})]$$

$$\phi M_n = 249.6 \text{ kipft}$$

Considering x-direction:

$M_{max} = 19.125 \text{ kipft}$ - Maximum moment in the x-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(19.125 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.076624$$

Status: **PASS**
 Ratio: **0.080**

Considering z-direction:

$M_{max} = 0.35535 \text{ kipft}$ - Maximum moment in the z-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(0.35535 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.0014237$$

Status: **PASS**
Ratio: **0.000**