


Project Details



Project Name: Mulawa 5x13 - V1Jb
Location: 4921 W Paseo De Las Colinas, Tucson, AZ 85745, USA
Unique ID: 4P-19.75-6TOP-SD-45-L-5Hx13W-CFG2
Dealer: _____

Date: Fri Apr 11 2025
Number of Modules: 65
Number of Poles: 4
Date Sold: _____



Array Dimensions N/S	18.81 ft
Array Dimensions E/W	74.53 ft
Winter Tilt Angle	5
Front Edge Clearance	11 ft

MT Solar Bill of Materials (4P-19.75-6TOP-SD-45-L-5Hx13W-CFG2)

Part	Short Description	BOM Qty
MTS-PC-6	6IN Pole Cap Assembly	4
MTS-HF-SD	H-Frame Assembly-SD	4
MTS-SD-Wing-45	45IN SD Wing	4
MTS-SD-Splice-90	90IN SD Splice	6
MTS-SD-Splice-57	57IN SD Splice	6
MTS-CLAMP-ANGLE-4PK	Angle Clamp	13

Rail Bill of Materials

Part	Qty
Rails (226in)	26
Rail Attachment	104

Part	Qty
Module Mid Clamp	104
Module End Clamp	52
Ground Lug	13

Site Details:



Site Address: 4921 W Paseo De Las Colinas, Tucson, AZ 85745, USA

Array Specification

Duty Classification:	SD
Module Width:	44.65 in
Module Length:	67.80in
Number of Rows:	5
Number of Columns:	13
Total Number of Modules:	65
Winter Tilt Angle:	5
Front Edge Clearance:	11
Total Array Height at Tilt:	12.64 ft
Total Frame Length:	74.25 ft
Module Info/Notes:	
Array Dimensions N/S:	18.81 ft
Array Dimensions E/W:	74.53 ft
Rail Length:	225.75 in
Rail Spacing:	2.87 ft

Support Specifications

Pole Size:	6in Pipe Sch 40
Pole Length above Grade:	11.82 ft
Number of Poles:	4
Pole Spacing:	19.75 ft

Foundation Specifications

Foundation Type:	Square
Foundation Dimensions:	48 x 48 in
Foundation Depth (below grade):	Pile 1: 4.00 ft Pile 2: 4.00 ft Pile 3: 4.00 ft Pile 4: 4.00 ft
Foundation Volume:	9.481 y ³

Site Info

Risk Category:	I
Exposure:	B
Soil Classification:	sand
Site Location:	4921 W Paseo De Las Colinas, Tucson, AZ 85745, USA
Wind Speed:	90 mph

Snow Load:

0 psf

Design Disclaimer

This software should be used for preliminary designs and should not be used as a final design unless reviewed, verified and designed by a qualified structural engineer.



AutoDesigner Input



```
{ "wind_speed_override": 90, "snow_load_override": null, "direct_snow_load": false, "add_angle_brace": false, "product_type": "Beam", "designer_name": "", "designer_email": "", "designer_phone": "", "project_id": "Mulawa 5x13 - V1Jb", "site_address": "4921 W Paseo De Las Colinas, Tucson, AZ 85745, USA", "module_info": "", "module_width": 44.65, "module_length": 67.8, "number_rows": 5, "number_columns": 13, "pole_mount_section": "4_40", "core_pipe_width": 65, "core_pipe_section": "2_40", "adjuster_section": "2_40", "core_beam_height": 65, "core_beam_section": "HSS3x2x1/8", "main_pipe_section": "2_12GA", "pole_spacing": "15", "tilt_angle": 5, "ground_clearance": 11, "risk_category": "I", "exposure_category": "B", "frame_duty_override": "auto", "pole_override": "auto", "soil_type": "sand", "customer_foundation_override": "48_Square", "foundation_type": "Square", "foundation_size": 48, "check_rails": true }
```

Design Notes:

- AISC Deflection checks are set to L/1 due to structure design intent
- Foundation Soil Parameters used in this Autodesign are all estimates, proper geotechnical reports are required to confirm soil profiles
- Wind speeds, snow loads and other site specific results are based on ASCE 7 2016
- Steel frame design checks are based on AISC 360 2016 (LRFD)









Rail Design Check

Rail Length: 18.8125 ft
Additional Restraints Required: 4ft Spread Clamps
Tributary Width: 2.866666666666667 ft
Material: Aluminium
Density: 169 lb/ft³
Elasticity Modulus: 10000 ksi
Fy: 34.5 ksi
Fu: 37 ksi
Wind uplift Case A (X): 0.0000 kip/ft
Wind uplift Case A (Y): 0.0128 kip/ft
Wind uplift Case A: 0.0000 kip/ft
Wind uplift Case B: 0.0000 kip/ft
Wind uplift Case B (X): 0.0000 kip/ft
Wind uplift Case B (Y): 0.0294 kip/ft




Result Check	Max Limit	Max Value	Utility	Status
Custom Stress Limit	34.5	4.4296582	0.128	PASS
Material Yield	34.5	4.4296582	0.128	PASS
Material Strength	37	4.4296582	0.120	PASS



Member 1, ULS: 1. 1.4D




FEM Results (Envelope Worst Case for each member)





Top Bending Stress Z (ksi)





Top Bending Stress Y (ksi)



Shear Stress Y (ksi)



Axial Stress (ksi)



Reaction Forces for Foundation 1 (Node ID#1), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	0.0014	2.1618	0.0319	0.1184	-0.0036	0.0061
ULS: 2. D + L	0.0014	2.1618	0.0319	0.1184	-0.0036	0.0061
ULS: 3. D + (S or Lr or R)	0.0014	2.1618	0.0319	0.1184	-0.0036	0.0061
ULS: 3. D + (S or Lr or R)	0.0014	2.1618	0.0319	0.1184	-0.0036	0.0061
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0014	2.1618	0.0319	0.1184	-0.0036	0.0061
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0014	2.1618	0.0319	0.1184	-0.0036	0.0061
ULS: 5b. D + 0.7E	0.0014	2.1618	0.0319	0.1184	-0.0036	0.0061
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	0.0014	2.1618	0.0319	0.1184	-0.0036	0.0061
ULS: 8. 0.6D + 0.7E	0.0009	1.2971	0.0191	0.0710	-0.0022	0.0036
ULS: 5a. D + 0.6W_Wind downforce Case A only	-0.1430	3.7668	0.0611	0.2264	-0.0144	2.0638
ULS: 5a. D + 0.6W_Wind downforce Case B only	-0.1430	3.7668	0.0611	0.2264	-0.0144	2.0638
ULS: 5a. D + 0.6W_Wind uplift Case A only	0.0360	1.7290	0.0247	0.0918	-0.0034	1.2392
ULS: 5a. D + 0.6W_Wind uplift Case B only	0.1015	1.1423	0.0120	0.0456	0.0083	-4.7925
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.1069	3.3655	0.0538	0.1994	-0.0117	1.5494
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.1069	3.3655	0.0538	0.1994	-0.0117	1.5494
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.0274	1.8372	0.0265	0.0985	-0.0034	0.9309
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.0765	1.3972	0.0170	0.0638	0.0054	-3.5928
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.1069	3.3655	0.0538	0.1994	-0.0117	1.5494
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.1069	3.3655	0.0538	0.1994	-0.0117	1.5494
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.0274	1.8372	0.0265	0.0985	-0.0034	0.9309
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.0765	1.3972	0.0170	0.0638	0.0054	-3.5928
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-0.1436	2.9020	0.0483	0.1791	-0.0129	2.0614
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-0.1436	2.9020	0.0483	0.1791	-0.0129	2.0614
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	0.0355	0.8643	0.0120	0.0445	-0.0019	1.2367
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	0.1010	0.2776	-0.0007	-0.0017	0.0098	-4.7949

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	5.2691
Shear X	-0.2408
Shear Z	0.0871
Moment X	0.3236
Moment Y (Twist)	0.0225
Moment Z	8.2404

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	3.7668
Shear X	-0.1436
Shear Z	0.0611
Moment X	0.2264
Moment Y (Twist)	0.0144
Moment Z	4.7949

Reaction Forces for Foundation 2 (Node ID#101), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	-0.0014	2.4549	-0.0047	-0.0174	0.0011	0.0374
ULS: 2. D + L	-0.0014	2.4549	-0.0047	-0.0174	0.0011	0.0374
ULS: 3. D + (S or Lr or R)	-0.0014	2.4549	-0.0047	-0.0174	0.0011	0.0374
ULS: 3. D + (S or Lr or R)	-0.0014	2.4549	-0.0047	-0.0174	0.0011	0.0374
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0014	2.4549	-0.0047	-0.0174	0.0011	0.0374

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0014	2.4549	-0.0047	-0.0174	0.0011	0.0374
ULS: 5b. D + 0.7E	-0.0014	2.4549	-0.0047	-0.0174	0.0011	0.0374
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	-0.0014	2.4549	-0.0047	-0.0174	0.0011	0.0374
ULS: 8. 0.6D + 0.7E	-0.0009	1.4730	-0.0028	-0.0104	0.0006	0.0224
ULS: 5a. D + 0.6W_Wind downforce Case A only	-0.1608	4.3231	-0.0086	-0.0324	-0.0000	2.3049
ULS: 5a. D + 0.6W_Wind downforce Case B only	-0.1608	4.3231	-0.0086	-0.0324	-0.0000	2.3049
ULS: 5a. D + 0.6W_Wind uplift Case A only	0.0460	1.9506	-0.0032	-0.0121	-0.0011	1.3354
ULS: 5a. D + 0.6W_Wind uplift Case B only	0.0914	1.2693	-0.0028	-0.0101	0.0065	-5.1206
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.1210	3.8561	-0.0076	-0.0286	0.0002	1.7380
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.1210	3.8561	-0.0076	-0.0286	0.0002	1.7380
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.0341	2.0767	-0.0036	-0.0135	-0.0006	1.0109
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.0682	1.5657	-0.0033	-0.0119	0.0051	-3.8311
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.1210	3.8561	-0.0076	-0.0286	0.0002	1.7380
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.1210	3.8561	-0.0076	-0.0286	0.0002	1.7380
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.0341	2.0767	-0.0036	-0.0135	-0.0006	1.0109
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.0682	1.5657	-0.0033	-0.0119	0.0051	-3.8311
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-0.1602	3.3411	-0.0067	-0.0254	-0.0005	2.2900
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-0.1602	3.3411	-0.0067	-0.0254	-0.0005	2.2900
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	0.0465	0.9686	-0.0013	-0.0052	-0.0015	1.3205
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	0.0920	0.2873	-0.0010	-0.0032	0.0060	-5.1355

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	6.0596
Shear X	-0.2670
Shear Z	-0.0122
Moment X	-0.0460
Moment Y (Twist)	0.0107
Moment Z	8.8347

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	4.3231
Shear X	-0.1608
Shear Z	-0.0086
Moment X	-0.0324
Moment Y (Twist)	0.0065
Moment Z	5.1355

Reaction Forces for Foundation 3 (Node ID#201), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	-0.0014	2.4549	0.0047	0.0174	-0.0011	0.0374
ULS: 2. D + L	-0.0014	2.4549	0.0047	0.0174	-0.0011	0.0374
ULS: 3. D + (S or Lr or R)	-0.0014	2.4549	0.0047	0.0174	-0.0011	0.0374
ULS: 3. D + (S or Lr or R)	-0.0014	2.4549	0.0047	0.0174	-0.0011	0.0374
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0014	2.4549	0.0047	0.0174	-0.0011	0.0374
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0014	2.4549	0.0047	0.0174	-0.0011	0.0374
ULS: 5b. D + 0.7E	-0.0014	2.4549	0.0047	0.0174	-0.0011	0.0374
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	-0.0014	2.4549	0.0047	0.0174	-0.0011	0.0374
ULS: 8. 0.6D + 0.7E	-0.0009	1.4730	0.0028	0.0104	-0.0006	0.0224
ULS: 5a. D + 0.6W_Wind downforce Case A only	-0.1608	4.3231	0.0086	0.0324	0.0000	2.3049
ULS: 5a. D + 0.6W_Wind downforce Case B only	-0.1608	4.3231	0.0086	0.0324	0.0000	2.3049
ULS: 5a. D + 0.6W_Wind uplift Case A only	0.0460	1.9506	0.0032	0.0121	0.0011	1.3354
ULS: 5a. D + 0.6W_Wind uplift Case B only	0.0914	1.2693	0.0028	0.0101	-0.0065	-5.1206

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.1210	3.8561	0.0076	0.0286	-0.0002	1.7380
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.1210	3.8561	0.0076	0.0286	-0.0002	1.7380
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.0341	2.0767	0.0036	0.0135	0.0006	1.0109
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.0682	1.5657	0.0033	0.0119	-0.0051	-3.8311
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.1210	3.8561	0.0076	0.0286	-0.0002	1.7380
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.1210	3.8561	0.0076	0.0286	-0.0002	1.7380
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.0341	2.0767	0.0036	0.0135	0.0006	1.0109
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.0682	1.5657	0.0033	0.0119	-0.0051	-3.8311
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-0.1602	3.3411	0.0067	0.0254	0.0005	2.2900
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-0.1602	3.3411	0.0067	0.0254	0.0005	2.2900
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	0.0465	0.9686	0.0013	0.0052	0.0015	1.3205
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	0.0920	0.2873	0.0010	0.0032	-0.0060	-5.1355

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	6.0596
Shear X	-0.2670
Shear Z	0.0122
Moment X	0.0460
Moment Y (Twist)	0.0107
Moment Z	8.8347

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	4.3231
Shear X	-0.1608
Shear Z	0.0086
Moment X	0.0324
Moment Y (Twist)	0.0065
Moment Z	5.1355

Reaction Forces for Foundation 4 (Node ID#301), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	0.0014	2.1618	-0.0319	-0.1184	0.0036	0.0061
ULS: 2. D + L	0.0014	2.1618	-0.0319	-0.1184	0.0036	0.0061
ULS: 3. D + (S or Lr or R)	0.0014	2.1618	-0.0319	-0.1184	0.0036	0.0061
ULS: 3. D + (S or Lr or R)	0.0014	2.1618	-0.0319	-0.1184	0.0036	0.0061
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0014	2.1618	-0.0319	-0.1184	0.0036	0.0061
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0014	2.1618	-0.0319	-0.1184	0.0036	0.0061
ULS: 5b. D + 0.7E	0.0014	2.1618	-0.0319	-0.1184	0.0036	0.0061
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	0.0014	2.1618	-0.0319	-0.1184	0.0036	0.0061
ULS: 8. 0.6D + 0.7E	0.0009	1.2971	-0.0191	-0.0710	0.0022	0.0036
ULS: 5a. D + 0.6W_Wind downforce Case A only	-0.1430	3.7668	-0.0611	-0.2264	0.0144	2.0638
ULS: 5a. D + 0.6W_Wind downforce Case B only	-0.1430	3.7668	-0.0611	-0.2264	0.0144	2.0638
ULS: 5a. D + 0.6W_Wind uplift Case A only	0.0360	1.7290	-0.0247	-0.0918	0.0034	1.2392
ULS: 5a. D + 0.6W_Wind uplift Case B only	0.1015	1.1423	-0.0120	-0.0456	-0.0083	-4.7925
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.1069	3.3655	-0.0538	-0.1994	0.0117	1.5494
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.1069	3.3655	-0.0538	-0.1994	0.0117	1.5494
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.0274	1.8372	-0.0265	-0.0985	0.0034	0.9309
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.0765	1.3972	-0.0170	-0.0638	-0.0054	-3.5928
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-0.1069	3.3655	-0.0538	-0.1994	0.0117	1.5494
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-0.1069	3.3655	-0.0538	-0.1994	0.0117	1.5494
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	0.0274	1.8372	-0.0265	-0.0985	0.0034	0.9309
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	0.0765	1.3972	-0.0170	-0.0638	-0.0054	-3.5928

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-0.1436	2.9020	-0.0483	-0.1791	0.0129	2.0614
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-0.1436	2.9020	-0.0483	-0.1791	0.0129	2.0614
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	0.0355	0.8643	-0.0120	-0.0445	0.0019	1.2367
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	0.1010	0.2776	0.0007	0.0017	-0.0098	-4.7949

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
 Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	5.2691
Shear X	-0.2408
Shear Z	-0.0871
Moment X	-0.3236
Moment Y (Twist)	0.0225
Moment Z	8.2405

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
 Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	3.7668
Shear X	-0.1436
Shear Z	-0.0611
Moment X	-0.2264
Moment Y (Twist)	0.0144
Moment Z	4.7949

Project Details

Design Code: AISC 360-16 LRFD
 Provision: LRFD
 Country: United States
 User Name: sales@mtsolar.us
 Unit System: imperial




Design Input Information


Design Factors			
Φ_t	Φ_c	Φ_b	Φ_v
0.9	0.9	0.9	0.9

Design Materials			
ID	E (ksi)	F_y (ksi)	F_u (ksi)
1	29000	50	65


Section Dimensions



ID	Name	d (in)	t_w (in)				
1	2in Pipe Sch 40	2.38	0.15				
4	4in Pipe Sch 40	4.50	0.24				
7	6in Pipe Sch 40	6.63	0.28				



ID	Name	d (in)	b (in)	t_w (in)	t_b (in)	r (in)	
15	HSS5x3x1/8	5.00	3.00	0.12	0.12	0.12	



ID	Name	d (in)	t_w (in)	b_t (in)	b_b (in)	t_t (in)	t_b (in)	r (in)
18	W6x9	5.90	0.17	3.94	3.94	0.21	0.21	0.25

Section Properties								
ID	Name	A (in ²)	J (in ⁴)	I_{yp} (in ⁴)	I_{zp} (in ⁴)	I_w (in ⁶)	S_{yp} (in ³)	S_{zp} (in ³)

113	18	4.88	4.00	7.50	1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.05,1.24,1.04,1.04,1.05,1.24,1.04,1.04,1.04,1.03,1.04,1.04,1.0	300	200	1
114	18	4.88	4.00	7.50	1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.03,1.09,1.04,1.04,1.03,1.09,1.04,1.04,1.04,1.05,1.04,1.04,1.0	300	200	1
115	18	6.63	6.63	10.20	1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.15,1.12,1.16,1.16,1.15,1.12,1.16,1.16,1.15,1.20,1.16,1.16,1.1	300	200	1
116	18	6.63	6.63	10.20	1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.17,1.14,1.16,1.16,1.17,1.14,1.16,1.16,1.16,1.15,1.16,1.16,1.1	300	200	1
201	7	24.82	24.82	11.82	-	300	200	1
202	4	1.30	1.30	2.00	-	300	200	1
203	15	0.92	0.92	1.42	1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.17,1.18,1.18,1.18,1.17,1.18,1.18,1.18,1.20,1.18,1.18,1.1	300	200	1
204	15	2.44	2.44	3.75	1.68,1.68,1.68,1.68,1.68,1.68,1.67,1.67,1.70,1.68,1.67,1.67,1.70,1.68,1.67,1.67,1.68,1.68,1.67,1.67,1.6	300	200	1
205	15	1.52	1.52	2.33	1.67,1.67,1.67,1.67,1.67,1.67,1.67,1.67,1.67,1.66,1.67,1.67,1.67,1.66,1.67,1.67,1.67,1.69,1.67,1.67,1.6	300	200	1
206	15	0.92	0.92	1.42	1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.17,1.18,1.18,1.18,1.17,1.18,1.18,1.18,1.20,1.18,1.18,1.1	300	200	1
207	15	1.52	1.52	2.33	1.67,1.67,1.67,1.67,1.67,1.67,1.67,1.67,1.67,1.65,1.67,1.67,1.67,1.65,1.67,1.67,1.67,1.69,1.67,1.67,1.6	300	200	1
208	18	1.33	1.33	2.05	2.08,2.08,2.08,2.08,2.08,2.08,2.08,2.08,2.08,2.12,2.03,2.08,2.08,2.12,2.03,2.08,2.08,2.09,2.07,2.08,2.08,2.0	300	200	1
209	1	2.60	2.60	4.00	-	300	200	1
210	15	2.44	2.44	3.75	1.68,1.68,1.68,1.68,1.68,1.68,1.67,1.67,1.70,1.68,1.67,1.67,1.70,1.68,1.67,1.67,1.68,1.68,1.67,1.67,1.6	300	200	1
211	18	1.33	1.33	2.05	2.08,2.08,2.08,2.08,2.08,2.08,2.08,2.08,2.07,1.77,2.08,2.08,2.07,1.77,2.08,2.08,2.07,2.32,2.08,2.08,2.0	300	200	1
212	4	1.30	1.30	2.00	-	300	200	1
213	18	4.88	4.00	7.50	1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.05,1.24,1.04,1.04,1.05,1.24,1.04,1.04,1.04,1.03,1.04,1.04,1.0	300	200	1
214	18	4.88	4.00	7.50	1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.04,1.03,1.09,1.04,1.04,1.03,1.09,1.04,1.04,1.04,1.05,1.04,1.04,1.0	300	200	1
215	18	6.63	6.63	10.20	1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.14,1.16,1.16,1.16,1.14,1.16,1.16,1.16,1.19,1.16,1.16,1.1	300	200	1
216	18	6.63	6.63	10.20	1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.16,1.17,1.15,1.16,1.16,1.17,1.15,1.16,1.16,1.16,1.16,1.16,1.16,1.1	300	200	1
301	7	24.82	24.82	11.82	-	300	200	1
302	4	1.30	1.30	2.00	-	300	200	1
303	15	0.92	0.92	1.42	1.19,1.19,1.19,1.19,1.19,1.19,1.18,1.18,1.19,1.17,1.18,1.18,1.19,1.17,1.18,1.18,1.19,1.20,1.18,1.18,1.1	300	200	1
304	15	2.44	2.44	3.75	1.68,1.68,1.68,1.68,1.68,1.68,1.67,1.67,1.70,1.68,1.67,1.67,1.70,1.68,1.67,1.67,1.68,1.68,1.67,1.67,1.6	300	200	1
305	15	1.52	1.52	2.33	1.67,1.67,1.67,1.67,1.67,1.67,1.67,1.67,1.67,1.65,1.67,1.67,1.67,1.65,1.67,1.67,1.67,1.70,1.67,1.67,1.6	300	200	1
306	15	0.92	0.92	1.42	1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.16,1.18,1.18,1.18,1.16,1.18,1.18,1.18,1.21,1.18,1.18,1.1	300	200	1
307	15	1.52	1.52	2.33	1.67,1.67,1.67,1.67,1.67,1.67,1.67,1.67,1.67,1.65,1.67,1.67,1.67,1.65,1.67,1.67,1.67,1.70,1.67,1.67,1.6	300	200	1
308	18	7.88	7.88	3.75	2.33,2.3	300	200	1
309	1	2.60	2.60	4.00	-	300	200	1
310	15	2.44	2.44	3.75	1.68,1.68,1.68,1.68,1.68,1.68,1.67,1.67,1.70,1.68,1.67,1.67,1.70,1.68,1.67,1.67,1.69,1.68,1.67,1.67,1.6	300	200	1
311	18	7.88	7.88	3.75	2.33,2.3	300	200	1
312	4	1.30	1.30	2.00	-	300	200	1
313	18	4.88	4.00	7.50	1.11,1.11,1.11,1.11,1.11,1.11,1.11,1.11,1.11,1.11,1.22,1.11,1.11,1.11,1.22,1.11,1.11,1.11,1.09,1.11,1.11,1.1	300	200	1
314	18	4.88	4.00	7.50	1.11,1.11,1.11,1.11,1.11,1.11,1.11,1.11,1.11,1.08,1.13,1.11,1.11,1.08,1.13,1.11,1.11,1.10,1.12,1.11,1.11,1.1	300	200	1

315	18	6.63	6.63	10.20	1.12,1.12,1.12,1.12,1.12,1.12,1.12,1.12,1.12,1.13,1.16,1.12,1.12,1.13,1.16,1.12,1.12,1.13,1.10,1.12,1.12,1.13,1.10,1.12,1.12,1.13,1.10,1.12,1.12,1.13,1.15	300	200	1
316	18	6.63	6.63	10.20	1.12,1.12,1.12,1.12,1.12,1.12,1.12,1.12,1.12,1.11,1.14,1.12,1.12,1.11,1.14,1.12,1.12,1.12,1.13,1.12,1.12,1.11,2.1.13,1.12,1.12,1.09,1.15	300	200	1

Member Design Capacity

Member ID	$\Phi_t P_n$ (kip)	$\Phi_c P_n$ (kip)	$\Phi_b M_{zn}$ (k-ft)	$\Phi_b M_{yn}$ (k-ft)	$\Phi_v V_{yn}$ (kip)	$\Phi_v V_{zn}$ (kip)
1	251.16	71.66	42.30	42.30	75.35	75.35
2	142.83	141.72	16.17	16.17	42.85	42.85
3	79.65	74.89	10.99	6.26	29.14	16.61
4	79.65	72.84	10.99	6.26	29.14	16.61
5	79.65	74.30	10.99	6.26	29.14	16.61
6	79.65	74.89	10.99	6.26	29.14	16.61
7	79.65	74.30	10.99	6.26	29.14	16.61
8	120.60	115.40	23.36	6.45	30.09	45.74
9	48.35	43.11	2.85	2.85	14.51	14.51
10	79.65	72.84	10.99	6.26	29.14	16.61
11	120.60	115.40	23.36	6.45	30.09	45.74
12	142.83	141.72	16.17	16.17	42.85	42.85
13	120.60	84.03	19.16	6.45	30.09	45.74
14	120.60	84.03	18.26	6.45	30.09	45.74
15	120.60	54.44	23.36	6.45	30.09	45.74
16	120.60	54.44	23.36	6.45	30.09	45.74
101	251.16	71.66	42.30	42.30	75.35	75.35
102	142.83	141.72	16.17	16.17	42.85	42.85
103	79.65	74.89	10.99	6.26	29.14	16.61
104	79.65	72.84	10.99	6.26	29.14	16.61
105	79.65	74.30	10.99	6.26	29.14	16.61
106	79.65	74.89	10.99	6.26	29.14	16.61
107	79.65	74.30	10.99	6.26	29.14	16.61
108	120.60	115.40	23.36	6.45	30.09	45.74
109	48.35	43.11	2.85	2.85	14.51	14.51
110	79.65	72.84	10.99	6.26	29.14	16.61
111	120.60	115.40	23.36	6.45	30.09	45.74
112	142.83	141.72	16.17	16.17	42.85	42.85
113	120.60	84.03	18.13	6.45	30.09	45.74
114	120.60	84.03	18.00	6.45	30.09	45.74
115	120.60	68.63	15.35	6.45	30.09	45.74
116	120.60	68.63	15.51	6.45	30.09	45.74
201	251.16	71.66	42.30	42.30	75.35	75.35
202	142.83	141.72	16.17	16.17	42.85	42.85
203	79.65	74.89	10.99	6.26	29.14	16.61
204	79.65	72.84	10.99	6.26	29.14	16.61
205	79.65	74.30	10.99	6.26	29.14	16.61
206	79.65	74.89	10.99	6.26	29.14	16.61
207	79.65	74.30	10.99	6.26	29.14	16.61
208	120.60	115.40	23.36	6.45	30.09	45.74
209	48.35	43.11	2.85	2.85	14.51	14.51
210	79.65	72.84	10.99	6.26	29.14	16.61
211	120.60	115.40	23.36	6.45	30.09	45.74
212	142.83	141.72	16.17	16.17	42.85	42.85

212	142.85	141.72	10.17	10.17	42.85	42.85
213	120.60	84.03	18.13	6.45	30.09	45.74
214	120.60	84.03	18.00	6.45	30.09	45.74
215	120.60	68.63	15.61	6.45	30.09	45.74
216	120.60	68.63	15.70	6.45	30.09	45.74
301	251.16	71.66	42.30	42.30	75.35	75.35
302	142.83	141.72	16.17	16.17	42.85	42.85
303	79.65	74.89	10.99	6.26	29.14	16.61
304	79.65	72.84	10.99	6.26	29.14	16.61
305	79.65	74.30	10.99	6.26	29.14	16.61
306	79.65	74.89	10.99	6.26	29.14	16.61
307	79.65	74.30	10.99	6.26	29.14	16.61
308	120.60	54.44	23.36	6.45	30.09	45.74
309	48.35	43.11	2.85	2.85	14.51	14.51
310	79.65	72.84	10.99	6.26	29.14	16.61
311	120.60	54.44	23.36	6.45	30.09	45.74
312	142.83	141.72	16.17	16.17	42.85	42.85
313	120.60	84.03	19.16	6.45	30.09	45.74
314	120.60	84.03	18.26	6.45	30.09	45.74
315	120.60	68.63	15.09	6.45	30.09	45.74
316	120.60	68.63	14.94	6.45	30.09	45.74

Design Ratio

Member ID	P	M _z	M _y	V _y	V _z	(P,M _z ,M _y)	Worst LC	KL/r	δ	Status
1	0.074	0.195	0.017	0.003	0.001	0.202	#16	0.663	Not Required	Pass
2	0.000	0.256	0.016	0.055	0.003	0.272	#13	0.034	Not Required	Pass
3	0.001	0.406	0.004	0.041	0.001	0.407	#13	0.044	Not Required	Pass
4	0.001	0.384	0.014	0.039	0.003	0.398	#13	0.078	Not Required	Pass
5	0.001	0.251	0.010	0.041	0.002	0.253	#13	0.073	Not Required	Pass
6	0.001	0.453	0.012	0.047	0.002	0.464	#13	0.044	Not Required	Pass
7	0.001	0.280	0.021	0.045	0.004	0.285	#13	0.073	Not Required	Pass
8	0.000	0.051	0.015	0.027	0.001	0.057	#13	0.088	Not Required	Pass
9	0.001	0.054	0.009	0.001	0.000	0.064	#13	0.198	Not Required	Pass
10	0.001	0.426	0.020	0.043	0.003	0.428	#13	0.078	Not Required	Pass
11	0.000	0.052	0.015	0.028	0.001	0.057	#13	0.088	Not Required	Pass
12	0.000	0.300	0.017	0.062	0.003	0.317	#13	0.052	Not Required	Pass
13	0.000	0.122	0.028	0.037	0.001	0.130	#13	0.265	Not Required	Pass
14	0.001	0.118	0.028	0.035	0.001	0.119	#13	0.177	Not Required	Pass
15	0.000	0.043	0.007	0.018	0.001	0.049	#13	Not Required	Not Required	Pass
16	0.000	0.041	0.007	0.017	0.001	0.047	#13	Not Required	Not Required	Pass
101	0.085	0.209	0.002	0.004	0.000	0.216	#16	0.663	Not Required	Pass
102	0.000	0.325	0.019	0.068	0.003	0.345	#13	0.052	Not Required	Pass
103	0.001	0.500	0.007	0.051	0.001	0.507	#13	0.044	Not Required	Pass
104	0.001	0.475	0.015	0.048	0.002	0.485	#13	0.078	Not Required	Pass
105	0.001	0.309	0.017	0.050	0.003	0.313	#13	0.073	Not Required	Pass
106	0.001	0.494	0.008	0.050	0.002	0.499	#13	0.044	Not Required	Pass
107	0.001	0.306	0.014	0.050	0.003	0.309	#13	0.073	Not Required	Pass
108	0.000	0.034	0.007	0.028	0.001	0.037	#13	0.088	Not Required	Pass
109	0.001	0.055	0.007	0.001	0.000	0.063	#13	0.198	Not Required	Pass
110	0.001	0.468	0.014	0.048	0.003	0.478	#13	0.078	Not Required	Pass

111	0.001	0.037	0.007	0.029	0.001	0.040	#13	0.088	Not Required	Pass
112	0.000	0.319	0.019	0.067	0.003	0.339	#13	0.052	Not Required	Pass
113	0.001	0.141	0.021	0.039	0.001	0.152	#13	0.265	Not Required	Pass
114	0.001	0.139	0.021	0.037	0.001	0.148	#13	0.265	Not Required	Pass
115	0.001	0.146	0.011	0.030	0.001	0.156	#13	0.439	Not Required	Pass
116	0.001	0.139	0.011	0.029	0.001	0.149	#13	0.439	Not Required	Pass
201	0.085	0.209	0.002	0.004	0.000	0.216	#16	0.663	Not Required	Pass
202	0.000	0.319	0.019	0.067	0.003	0.339	#13	0.052	Not Required	Pass
203	0.001	0.494	0.008	0.050	0.002	0.499	#13	0.044	Not Required	Pass
204	0.001	0.468	0.014	0.048	0.003	0.478	#13	0.078	Not Required	Pass
205	0.001	0.306	0.014	0.050	0.003	0.309	#13	0.073	Not Required	Pass
206	0.001	0.500	0.007	0.051	0.001	0.507	#13	0.044	Not Required	Pass
207	0.001	0.309	0.017	0.050	0.003	0.313	#13	0.073	Not Required	Pass
208	0.000	0.039	0.010	0.029	0.001	0.040	#13	0.088	Not Required	Pass
209	0.001	0.055	0.007	0.001	0.000	0.063	#13	0.198	Not Required	Pass
210	0.001	0.475	0.015	0.048	0.002	0.485	#13	0.078	Not Required	Pass
211	0.000	0.042	0.010	0.030	0.001	0.043	#13	0.088	Not Required	Pass
212	0.000	0.325	0.019	0.068	0.003	0.345	#13	0.052	Not Required	Pass
213	0.001	0.141	0.021	0.039	0.001	0.152	#13	0.265	Not Required	Pass
214	0.001	0.139	0.021	0.037	0.001	0.148	#13	0.265	Not Required	Pass
215	0.001	0.130	0.011	0.029	0.001	0.139	#13	0.439	Not Required	Pass
216	0.001	0.122	0.011	0.028	0.001	0.132	#13	0.439	Not Required	Pass
301	0.074	0.195	0.017	0.003	0.001	0.202	#16	0.663	Not Required	Pass
302	0.000	0.300	0.017	0.062	0.003	0.317	#13	0.052	Not Required	Pass
303	0.001	0.453	0.012	0.047	0.002	0.464	#13	0.044	Not Required	Pass
304	0.001	0.426	0.020	0.043	0.003	0.428	#13	0.078	Not Required	Pass
305	0.001	0.280	0.021	0.045	0.004	0.285	#13	0.073	Not Required	Pass
306	0.001	0.406	0.004	0.041	0.001	0.407	#13	0.044	Not Required	Pass
307	0.001	0.251	0.010	0.041	0.002	0.253	#13	0.073	Not Required	Pass
308	0.000	0.041	0.007	0.017	0.001	0.047	#13	Not Required	Not Required	Pass
309	0.001	0.054	0.009	0.001	0.000	0.064	#13	0.198	Not Required	Pass
310	0.001	0.384	0.014	0.039	0.003	0.398	#13	0.078	Not Required	Pass
311	0.000	0.043	0.007	0.018	0.001	0.049	#13	Not Required	Not Required	Pass
312	0.000	0.256	0.016	0.055	0.003	0.272	#13	0.034	Not Required	Pass
313	0.000	0.122	0.028	0.037	0.001	0.130	#13	0.177	Not Required	Pass
314	0.001	0.118	0.028	0.035	0.001	0.119	#13	0.265	Not Required	Pass
315	0.001	0.149	0.015	0.028	0.001	0.159	#13	0.439	Not Required	Pass
316	0.001	0.142	0.015	0.027	0.001	0.153	#13	0.439	Not Required	Pass

Definitions

Φ_t	Safety factor for tensile
Φ_c	Safety factor for compression
Φ_b	Safety factor for flexure
Φ_v	Safety factor for shear
E	Modulus of elasticity
F_y	Specified minimum yield stress
F_u	Specified minimum tensile strength
A	Cross-sectional area
J	Torsional constant
I_{yp}	Moment of inertia about the Y axes
I_{zp}	Moment of inertia about the Z axes
I_w	Warping constant
S_{yp}	Plastic section modulus about the Y axis
S_{zp}	Plastic section modulus about the Z axis

KL	Effective length
C_b	Buckling modification factor (from all load combinations)
L_b	Length between braced points
LST	Limited slenderness for tension
LSC	Limited slenderness for compression
LD	Limited deflection
P_n	Nominal axial strength (tension/compression)
M_n	Nominal flexural strength (about Z/Y axis)
V_n	Nominal shear strength (along Z/Y axis)
P	Design ratio in case of axial force
M_z	Design ratio in case of bending about Z axis
M_y	Design ratio in case of bending about Y axis
V_y	Design ratio in case of shear along Y axis
V_z	Design ratio in case of shear along Z axis
(P, M_z , M_y)	Design ratio in case of axial force and bending action
KL/r	Design ratio in case of section slenderness
δ	Design ratio in case of member deflection
OK	Capacity is provided
NG	Capacity is not provided

REFERENCES	CALCULATIONS	RESULTS
------------	--------------	---------


SkyCiv Foundation Design

Pile Foundation

Design Information :

Design code : IBC 2021 (International Building Code)
Unit System : Imperial

Pile Input



Geometry

Pile shape: rectangular

$b = 48$ in - Pile width

$D = 48$ in - Pile depth

$L = 4$ ft - Total pile length

$h_1 = 0$ ft - Lateral load height from the top of the pile,

$h_2 = 0$ ft - Depth to resisting surface

$h_e = 0$ ft - Length of pile above the ground

Tabulation of Soil Parameters

Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000

Tabulation of Loads

Load Component	ASD	LRFD
P (kip)	3.767	5.269
V_x (kip)	-0.144	-0.241
V_z (kip)	0.061	0.087
M_x (kipft)	0.226	0.324
M_z (kipft)	4.795	8.240

Material Properties

$f'_{ck} = 2.5$ ksi - Concrete strength.

Required depth to resist lateral loads (ASD)

H - Point of application of the lateral load

$$H = h_1 + h_2 + h_e$$

$$H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$$

$$H = 0 \text{ ft}$$

Considering x-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-0.144 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.02293 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(4.795 \text{ kipft}) + ((-0.144 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.76354 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,x} = 3.8219 \text{ ft}$ - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.061 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.0097134 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.226 \text{ kipft}) + ((0.061 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.035987 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,z} = 1.5588 \text{ ft}$ - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = \text{MAX}[(3.8219 \text{ ft}), (1.5588 \text{ ft})]$$

$$L_{e,req} = 3.822 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_e - h_2$$

$$L_e = (4 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 4 \text{ ft}$$

Ratio - Embedded depth

$$\text{Ratio} = \frac{L_{e,req}}{L_e}$$

$$\text{Ratio} = \frac{(3.822 \text{ ft})}{(4 \text{ ft})}$$

$$\text{Ratio} = 0.9555$$

Status: **PASS**
Ratio: **0.960**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_v}{A}$$

$$q = \frac{(3.767 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.23544 \text{ kip/ft}^2$$

Check bearing capacity ratio:

Ratio - Capacity

$$\text{Ratio} = \frac{q}{q_a}$$

$$\text{Ratio} = \frac{(0.23544 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$\text{Ratio} = 0.11772$$

Status: **PASS**
Ratio: **0.120**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(4 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.02293 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.76354 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.76354 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (-0.02293 \text{ kip/ft}) \times (4 \text{ ft})^2)}{(6 \times (0.76354 \text{ kipft/ft})) + (4 \times (-0.02293 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.6914 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (0.76354 \text{ kipft/ft})) + (3 \times (-0.02293 \text{ kip/ft}) \times (4 \text{ ft}))]^2}{(4 \text{ ft})^2 \times [(3 \times (0.76354 \text{ kipft/ft})) + (2 \times (-0.02293 \text{ kip/ft}) \times (4 \text{ ft}))]}$$

$$p = 0.1718 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.76354 \text{ kipft/ft})) + ((-0.02293 \text{ kip/ft}) \times (4 \text{ ft}))]}{(4 \text{ ft})^2}$$

$$s = 0.53826 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(2.6914 \text{ ft})}{2}$$

$$p_a = 0.20185 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.1718 \text{ kip/ft}^2)}{(0.20185 \text{ kip/ft}^2)}$$

$$Ratio = 0.85109$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (4 \text{ ft})$$

$$p_s = 0.6 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.53826 \text{ kip/ft}^2)}{(0.6 \text{ kip/ft}^2)}$$

$$Ratio = 0.89709$$

Status: **PASS**
Ratio: **0.850**

Status: **PASS**
Ratio: **0.900**

Considering z-direction:

$H_o = 0.0097134 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.035987 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.035987 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (0.0097134 \text{ kip/ft}) \times (4 \text{ ft})^2)}{(6 \times (0.035987 \text{ kipft/ft})) + (4 \times (0.0097134 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.8062 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (0.035987 \text{ kipft/ft})) + (3 \times (0.0097134 \text{ kip/ft}) \times (4 \text{ ft}))]^2}{(4 \text{ ft})^2 \times [(3 \times (0.035987 \text{ kipft/ft})) + (2 \times (0.0097134 \text{ kip/ft}) \times (4 \text{ ft}))]}$$

$$p = 0.017134 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.035987 \text{ kipft/ft})) + ((0.0097134 \text{ kip/ft}) \times (4 \text{ ft}))]}{(4 \text{ ft})^2}$$

$$s = 0.041561 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(2.8062 \text{ ft})}{2}$$

$$p_a = 0.21046 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.017134 \text{ kip/ft}^2)}{(0.21046 \text{ kip/ft}^2)}$$

$$Ratio = 0.081409$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (4 \text{ ft})$$

$$p_s = 0.6 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity


$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.041561 \text{ kip/ft}^2)}{(0.6 \text{ kip/ft}^2)}$$

$$Ratio = 0.069268$$

Status: **PASS**
Ratio: **0.080**

Status: **PASS**
Ratio: **0.070**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-0.241 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.038376 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(8.24 \text{ kipft}) + ((-0.241 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 1.3121 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(1.3121 \text{ kipft/ft})}{(-0.038376 \text{ kip/ft})}$$

$$E = 34.191 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (1.3121 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (-0.038376 \text{ kip/ft}) \times (4 \text{ ft})^2)}{6 \times (1.3121 \text{ kipft/ft}) + 4 \times (-0.038376 \text{ kip/ft}) \times (4 \text{ ft})}$$

$$a = \frac{(-0.038376 \text{ kip/ft}) \times (48 \text{ in})}{(6 \times (1.3121 \text{ kipft/ft})) + (4 \times (-0.038376 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.6908 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.038376 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (34.191 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.6908 \text{ ft})}{(4 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (34.191 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.6908 \text{ ft})}{(4 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 2.4299 \text{ kip}$$

M_{max} - Max bending moment located at depth a/2,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.038376 \text{ kip/ft}) \times (48 \text{ in}) \times (4 \text{ ft})) \times \left[\left(\frac{(34.191 \text{ ft})}{(4 \text{ ft})} + \frac{(2.6908 \text{ ft})}{2 \times (4 \text{ ft})} \right) - \left[\left(\frac{4 \times (34.191 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.6908 \text{ ft})}{2 \times (4 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (34.191 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.6908 \text{ ft})}{2 \times (4 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 4.8032 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.087 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.013854 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.324 \text{ kipft}) + ((0.087 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.051592 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.051592 \text{ kipft/ft})}{(0.013854 \text{ kip/ft})}$$

$$E = 3.7241 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.051592 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (0.013854 \text{ kip/ft}) \times (4 \text{ ft})^2)}{(6 \times (0.051592 \text{ kipft/ft})) + (4 \times (0.013854 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.8058 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((0.013854 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (3.7241 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.8058 \text{ ft})}{(4 \text{ ft})} \right)^2 \right] \right. \\ \left. + \left[4 \times \left(\frac{3 \times (3.7241 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.8058 \text{ ft})}{(4 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.12792 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o \cdot b \cdot L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) \right. \\ \left. - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((0.013854 \text{ kip/ft}) \times (48 \text{ in}) \times (4 \text{ ft})) \times \left[\left(\frac{(3.7241 \text{ ft})}{(4 \text{ ft})} + \frac{(2.8058 \text{ ft})}{2 \times (4 \text{ ft})} \right) \right. \\ \left. - \left[\left(\frac{4 \times (3.7241 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.8058 \text{ ft})}{2 \times (4 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (3.7241 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.8058 \text{ ft})}{2 \times (4 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 0.23589 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 2.5 \text{ ksi}$ - Concrete strength,

$f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,

$\phi = 0.65$ - Reduction factor for axial strength,

$\alpha = 0.8$ - Alpha factor for axial strength,

$A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(5.269 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (2.5 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (2.5 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -84.421 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-84.421 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \cdot \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

Table 22.4.2.1

22.4.2.2, 10.6.1.1

<p>25.2.3 s_{rebar} - Minimum spacing of reinforcement,</p> <p>25.7.2.2 Since longitudinal reinforcement is \leq No. 10ø: Use #3(0.375 in)</p> <p>25.7.2.1 s_{ties} - Maximum spacing of ties,</p>	<p style="text-align: center;">$Ratio = 0.96556$</p> <p style="text-align: center;">$s_{rebar} = Max[1.5, (1.5 d_{bar})]$</p> <p style="text-align: center;">$s_{rebar} = Max[1.5, (1.5 \times (0.625 \text{ in}))]$</p> <p style="text-align: center;">$s_{rebar} = 1.5 \text{ in}$</p> <p>Ties:</p> <p style="text-align: center;">$s_{ties} = Min[(16 d_{bar}), (48 d_{ties}), Min(D, b)]$</p> <p style="text-align: center;">$s_{ties} = Min[(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), Min((48 \text{ in}), (48 \text{ in}))]$</p> <p style="text-align: center;">$s_{ties} = 10 \text{ in}$</p> <p>Summary:</p> <p style="text-align: center;">Main reinforcement: 14 - #5 (0.625 in) Ties: #3(0.375 in) - 10 in</p>	<p>Status: PASS Ratio: 0.970</p>
<p>22.4.2.2 ϕP_N - Allowable axial compressive strength</p>	<p>Axial Compression Strength (ACI 318-19, LRFD)</p> <p style="text-align: center;">$\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_y k A_{st})]$</p> <p style="text-align: center;">$\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (2.5 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$</p> <p style="text-align: center;">$\phi P_N = 2675.2 \text{ kip}$</p> <p><i>Ratio - Capacity</i></p> <p style="text-align: center;">$Ratio = \frac{P}{\phi P_N}$</p> <p style="text-align: center;">$Ratio = \frac{(5.269 \text{ kip})}{(2675.2 \text{ kip})}$</p> <p style="text-align: center;">$Ratio = 0.0019696$</p>	<p>Status: PASS Ratio: 0.000</p>
<p>22.5.2.2 b_w = 48 in - Effective width, d - Effective depth</p> <p>22.5.5.1.3 λ_s - size effect modification factor</p> <p>22.5.5.1.1 $V_{c,max}$ - Max shear strength of concrete</p>	<p>Shear Strength (ACI 318-19, LRFD)</p> <p>Parameters:</p> <p style="text-align: center;">$d = 0.80 D$</p> <p style="text-align: center;">$d = 0.80 \times (48 \text{ in})$</p> <p style="text-align: center;">$d = 38.4 \text{ in}$</p> <p style="text-align: center;">$\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = 0.64282$</p> <p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,</p> <p style="text-align: center;">$V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$</p> <p style="text-align: center;">$V_{c,max} = 5 \times (0.64282) \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$</p>	

$$V_{c,max} = 296.21 \text{ kip}$$

22.5.5.1.1(a) The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $P = 5.269 \text{ kip} \rightarrow 5269 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck} + \frac{P}{6 A_g}} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + \frac{(5269 \text{ lbf})}{6 \times (2304 \text{ in}^2)}} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 119.19 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck} + (0.05 f'_{ck})} \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + (0.05 \times (2500 \text{ psi}))} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 348.89 \text{ kip}$$

V_c - Governing shear strength of concrete

$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(296.21 \text{ kip}), (119.19 \text{ kip}), (348.89 \text{ kip})]$$

$$V_c = 119.19 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{s,a}$ - Shear strength of steel (a)

$$V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$$

$$V_{s,a} = 8 \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{s,a} = 737.28 \text{ kip}$$

A_v - Ties rebar area,

$$A_v = \frac{\pi d_{ties}^2}{4}$$

$$A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$$

$$A_v = 0.11045 \text{ in}^2$$

22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)

$$V_{s,b} = \frac{2 A_v f_{yw} d}{s_{ties}}$$

$$V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$$

$$V_{s,b} = 50.894 \text{ kip}$$

V_s - Governing shear strength of steel

$$V_s = \text{MIN}[V_{s,a}, V_{s,b}]$$

$$V_s = \text{MIN}[(737.28 \text{ kip}), (50.894 \text{ kip})]$$

$$V_s = 50.894 \text{ kip}$$

22.5.1.1 ϕV_n - Allowable shear strength

$$\phi V_n = \phi (V_c + V_s)$$

$$\phi V_n = (0.65) \times ((119.19 \text{ kip}) + (50.894 \text{ kip}))$$

$$\phi V_n = 110.55 \text{ kip}$$

Considering x-direction:

$V_{max} = 2.4299 \text{ kip}$ - Maximum shear force in the x-direction,

$Ratio$ - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(2.4299 \text{ kip})}{(110.55 \text{ kip})}$$

$$Ratio = 0.021979$$

Considering z-direction:

$V_{max} = 0.12792 \text{ kip}$ - Maximum shear force in the z-direction,

$Ratio$ - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(0.12792 \text{ kip})}{(110.55 \text{ kip})}$$

$$Ratio = 0.0011571$$

Status: **PASS**
Ratio: **0.020**

Status: **PASS**
Ratio: **0.000**

Flexural Strength (ACI 318-19, LRFD)

S_m - Section modulus

$$S_m = \frac{b D^2}{6}$$

$$S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$$

$$S_m = 18432 \text{ in}^3$$

$\lambda = 1$ - Concrete modification factor (Normal concrete),

Allowable flexural strength:

M_n shall be the lesser of:

$\phi M_{n,1}$

$$\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$$

$$\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{(2.5 \text{ ksi})} \times 18432.001 \text{ in}^3$$

$$\phi M_{n,1} = 249.600 \text{ kipft}$$

14.5.2.1b

$\phi M_{n,2}$

$$\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$$

$$\phi M_{n,2} = (0.65) \times 0.85 \times (2.5 \text{ ksi}) \times (18432 \text{ in}^3)$$

$$\phi M_{n,2} = 2121.6 \text{ kipft}$$

Therefore,

ϕM_n - Allowable flexural strength,

$$\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$$

$$\phi M_n = \text{MIN}[(249.6 \text{ kipft}), (2121.6 \text{ kipft})]$$

$$\phi M_n = 249.6 \text{ kipft}$$

Considering x-direction:

$M_{max} = 4.8032 \text{ kipft}$ - Maximum moment in the x-direction,

$Ratio$ - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(4.8032 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.019244$$

Status: **PASS**
Ratio: **0.020**

Considering z-direction:

$M_{max} = 0.23589 \text{ kipft}$ - Maximum moment in the z-direction,

$Ratio$ - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$\text{Ratio} = \frac{(0.23589 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$\text{Ratio} = 0.00094505$$

Status: **PASS**
Ratio: **0.000**

REFERENCES	CALCULATIONS	RESULTS
------------	--------------	---------


SkyCiv Foundation Design

Pile Foundation

Design Information :

Design code : IBC 2021 (International Building Code)
Unit System : Imperial

Pile Input



Geometry

Pile shape: rectangular

$b = 48$ in - Pile width

$D = 48$ in - Pile depth

$L = 4$ ft - Total pile length

$h_1 = 0$ ft - Lateral load height from the top of the pile,

$h_2 = 0$ ft - Depth to resisting surface

$h_e = 0$ ft - Length of pile above the ground

Tabulation of Soil Parameters

Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000

Tabulation of Loads

Load Component	ASD	LRFD
P (kip)	4.323	6.060
V_x (kip)	-0.161	-0.267
V_z (kip)	-0.009	-0.012
M_x (kipft)	-0.032	-0.046
M_z (kipft)	5.136	8.835

Material Properties

$f'_{ck} = 2.5$ ksi - Concrete strength.

Required depth to resist lateral loads (ASD)

H - Point of application of the lateral load

$$H = h_1 + h_2 + h_e$$

$$H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$$

$$H = 0 \text{ ft}$$

Considering x-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-0.161 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.025637 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(5.136 \text{ kipft}) + ((-0.161 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.81783 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,x} = 3.9023 \text{ ft}$ - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.009 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.0014331 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.032 \text{ kipft}) + ((-0.009 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.0050955 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,z} = 0.70316 \text{ ft}$ - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = \text{MAX}[(3.9023 \text{ ft}), (0.70316 \text{ ft})]$$

$$L_{e,req} = 3.902 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_e - h_2$$

$$L_e = (4 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 4 \text{ ft}$$

Ratio - Embedded depth

$$\text{Ratio} = \frac{L_{e,req}}{L_e}$$

$$\text{Ratio} = \frac{(3.902 \text{ ft})}{(4 \text{ ft})}$$

$$\text{Ratio} = 0.9755$$

Status: **PASS**
Ratio: **0.980**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_v}{A}$$

$$q = \frac{(4.323 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.27019 \text{ kip/ft}^2$$

Check bearing capacity ratio:

Ratio - Capacity

$$\text{Ratio} = \frac{q}{q_a}$$

$$\text{Ratio} = \frac{(0.27019 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$\text{Ratio} = 0.13509$$

Status: **PASS**
Ratio: **0.140**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(4 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.025637 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.81783 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.81783 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (-0.025637 \text{ kip/ft}) \times (4 \text{ ft})^2)}{(6 \times (0.81783 \text{ kipft/ft})) + (4 \times (-0.025637 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.6924 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (0.81783 \text{ kipft/ft})) + (3 \times (-0.025637 \text{ kip/ft}) \times (4 \text{ ft}))]^2}{(4 \text{ ft})^2 \times [(3 \times (0.81783 \text{ kipft/ft})) + (2 \times (-0.025637 \text{ kip/ft}) \times (4 \text{ ft}))]}$$

$$p = 0.18312 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.81783 \text{ kipft/ft})) + ((-0.025637 \text{ kip/ft}) \times (4 \text{ ft}))]}{(4 \text{ ft})^2}$$

$$s = 0.57492 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(2.6924 \text{ ft})}{2}$$

$$p_a = 0.20193 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.18312 \text{ kip/ft}^2)}{(0.20193 \text{ kip/ft}^2)}$$

$$Ratio = 0.90685$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (4 \text{ ft})$$

$$p_s = 0.6 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.57492 \text{ kip/ft}^2)}{(0.6 \text{ kip/ft}^2)}$$

$$Ratio = 0.9582$$

Status: **PASS**
Ratio: **0.910**

Status: **PASS**
Ratio: **0.960**

Considering z-direction:

$H_o = -0.0014331 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.0050955 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.0050955 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (-0.0014331 \text{ kip/ft}) \times (4 \text{ ft})^2)}{(6 \times (0.0050955 \text{ kipft/ft})) + (4 \times (-0.0014331 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.8095 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 [(4 \times (0.0050955 \text{ kipft/ft})) + (3 \times (-0.0014331 \text{ kip/ft}) \times (4 \text{ ft}))]^2}{(4 \text{ ft})^2 \times [(3 \times (0.0050955 \text{ kipft/ft})) + (2 \times (-0.0014331 \text{ kip/ft}) \times (4 \text{ ft}))]}$$

$$p = 0.0001244 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.0050955 \text{ kipft/ft})) + ((-0.0014331 \text{ kip/ft}) \times (4 \text{ ft}))]}{(4 \text{ ft})^2}$$

$$s = 0.001672 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(2.8095 \text{ ft})}{2}$$

$$p_a = 0.21071 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.0001244 \text{ kip/ft}^2)}{(0.21071 \text{ kip/ft}^2)}$$

$$Ratio = 0.00059039$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (4 \text{ ft})$$

$$p_s = 0.6 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity


$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.001672 \text{ kip/ft}^2)}{(0.6 \text{ kip/ft}^2)}$$

$$Ratio = 0.0027866$$

Status: **PASS**
Ratio: **0.000**

Status: **PASS**
Ratio: **0.000**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-0.267 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.042516 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(8.835 \text{ kipft}) + ((-0.267 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 1.4068 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(1.4068 \text{ kipft/ft})}{(-0.042516 \text{ kip/ft})}$$

$$E = 33.09 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (1.4068 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (-0.042516 \text{ kip/ft}) \times (4 \text{ ft})^2)}{(6 \times (1.4068 \text{ kipft/ft})) + (4 \times (-0.042516 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = \frac{(-0.042516 \text{ kip/ft}) \times (48 \text{ in})}{(6 \times (1.4068 \text{ kipft/ft})) + (4 \times (-0.042516 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.6915 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.042516 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (33.09 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.6915 \text{ ft})}{(4 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (33.09 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.6915 \text{ ft})}{(4 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 2.6088 \text{ kip}$$

M_{max} - Max bending moment located at depth a/2,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.042516 \text{ kip/ft}) \times (48 \text{ in}) \times (4 \text{ ft})) \times \left[\left(\frac{(33.09 \text{ ft})}{(4 \text{ ft})} + \frac{(2.6915 \text{ ft})}{2 \times (4 \text{ ft})} \right) - \left[\left(\frac{4 \times (33.09 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.6915 \text{ ft})}{2 \times (4 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (33.09 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.6915 \text{ ft})}{2 \times (4 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 5.1551 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.012 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.0019108 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.046 \text{ kipft}) + ((-0.012 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.0073248 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.0073248 \text{ kipft/ft})}{(-0.0019108 \text{ kip/ft})}$$

$$E = 3.8333 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.0073248 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (-0.0019108 \text{ kip/ft}) \times (4 \text{ ft})^2)}{(6 \times (0.0073248 \text{ kipft/ft})) + (4 \times (-0.0019108 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.8034 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.0019108 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (3.8333 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.8034 \text{ ft})}{(4 \text{ ft})} \right)^2 \right] \right. \\ \left. + \left[4 \times \left(\frac{3 \times (3.8333 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.8034 \text{ ft})}{(4 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.018012 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o \ b \ L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) \right. \\ \left. - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.0019108 \text{ kip/ft}) \times (48 \text{ in}) \times (4 \text{ ft})) \times \left[\left(\frac{(3.8333 \text{ ft})}{(4 \text{ ft})} + \frac{(2.8034 \text{ ft})}{2 \times (4 \text{ ft})} \right) \right. \\ \left. - \left[\left(\frac{4 \times (3.8333 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.8034 \text{ ft})}{2 \times (4 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (3.8333 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.8034 \text{ ft})}{2 \times (4 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 0.03327 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 2.5 \text{ ksi}$ - Concrete strength,

$f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,

$\phi = 0.65$ - Reduction factor for axial strength,

$\alpha = 0.8$ - Alpha factor for axial strength,

$A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(6.06 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (2.5 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (2.5 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -84.395 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-84.395 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

Table 22.4.2.1

22.4.2.2, 10.6.1.1

<p>25.2.3</p> <p>25.7.2.2</p> <p>25.7.2.1</p>	<p style="text-align: center;">$Ratio = 0.96556$</p> <p>$s_{rebar} = Max[1.5, (1.5 d_{bar})]$</p> <p>$s_{rebar} = Max[1.5, (1.5 \times (0.625 \text{ in}))]$</p> <p>$s_{rebar} = 1.5 \text{ in}$</p> <p>Ties:</p> <p>Since longitudinal reinforcement is \leq No. 10ø: Use #3(0.375 in)</p> <p>$s_{ties} = Min[(16 d_{bar}), (48 d_{ties}), Min(D, b)]$</p> <p>$s_{ties} = Min[(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), Min((48 \text{ in}), (48 \text{ in}))]$</p> <p>$s_{ties} = 10 \text{ in}$</p> <p>Summary:</p> <p style="text-align: center;">Main reinforcement: 14 - #5 (0.625 in) Ties: #3(0.375 in) - 10 in</p>	<p>Status: PASS Ratio: 0.970</p>
<p>22.4.2.2</p>	<p>Axial Compression Strength (ACI 318-19, LRFD)</p> <p>ϕP_N - Allowable axial compressive strength</p> <p style="text-align: center;">$\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_y k A_{st})]$</p> <p style="text-align: center;">$\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (2.5 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$</p> <p style="text-align: center;">$\phi P_N = 2675.2 \text{ kip}$</p> <p>Ratio - Capacity</p> <p style="text-align: center;">$Ratio = \frac{P}{\phi P_N}$</p> <p style="text-align: center;">$Ratio = \frac{(6.06 \text{ kip})}{(2675.2 \text{ kip})}$</p> <p style="text-align: center;">$Ratio = 0.0022653$</p>	<p>Status: PASS Ratio: 0.000</p>
<p>22.5.2.2</p> <p>22.5.5.1.3</p> <p>22.5.5.1.1</p>	<p>Shear Strength (ACI 318-19, LRFD)</p> <p>Parameters:</p> <p>$b_w = 48 \text{ in}$ - Effective width, d - Effective depth</p> <p style="text-align: center;">$d = 0.80 D$</p> <p style="text-align: center;">$d = 0.80 \times (48 \text{ in})$</p> <p style="text-align: center;">$d = 38.4 \text{ in}$</p> <p>λ_s - size effect modification factor</p> <p style="text-align: center;">$\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = 0.64282$</p> <p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,</p> <p>$V_{c,max}$ - Max shear strength of concrete</p> <p style="text-align: center;">$V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$</p> <p style="text-align: center;">$V_{c,max} = 5 \times (0.64282) \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$</p>	

$$V_{c,max} = 296.21 \text{ kip}$$

22.5.5.1.1(a) The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $P = 6.06 \text{ kip} \rightarrow 6060 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck} + \frac{P}{6 A_g}} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + \frac{(6060 \text{ lbf})}{6 \times (2304 \text{ in}^2)}} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 119.29 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck} + (0.05 f'_{ck})} \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + (0.05 \times (2500 \text{ psi}))} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 348.89 \text{ kip}$$

V_c - Governing shear strength of concrete

$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(296.21 \text{ kip}), (119.29 \text{ kip}), (348.89 \text{ kip})]$$

$$V_c = 119.29 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{s,a}$ - Shear strength of steel (a)

$$V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$$

$$V_{s,a} = 8 \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{s,a} = 737.28 \text{ kip}$$

A_v - Ties rebar area,

$$A_v = \frac{\pi d_{ties}^2}{4}$$

$$A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$$

$$A_v = 0.11045 \text{ in}^2$$

22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)

$$V_{s,b} = \frac{2 A_v f_{yw} d}{s_{ties}}$$

$$V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$$

$$V_{s,b} = 50.894 \text{ kip}$$

V_s - Governing shear strength of steel

$$V_s = \text{MIN}[V_{s,a}, V_{s,b}]$$

$$V_s = \text{MIN}[(737.28 \text{ kip}), (50.894 \text{ kip})]$$

$$V_s = 50.894 \text{ kip}$$

22.5.1.1 ϕV_n - Allowable shear strength

$$\phi V_n = \phi (V_c + V_s)$$

$$\phi V_n = (0.65) \times ((119.29 \text{ kip}) + (50.894 \text{ kip}))$$

$$\phi V_n = 110.62 \text{ kip}$$

Considering x-direction:

$V_{max} = 2.6088 \text{ kip}$ - Maximum shear force in the x-direction,

$Ratio$ - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(2.6088 \text{ kip})}{(110.62 \text{ kip})}$$

$$Ratio = 0.023583$$

Status: **PASS**
Ratio: **0.020**

Considering z-direction:

$V_{max} = 0.018012 \text{ kip}$ - Maximum shear force in the z-direction,

Ratio - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(0.018012 \text{ kip})}{(110.62 \text{ kip})}$$

$$Ratio = 0.00016282$$

Status: **PASS**
Ratio: **0.000**

Flexural Strength (ACI 318-19, LRFD)

S_m - Section modulus

$$S_m = \frac{b D^2}{6}$$

$$S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$$

$$S_m = 18432 \text{ in}^3$$

$\lambda = 1$ - Concrete modification factor (Normal concrete),

Allowable flexural strength:

M_n shall be the lesser of:

$\phi M_{n,1}$

$$\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$$

$$\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{(2.5 \text{ ksi})} \times 18432.001 \text{ in}^3$$

$$\phi M_{n,1} = 249.600 \text{ kipft}$$

14.5.2.1b

$\phi M_{n,2}$

$$\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$$

$$\phi M_{n,2} = (0.65) \times 0.85 \times (2.5 \text{ ksi}) \times (18432 \text{ in}^3)$$

$$\phi M_{n,2} = 2121.6 \text{ kipft}$$

Therefore,

ϕM_n - Allowable flexural strength,

$$\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$$

$$\phi M_n = \text{MIN}[(249.6 \text{ kipft}), (2121.6 \text{ kipft})]$$

$$\phi M_n = 249.6 \text{ kipft}$$

Considering x-direction:

$M_{max} = 5.1551 \text{ kipft}$ - Maximum moment in the x-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(5.1551 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.020653$$

Status: **PASS**
Ratio: **0.020**

Considering z-direction:

$M_{max} = 0.03327 \text{ kipft}$ - Maximum moment in the z-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$\text{Ratio} = \frac{(0.03327 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$\text{Ratio} = 0.0001333$$

Status: **PASS**
Ratio: **0.000**

REFERENCES	CALCULATIONS	RESULTS
------------	--------------	---------


SkyCiv Foundation Design

Pile Foundation

Design Information :

Design code : IBC 2021 (International Building Code)
Unit System : Imperial

Pile Input



Geometry

Pile shape: rectangular

$b = 48$ in - Pile width

$D = 48$ in - Pile depth

$L = 4$ ft - Total pile length

$h_1 = 0$ ft - Lateral load height from the top of the pile,

$h_2 = 0$ ft - Depth to resisting surface

$h_e = 0$ ft - Length of pile above the ground

Tabulation of Soil Parameters

Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000

Tabulation of Loads

Load Component	ASD	LRFD
P (kip)	4.323	6.060
V_x (kip)	-0.161	-0.267
V_z (kip)	0.009	0.012
M_x (kipft)	0.032	0.046
M_z (kipft)	5.136	8.835

Material Properties

$f'_{ck} = 2.5$ ksi - Concrete strength.

Required depth to resist lateral loads (ASD)

H - Point of application of the lateral load

$$H = h_1 + h_2 + h_e$$

$$H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$$

$$H = 0 \text{ ft}$$

Considering x-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-0.161 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.025637 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(5.136 \text{ kipft}) + ((-0.161 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.81783 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_e^3 - \left(14.14 \times \frac{H_o \times L_x}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,x} = 3.9023 \text{ ft}$ - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.009 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.0014331 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.032 \text{ kipft}) + ((0.009 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.0050955 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_e^3 - \left(14.14 \times \frac{H_o \times L_z}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,z} = 0.78021 \text{ ft}$ - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = \text{MAX}[(3.9023 \text{ ft}), (0.78021 \text{ ft})]$$

$$L_{e,req} = 3.902 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_e - h_2$$

$$L_e = (4 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 4 \text{ ft}$$

Ratio - Embedded depth

$$\text{Ratio} = \frac{L_{e,req}}{L_e}$$

$$\text{Ratio} = \frac{(3.902 \text{ ft})}{(4 \text{ ft})}$$

$$\text{Ratio} = 0.9755$$

Status: **PASS**
Ratio: **0.980**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_v}{A}$$

$$q = \frac{(4.323 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.27019 \text{ kip/ft}^2$$

Check bearing capacity ratio:

Ratio - Capacity

$$\text{Ratio} = \frac{q}{q_a}$$

$$\text{Ratio} = \frac{(0.27019 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$\text{Ratio} = 0.13509$$

Status: **PASS**
Ratio: **0.140**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(4 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.025637 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.81783 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.81783 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (-0.025637 \text{ kip/ft}) \times (4 \text{ ft})^2)}{(6 \times (0.81783 \text{ kipft/ft})) + (4 \times (-0.025637 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.6924 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (0.81783 \text{ kipft/ft})) + (3 \times (-0.025637 \text{ kip/ft}) \times (4 \text{ ft}))]^2}{(4 \text{ ft})^2 \times [(3 \times (0.81783 \text{ kipft/ft})) + (2 \times (-0.025637 \text{ kip/ft}) \times (4 \text{ ft}))]}$$

$$p = 0.18312 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.81783 \text{ kipft/ft})) + ((-0.025637 \text{ kip/ft}) \times (4 \text{ ft}))]}{(4 \text{ ft})^2}$$

$$s = 0.57492 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(2.6924 \text{ ft})}{2}$$

$$p_a = 0.20193 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.18312 \text{ kip/ft}^2)}{(0.20193 \text{ kip/ft}^2)}$$

$$Ratio = 0.90685$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (4 \text{ ft})$$

$$p_s = 0.6 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.57492 \text{ kip/ft}^2)}{(0.6 \text{ kip/ft}^2)}$$

$$Ratio = 0.9582$$

Status: **PASS**
Ratio: **0.910**

Status: **PASS**
Ratio: **0.960**

Considering z-direction:

$H_o = 0.0014331 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.0050955 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.0050955 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (0.0014331 \text{ kip/ft}) \times (4 \text{ ft})^2)}{(6 \times (0.0050955 \text{ kipft/ft})) + (4 \times (0.0014331 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.8095 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (0.0050955 \text{ kipft/ft})) + (3 \times (0.0014331 \text{ kip/ft}) \times (4 \text{ ft}))]^2}{(4 \text{ ft})^2 \times [(3 \times (0.0050955 \text{ kipft/ft})) + (2 \times (0.0014331 \text{ kip/ft}) \times (4 \text{ ft}))]}$$

$$p = 0.0024746 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.0050955 \text{ kipft/ft})) + ((0.0014331 \text{ kip/ft}) \times (4 \text{ ft}))]}{(4 \text{ ft})^2}$$

$$s = 0.0059713 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(2.8095 \text{ ft})}{2}$$

$$p_a = 0.21071 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.0024746 \text{ kip/ft}^2)}{(0.21071 \text{ kip/ft}^2)}$$

$$Ratio = 0.011744$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (4 \text{ ft})$$

$$p_s = 0.6 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity


$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.0059713 \text{ kip/ft}^2)}{(0.6 \text{ kip/ft}^2)}$$

$$Ratio = 0.0099522$$

Status: **PASS**
Ratio: **0.010**

Status: **PASS**
Ratio: **0.010**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-0.267 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.042516 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(8.835 \text{ kipft}) + ((-0.267 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 1.4068 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(1.4068 \text{ kipft/ft})}{(-0.042516 \text{ kip/ft})}$$

$$E = 33.09 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (1.4068 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (-0.042516 \text{ kip/ft}) \times (4 \text{ ft})^2)}{6 \times (1.4068 \text{ kipft/ft}) + 4 \times (-0.042516 \text{ kip/ft}) \times (4 \text{ ft})}$$

$$a = \frac{(-0.042516 \text{ kip/ft}) \times (48 \text{ in})}{(6 \times (1.4068 \text{ kipft/ft})) + (4 \times (-0.042516 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.6915 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.042516 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (33.09 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.6915 \text{ ft})}{(4 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (33.09 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.6915 \text{ ft})}{(4 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 2.6088 \text{ kip}$$

M_{max} - Max bending moment located at depth a/2,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.042516 \text{ kip/ft}) \times (48 \text{ in}) \times (4 \text{ ft})) \times \left[\left(\frac{(33.09 \text{ ft})}{(4 \text{ ft})} + \frac{(2.6915 \text{ ft})}{2 \times (4 \text{ ft})} \right) - \left[\left(\frac{4 \times (33.09 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.6915 \text{ ft})}{2 \times (4 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (33.09 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.6915 \text{ ft})}{2 \times (4 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 5.1551 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.012 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.0019108 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.046 \text{ kipft}) + ((0.012 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.0073248 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.0073248 \text{ kipft/ft})}{(0.0019108 \text{ kip/ft})}$$

$$E = 3.8333 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.0073248 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (0.0019108 \text{ kip/ft}) \times (4 \text{ ft})^2)}{(6 \times (0.0073248 \text{ kipft/ft})) + (4 \times (0.0019108 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.8034 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((0.0019108 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (3.8333 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.8034 \text{ ft})}{(4 \text{ ft})} \right)^2 \right] \right. \\ \left. + \left[4 \times \left(\frac{3 \times (3.8333 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.8034 \text{ ft})}{(4 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.018012 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o \cdot b \cdot L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) \right. \\ \left. - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((0.0019108 \text{ kip/ft}) \times (48 \text{ in}) \times (4 \text{ ft})) \times \left[\left(\frac{(3.8333 \text{ ft})}{(4 \text{ ft})} + \frac{(2.8034 \text{ ft})}{2 \times (4 \text{ ft})} \right) \right. \\ \left. - \left[\left(\frac{4 \times (3.8333 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.8034 \text{ ft})}{2 \times (4 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (3.8333 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.8034 \text{ ft})}{2 \times (4 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 0.03327 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 2.5 \text{ ksi}$ - Concrete strength,

$f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,

$\phi = 0.65$ - Reduction factor for axial strength,

$\alpha = 0.8$ - Alpha factor for axial strength,

$A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(6.06 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (2.5 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (2.5 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -84.395 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-84.395 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

Table 22.4.2.1

22.4.2.2, 10.6.1.1

<p>25.2.3</p> <p>25.7.2.2</p> <p>25.7.2.1</p>	<p style="text-align: center;">$Ratio = 0.96556$</p> <p>$s_{rebar} = \text{Min spacing of reinforcement,}$</p> $s_{rebar} = \text{Max}[1.5, (1.5 d_{bar})]$ $s_{rebar} = \text{Max}[1.5, (1.5 \times (0.625 \text{ in}))]$ $s_{rebar} = 1.5 \text{ in}$ <p>Ties:</p> <p>Since longitudinal reinforcement is \leq No. 10ø: Use #3(0.375 in)</p> <p>s_{ties} - Maximum spacing of ties,</p> $s_{ties} = \text{Min}[(16 d_{bar}), (48 d_{ties}), \text{Min}(D, b)]$ $s_{ties} = \text{Min}[(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), \text{Min}((48 \text{ in}), (48 \text{ in}))]$ $s_{ties} = 10 \text{ in}$ <p>Summary:</p> <p style="text-align: center;">Main reinforcement: 14 - #5 (0.625 in) Ties: #3(0.375 in) - 10 in</p>	<p>Status: PASS Ratio: 0.970</p>
<p>22.4.2.2</p>	<p>Axial Compression Strength (ACI 318-19, LRFD)</p> <p>ϕP_N - Allowable axial compressive strength</p> $\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_{yk} A_{st})]$ $\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (2.5 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$ $\phi P_N = 2675.2 \text{ kip}$ <p><i>Ratio</i> - Capacity</p> $Ratio = \frac{P}{\phi P_N}$ $Ratio = \frac{(6.06 \text{ kip})}{(2675.2 \text{ kip})}$ $Ratio = 0.0022653$	<p>Status: PASS Ratio: 0.000</p>
<p>22.5.2.2</p> <p>22.5.5.1.3</p> <p>22.5.5.1.1</p>	<p>Shear Strength (ACI 318-19, LRFD)</p> <p>Parameters:</p> <p>$b_w = 48 \text{ in}$ - Effective width, d - Effective depth</p> $d = 0.80 D$ $d = 0.80 \times (48 \text{ in})$ $d = 38.4 \text{ in}$ <p>λ_s - size effect modification factor</p> $\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$ $\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$ $\lambda_s = 0.64282$ <p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,</p> <p>$V_{c,max}$ - Max shear strength of concrete</p> $V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$ $V_{c,max} = 5 \times (0.64282) \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$	

$$V_{c,max} = 296.21 \text{ kip}$$

22.5.5.1.1(a) The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $P = 6.06 \text{ kip} \rightarrow 6060 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck} + \frac{P}{6 A_g}} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + \frac{(6060 \text{ lbf})}{6 \times (2304 \text{ in}^2)}} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 119.29 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck} + (0.05 f'_{ck})} \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + (0.05 \times (2500 \text{ psi}))} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 348.89 \text{ kip}$$

V_c - Governing shear strength of concrete

$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(296.21 \text{ kip}), (119.29 \text{ kip}), (348.89 \text{ kip})]$$

$$V_c = 119.29 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{s,a}$ - Shear strength of steel (a)

$$V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$$

$$V_{s,a} = 8 \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{s,a} = 737.28 \text{ kip}$$

A_v - Ties rebar area,

$$A_v = \frac{\pi d_{ties}^2}{4}$$

$$A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$$

$$A_v = 0.11045 \text{ in}^2$$

22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)

$$V_{s,b} = \frac{2 A_v f_{yw} d}{s_{ties}}$$

$$V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$$

$$V_{s,b} = 50.894 \text{ kip}$$

V_s - Governing shear strength of steel

$$V_s = \text{MIN}[V_{s,a}, V_{s,b}]$$

$$V_s = \text{MIN}[(737.28 \text{ kip}), (50.894 \text{ kip})]$$

$$V_s = 50.894 \text{ kip}$$

22.5.1.1 ϕV_n - Allowable shear strength

$$\phi V_n = \phi (V_c + V_s)$$

$$\phi V_n = (0.65) \times ((119.29 \text{ kip}) + (50.894 \text{ kip}))$$

$$\phi V_n = 110.62 \text{ kip}$$

Considering x-direction:

$V_{max} = 2.6088 \text{ kip}$ - Maximum shear force in the x-direction,

$Ratio$ - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(2.6088 \text{ kip})}{(110.62 \text{ kip})}$$

$$Ratio = 0.023583$$

Status: **PASS**
Ratio: **0.020**

Considering z-direction:

$V_{max} = 0.018012 \text{ kip}$ - Maximum shear force in the z-direction,

Ratio - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(0.018012 \text{ kip})}{(110.62 \text{ kip})}$$

$$Ratio = 0.00016282$$

Status: **PASS**
Ratio: **0.000**

Flexural Strength (ACI 318-19, LRFD)

S_m - Section modulus

$$S_m = \frac{b D^2}{6}$$

$$S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$$

$$S_m = 18432 \text{ in}^3$$

$\lambda = 1$ - Concrete modification factor (Normal concrete),

Allowable flexural strength:

M_n shall be the lesser of:

$\phi M_{n,1}$

$$\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$$

$$\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{(2.5 \text{ ksi})} \times 18432.001 \text{ in}^3$$

$$\phi M_{n,1} = 249.600 \text{ kipft}$$

14.5.2.1b

$\phi M_{n,2}$

$$\phi M_{n,2} = \phi \times 0.85 \times f'_{ck} \times S_m$$

$$\phi M_{n,2} = (0.65) \times 0.85 \times (2.5 \text{ ksi}) \times (18432 \text{ in}^3)$$

$$\phi M_{n,2} = 2121.6 \text{ kipft}$$

Therefore,

ϕM_n - Allowable flexural strength,

$$\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$$

$$\phi M_n = \text{MIN}[(249.6 \text{ kipft}), (2121.6 \text{ kipft})]$$

$$\phi M_n = 249.6 \text{ kipft}$$

Considering x-direction:

$M_{max} = 5.1551 \text{ kipft}$ - Maximum moment in the x-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(5.1551 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.020653$$

Status: **PASS**
Ratio: **0.020**

Considering z-direction:

$M_{max} = 0.03327 \text{ kipft}$ - Maximum moment in the z-direction,

Ratio - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$\text{Ratio} = \frac{(0.03327 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$\text{Ratio} = 0.0001333$$

Status: **PASS**
Ratio: **0.000**

REFERENCES	CALCULATIONS	RESULTS
------------	--------------	---------


SkyCiv Foundation Design

Pile Foundation

Design Information :

Design code : IBC 2021 (International Building Code)
Unit System : Imperial

Pile Input



Geometry

Pile shape: rectangular

$b = 48$ in - Pile width

$D = 48$ in - Pile depth

$L = 4$ ft - Total pile length

$h_1 = 0$ ft - Lateral load height from the top of the pile,

$h_2 = 0$ ft - Depth to resisting surface

$h_e = 0$ ft - Length of pile above the ground

Tabulation of Soil Parameters

Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000

Tabulation of Loads

Load Component	ASD	LRFD
P (kip)	3.767	5.269
V_x (kip)	-0.144	-0.241
V_z (kip)	-0.061	-0.087
M_x (kipft)	-0.226	-0.324
M_z (kipft)	4.795	8.240

Material Properties

$f'_{ck} = 2.5$ ksi - Concrete strength.

Required depth to resist lateral loads (ASD)

H - Point of application of the lateral load

$$H = h_1 + h_2 + h_e$$

$$H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$$

$$H = 0 \text{ ft}$$

Considering x-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-0.144 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.02293 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(4.795 \text{ kipft}) + ((-0.144 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.76354 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,x} = 3.8219 \text{ ft}$ - Required depth in x-direction,

Considering z-direction:

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.061 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.0097134 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.226 \text{ kipft}) + ((-0.061 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.035987 \text{ kipft/ft}$$

Required depth of embedment in earth:

$$L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R} \right) - \left(18.85 \times \frac{M_o}{R} \right) = 0$$

Solving the cubic equation:

$L_{e,z} = 1.2866 \text{ ft}$ - Required depth in z-direction,

Minimum embedded depth required:

$L_{e,req}$ - Depth of pile required,

$$L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$$

$$L_{e,req} = \text{MAX}[(3.8219 \text{ ft}), (1.2866 \text{ ft})]$$

$$L_{e,req} = 3.822 \text{ ft}$$

L_e - Actual embedded length of pile,

$$L_e = L - h_e - h_2$$

$$L_e = (4 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$$

$$L_e = 4 \text{ ft}$$

Ratio - Embedded depth

$$\text{Ratio} = \frac{L_{e,req}}{L_e}$$

$$\text{Ratio} = \frac{(3.822 \text{ ft})}{(4 \text{ ft})}$$

$$\text{Ratio} = 0.9555$$

Status: **PASS**
Ratio: **0.960**

End-bearing Capacity (ASD)

A - Pile cross-section area

$$A = b D$$

$$A = (48 \text{ in}) \times (48 \text{ in})$$

$$A = 16 \text{ ft}^2$$

q - End-bearing pressure

$$q = \frac{P_v}{A}$$

$$q = \frac{(3.767 \text{ kip})}{(16 \text{ ft}^2)}$$

$$q = 0.23544 \text{ kip/ft}^2$$

Check bearing capacity ratio:

Ratio - Capacity

$$\text{Ratio} = \frac{q}{q_a}$$

$$\text{Ratio} = \frac{(0.23544 \text{ kip/ft}^2)}{(2000 \text{ psf})}$$

$$\text{Ratio} = 0.11772$$

Status: **PASS**
Ratio: **0.120**

Czerniak

Lateral Soil Pressure (ASD):

L/D - Length to least lateral dimension ratio,

$$L/D = \frac{L}{D}$$

$$L/D = \frac{(4 \text{ ft})}{(48 \text{ in})}$$

$$L/D = 1$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.02293 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.76354 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.76354 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (-0.02293 \text{ kip/ft}) \times (4 \text{ ft})^2)}{(6 \times (0.76354 \text{ kipft/ft})) + (4 \times (-0.02293 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.6914 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 \times [(4 \times (0.76354 \text{ kipft/ft})) + (3 \times (-0.02293 \text{ kip/ft}) \times (4 \text{ ft}))]^2}{(4 \text{ ft})^2 \times [(3 \times (0.76354 \text{ kipft/ft})) + (2 \times (-0.02293 \text{ kip/ft}) \times (4 \text{ ft}))]}$$

$$p = 0.1718 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.76354 \text{ kipft/ft})) + ((-0.02293 \text{ kip/ft}) \times (4 \text{ ft}))]}{(4 \text{ ft})^2}$$

$$s = 0.53826 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(2.6914 \text{ ft})}{2}$$

$$p_a = 0.20185 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.1718 \text{ kip/ft}^2)}{(0.20185 \text{ kip/ft}^2)}$$

$$Ratio = 0.85109$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (4 \text{ ft})$$

$$p_s = 0.6 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.53826 \text{ kip/ft}^2)}{(0.6 \text{ kip/ft}^2)}$$

$$Ratio = 0.89709$$

Status: **PASS**
Ratio: **0.850**

Status: **PASS**
Ratio: **0.900**

Considering z-direction:

$H_o = -0.0097134 \text{ kip/ft}$ - Lateral force per length of pile,

$M_o = 0.035987 \text{ kipft/ft}$ - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.035987 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (-0.0097134 \text{ kip/ft}) \times (4 \text{ ft})^2)}{(6 \times (0.035987 \text{ kipft/ft})) + (4 \times (-0.0097134 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.8062 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{0.75 [(4 \times (0.035987 \text{ kipft/ft})) + (3 \times (-0.0097134 \text{ kip/ft}) \times (4 \text{ ft}))]^2}{(4 \text{ ft})^2 [(3 \times (0.035987 \text{ kipft/ft})) + (2 \times (-0.0097134 \text{ kip/ft}) \times (4 \text{ ft}))]}$$

$$p = 0.0011622 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{6 \times [(2 \times (0.035987 \text{ kipft/ft})) + ((-0.0097134 \text{ kip/ft}) \times (4 \text{ ft}))]}{(4 \text{ ft})^2}$$

$$s = 0.01242 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(2.8062 \text{ ft})}{2}$$

$$p_a = 0.21046 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$Ratio = \frac{p}{p_a}$$

$$Ratio = \frac{(0.0011622 \text{ kip/ft}^2)}{(0.21046 \text{ kip/ft}^2)}$$

$$Ratio = 0.0055222$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (4 \text{ ft})$$

$$p_s = 0.6 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity


$$Ratio = \frac{s}{p_s}$$

$$Ratio = \frac{(0.01242 \text{ kip/ft}^2)}{(0.6 \text{ kip/ft}^2)}$$

$$Ratio = 0.020701$$

Status: **PASS**
Ratio: **0.010**

Status: **PASS**
Ratio: **0.020**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-0.241 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.038376 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_z + (V_x H)}{1.57 D}$$

$$M_o = \frac{(8.24 \text{ kipft}) + ((-0.241 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 1.3121 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(1.3121 \text{ kipft/ft})}{(-0.038376 \text{ kip/ft})}$$

$$E = 34.191 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (1.3121 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (-0.038376 \text{ kip/ft}) \times (4 \text{ ft})^2)}{6 \times (1.3121 \text{ kipft/ft}) + 4 \times (-0.038376 \text{ kip/ft}) \times (4 \text{ ft})}$$

$$a = \frac{(-0.038376 \text{ kip/ft}) \times (48 \text{ in})}{(6 \times (1.3121 \text{ kipft/ft})) + (4 \times (-0.038376 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.6908 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.038376 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (34.191 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.6908 \text{ ft})}{(4 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (34.191 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.6908 \text{ ft})}{(4 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 2.4299 \text{ kip}$$

M_{max} - Max bending moment located at depth a/2,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.038376 \text{ kip/ft}) \times (48 \text{ in}) \times (4 \text{ ft})) \times \left[\left(\frac{(34.191 \text{ ft})}{(4 \text{ ft})} + \frac{(2.6908 \text{ ft})}{2 \times (4 \text{ ft})} \right) - \left[\left(\frac{4 \times (34.191 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.6908 \text{ ft})}{2 \times (4 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (34.191 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.6908 \text{ ft})}{2 \times (4 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 4.8032 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.087 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.013854 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(0.324 \text{ kipft}) + ((-0.087 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.051592 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.051592 \text{ kipft/ft})}{(-0.013854 \text{ kip/ft})}$$

$$E = 3.7241 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.051592 \text{ kipft/ft}) \times (4 \text{ ft})) + (3 \times (-0.013854 \text{ kip/ft}) \times (4 \text{ ft})^2)}{(6 \times (0.051592 \text{ kipft/ft})) + (4 \times (-0.013854 \text{ kip/ft}) \times (4 \text{ ft}))}$$

$$a = 2.8058 \text{ ft}$$

V_{max} - Max shear force located at depth a,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.013854 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (3.7241 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.8058 \text{ ft})}{(4 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (3.7241 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.8058 \text{ ft})}{(4 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.12792 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o \cdot b \cdot L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.013854 \text{ kip/ft}) \times (48 \text{ in}) \times (4 \text{ ft})) \times \left[\left(\frac{(3.7241 \text{ ft})}{(4 \text{ ft})} + \frac{(2.8058 \text{ ft})}{2 \times (4 \text{ ft})} \right) - \left[\left(\frac{4 \times (3.7241 \text{ ft})}{(4 \text{ ft})} + 3 \right) \times \left(\frac{(2.8058 \text{ ft})}{2 \times (4 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (3.7241 \text{ ft})}{(4 \text{ ft})} + 2 \right) \times \left(\frac{(2.8058 \text{ ft})}{2 \times (4 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 0.23589 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 2.5 \text{ ksi}$ - Concrete strength,

$f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,

$\phi = 0.65$ - Reduction factor for axial strength,

$\alpha = 0.8$ - Alpha factor for axial strength,

$A_g = 2304 \text{ in}^2$ - Gross area of concrete,

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(5.269 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (2.5 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (2.5 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$$

$$A_{st,required} = -84.421 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-84.421 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$$

$$A_{min} = 4.1472 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 14$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 4.2951 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$$

Table 22.4.2.1

22.4.2.2, 10.6.1.1

<p>25.2.3</p> <p>25.7.2.2</p> <p>25.7.2.1</p>	<p style="text-align: center;">$Ratio = 0.96556$</p> <p>$s_{rebar} = Max[1.5, (1.5 d_{bar})]$</p> <p>$s_{rebar} = Max[1.5, (1.5 \times (0.625 \text{ in}))]$</p> <p>$s_{rebar} = 1.5 \text{ in}$</p> <p>Ties:</p> <p>Since longitudinal reinforcement is \leq No. 10: Use #3(0.375 in)</p> <p>$s_{ties} = Min[(16 d_{bar}), (48 d_{ties}), Min(D, b)]$</p> <p>$s_{ties} = Min[(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), Min((48 \text{ in}), (48 \text{ in}))]$</p> <p>$s_{ties} = 10 \text{ in}$</p> <p>Summary:</p> <p style="text-align: center;">Main reinforcement: 14 - #5 (0.625 in) Ties: #3(0.375 in) - 10 in</p>	<p>Status: PASS Ratio: 0.970</p>
<p>22.4.2.2</p>	<p>Axial Compression Strength (ACI 318-19, LRFD)</p> <p>ϕP_N - Allowable axial compressive strength</p> <p style="text-align: center;">$\phi P_N = \phi 0.80 [(0.85 f'_{ck} [A_g - A_{st}]) + (f_y A_{st})]$</p> <p style="text-align: center;">$\phi P_N = (0.65) \times 0.80 \times [(0.85 \times (2.5 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2))]$</p> <p style="text-align: center;">$\phi P_N = 2675.2 \text{ kip}$</p> <p>Ratio - Capacity</p> <p style="text-align: center;">$Ratio = \frac{P}{\phi P_N}$</p> <p style="text-align: center;">$Ratio = \frac{(5.269 \text{ kip})}{(2675.2 \text{ kip})}$</p> <p style="text-align: center;">$Ratio = 0.0019696$</p>	<p>Status: PASS Ratio: 0.000</p>
<p>22.5.2.2</p> <p>22.5.5.1.3</p> <p>22.5.5.1.1</p>	<p>Shear Strength (ACI 318-19, LRFD)</p> <p>Parameters:</p> <p>$b_w = 48 \text{ in}$ - Effective width, d - Effective depth</p> <p style="text-align: center;">$d = 0.80 D$</p> <p style="text-align: center;">$d = 0.80 \times (48 \text{ in})$</p> <p style="text-align: center;">$d = 38.4 \text{ in}$</p> <p>λ_s - size effect modification factor</p> <p style="text-align: center;">$\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$</p> <p style="text-align: center;">$\lambda_s = 0.64282$</p> <p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,</p> <p>$V_{c,max}$ - Max shear strength of concrete</p> <p style="text-align: center;">$V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$</p> <p style="text-align: center;">$V_{c,max} = 5 \times (0.64282) \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$</p>	

$$V_{c,max} = 296.21 \text{ kip}$$

22.5.5.1.1(a) The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $P = 5.269 \text{ kip} \rightarrow 5269 \text{ lbf}$,
 $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck} + \frac{P}{6 A_g}} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + \frac{(5269 \text{ lbf})}{6 \times (2304 \text{ in}^2)}} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,a} = 119.19 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck} + (0.05 f'_{ck})} \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi}) + (0.05 \times (2500 \text{ psi}))} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{c,b} = 348.89 \text{ kip}$$

V_c - Governing shear strength of concrete

$$V_c = \text{Min}[V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min}[(296.21 \text{ kip}), (119.19 \text{ kip}), (348.89 \text{ kip})]$$

$$V_c = 119.19 \text{ kip}$$

22.5.5.1.2 The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$,
 $V_{s,a}$ - Shear strength of steel (a)

$$V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$$

$$V_{s,a} = 8 \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$$

$$V_{s,a} = 737.28 \text{ kip}$$

A_v - Ties rebar area,

$$A_v = \frac{\pi d_{ties}^2}{4}$$

$$A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$$

$$A_v = 0.11045 \text{ in}^2$$

22.5.8.5.3 $V_{s,b}$ - Shear strength of steel (b)

$$V_{s,b} = \frac{2 A_v f_{yw} d}{s_{ties}}$$

$$V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$$

$$V_{s,b} = 50.894 \text{ kip}$$

V_s - Governing shear strength of steel

$$V_s = \text{MIN}[V_{s,a}, V_{s,b}]$$

$$V_s = \text{MIN}[(737.28 \text{ kip}), (50.894 \text{ kip})]$$

$$V_s = 50.894 \text{ kip}$$

22.5.1.1 ϕV_n - Allowable shear strength

$$\phi V_n = \phi (V_c + V_s)$$

$$\phi V_n = (0.65) \times ((119.19 \text{ kip}) + (50.894 \text{ kip}))$$

$$\phi V_n = 110.55 \text{ kip}$$

Considering x-direction:

$V_{max} = 2.4299 \text{ kip}$ - Maximum shear force in the x-direction,

$Ratio$ - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(2.4299 \text{ kip})}{(110.55 \text{ kip})}$$

$$Ratio = 0.021979$$

Considering z-direction:

$V_{max} = 0.12792 \text{ kip}$ - Maximum shear force in the z-direction,

$Ratio$ - Capacity

$$Ratio = \frac{V_{max}}{\phi V_n}$$

$$Ratio = \frac{(0.12792 \text{ kip})}{(110.55 \text{ kip})}$$

$$Ratio = 0.0011571$$

Status: **PASS**
Ratio: **0.020**

Status: **PASS**
Ratio: **0.000**

Flexural Strength (ACI 318-19, LRFD)

S_m - Section modulus

$$S_m = \frac{b D^2}{6}$$

$$S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$$

$$S_m = 18432 \text{ in}^3$$

$\lambda = 1$ - Concrete modification factor (Normal concrete),

Allowable flexural strength:

M_n shall be the lesser of:

$\phi M_{n,1}$

$$\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$$

$$\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{(2.5 \text{ ksi})} \times 18432.001 \text{ in}^3$$

$$\phi M_{n,1} = 249.600 \text{ kipft}$$

14.5.2.1b

$\phi M_{n,2}$

$$\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$$

$$\phi M_{n,2} = (0.65) \times 0.85 \times (2.5 \text{ ksi}) \times (18432 \text{ in}^3)$$

$$\phi M_{n,2} = 2121.6 \text{ kipft}$$

Therefore,

ϕM_n - Allowable flexural strength,

$$\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$$

$$\phi M_n = \text{MIN}[(249.6 \text{ kipft}), (2121.6 \text{ kipft})]$$

$$\phi M_n = 249.6 \text{ kipft}$$

Considering x-direction:

$M_{max} = 4.8032 \text{ kipft}$ - Maximum moment in the x-direction,

$Ratio$ - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(4.8032 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$Ratio = 0.019244$$

Status: **PASS**
Ratio: **0.020**

Considering z-direction:

$M_{max} = 0.23589 \text{ kipft}$ - Maximum moment in the z-direction,

$Ratio$ - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$\text{Ratio} = \frac{(0.23589 \text{ kipft})}{(249.6 \text{ kipft})}$$

$$\text{Ratio} = 0.00094505$$

Status: **PASS**
Ratio: **0.000**