

Your Project Calculations



Project Name: Dustin J 460WBi 2 pole

S3D Model Link:

https://platform.skyciv.com/structural?preload_name=Dustin%20J%20460WBi%202%20pole&preload_path=Shared%20Enterprise%20Folder/MT_Solar_Projects/8_2023

Public Model Link:

https://platform.skyciv.com/structural-viewer?project_id=QhPU1FkccDLix7RCguNd48fXnbzHYTtnRQL33O1ygO1DKdC5MyZn1mi6zlsMO6jX

Array Specification

Product:	Beam
Unique ID:	2P-17-8TOP-HD-24-L-5Hx4W-6977
Duty Classification:	HD
Module Width:	40.63 in
Module Length:	86.81in
Number of Rows:	5
Number of Columns:	4
Total Number of Modules:	20
Desired Tilt Angle:	43
Front Edge Clearance:	5
Total Array Height at Tilt:	16.62 ft
Total Frame Length:	28.50 ft
Frame Weight:	1618 lbs
Array Dimensions N/S:	17.14 ft
Array Dimensions E/W:	29.27 ft
Rail Length:	205.65 in
Rail Spacing:	3.62 ft
Rail Check:	Not Checked

Support Specifications


Pole Size:	8in Pipe Sch 40
Pole Length above Grade:	10.84 ft
Number of Poles:	2
Pole Spacing:	17 ft

Foundation Specifications

Foundation Type:	Square
Foundation Dimensions:	48 x 48 in
Foundation Depth (below grade):	Pile 1: 7.25 ft Pile 2: 7.25 ft
Foundation Volume:	8.593 y ³
Foundation Result:	PASSED
Mount Twist:	1.025900 kip

Site Info

Risk Category:	I
Exposure:	C
Soil Classification:	sand
Site Location:	N46696 Holden Rd, Eleva, WI 54738, USA
Wind Speed:	100 mph
Snow Load:	50 psf
Design Uplift Pressure:	Multiple pressures
Design Downforce Pressure:	Multiple pressures
Design Snow Pressure:	0.014845 ksf



Design Disclaimer


This software should be used for preliminary designs and should not be used as a final design unless reviewed, verified and designed by a qualified structural engineer.



AutoDesigner Input



```
{
  "wind_speed_override": null,
  "snow_load_override": null,
  "direct_snow_load": false,
  "product_type": "Beam",
  "project_id": "Dustin J 460WBi 2 pole",
  "site_address": "N46696 Holden Rd, Eleva, WI 54738, USA",
  "module_width": 40.63,
  "module_length": 86.81,
  "number_rows": 5,
  "number_columns": 4,
  "pole_mount_section": "4_40",
  "core_pipe_width": 65,
  "core_pipe_section": "2_40",
  "adjuster_section": "2_40",
  "core_beam_height": 65,
  "core_beam_section": "HSS3x2x1/8",
  "main_pipe_section": "2_12GA",
  "pole_spacing": 15,
  "tilt_angle": 43,
  "ground_clearance": 5,
  "risk_category": "I",
  "exposure_category": "C",
  "frame_duty_override": "auto",
  "pole_override": "auto",
  "soil_type": "sand",
  "customer_foundation_override": "48_Square",
  "foundation_type": "Square",
  "foundation_size": 48,
  "check_rails": false
}
```

Design Notes:



- AISC Deflection checks are set to L/1 due to structure design intent
- Foundation Design and Sizing is approximate only










FEM Results (Envelope Worst Case for each member)







Reaction Forces for Foundation 1 (Node ID#1), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	0.0000	1.9320	0.0451	0.1436	-0.0358	0.0227
ULS: 2. D + L	0.0000	1.9320	0.0451	0.1436	-0.0358	0.0227
ULS: 3. D + (S or Lr or R)	0.0000	4.5834	0.1302	0.4151	-0.1041	0.0320
ULS: 3. D + (S or Lr or R)	0.0000	1.9320	0.0451	0.1436	-0.0358	0.0227
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0000	3.9205	0.1089	0.3472	-0.0870	0.0297
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0000	1.9320	0.0451	0.1436	-0.0358	0.0227
ULS: 5b. D + 0.7E	0.0000	1.9320	0.0451	0.1436	-0.0358	0.0227
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	0.0000	3.9205	0.1089	0.3472	-0.0870	0.0297
ULS: 8. 0.6D + 0.7E	0.0000	1.1592	0.0270	0.0861	-0.0215	0.0136
ULS: 5a. D + 0.6W_Wind downforce Case A only	-3.5701	5.7605	0.1996	0.6062	-0.6066	40.4959
ULS: 5a. D + 0.6W_Wind downforce Case B only	-3.5701	5.7605	0.1996	0.6062	-0.6066	40.4959
ULS: 5a. D + 0.6W_Wind uplift Case A only	2.6841	-0.9463	-0.0706	-0.2018	0.3926	-28.0988
ULS: 5a. D + 0.6W_Wind uplift Case B only	2.3317	-0.5685	-0.0562	-0.1590	0.3393	-31.9319
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-2.6776	6.7919	0.2248	0.6942	-0.5151	30.3846
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-2.6776	6.7919	0.2248	0.6942	-0.5151	30.3846
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	2.0131	1.7618	0.0222	0.0882	0.2342	-21.0615
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.7488	2.0452	0.0330	0.1203	0.1943	-23.9363
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-2.6776	4.8034	0.1610	0.4905	-0.4639	30.3776
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-2.6776	4.8034	0.1610	0.4905	-0.4639	30.3776
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	2.0131	-0.2267	-0.0416	-0.1155	0.2855	-21.0684
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.7488	0.0567	-0.0309	-0.0833	0.2456	-23.9433
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-3.5701	4.9877	0.1816	0.5488	-0.5923	40.4868
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-3.5701	4.9877	0.1816	0.5488	-0.5923	40.4868
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	2.6841	-1.7191	-0.0886	-0.2592	0.4069	-28.1079
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	2.3317	-1.3413	-0.0742	-0.2164	0.3537	-31.9410

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	10.0249
Shear X	-5.9502
Shear Z	0.3540
Moment X	1.0794
Moment Y (Twist)	1.0260
Moment Z	68.2383

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	6.7919
Shear X	-3.5701
Shear Z	0.2248
Moment X	0.6942
Moment Y (Twist)	0.6066
Moment Z	40.4959

Reaction Forces for Foundation 2 (Node ID#101), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	-0.0000	1.9320	-0.0451	-0.1436	0.0358	0.0227
ULS: 2. D + L	-0.0000	1.9320	-0.0451	-0.1436	0.0358	0.0227
ULS: 3. D + (S or Lr or R)	-0.0000	4.5834	-0.1302	-0.4151	0.1041	0.0320
ULS: 3. D + (S or Lr or R)	-0.0000	1.9320	-0.0451	-0.1436	0.0358	0.0227
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0000	3.9205	-0.1089	-0.3472	0.0871	0.0297
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0000	1.9320	-0.0451	-0.1436	0.0358	0.0227
ULS: 5b. D + 0.7E	-0.0000	1.9320	-0.0451	-0.1436	0.0358	0.0227

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	-0.0000	3.9205	-0.1089	-0.3472	0.0871	0.0297
ULS: 8. 0.6D + 0.7E	-0.0000	1.1592	-0.0270	-0.0861	0.0215	0.0136
ULS: 5a. D + 0.6W_Wind downforce Case A only	-3.5701	5.7605	-0.1996	-0.6062	0.6066	40.4959
ULS: 5a. D + 0.6W_Wind downforce Case B only	-3.5701	5.7605	-0.1996	-0.6062	0.6066	40.4959
ULS: 5a. D + 0.6W_Wind uplift Case A only	2.6841	-0.9463	0.0706	0.2018	-0.3926	-28.0988
ULS: 5a. D + 0.6W_Wind uplift Case B only	2.3317	-0.5685	0.0562	0.1590	-0.3393	-31.9319
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-2.6776	6.7919	-0.2248	-0.6942	0.5152	30.3846
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-2.6776	6.7919	-0.2248	-0.6942	0.5152	30.3846
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	2.0131	1.7618	-0.0222	-0.0882	-0.2342	-21.0615
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.7488	2.0452	-0.0330	-0.1203	-0.1943	-23.9363
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-2.6776	4.8034	-0.1610	-0.4905	0.4639	30.3776
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-2.6776	4.8034	-0.1610	-0.4905	0.4639	30.3776
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	2.0131	-0.2267	0.0416	0.1155	-0.2855	-21.0684
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.7488	0.0567	0.0309	0.0833	-0.2455	-23.9433
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-3.5701	4.9877	-0.1816	-0.5488	0.5923	40.4868
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-3.5701	4.9877	-0.1816	-0.5488	0.5923	40.4868
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	2.6841	-1.7191	0.0886	0.2592	-0.4069	-28.1079
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	2.3317	-1.3413	0.0742	0.2164	-0.3536	-31.9410

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	10.0249
Shear X	-5.9502
Shear Z	-0.3540
Moment X	-1.0794
Moment Y (Twist)	1.0259
Moment Z	68.2394

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	6.7919
Shear X	-3.5701
Shear Z	-0.2248
Moment X	-0.6942
Moment Y (Twist)	0.6066
Moment Z	40.4959

Project Details

Design Code: AISC 360-16 LRFD
 Provision: LRFD
 Country: United States

User Name: sales@mtsolar.us
 Project Name: Dustin J 460WBi 2 pole
 Unit System: imperial



Design Input Information

Design Factors			
Φ_t	Φ_c	Φ_b	Φ_v
0.9	0.9	0.9	0.9

Design Materials			
ID	E (ksi)	F_y (ksi)	F_u (ksi)
1	29000	50	65

Section Dimensions								
ID	Name	d (in)	t_w (in)					
2	2in Pipe Sch 80	2.38	0.22					
5	4in Pipe Sch 80	4.50	0.34					
9	8in Pipe Sch 40	8.63	0.32					
ID	Name	d (in)	b (in)	t_w (in)	t_b (in)	r (in)		
16	HSS5x3x16	5.00	3.00	0.17	0.17	0.17		
ID	Name	d (in)	t_w (in)	b_t (in)	b_b (in)	t_t (in)	t_b (in)	r (in)
19	W8x10	7.89	0.17	3.94	3.94	0.20	0.20	0.30

Section Properties								
ID	Name	A (in ²)	J (in ⁴)	I_{yp} (in ⁴)	I_{zp} (in ⁴)	I_w (in ⁶)	S_{yp} (in ³)	S_{zp} (in ³)
2	2in Pipe Sch 80	1.48	1.74	0.87	0.87	0.00	1.02	1.02
5	4in Pipe Sch 80	4.41	19.22	9.61	9.61	0.00	5.85	5.85

9	8in Pipe Sch 40	8.40	144.98	72.49	72.49	0.00	22.21	22.21
16	HSS5x3x3/16	2.58	8.64	3.85	8.53	92.39	2.96	4.21
19	W8x10	2.96	0.04	2.09	30.80	30.90	1.66	8.87

Member Properties								
Member ID	Section ID	K _z L (ft)	K _y L (ft)	L _b (ft)	C _b	L S T	L S C	L D
1	9	22.77	22.77	10.84	-	300	200	1
2	5	1.30	1.30	2.00	-	300	200	1
3	16	0.92	0.92	1.42	1.19,1.18,1.19,1.18,1.18,1.19,1.18,1.18,1.17,1.17,1.18,1.18,1.17,1.17,1.18,1.18,1.19,1.11,1.18,1.18,1.17,1.17,1.18,1.18,1.17,1.17	300	200	1
4	16	2.44	2.44	3.75	1.69,1.68,1.69,1.67,1.68,1.69,1.67,1.67,1.66,1.55,1.67,1.67,1.66,1.64,1.67,1.67,1.70,1.68,1.67,1.67,1.65,2.30,1.67,1.67,1.66,1.65	300	200	1
5	16	1.52	1.52	2.33	1.68,1.67,1.68,1.67,1.68,1.68,1.67,1.67,1.66,1.66,1.67,1.67,1.66,1.66,1.67,1.67,1.68,1.58,1.67,1.67,1.66,1.66,1.67,1.67,1.66,1.66	300	200	1
6	16	0.92	0.92	1.42	1.19,1.19,1.19,1.18,1.19,1.19,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.19,2.25,1.18,1.18,1.17,1.18,1.18,1.18,1.18,1.18	300	200	1
7	16	1.52	1.52	2.33	1.68,1.67,1.68,1.67,1.68,1.68,1.67,1.67,1.66,1.66,1.67,1.67,1.66,1.66,1.67,1.67,1.68,1.23,1.67,1.67,1.66,1.66,1.67,1.67,1.66,1.67	300	200	1
8	19	1.33	1.33	2.05	1.28,1.28,1.28,1.29,1.28,1.28,1.28,1.28,1.27,1.15,1.27,1.27,1.27,1.23,1.28,1.28,1.33,1.30,1.28,1.28,1.27,1.06,1.27,1.27,1.27,1.24	300	200	1
9	2	2.60	2.60	4.00	-	300	200	1
10	16	2.44	2.44	3.75	1.69,1.68,1.69,1.67,1.68,1.69,1.67,1.67,1.66,1.61,1.67,1.67,1.66,1.65,1.67,1.67,1.69,1.68,1.67,1.67,1.66,1.33,1.67,1.67,1.66,1.66	300	200	1
11	19	1.33	1.33	2.05	1.29,1.29,1.29,1.29,1.29,1.29,1.28,1.28,1.27,1.28,1.28,1.28,1.27,1.28,1.28,1.28,1.33,1.14,1.28,1.28,1.27,1.28,1.28,1.28,1.27,1.28	300	200	1
12	5	1.30	1.30	2.00	-	300	200	1
13	19	4.88	4.00	7.50	1.23,1.24,1.23,1.24,1.23,1.23,1.26,1.26,1.26,1.33,1.26,1.26,1.26,1.31,1.25,1.25,1.19,1.42,1.26,1.26,1.27,1.33,1.26,1.26,1.26,1.31	300	200	1
14	19	4.88	4.00	7.50	1.22,1.23,1.22,1.23,1.23,1.22,1.24,1.24,1.27,1.15,1.24,1.24,1.26,1.07,1.24,1.24,1.14,1.28,1.24,1.24,1.27,1.25,1.24,1.24,1.26,1.09	300	200	1
15	19	4.20	4.20	2.00	2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.33,2.32,2.33,2.33,2.33,2.33,2.33,2.33,2.33	300	200	1
16	19	4.20	4.20	2.00	2.33,2.33	300	200	1
101	9	22.77	22.77	10.84	-	300	200	1
102	5	1.30	1.30	2.00	-	300	200	1
103	16	0.92	0.92	1.42	1.19,1.19,1.19,1.18,1.19,1.19,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.18,1.19,2.26,1.18,1.18,1.17,1.18,1.18,1.18,1.18	300	200	1
104	16	2.44	2.44	3.75	1.69,1.68,1.69,1.67,1.68,1.69,1.67,1.67,1.66,1.62,1.67,1.67,1.66,1.65,1.67,1.67,1.69,1.68,1.67,1.67,1.66,1.33,1.67,1.67,1.66,1.66	300	200	1
105	16	1.52	1.52	2.33	1.68,1.67,1.68,1.67,1.68,1.68,1.67,1.67,1.66,1.66,1.67,1.67,1.66,1.66,1.67,1.67,1.68,1.23,1.67,1.67,1.66,1.66,1.67,1.67,1.66,1.67	300	200	1
106	16	0.92	0.92	1.42	1.19,1.18,1.19,1.18,1.18,1.19,1.18,1.18,1.17,1.17,1.18,1.18,1.17,1.17,1.18,1.18,1.19,1.11,1.18,1.18,1.17,1.17,1.18,1.18,1.17,1.17	300	200	1
107	16	1.52	1.52	2.33	1.68,1.67,1.68,1.67,1.68,1.68,1.67,1.67,1.66,1.66,1.67,1.67,1.66,1.66,1.67,1.67,1.68,1.58,1.67,1.67,1.66,1.66,1.67,1.67,1.66,1.66	300	200	1

[illegible]

Member Design Capacity

Member ID	$\Phi_t P_n$ (kip)	$\Phi_c P_n$ (kip)	$\Phi_b M_{zn}$ (k-ft)	$\Phi_b M_{yn}$ (k-ft)	$\Phi_v V_{yn}$ (kip)	$\Phi_v V_{zn}$ (kip)
1	377.97	200.77	83.29	83.29	113.39	113.39
2	198.33	196.72	21.95	21.95	59.50	59.50
3	116.10	115.41	15.79	11.10	42.08	23.28
4	116.10	111.33	15.79	11.10	42.08	23.28
5	116.10	114.23	15.79	11.10	42.08	23.28
6	116.10	115.41	15.79	11.10	42.08	23.28
7	116.10	114.23	15.79	11.10	42.08	23.28
8	133.20	126.01	32.87	6.12	40.24	43.62
9	66.48	58.89	3.82	3.82	19.94	19.94
10	116.10	111.33	15.79	11.10	42.08	23.28
11	133.20	126.01	32.87	6.12	40.24	43.62
12	198.33	196.72	21.95	21.95	59.50	59.50
13	133.20	104.94	27.27	6.12	40.24	43.62
14	133.20	104.94	24.52	6.12	40.24	43.62
15	133.20	102.39	32.87	6.12	40.24	43.62
16	133.20	102.39	32.87	6.12	40.24	43.62
101	377.97	200.77	83.29	83.29	113.39	113.39
102	198.33	196.72	21.95	21.95	59.50	59.50
103	116.10	115.41	15.79	11.10	42.08	23.28
104	116.10	111.33	15.79	11.10	42.08	23.28
105	116.10	114.23	15.79	11.10	42.08	23.28
106	116.10	115.41	15.79	11.10	42.08	23.28
107	116.10	114.23	15.79	11.10	42.08	23.28
108	133.20	102.39	32.87	6.12	40.24	43.62
109	66.48	58.89	3.82	3.82	19.94	19.94
110	116.10	111.33	15.79	11.10	42.08	23.28
111	133.20	102.39	32.87	6.12	40.24	43.62
112	198.33	196.72	21.95	21.95	59.50	59.50
113	133.20	104.94	27.27	6.12	40.24	43.62
114	133.20	104.94	24.52	6.12	40.24	43.62

115	133.20	93.89	24.18	6.12	40.24	43.62
116	133.20	93.89	23.49	6.12	40.24	43.62


Design Ratio

Member ID	P	M _z	M _y	V _y	V _z	(P,M _z ,M _y)	Worst LC	KL/r	δ	Status
1	0.050	0.819	0.033	0.052	0.003	0.857	#13	0.465	Not Required	Pass
2	0.001	0.302	0.232	0.071	0.048	0.534	#13	0.053	Not Required	Pass
3	0.008	0.624	0.043	0.062	0.009	0.642	#13	0.045	Not Required	Pass
4	0.007	0.568	0.076	0.057	0.019	0.623	#13	0.080	Not Required	Pass
5	0.007	0.387	0.060	0.062	0.014	0.390	#13	0.074	Not Required	Pass
6	0.011	0.747	0.099	0.076	0.028	0.807	#13	0.045	Not Required	Pass
7	0.011	0.463	0.133	0.074	0.033	0.482	#13	0.074	Not Required	Pass
8	0.002	0.140	0.095	0.043	0.015	0.207	#21	0.095	Not Required	Pass
9	0.002	0.052	0.069	0.002	0.003	0.120	#13	0.204	Not Required	Pass
10	0.012	0.686	0.127	0.069	0.028	0.714	#13	0.080	Not Required	Pass
11	0.004	0.150	0.093	0.047	0.015	0.210	#21	0.095	Not Required	Pass
12	0.001	0.427	0.278	0.091	0.053	0.706	#13	0.053	Not Required	Pass
13	0.004	0.127	0.316	0.065	0.021	0.375	#21	0.286	Not Required	Pass
14	0.004	0.120	0.311	0.059	0.021	0.365	#21	0.190	Not Required	Pass
15	0.000	0.024	0.046	0.020	0.007	0.065	#21	Not Required	Not Required	Pass
16	0.000	0.022	0.046	0.018	0.007	0.064	#21	Not Required	Not Required	Pass
101	0.050	0.819	0.033	0.052	0.003	0.857	#13	0.465	Not Required	Pass
102	0.001	0.427	0.278	0.091	0.053	0.706	#13	0.053	Not Required	Pass
103	0.011	0.747	0.099	0.076	0.028	0.807	#13	0.045	Not Required	Pass
104	0.012	0.686	0.127	0.069	0.028	0.714	#13	0.080	Not Required	Pass
105	0.011	0.463	0.133	0.074	0.033	0.482	#13	0.074	Not Required	Pass
106	0.008	0.624	0.043	0.062	0.009	0.642	#13	0.045	Not Required	Pass
107	0.007	0.388	0.060	0.062	0.014	0.390	#13	0.074	Not Required	Pass
108	0.000	0.022	0.046	0.018	0.007	0.064	#21	Not Required	Not Required	Pass
109	0.002	0.052	0.069	0.002	0.003	0.120	#13	0.204	Not Required	Pass
110	0.007	0.568	0.076	0.057	0.019	0.623	#13	0.080	Not Required	Pass
111	0.000	0.024	0.046	0.020	0.007	0.065	#21	Not Required	Not Required	Pass
112	0.001	0.302	0.232	0.071	0.048	0.534	#13	0.053	Not Required	Pass
113	0.004	0.127	0.316	0.065	0.021	0.375	#21	0.190	Not Required	Pass
114	0.004	0.120	0.311	0.059	0.021	0.365	#21	0.286	Not Required	Pass
115	0.005	0.255	0.178	0.047	0.015	0.378	#21	0.346	Not Required	Pass
116	0.002	0.236	0.179	0.043	0.015	0.371	#21	0.346	Not Required	Pass

Definitions

Φ _t	Safety factor for tensile
Φ _c	Safety factor for compression
Φ _b	Safety factor for flexure
Φ _v	Safety factor for shear
E	Modulus of elasticity
F _y	Specified minimum yield stress
F _u	Specified minimum tensile strength
A	Cross-sectional area
J	Torsional constant
I _{yp}	Moment of inertia about the Y axes
I _{zp}	Moment of inertia about the Z axes
I _w	Warping constant
S _{yp}	Plastic section modulus about the Y axis
S _{zp}	Plastic section modulus about the Z axis
KL	Effective length
C _n	Buckling modification factor (from all load combinations)

L_b	Length between braced points
LST	Limited slenderness for tension
LSC	Limited slenderness for compression
LD	Limited deflection
P_n	Nominal axial strength (tension/compression)
M_n	Nominal flexural strength (about Z/Y axis)
V_n	Nominal shear strength (along Z/Y axis)
P	Design ratio in case of axial force
M_z	Design ratio in case of bending about Z axis
M_y	Design ratio in case of bending about Y axis
V_y	Design ratio in case of shear along Y axis
V_z	Design ratio in case of shear along Z axis
(P, M_z , M_y)	Design ratio in case of axial force and bending action
KL/r	Design ratio in case of section slenderness
δ	Design ratio in case of member deflection
OK	Capacity is provided
NG	Capacity is not provided

REFERENCES	CALCULATIONS	RESULTS																										
	SkyCiv Foundation Design Pile Foundation Design Information : Design code : IBC 2021 (International Building Code) Unit System : Imperial																											
	Pile Input  Geometry Pile shape: rectangular b = 48 in - Pile width D = 48 in - Pile depth L = 7.25 ft - Total pile length h1 = 0 ft - Lateral load height from the top of the pile, h2 = 0 ft - Depth to resisting surface he = 0 ft - Length of pile above the ground Tabulation of Soil Parameters <table><tr><th>Layer</th><th>Label</th><th>Allowable Bearing Pressure (qa) (psf)</th><th>Allowable Lateral Pressure (R) (psf/ft)</th></tr><tr><td>1</td><td>Sand, silty sand, clayey sand, silty gravel & clayey gravel</td><td>2000.000</td><td>150.000</td></tr></table> Tabulation of Loads <table><tr><th>Load Component</th><th>ASD</th><th>LRFD</th></tr><tr><td>P (kip)</td><td>6.792</td><td>10.025</td></tr><tr><td>Vx (kip)</td><td>-3.570</td><td>-5.950</td></tr><tr><td>Vz (kip)</td><td>0.225</td><td>0.354</td></tr><tr><td>Mx (kipft)</td><td>0.694</td><td>1.079</td></tr><tr><td>Mz (kipft)</td><td>40.496</td><td>68.238</td></tr></table> Material Properties f'ck = 2.5 ksi - Concrete strength,	Layer	Label	Allowable Bearing Pressure (qa) (psf)	Allowable Lateral Pressure (R) (psf/ft)	1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000	Load Component	ASD	LRFD	P (kip)	6.792	10.025	Vx (kip)	-3.570	-5.950	Vz (kip)	0.225	0.354	Mx (kipft)	0.694	1.079	Mz (kipft)	40.496	68.238	
Layer	Label	Allowable Bearing Pressure (qa) (psf)	Allowable Lateral Pressure (R) (psf/ft)																									
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000																									
Load Component	ASD	LRFD																										
P (kip)	6.792	10.025																										
Vx (kip)	-3.570	-5.950																										
Vz (kip)	0.225	0.354																										
Mx (kipft)	0.694	1.079																										
Mz (kipft)	40.496	68.238																										
	Required depth to resist lateral loads (ASD) H - Point of application of the lateral load $H = h_1 + h_2 + h_e$ $H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$ $H = 0 \text{ ft}$ Considering x-direction: H_o - Lateral force per length of pile, $H_o = \frac{V_x}{1.57 D}$ $H_o = \frac{(-3.57 \text{ kip})}{1.57 \times (48 \text{ in})}$ $H_o = -0.56847 \text{ kip/ft}$ M_o - Moment per length of pile, $M_o = \frac{M_z + (V_x H)}{1.57 D}$																											

	$M_o = \frac{(40.496 \text{ kipft}) + ((-3.57 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$ $M_o = 6.4484 \text{ kipft/ft}$ Required depth of embedment in earth: $L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$ Solving the cubic equation: $L_{e,x} = 6.6198 \text{ ft}$ - Required depth in x-direction, Considering z-direction: H_o - Lateral force per length of pile, $H_o = \frac{V_z}{1.57 b}$ $H_o = \frac{(0.225 \text{ kip})}{1.57 \times (48 \text{ in})}$ $H_o = 0.035828 \text{ kip/ft}$ M_o - Moment per length of pile, $M_o = \frac{M_x + (V_z H)}{1.57 b}$ $M_o = \frac{(0.694 \text{ kipft}) + ((0.225 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$ $M_o = 0.11051 \text{ kipft/ft}$ Required depth of embedment in earth: $L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$ Solving the cubic equation: $L_{e,z} = 2.4116 \text{ ft}$ - Required depth in z-direction, Minimum embedded depth required: $L_{e,req}$ - Depth of pile required, $L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$ $L_{e,req} = \text{MAX}[(6.6198 \text{ ft}), (2.4116 \text{ ft})]$ $L_{e,req} = 6.62 \text{ ft}$ L_e - Actual embedded length of pile, $L_e = L - h_e - h_2$ $L_e = (7.25 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$ $L_e = 7.25 \text{ ft}$ Ratio - Embedded depth $\text{Ratio} = \frac{L_{e,req}}{L_e}$ $\text{Ratio} = \frac{(6.62 \text{ ft})}{(7.25 \text{ ft})}$ $\text{Ratio} = 0.9131$	Status: PASS Ratio: 0.910
	End-bearing Capacity (ASD) A - Pile cross-section area $A = b D$ $A = (48 \text{ in}) \times (48 \text{ in})$ $A = 16 \text{ ft}^2$ q - End-bearing pressure $q = \frac{P_o}{A}$ $q = \frac{(6.792 \text{ kip})}{(16 \text{ ft}^2)}$ $q = 0.4245 \text{ kip/ft}^2$	


	$q = 0.4245 \text{ kip/ft}$	
	Check bearing capacity ratio: Ratio - Capacity $Ratio = \frac{q}{q_a}$ $Ratio = \frac{(0.4245 \text{ kip/ft}^2)}{(2000 \text{ psf})}$ $Ratio = 0.21225$	Status: PASS Ratio: 0.210
Czerniak	Lateral Soil Pressure (ASD): L/D - Length to least lateral dimension ratio, $L/D = \frac{L}{D}$ $L/D = \frac{(7.25 \text{ ft})}{(48 \text{ in})}$ $L/D = 1.8125$ Since $L/D \leq 10$, Pile is short. Considering x-direction: $H_o = -0.56847 \text{ kip/ft}$ - Lateral force per length of pile, $M_o = 6.4484 \text{ kipft/ft}$ - Overturning moment per length of pile, a - Distance from resting surface to pivot point, $a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$ $a = \frac{(4 \times (6.4484 \text{ kipft/ft}) \times (7.25 \text{ ft})) + (3 \times (-0.56847 \text{ kip/ft}) \times (7.25 \text{ ft})^2)}{(6 \times (6.4484 \text{ kipft/ft})) + (4 \times (-0.56847 \text{ kip/ft}) \times (7.25 \text{ ft}))}$ $a = 5.0138 \text{ ft}$ p - Earth pressure against the pile at distance $a/2$ from resting surface, $p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$ $p = \frac{0.75 [(4 \times (6.4484 \text{ kipft/ft})) + (3 \times (-0.56847 \text{ kip/ft}) \times (7.25 \text{ ft}))]^2}{(7.25 \text{ ft})^2 [(3 \times (6.4484 \text{ kipft/ft})) + (2 \times (-0.56847 \text{ kip/ft}) \times (7.25 \text{ ft}))]}$ $p = 0.23178 \text{ kip/ft}^2$ s - Earth pressure against the pile at distance L_e, $s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$ $s = \frac{6 \times [(2 \times (6.4484 \text{ kipft/ft})) + ((-0.56847 \text{ kip/ft}) \times (7.25 \text{ ft}))]}{(7.25 \text{ ft})^2}$ $s = 1.0017 \text{ kip/ft}^2$ Check lateral soil pressure capacity: p_a - Allowable lateral soil pressure at depth $a/2$, $p_a = R \frac{a}{2}$ $p_a = (150 \text{ psf/ft}) \times \frac{(5.0138 \text{ ft})}{2}$ $p_a = 0.37604 \text{ kip/ft}^2$ Ratio - Lateral soil capacity $Ratio = \frac{p}{p_a}$ $Ratio = \frac{(0.23178 \text{ kip/ft}^2)}{(0.37604 \text{ kip/ft}^2)}$ $Ratio = 0.61638$ p_s - Allowable lateral soil pressure at depth L_e,	Status: PASS Ratio: 0.620

	$p_s = R L_e$ $p_s = (150 \text{ psf/ft}) \times (7.25 \text{ ft})$ $p_s = 1.0875 \text{ kip/ft}^2$ Ratio - Lateral soil capacity $\text{Ratio} = \frac{s}{p_s}$ $\text{Ratio} = \frac{(1.0017 \text{ kip/ft}^2)}{(1.0875 \text{ kip/ft}^2)}$ $\text{Ratio} = 0.92111$	Status: PASS Ratio: 0.920
	Considering z-direction: $H_o = 0.035828 \text{ kip/ft}$ - Lateral force per length of pile, $M_o = 0.11051 \text{ kipft/ft}$ - Overturning moment per length of pile, a - Distance from resting surface to pivot point, $a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$ $a = \frac{(4 \times (0.11051 \text{ kipft/ft}) \times (7.25 \text{ ft})) + (3 \times (0.035828 \text{ kip/ft}) \times (7.25 \text{ ft})^2)}{(6 \times (0.11051 \text{ kipft/ft})) + (4 \times (0.035828 \text{ kip/ft}) \times (7.25 \text{ ft}))}$ $a = 5.2021 \text{ ft}$ p - Earth pressure against the pile at distance $a/2$ from resting surface, $p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^3 [(3 M_o) + (2 H_o L_e)]}$ $p = \frac{0.75 \times [(4 \times (0.11051 \text{ kipft/ft})) + (3 \times (0.035828 \text{ kip/ft}) \times (7.25 \text{ ft}))]^2}{(7.25 \text{ ft})^3 \times [(3 \times (0.11051 \text{ kipft/ft})) + (2 \times (0.035828 \text{ kip/ft}) \times (7.25 \text{ ft}))]}$ $p = 0.025008 \text{ kip/ft}^2$ s - Earth pressure against the pile at distance L_e, $s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$ $s = \frac{6 \times [(2 \times (0.11051 \text{ kipft/ft})) + ((0.035828 \text{ kip/ft}) \times (7.25 \text{ ft}))]}{(7.25 \text{ ft})^2}$ $s = 0.05488 \text{ kip/ft}^2$ Check lateral soil pressure capacity: p_a - Allowable lateral soil pressure at depth $a/2$, $p_a = R \frac{a}{2}$ $p_a = (150 \text{ psf/ft}) \times \frac{(5.2021 \text{ ft})}{2}$ $p_a = 0.39016 \text{ kip/ft}^2$ Ratio - Lateral soil capacity $\text{Ratio} = \frac{p}{p_a}$ $\text{Ratio} = \frac{(0.025008 \text{ kip/ft}^2)}{(0.39016 \text{ kip/ft}^2)}$ $\text{Ratio} = 0.064097$ p_s - Allowable lateral soil pressure at depth L_e, $p_s = R L_e$ $p_s = (150 \text{ psf/ft}) \times (7.25 \text{ ft})$ $p_s = 1.0875 \text{ kip/ft}^2$ Ratio - Lateral soil capacity $\text{Ratio} = \frac{s}{p_s}$	Status: PASS Ratio: 0.060

$$Ratio = \frac{(0.05488 \text{ kip/ft}^2)}{(1.0875 \text{ kip/ft}^2)}$$

$$Ratio = 0.050464$$

Status: **PASS**
Ratio: **0.050**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{1.57 D}$$

$$H_o = \frac{(-5.95 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.94745 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_x H)}{1.57 D}$$

$$M_o = \frac{(68.238 \text{ kipft}) + ((-5.95 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 10.866 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(10.866 \text{ kipft/ft})}{(-0.94745 \text{ kip/ft})}$$

$$E = 11.469 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (10.866 \text{ kipft/ft}) \times (7.25 \text{ ft})) + (3 \times (-0.94745 \text{ kip/ft}) \times (7.25 \text{ ft})^2)}{(6 \times (10.866 \text{ kipft/ft})) + (4 \times (-0.94745 \text{ kip/ft}) \times (7.25 \text{ ft}))}$$

$$a = 5.0125 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.94745 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (11.469 \text{ ft})}{(7.25 \text{ ft})} + 3 \right) \times \left(\frac{(5.0125 \text{ ft})}{(7.25 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (11.469 \text{ ft})}{(7.25 \text{ ft})} + 2 \right) \times \left(\frac{(5.0125 \text{ ft})}{(7.25 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 13.107 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.94745 \text{ kip/ft}) \times (48 \text{ in}) \times (7.25 \text{ ft})) \times \left[\left(\frac{(11.469 \text{ ft})}{(7.25 \text{ ft})} + \frac{(5.0125 \text{ ft})}{2 \times (7.25 \text{ ft})} \right) - \left[\left(\frac{4 \times (11.469 \text{ ft})}{(7.25 \text{ ft})} + 3 \right) \times \left(\frac{(5.0125 \text{ ft})}{2 \times (7.25 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (11.469 \text{ ft})}{(7.25 \text{ ft})} + 2 \right) \times \left(\frac{(5.0125 \text{ ft})}{2 \times (7.25 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 45.022 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(0.354 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = 0.056369 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(1.079 \text{ kipft}) + ((0.354 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.17182 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.17182 \text{ kipft/ft})}{(0.056369 \text{ kip/ft})}$$

$$E = 3.048 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.17182 \text{ kipft/ft}) \times (7.25 \text{ ft})) + (3 \times (0.056369 \text{ kip/ft}) \times (7.25 \text{ ft})^2)}{(6 \times (0.17182 \text{ kipft/ft})) + (4 \times (0.056369 \text{ kip/ft}) \times (7.25 \text{ ft}))}$$

$$a = 5.2038 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((0.056369 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (3.048 \text{ ft})}{(7.25 \text{ ft})} + 3 \right) \times \left(\frac{(5.2038 \text{ ft})}{(7.25 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (3.048 \text{ ft})}{(7.25 \text{ ft})} + 2 \right) \times \left(\frac{(5.2038 \text{ ft})}{(7.25 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.31837 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,


$$M_{max} = (H_o b L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((0.056369 \text{ kip/ft}) \times (48 \text{ in}) \times (7.25 \text{ ft})) \times \left[\left(\frac{(3.048 \text{ ft})}{(7.25 \text{ ft})} + \frac{(5.2038 \text{ ft})}{2 \times (7.25 \text{ ft})} \right) - \left[\left(\frac{4 \times (3.048 \text{ ft})}{(7.25 \text{ ft})} + 3 \right) \times \left(\frac{(5.2038 \text{ ft})}{2 \times (7.25 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (3.048 \text{ ft})}{(7.25 \text{ ft})} + 2 \right) \times \left(\frac{(5.2038 \text{ ft})}{2 \times (7.25 \text{ ft})} \right)^4 \right] \right]$$

		$M_{max} = 1.0086 \text{ kipft}$	
		Minimum Reinforcement Check (LRFD) Parameters: $f'_{ck} = 2.5 \text{ ksi}$ - Concrete strength, $f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength, $\phi = 0.65$ - Reduction factor for axial strength, $\alpha = 0.8$ - Alpha factor for axial strength, $A_g = 2304 \text{ in}^2$ - Gross area of concrete, Longitudinal reinforcement: Required reinforcement due to axial load, $A_{st,required}$ $A_{st,required}$ $A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$ $A_{st,required} = \text{Min} \left[\frac{\frac{(10.025 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (2.5 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (2.5 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$ $A_{st,required} = -84.263 \text{ in}^2$ A_{min} - Governing minimum reinforcement area, $A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$ $A_{min} = \text{Max} [(-84.263 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$ $A_{min} = 4.1472 \text{ in}^2$ n_{rebar} - Required number of reinforcement, $n_{rebar} = \frac{A_{min}}{A_{rebar}}$ $n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$ $n_{rebar} = 14$ A_{st} - Actual total reinforcement area, $A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$ $A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$ $A_{st} = 4.2951 \text{ in}^2$ Ratio - Capacity $\text{Ratio} = \frac{A_{min}}{A_{st}}$ $\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$ $\text{Ratio} = 0.96556$ 25.2.3 s_{rebar} - Minimum spacing of reinforcement, $s_{rebar} = \text{Max} [1.5, (1.5 d_{bar})]$ $s_{rebar} = \text{Max} [1.5, (1.5 \times (0.625 \text{ in}))]$ $s_{rebar} = 1.5 \text{ in}$ Ties: 25.7.2.2 Since longitudinal reinforcement is $\leq \text{No. } 10\phi$: Use #3(0.375 in) 25.7.2.1 s_{ties} - Maximum spacing of ties, $s_{ties} = \text{Min} [(16 d_{bar}), (48 d_{ties}), \text{Min}(D, b)]$ $s_{ties} = \text{Min} [(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), \text{Min}((48 \text{ in}), (48 \text{ in}))]$ $s_{ties} = 10 \text{ in}$ Summary: Main reinforcement: 14 - #5 (0.625 in)	Status: PASS Ratio: 0.970

	Ties: #3(0.375 in) - 10 in	
22.4.2.2	Axial Compression Strength (ACI 318-19, LRFD) ϕP_N - Allowable axial compressive strength $\phi P_N = \phi 0.80 \left[(0.85 f'_{ck} [A_g - A_{st}]) + (f_{yk} A_{st}) \right]$ $\phi P_N = (0.65) \times 0.80 \times \left[(0.85 \times (2.5 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2)) \right]$ $\phi P_N = 2675.2 \text{ kip}$ Ratio - Capacity $Ratio = \frac{P}{\phi P_N}$ $Ratio = \frac{(10.025 \text{ kip})}{(2675.2 \text{ kip})}$ $Ratio = 0.0037474$	Status: PASS Ratio: 0.000
22.5.2.2	Shear Strength (ACI 318-19, LRFD) Parameters: $b_w = 48 \text{ in}$ - Effective width, d - Effective depth $d = 0.80 D$ $d = 0.80 \times (48 \text{ in})$ $d = 38.4 \text{ in}$	
22.5.5.1.3	λ_s - size effect modification factor $\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$ $\lambda_s = MIN \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$ $\lambda_s = 0.64282$	
22.5.5.1.1	The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $V_{c,max}$ - Max shear strength of concrete $V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$ $V_{c,max} = 5 \times (0.64282) \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{c,max} = 296.21 \text{ kip}$	
22.5.5.1.1(a)	The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $P = 10.025 \text{ kip} \rightarrow 10025 \text{ lbf}$, $V_{c,a}$ - Shear strength of concrete (a) $V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck}} + \frac{P}{6 A_g} \right] b_w d$ $V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi})} + \frac{(10025 \text{ lbf})}{6 \times (2304 \text{ in}^2)} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{c,a} = 119.82 \text{ kip}$	
22.5.5.1.2	The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $V_{c,b}$ - Shear strength of concrete (b) $V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck}} + (0.05 f'_{ck}) \right] b_w d$ $V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi})} + (0.05 \times (2500 \text{ psi})) \right] \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{c,b} = 348.89 \text{ kip}$ V_c - Governing shear strength of concrete $V_c = MIN [V_{c,max}, V_{c,a}, V_{c,b}]$ $V_c = MIN [(296.21 \text{ kip}), (119.82 \text{ kip}), (348.89 \text{ kip})]$ $V_c = 119.82 \text{ kip}$	

14.5.2.1b	$\lambda = 1$ - Concrete modification factor (Normal concrete), Allowable flexural strength: M_n shall be the lesser of: $\phi M_{n,1}$ $\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$ $\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{2.5 \text{ ksi}} \times 18432.001 \text{ in}^3$ $\phi M_{n,1} = 249.600 \text{ kipft}$ $\phi M_{n,2}$ $\phi M_{n,2} = \phi \times 0.85 \times f'_c \times S_m$ $\phi M_{n,2} = (0.65) \times 0.85 \times (2.5 \text{ ksi}) \times (18432 \text{ in}^3)$ $\phi M_{n,2} = 2121.6 \text{ kipft}$ Therefore, ϕM_n - Allowable flexural strength, $\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$ $\phi M_n = \text{MIN}[(249.6 \text{ kipft}), (2121.6 \text{ kipft})]$ $\phi M_n = 249.6 \text{ kipft}$ Considering x-direction: $M_{max} = 45.022 \text{ kipft}$ - Maximum moment in the x-direction, Ratio - Capacity $\text{Ratio} = \frac{M_{max}}{\phi M_n}$ $\text{Ratio} = \frac{(45.022 \text{ kipft})}{(249.6 \text{ kipft})}$ $\text{Ratio} = 0.18038$	Status: PASS Ratio: 0.180
	Considering z-direction: $M_{max} = 1.0086 \text{ kipft}$ - Maximum moment in the z-direction, Ratio - Capacity $\text{Ratio} = \frac{M_{max}}{\phi M_n}$ $\text{Ratio} = \frac{(1.0086 \text{ kipft})}{(249.6 \text{ kipft})}$ $\text{Ratio} = 0.0040409$	Status: PASS Ratio: 0.000

REFERENCES	CALCULATIONS	RESULTS																										
	SkyCiv Foundation Design Pile Foundation Design Information : Design code : IBC 2021 (International Building Code) Unit System : Imperial																											
	Pile Input  Geometry Pile shape: rectangular b = 48 in - Pile width D = 48 in - Pile depth L = 7.25 ft - Total pile length h1 = 0 ft - Lateral load height from the top of the pile, h2 = 0 ft - Depth to resisting surface he = 0 ft - Length of pile above the ground Tabulation of Soil Parameters <table><thead><tr><th>Layer</th><th>Label</th><th>Allowable Bearing Pressure (qa) (psf)</th><th>Allowable Lateral Pressure (R) (psf/ft)</th></tr></thead><tbody><tr><td>1</td><td>Sand, silty sand, clayey sand, silty gravel & clayey gravel</td><td>2000.000</td><td>150.000</td></tr></tbody></table> Tabulation of Loads <table><thead><tr><th>Load Component</th><th>ASD</th><th>LRFD</th></tr></thead><tbody><tr><td>P (kip)</td><td>6.792</td><td>10.025</td></tr><tr><td>Vx (kip)</td><td>-3.570</td><td>-5.950</td></tr><tr><td>Vz (kip)</td><td>-0.225</td><td>-0.354</td></tr><tr><td>Mx (kipft)</td><td>-0.694</td><td>-1.079</td></tr><tr><td>Mz (kipft)</td><td>40.496</td><td>68.239</td></tr></tbody></table> Material Properties f'ck = 2.5 ksi - Concrete strength,	Layer	Label	Allowable Bearing Pressure (qa) (psf)	Allowable Lateral Pressure (R) (psf/ft)	1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000	Load Component	ASD	LRFD	P (kip)	6.792	10.025	Vx (kip)	-3.570	-5.950	Vz (kip)	-0.225	-0.354	Mx (kipft)	-0.694	-1.079	Mz (kipft)	40.496	68.239	
Layer	Label	Allowable Bearing Pressure (qa) (psf)	Allowable Lateral Pressure (R) (psf/ft)																									
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000																									
Load Component	ASD	LRFD																										
P (kip)	6.792	10.025																										
Vx (kip)	-3.570	-5.950																										
Vz (kip)	-0.225	-0.354																										
Mx (kipft)	-0.694	-1.079																										
Mz (kipft)	40.496	68.239																										
	Required depth to resist lateral loads (ASD) H - Point of application of the lateral load $H = h_1 + h_2 + h_e$ $H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$ $H = 0 \text{ ft}$ Considering x-direction: H_o - Lateral force per length of pile, $H_o = \frac{V_x}{1.57 D}$ $H_o = \frac{(-3.57 \text{ kip})}{1.57 \times (48 \text{ in})}$ $H_o = -0.56847 \text{ kip/ft}$ M_o - Moment per length of pile, $M_o = \frac{M_z + (V_x H)}{1.57 D}$																											

	$M_o = \frac{(40.496 \text{ kipft}) + ((-3.57 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$ $M_o = 6.4484 \text{ kipft/ft}$ Required depth of embedment in earth: $L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$ Solving the cubic equation: $L_{e,x} = 6.6198 \text{ ft}$ - Required depth in x-direction, Considering z-direction: H_o - Lateral force per length of pile, $H_o = \frac{V_z}{1.57 b}$ $H_o = \frac{(-0.225 \text{ kip})}{1.57 \times (48 \text{ in})}$ $H_o = -0.035828 \text{ kip/ft}$ M_o - Moment per length of pile, $M_o = \frac{M_x + (V_z H)}{1.57 b}$ $M_o = \frac{(0.694 \text{ kipft}) + ((-0.225 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$ $M_o = 0.11051 \text{ kipft/ft}$ Required depth of embedment in earth: $L_z^3 - \left(14.14 \times \frac{H_o \times L_z}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$ Solving the cubic equation: $L_{e,z} = 1.7249 \text{ ft}$ - Required depth in z-direction, Minimum embedded depth required: $L_{e,req}$ - Depth of pile required, $L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$ $L_{e,req} = \text{MAX}[(6.6198 \text{ ft}), (1.7249 \text{ ft})]$ $L_{e,req} = 6.62 \text{ ft}$ L_e - Actual embedded length of pile, $L_e = L - h_e - h_2$ $L_e = (7.25 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$ $L_e = 7.25 \text{ ft}$ Ratio - Embedded depth $\text{Ratio} = \frac{L_{e,req}}{L_e}$ $\text{Ratio} = \frac{(6.62 \text{ ft})}{(7.25 \text{ ft})}$ $\text{Ratio} = 0.9131$	Status: PASS Ratio: 0.910
	End-bearing Capacity (ASD) A - Pile cross-section area $A = b D$ $A = (48 \text{ in}) \times (48 \text{ in})$ $A = 16 \text{ ft}^2$ q - End-bearing pressure $q = \frac{P_o}{A}$ $q = \frac{(6.792 \text{ kip})}{(16 \text{ ft}^2)}$ $q = 0.4245 \text{ kip/ft}^2$	


	$q = 0.4245 \text{ kip/ft}$	
	Check bearing capacity ratio: Ratio - Capacity $Ratio = \frac{q}{q_a}$ $Ratio = \frac{(0.4245 \text{ kip/ft}^2)}{(2000 \text{ psf})}$ $Ratio = 0.21225$	Status: PASS Ratio: 0.210
Czerniak	Lateral Soil Pressure (ASD): L/D - Length to least lateral dimension ratio, $L/D = \frac{L}{D}$ $L/D = \frac{(7.25 \text{ ft})}{(48 \text{ in})}$ $L/D = 1.8125$ Since $L/D \leq 10$, Pile is short. Considering x-direction: $H_o = -0.56847 \text{ kip/ft}$ - Lateral force per length of pile, $M_o = 6.4484 \text{ kipft/ft}$ - Overturning moment per length of pile, a - Distance from resting surface to pivot point, $a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$ $a = \frac{(4 \times (6.4484 \text{ kipft/ft}) \times (7.25 \text{ ft})) + (3 \times (-0.56847 \text{ kip/ft}) \times (7.25 \text{ ft})^2)}{(6 \times (6.4484 \text{ kipft/ft})) + (4 \times (-0.56847 \text{ kip/ft}) \times (7.25 \text{ ft}))}$ $a = 5.0138 \text{ ft}$ p - Earth pressure against the pile at distance $a/2$ from resting surface, $p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$ $p = \frac{0.75 [(4 \times (6.4484 \text{ kipft/ft})) + (3 \times (-0.56847 \text{ kip/ft}) \times (7.25 \text{ ft}))]^2}{(7.25 \text{ ft})^2 [(3 \times (6.4484 \text{ kipft/ft})) + (2 \times (-0.56847 \text{ kip/ft}) \times (7.25 \text{ ft}))]}$ $p = 0.23178 \text{ kip/ft}^2$ s - Earth pressure against the pile at distance L_e, $s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$ $s = \frac{6 \times [(2 \times (6.4484 \text{ kipft/ft})) + ((-0.56847 \text{ kip/ft}) \times (7.25 \text{ ft}))]}{(7.25 \text{ ft})^2}$ $s = 1.0017 \text{ kip/ft}^2$ Check lateral soil pressure capacity: p_a - Allowable lateral soil pressure at depth $a/2$, $p_a = R \frac{a}{2}$ $p_a = (150 \text{ psf/ft}) \times \frac{(5.0138 \text{ ft})}{2}$ $p_a = 0.37604 \text{ kip/ft}^2$ Ratio - Lateral soil capacity $Ratio = \frac{p}{p_a}$ $Ratio = \frac{(0.23178 \text{ kip/ft}^2)}{(0.37604 \text{ kip/ft}^2)}$ $Ratio = 0.61638$ p_s - Allowable lateral soil pressure at depth L_e,	Status: PASS Ratio: 0.620

	$p_s = R L_e$ $p_s = (150 \text{ psf/ft}) \times (7.25 \text{ ft})$ $p_s = 1.0875 \text{ kip/ft}^2$ Ratio - Lateral soil capacity $\text{Ratio} = \frac{s}{p_s}$ $\text{Ratio} = \frac{(1.0017 \text{ kip/ft}^2)}{(1.0875 \text{ kip/ft}^2)}$ $\text{Ratio} = 0.92111$	Status: PASS Ratio: 0.920
	Considering z-direction: $H_o = -0.035828 \text{ kip/ft}$ - Lateral force per length of pile, $M_o = 0.11051 \text{ kipft/ft}$ - Overturning moment per length of pile, a - Distance from resting surface to pivot point, $a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$ $a = \frac{(4 \times (0.11051 \text{ kipft/ft}) \times (7.25 \text{ ft})) + (3 \times (-0.035828 \text{ kip/ft}) \times (7.25 \text{ ft})^2)}{(6 \times (0.11051 \text{ kipft/ft})) + (4 \times (-0.035828 \text{ kip/ft}) \times (7.25 \text{ ft}))}$ $a = 5.2021 \text{ ft}$ p - Earth pressure against the pile at distance $a/2$ from resting surface, $p = \frac{0.75 [(4 M_o) + (3 H_o L_e)]^2}{L_e^3 [(3 M_o) + (2 H_o L_e)]}$ $p = \frac{0.75 \times [(4 \times (0.11051 \text{ kipft/ft})) + (3 \times (-0.035828 \text{ kip/ft}) \times (7.25 \text{ ft}))]^2}{(7.25 \text{ ft})^3 \times [(3 \times (0.11051 \text{ kipft/ft})) + (2 \times (-0.035828 \text{ kip/ft}) \times (7.25 \text{ ft}))]}$ $p = -0.008632 \text{ kip/ft}^2$ s - Earth pressure against the pile at distance L_e, $s = \frac{6 [(2 M_o) + (H_o L_e)]}{L_e^2}$ $s = \frac{6 \times [(2 \times (0.11051 \text{ kipft/ft})) + ((-0.035828 \text{ kip/ft}) \times (7.25 \text{ ft}))]}{(7.25 \text{ ft})^2}$ $s = -0.0044215 \text{ kip/ft}^2$ Check lateral soil pressure capacity: p_a - Allowable lateral soil pressure at depth $a/2$, $p_a = R \frac{a}{2}$ $p_a = (150 \text{ psf/ft}) \times \frac{(5.2021 \text{ ft})}{2}$ $p_a = 0.39016 \text{ kip/ft}^2$ Ratio - Lateral soil capacity $\text{Ratio} = \frac{p}{p_a}$ $\text{Ratio} = \frac{(-0.008632 \text{ kip/ft}^2)}{(0.39016 \text{ kip/ft}^2)}$ $\text{Ratio} = -0.022124$ p_s - Allowable lateral soil pressure at depth L_e, $p_s = R L_e$ $p_s = (150 \text{ psf/ft}) \times (7.25 \text{ ft})$ $p_s = 1.0875 \text{ kip/ft}^2$ Ratio - Lateral soil capacity $\text{Ratio} = \frac{s}{p_s}$	Status: PASS Ratio: -0.020

$$Ratio = \frac{(-0.0044215 \text{ kip/ft}^2)}{(1.0875 \text{ kip/ft}^2)}$$

$$Ratio = -0.0040657$$

Status: **PASS**
Ratio: **0.000**



Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_e}{1.57 D}$$

$$H_o = \frac{(-5.95 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.94745 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_e + (V_e H)}{1.57 D}$$

$$M_o = \frac{(68.239 \text{ kipft}) + ((-5.95 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 10.866 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(10.866 \text{ kipft/ft})}{(-0.94745 \text{ kip/ft})}$$

$$E = 11.469 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (10.866 \text{ kipft/ft}) \times (7.25 \text{ ft})) + (3 \times (-0.94745 \text{ kip/ft}) \times (7.25 \text{ ft})^2)}{(6 \times (10.866 \text{ kipft/ft})) + (4 \times (-0.94745 \text{ kip/ft}) \times (7.25 \text{ ft}))}$$

$$a = 5.0125 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.94745 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (11.469 \text{ ft})}{(7.25 \text{ ft})} + 3 \right) \times \left(\frac{(5.0125 \text{ ft})}{(7.25 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (11.469 \text{ ft})}{(7.25 \text{ ft})} + 2 \right) \times \left(\frac{(5.0125 \text{ ft})}{(7.25 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 13.107 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o D L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.94745 \text{ kip/ft}) \times (48 \text{ in}) \times (7.25 \text{ ft})) \times \left[\left(\frac{(11.469 \text{ ft})}{(7.25 \text{ ft})} + \frac{(5.0125 \text{ ft})}{2 \times (7.25 \text{ ft})} \right) - \left[\left(\frac{4 \times (11.469 \text{ ft})}{(7.25 \text{ ft})} + 3 \right) \times \left(\frac{(5.0125 \text{ ft})}{2 \times (7.25 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (11.469 \text{ ft})}{(7.25 \text{ ft})} + 2 \right) \times \left(\frac{(5.0125 \text{ ft})}{2 \times (7.25 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 45.022 \text{ kipft}$$

Shear force and Bending moment (z-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_z}{1.57 b}$$

$$H_o = \frac{(-0.354 \text{ kip})}{1.57 \times (48 \text{ in})}$$

$$H_o = -0.056369 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_z H)}{1.57 b}$$

$$M_o = \frac{(1.079 \text{ kipft}) + ((-0.354 \text{ kip}) \times (0 \text{ ft}))}{1.57 \times (48 \text{ in})}$$

$$M_o = 0.17182 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(0.17182 \text{ kipft/ft})}{(-0.056369 \text{ kip/ft})}$$

$$E = 3.048 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (0.17182 \text{ kipft/ft}) \times (7.25 \text{ ft})) + (3 \times (-0.056369 \text{ kip/ft}) \times (7.25 \text{ ft})^2)}{(6 \times (0.17182 \text{ kipft/ft})) + (4 \times (-0.056369 \text{ kip/ft}) \times (7.25 \text{ ft}))}$$

$$a = 5.2038 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o b) \left[1 - \left[3 \left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{L_e} \right)^2 \right] + \left[4 \left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{L_e} \right)^3 \right] \right]$$

$$V_{max} = ((-0.056369 \text{ kip/ft}) \times (48 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (3.048 \text{ ft})}{(7.25 \text{ ft})} + 3 \right) \times \left(\frac{(5.2038 \text{ ft})}{(7.25 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (3.048 \text{ ft})}{(7.25 \text{ ft})} + 2 \right) \times \left(\frac{(5.2038 \text{ ft})}{(7.25 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 0.31837 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o b L_e) \left[\left(\frac{E}{L_e} + \frac{a}{2 L_e} \right) - \left[\left(\frac{4 E}{L_e} + 3 \right) \left(\frac{a}{2 L_e} \right)^3 \right] + \left[\left(\frac{3 E}{L_e} + 2 \right) \left(\frac{a}{2 L_e} \right)^4 \right] \right]$$

$$M_{max} = ((-0.056369 \text{ kip/ft}) \times (48 \text{ in}) \times (7.25 \text{ ft})) \times \left[\left(\frac{(3.048 \text{ ft})}{(7.25 \text{ ft})} + \frac{(5.2038 \text{ ft})}{2 \times (7.25 \text{ ft})} \right) - \left[\left(\frac{4 \times (3.048 \text{ ft})}{(7.25 \text{ ft})} + 3 \right) \times \left(\frac{(5.2038 \text{ ft})}{2 \times (7.25 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (3.048 \text{ ft})}{(7.25 \text{ ft})} + 2 \right) \times \left(\frac{(5.2038 \text{ ft})}{2 \times (7.25 \text{ ft})} \right)^4 \right] \right]$$

		$M_{max} = 1.0086 \text{ kipft}$	
		Minimum Reinforcement Check (LRFD) Parameters: $f'_{ck} = 2.5 \text{ ksi}$ - Concrete strength, $f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength, $\phi = 0.65$ - Reduction factor for axial strength, $\alpha = 0.8$ - Alpha factor for axial strength, $A_g = 2304 \text{ in}^2$ - Gross area of concrete, Longitudinal reinforcement: Required reinforcement due to axial load, $A_{st,required}$ $A_{st,required}$ $A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$ $A_{st,required} = \text{Min} \left[\frac{\frac{(10.025 \text{ kip})}{(0.65) \times (0.8)} - (0.85 \times (2.5 \text{ ksi}) \times (2304 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (2.5 \text{ ksi}))}, (0.08 \times (2304 \text{ in}^2)) \right]$ $A_{st,required} = -84.263 \text{ in}^2$ A_{min} - Governing minimum reinforcement area, $A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$ $A_{min} = \text{Max} [(-84.263 \text{ in}^2), (0.0018 \times (2304 \text{ in}^2))]$ $A_{min} = 4.1472 \text{ in}^2$ n_{rebar} - Required number of reinforcement, $n_{rebar} = \frac{A_{min}}{A_{rebar}}$ $n_{rebar} = \frac{(4.1472 \text{ in}^2)}{(0.3068 \text{ in}^2)}$ $n_{rebar} = 14$ A_{st} - Actual total reinforcement area, $A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$ $A_{st} = (14) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$ $A_{st} = 4.2951 \text{ in}^2$ Ratio - Capacity $\text{Ratio} = \frac{A_{min}}{A_{st}}$ $\text{Ratio} = \frac{(4.1472 \text{ in}^2)}{(4.2951 \text{ in}^2)}$ $\text{Ratio} = 0.96556$ 25.2.3 s_{rebar} - Minimum spacing of reinforcement, $s_{rebar} = \text{Max} [1.5, (1.5 d_{bar})]$ $s_{rebar} = \text{Max} [1.5, (1.5 \times (0.625 \text{ in}))]$ $s_{rebar} = 1.5 \text{ in}$ Ties: 25.7.2.2 Since longitudinal reinforcement is $\leq \text{No. } 10\phi$: Use #3(0.375 in) 25.7.2.1 s_{ties} - Maximum spacing of ties, $s_{ties} = \text{Min} [(16 d_{bar}), (48 d_{ties}), \text{Min}(D, b)]$ $s_{ties} = \text{Min} [(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), \text{Min}((48 \text{ in}), (48 \text{ in}))]$ $s_{ties} = 10 \text{ in}$ Summary: Main reinforcement: 14 - #5 (0.625 in)	Status: PASS Ratio: 0.970

	Ties: #3(0.375 in) - 10 in	
22.4.2.2	Axial Compression Strength (ACI 318-19, LRFD) ϕP_N - Allowable axial compressive strength $\phi P_N = \phi 0.80 \left[(0.85 f'_{ck} [A_g - A_{st}]) + (f_{yk} A_{st}) \right]$ $\phi P_N = (0.65) \times 0.80 \times \left[(0.85 \times (2.5 \text{ ksi}) \times [(2304 \text{ in}^2) - (4.2951 \text{ in}^2)]) + ((60 \text{ ksi}) \times (4.2951 \text{ in}^2)) \right]$ $\phi P_N = 2675.2 \text{ kip}$ Ratio - Capacity $\text{Ratio} = \frac{P}{\phi P_N}$ $\text{Ratio} = \frac{(10.025 \text{ kip})}{(2675.2 \text{ kip})}$ $\text{Ratio} = 0.0037474$	Status: PASS Ratio: 0.000
22.5.2.2	Shear Strength (ACI 318-19, LRFD) Parameters: $b_w = 48 \text{ in}$ - Effective width, d - Effective depth $d = 0.80 D$ $d = 0.80 \times (48 \text{ in})$ $d = 38.4 \text{ in}$	
22.5.5.1.3	λ_s - size effect modification factor $\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$ $\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{(38.4 \text{ in})}{10}}}, 1 \right]$ $\lambda_s = 0.64282$	
22.5.5.1.1	The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $V_{c,max}$ - Max shear strength of concrete $V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$ $V_{c,max} = 5 \times (0.64282) \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{c,max} = 296.21 \text{ kip}$	
22.5.5.1.1(a)	The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $P = 10.025 \text{ kip} \rightarrow 10025 \text{ lbf}$, $V_{c,a}$ - Shear strength of concrete (a) $V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck}} + \frac{P}{6 A_g} \right] b_w d$ $V_{c,a} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi})} + \frac{(10025 \text{ lbf})}{6 \times (2304 \text{ in}^2)} \right] \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{c,a} = 119.82 \text{ kip}$	
22.5.5.1.2	The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $V_{c,b}$ - Shear strength of concrete (b) $V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck}} + (0.05 f'_{ck}) \right] b_w d$ $V_{c,b} = \left[2 \times (0.64282) \times \sqrt{(2500 \text{ psi})} + (0.05 \times (2500 \text{ psi})) \right] \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{c,b} = 348.89 \text{ kip}$ V_c - Governing shear strength of concrete $V_c = \text{Min} [V_{c,max}, V_{c,a}, V_{c,b}]$ $V_c = \text{Min} [(296.21 \text{ kip}), (119.82 \text{ kip}), (348.89 \text{ kip})]$ $V_c = 119.82 \text{ kip}$	

22.5.1.2 22.5.8.5.3 22.5.1.1	The following variables were converted to be consistent with empirical formula $f'_{ck} = 2.5 \text{ ksi} \rightarrow 2500 \text{ psi}$, $V_{s,a}$ - Shear strength of steel (a) $V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$ $V_{s,a} = 8 \times \sqrt{(2500 \text{ psi})} \times (48 \text{ in}) \times (38.4 \text{ in})$ $V_{s,a} = 737.28 \text{ kip}$ A_v - Ties rebar area, $A_v = \frac{\pi d_{tes}^2}{4}$ $A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$ $A_v = 0.11045 \text{ in}^2$ $V_{s,b}$ - Shear strength of steel (b) $V_{s,b} = \frac{2 A_v f_{ysk} d}{s_{ties}}$ $V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (38.4 \text{ in})}{(10 \text{ in})}$ $V_{s,b} = 50.894 \text{ kip}$ V_s - Governing shear strength of steel $V_s = MIN[V_{s,a}, V_{s,b}]$ $V_s = MIN[(737.28 \text{ kip}), (50.894 \text{ kip})]$ $V_s = 50.894 \text{ kip}$ ϕV_n - Allowable shear strength $\phi V_n = \phi (V_c + V_s)$ $\phi V_n = (0.65) \times ((119.82 \text{ kip}) + (50.894 \text{ kip}))$ $\phi V_n = 110.97 \text{ kip}$ Considering x-direction: $V_{max} = 13.107 \text{ kip}$ - Maximum shear force in the x-direction, <i>Ratio</i> - Capacity $Ratio = \frac{V_{max}}{\phi V_n}$ $Ratio = \frac{(13.107 \text{ kip})}{(110.97 \text{ kip})}$ $Ratio = 0.11812$ Considering z-direction: $V_{max} = 0.31837 \text{ kip}$ - Maximum shear force in the z-direction, <i>Ratio</i> - Capacity $Ratio = \frac{V_{max}}{\phi V_n}$ $Ratio = \frac{(0.31837 \text{ kip})}{(110.97 \text{ kip})}$ $Ratio = 0.0028691$	Status: PASS Ratio: 0.120 Status: PASS Ratio: 0.000
	Flexural Strength (ACI 318-19, LRFD) S_m - Section modulus $S_m = \frac{b D^3}{6}$ $S_m = \frac{(48 \text{ in}) \times (48 \text{ in})^2}{6}$ $S_m = 18432 \text{ in}^3$	

14.5.2.1b	$\lambda = 1$ - Concrete modification factor (Normal concrete), Allowable flexural strength: M_n shall be the lesser of: $\phi M_{n,1}$ $\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$ $\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{2.5 \text{ ksi}} \times 18432.001 \text{ in}^3$ $\phi M_{n,1} = 249.600 \text{ kipft}$ $\phi M_{n,2}$ $\phi M_{n,2} = \phi \times 0.85 \times f'_{ck} \times S_m$ $\phi M_{n,2} = (0.65) \times 0.85 \times (2.5 \text{ ksi}) \times (18432 \text{ in}^3)$ $\phi M_{n,2} = 2121.6 \text{ kipft}$ Therefore, ϕM_n - Allowable flexural strength, $\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$ $\phi M_n = \text{MIN}[(249.6 \text{ kipft}), (2121.6 \text{ kipft})]$ $\phi M_n = 249.6 \text{ kipft}$ Considering x-direction: $M_{max} = 45.022 \text{ kipft}$ - Maximum moment in the x-direction, Ratio - Capacity $\text{Ratio} = \frac{M_{max}}{\phi M_n}$ $\text{Ratio} = \frac{(45.022 \text{ kipft})}{(249.6 \text{ kipft})}$ $\text{Ratio} = 0.18038$	Status: PASS Ratio: 0.180
	Considering z-direction: $M_{max} = 1.0086 \text{ kipft}$ - Maximum moment in the z-direction, Ratio - Capacity $\text{Ratio} = \frac{M_{max}}{\phi M_n}$ $\text{Ratio} = \frac{(1.0086 \text{ kipft})}{(249.6 \text{ kipft})}$ $\text{Ratio} = 0.0040409$	Status: PASS Ratio: 0.000