

Your Project Calculations



Project Name: CabinPower-RevA

S3D Model Link:

https://platform.skyciv.com/structural?preload_name=CabinPower-RevA&preload_path=Shared%20Enterprise%20Folder/MT_Solar_Projects/5_2023

Public Model Link:

https://platform.skyciv.com/structural-viewer?project_id=OKuzheGYVRNawi7EoksCn35FGZApj3vxzK32ftA5iP5pqrnWWPvFoDbj4WMBRqF

Array Specification

Product:	Beam
Unique ID:	1P-0-6TOP-SD-12-L-5Hx2W-99K2
Duty Classification:	SD
Module Width:	39.21 in
Module Length:	65.24in
Number of Rows:	5
Number of Columns:	2
Total Number of Modules:	10
Desired Tilt Angle:	45
Front Edge Clearance:	6
Total Array Height at Tilt:	17.63 ft
Total Frame Length:	9.50 ft
Frame Weight:	660 lbs
Array Dimensions N/S:	16.55 ft
Array Dimensions E/W:	11.04 ft
Rail Length:	198.55 in
Rail Spacing:	2.76 ft
Rail Check:	PASS (94% utilized)

Support Specifications

Pole Size:	6in Pipe Sch 80
Pole Length above Grade:	11.85 ft
Number of Poles:	1
Pole Spacing:	0

Foundation Specifications

Foundation Type:	Round
Foundation Dimensions:	Ø36 in
Foundation Depth (below grade):	Pile 1: 9.50 ft
Foundation Volume:	2.487 y ³
Foundation Result:	PASSED
Mount Twist:	0.000003 kip

Site Info

Risk Category:	I
Exposure:	C
Soil Classification:	sand
Site Location:	513 US-1, Hodgdon, ME 04730, USA
Wind Speed:	95 mph
Snow Load:	100 psf
Design Uplift Pressure:	Multiple pressures
Design Downforce Pressure:	Multiple pressures
Design Snow Pressure:	0.027491 ksf



Design Disclaimer


This software should be used for preliminary designs and should not be used as a final design unless reviewed, verified and designed by a qualified structural engineer.



AutoDesigner Input



```
{
  "wind_speed_override": null,
  "snow_load_override": null,
  "direct_snow_load": false,
  "product_type": "Beam",
  "project_id": "CabinPower-RevA",
  "site_address": "513 US-1, Hodgdon, ME 04730, USA",
  "module_width": 39.21,
  "module_length": 65.24,
  "number_rows": 5,
  "number_columns": 2,
  "pole_mount_section": "4_40",
  "core_pipe_width": 65,
  "core_pipe_section": "2_40",
  "adjuster_section": "2_40",
  "core_beam_height": 65,
  "core_beam_section": "HSS3x2x1/8",
  "main_pipe_section": "2_12GA",
  "pole_spacing": 15,
  "tilt_angle": 45,
  "ground_clearance": 6,
  "risk_category": "I",
  "exposure_category": "C",
  "frame_duty_override": "auto",
  "pole_override": "auto",
  "soil_type": "sand",
  "foundation_type": "Round",
  "foundation_size": 36,
  "check_rails": true
}
```

Design Notes:

- AISC Deflection checks are set to L/1 due to structure design intent








Rail Design Check

Rail Length: 16.545833333333334 ft
Additional Restraints Required: None
Tributary Width: 2.76 ft
Material: Aluminium
Density: 169 lb/ft³
Elasticity Modulus: 10000 ksi
Fy: 34.5 ksi
Fu: 37 ksi
Snow (X): 0.0537 kip/ft
Snow (Y): -0.0537 kip/ft
Wind uplift Case A: 0.0690 kip/ft
Wind uplift Case A: 0.0690 kip/ft
Wind uplift Case B (X): 0.0000 kip/ft
Wind uplift Case B (Y): 0.0882 kip/ft







Result Check	Max Limit	Max Value	Utility	Status
Custom Stress Limit	34.5	32.44956126	0.941	PASS
Material Yield	34.5	32.44956126	0.941	PASS
Material Strength	37	32.44956126	0.877	PASS


Member 1, ULS: 1. 1.4D



FEM Results (Envelope Worst Case for each member)







Reaction Forces for Foundation 1 (Node ID#1), (kip, kip-ft)

ASD Load Combination Results

Name	Fx	Fy	Fz	Mx	My	Mz
ULS: 1. D	0.0000	1.5110	-0.0000	-0.0000	0.0000	0.0161
ULS: 2. D + L	0.0000	1.5110	-0.0000	-0.0000	0.0000	0.0161
ULS: 3. D + (S or Lr or R)	-0.0000	4.5665	0.0000	-0.0000	0.0000	0.0335
ULS: 3. D + (S or Lr or R)	0.0000	1.5110	-0.0000	-0.0000	0.0000	0.0161
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	-0.0000	3.8027	0.0000	-0.0000	0.0000	0.0291
ULS: 4. D + 0.75L + 0.75(S or Lr or R)	0.0000	1.5110	-0.0000	-0.0000	0.0000	0.0161
ULS: 5b. D + 0.7E	0.0000	1.5110	-0.0000	-0.0000	0.0000	0.0161
ULS: 6b. D + 0.75L + 0.75(0.7)E + 0.75S	-0.0000	3.8027	0.0000	-0.0000	0.0000	0.0291
ULS: 8. 0.6D + 0.7E	0.0000	0.9066	-0.0000	-0.0000	0.0000	0.0097
ULS: 5a. D + 0.6W_Wind downforce Case A only	-2.5304	4.0414	-0.0000	-0.0000	0.0000	31.6366
ULS: 5a. D + 0.6W_Wind downforce Case B only	-2.5304	4.0414	-0.0000	-0.0000	0.0000	31.6366
ULS: 5a. D + 0.6W_Wind uplift Case A only	1.8305	-0.3195	-0.0000	-0.0000	0.0000	-20.7463
ULS: 5a. D + 0.6W_Wind uplift Case B only	1.6151	-0.1041	0.0000	-0.0000	0.0000	-23.2968
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-1.8978	5.7004	0.0000	-0.0000	0.0000	23.7445
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-1.8978	5.7004	0.0000	-0.0000	0.0000	23.7445
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.3729	2.4298	-0.0000	-0.0000	0.0000	-15.5427
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.2113	2.5913	0.0000	-0.0000	0.0000	-17.4556
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case A only	-1.8978	3.4088	-0.0000	-0.0000	0.0000	23.7315
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind downforce Case B only	-1.8978	3.4088	-0.0000	-0.0000	0.0000	23.7315
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case A only	1.3729	0.1382	-0.0000	-0.0000	0.0000	-15.5557
ULS: 6a. D + 0.75L + 0.75(0.6)W + 0.75(S or Lr or R)_Wind uplift Case B only	1.2113	0.2997	0.0000	-0.0000	0.0000	-17.4686
ULS: 7. 0.6D + 0.6W_Wind downforce Case A only	-2.5304	3.4370	-0.0000	-0.0000	0.0000	31.6302
ULS: 7. 0.6D + 0.6W_Wind downforce Case B only	-2.5304	3.4370	-0.0000	-0.0000	0.0000	31.6302
ULS: 7. 0.6D + 0.6W_Wind uplift Case A only	1.8305	-0.9239	-0.0000	-0.0000	0.0000	-20.7527
ULS: 7. 0.6D + 0.6W_Wind uplift Case B only	1.6151	-0.7085	0.0000	-0.0000	0.0000	-23.3033

Worst Case Reactions LRFD

These calculations are taken directly from the FEA via SkyCiv and are used in the Concrete Checks of the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	8.8107
Shear X	-4.2173
Shear Z	0.0000
Moment X	-0.0000
Moment Y (Twist)	0.0000
Moment Z	53.8681

Worst Case Reactions ASD

These results are taken from the worst case values in the above table and are used in the Soil Checks in the Foundation Module.
Note: Worst case values are assumed as downforce wind load cases.

Result	Value (kip, kip-ft)
Axial	5.7004
Shear X	-2.5304
Shear Z	-0.0000
Moment X	-0.0000
Moment Y (Twist)	0.0000
Moment Z	31.6366

Project Details

Design Code: AISC 360-16 LRFD
 Provision: LRFD
 Country: United States

User Name: sales@mtsolar.us
 Project Name: CabinPower-RevA
 Unit System: imperial



Design Input Information

Design Factors			
Φ_t	Φ_c	Φ_b	Φ_v
0.9	0.9	0.9	0.9

Design Materials			
ID	E (ksi)	F _y (ksi)	F _u (ksi)
1	29000	50	65

Section Dimensions							

ID	Name	d (in)	t _w (in)				
1	2in Pipe Sch 40	2.38	0.15				
4	4in Pipe Sch 40	4.50	0.24				
8	6in Pipe Sch 80	6.63	0.43				

Section Dimensions							

ID	Name	d (in)	b (in)	t _w (in)	t _b (in)	r (in)	
15	HSS5x3x1/8	5.00	3.00	0.12	0.12	0.12	

Section Dimensions							

ID	Name	d (in)	t _w (in)	b _t (in)	b _b (in)	t _t (in)	t _b (in)	r (in)
18	W6x9	5.90	0.17	3.94	3.94	0.21	0.21	0.25

Section Properties								
ID	Name	A (in ²)	J (in ⁴)	I _{yp} (in ⁴)	I _{zp} (in ⁴)	I _w (in ⁶)	S _{yp} (in ³)	S _{zp} (in ³)
1	2in Pipe Sch 40	1.07	1.33	0.67	0.67	0.00	0.76	0.76
4	4in Pipe Sch 40	3.17	14.47	7.23	7.23	0.00	4.31	4.31

10	79.65	72.01	10.99	4.60	29.14	16.61
11	120.60	113.97	23.36	6.45	30.09	45.74
12	142.83	141.72	16.17	16.17	42.85	42.85
13	120.60	98.23	20.07	6.45	30.09	45.74
14	120.60	98.23	17.78	6.45	30.09	45.74
15	120.60	113.97	23.36	6.45	30.09	45.74
16	120.60	113.97	23.36	6.45	30.09	45.74

Design Ratio


Member ID	P	M _z	M _y	V _y	V _z	(P,M _z ,M _y)	Worst LC	KL/r	δ	Status
1	0.086	0.866	0.000	0.037	0.000	0.902	#13	0.680	Not Required	Pass
2	0.003	0.410	0.251	0.098	0.049	0.618	#13	0.052	Not Required	Pass
3	0.015	0.720	0.213	0.072	0.044	0.875	#21	0.044	Not Required	Pass
4	0.014	0.652	0.133	0.065	0.017	0.756	#21	0.078	Not Required	Pass
5	0.015	0.447	0.092	0.072	0.010	0.454	#13	0.073	Not Required	Pass
6	0.015	0.720	0.213	0.072	0.044	0.875	#21	0.044	Not Required	Pass
7	0.015	0.447	0.092	0.072	0.010	0.454	#13	0.073	Not Required	Pass
8	0.000	0.008	0.018	0.013	0.005	0.026	#21	Not Required	Not Required	Pass
9	0.011	0.043	0.046	0.001	0.000	0.091	#13	0.132	Not Required	Pass
10	0.014	0.652	0.133	0.065	0.017	0.756	#21	0.078	Not Required	Pass
11	0.000	0.009	0.018	0.015	0.005	0.026	#21	Not Required	Not Required	Pass
12	0.003	0.410	0.251	0.098	0.049	0.618	#13	0.052	Not Required	Pass
13	0.001	0.098	0.134	0.040	0.014	0.207	#21	0.177	Not Required	Pass
14	0.003	0.095	0.134	0.036	0.014	0.203	#21	0.177	Not Required	Pass
15	0.000	0.009	0.018	0.015	0.005	0.026	#21	Not Required	Not Required	Pass
16	0.000	0.008	0.018	0.013	0.005	0.026	#21	Not Required	Not Required	Pass

Definitions

Φ _t	Safety factor for tensile
Φ _c	Safety factor for compression
Φ _b	Safety factor for flexure
Φ _v	Safety factor for shear
E	Modulus of elasticity
F _y	Specified minimum yield stress
F _u	Specified minimum tensile strength
A	Cross-sectional area
J	Torsional constant
I _{yp}	Moment of inertia about the Y axes
I _{zp}	Moment of inertia about the Z axes
I _w	Warping constant
S _{yp}	Plastic section modulus about the Y axis
S _{zp}	Plastic section modulus about the Z axis
KL	Effective length
C _b	Buckling modification factor (from all load combinations)
L _b	Length between braced points
LST	Limited slenderness for tension
LSC	Limited slenderness for compression
LD	Limited deflection
P _n	Nominal axial strength (tension/compression)
M _n	Nominal flexural strength (about Z/Y axis)
V _n	Nominal shear strength (along Z/Y axis)
P	Design ratio in case of axial force
M _z	Design ratio in case of bending about Z axis
M _y	Design ratio in case of bending about Y axis
V _y	Design ratio in case of shear along Y axis
V _z	Design ratio in case of shear along Z axis
(P,M _z ,M _y)	Design ratio in case of axial force and bending action
KL/r	Design ratio in case of section slenderness
δ	Design ratio in case of member deflection
OK	Capacity is provided

ON
NG

Capacity is provided
Capacity is not provided

REFERENCES	CALCULATIONS	RESULTS																										
	<p>SkyCiv Foundation Design Pile Foundation</p> <p>Design Information : Design code : IBC 2021 (International Building Code) Unit System : Imperial</p>																											
	<p>Pile Input</p>  <p>Geometry Pile shape: round $D = 36$ in - Pile diameter $L = 9.5$ ft - Total pile length $h_1 = 0$ ft - Lateral load height from the top of the pile, $h_2 = 0$ ft - Depth to resting surface $h_e = 0$ ft - Length of pile above the ground</p> <p>Tabulation of Soil Parameters</p> <table border="1" data-bbox="416 1077 1193 1171"> <thead> <tr> <th>Layer</th> <th>Label</th> <th>Allowable Bearing Pressure (q_a) (psf)</th> <th>Allowable Lateral Pressure (R) (psf/ft)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Sand, silty sand, clayey sand, silty gravel & clayey gravel</td> <td>2000.000</td> <td>150.000</td> </tr> </tbody> </table> <p>Tabulation of Loads</p> <table border="1" data-bbox="676 1263 935 1435"> <thead> <tr> <th>Load Component</th> <th>ASD</th> <th>LRFD</th> </tr> </thead> <tbody> <tr> <td>P (kip)</td> <td>5.700</td> <td>8.811</td> </tr> <tr> <td>V_x (kip)</td> <td>-2.530</td> <td>-4.217</td> </tr> <tr> <td>V_z (kip)</td> <td>0.000</td> <td>0.000</td> </tr> <tr> <td>M_x (kipft)</td> <td>0.000</td> <td>0.000</td> </tr> <tr> <td>M_z (kipft)</td> <td>31.637</td> <td>53.868</td> </tr> </tbody> </table> <p>Material Properties $f'_{ck} = 3$ ksi - Concrete strength,</p>	Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)	1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000	Load Component	ASD	LRFD	P (kip)	5.700	8.811	V_x (kip)	-2.530	-4.217	V_z (kip)	0.000	0.000	M_x (kipft)	0.000	0.000	M_z (kipft)	31.637	53.868	
Layer	Label	Allowable Bearing Pressure (q_a) (psf)	Allowable Lateral Pressure (R) (psf/ft)																									
1	Sand, silty sand, clayey sand, silty gravel & clayey gravel	2000.000	150.000																									
Load Component	ASD	LRFD																										
P (kip)	5.700	8.811																										
V_x (kip)	-2.530	-4.217																										
V_z (kip)	0.000	0.000																										
M_x (kipft)	0.000	0.000																										
M_z (kipft)	31.637	53.868																										
	<p>Required depth to resist lateral loads (ASD) H - Point of application of the lateral load</p> $H = h_1 + h_2 + h_e$ $H = (0 \text{ ft}) + (0 \text{ ft}) + (0 \text{ ft})$ $H = 0 \text{ ft}$ <p>Considering x-direction: H_o - Lateral force per length of pile,</p> $H_o = \frac{V_x}{D}$ $H_o = \frac{(-2.53 \text{ kip})}{(36 \text{ in})}$ $H_o = -0.84333 \text{ kip/ft}$ <p>M_o - Moment per length of pile,</p> $M_o = \frac{M_x + (V_x H)}{D}$																											

	$M_o = \frac{(31.637 \text{ kipft}) + ((-2.53 \text{ kip}) \times (0 \text{ ft}))}{(36 \text{ in})}$ $M_o = 10.546 \text{ kipft/ft}$ <p>Required depth of embedment in earth:</p> $L_x^3 - \left(14.14 \times \frac{H_o \times L_x}{R}\right) - \left(18.85 \times \frac{M_o}{R}\right) = 0$ <p>Solving the cubic equation: $L_{e,x} = 8.6182 \text{ ft}$ - Required depth in x-direction,</p> <p>Considering z-direction: $L_{e,z} = 0 \text{ ft}$ - Required depth in z-direction,</p> <p>Minimum embedded depth required: $L_{e,req}$ - Depth of pile required,</p> $L_{e,req} = \text{MAX}[L_{e,x}, L_{e,z}]$ $L_{e,req} = \text{MAX}[(8.6182 \text{ ft}), (0 \text{ ft})]$ $L_{e,req} = 8.618 \text{ ft}$ <p>L_e - Actual embedded length of pile,</p> $L_e = L - h_c - h_2$ $L_e = (9.5 \text{ ft}) - (0 \text{ ft}) - (0 \text{ ft})$ $L_e = 9.5 \text{ ft}$ <p>Ratio - Embedded depth</p> $\text{Ratio} = \frac{L_{e,req}}{L_e}$ $\text{Ratio} = \frac{(8.618 \text{ ft})}{(9.5 \text{ ft})}$ $\text{Ratio} = 0.90716$	<p>Status: PASS Ratio: 0.910</p>
	<p>End-bearing Capacity (ASD)</p> <p>A - Pile cross-section area</p> $A = \pi \left(\frac{D}{2}\right)^2$ $A = \pi \times \left(\frac{(36 \text{ in})}{2}\right)^2$ $A = 7.0686 \text{ ft}^2$ <p>q - End-bearing pressure</p> $q = \frac{P_c}{A}$ $q = \frac{(5.7 \text{ kip})}{(7.0686 \text{ ft}^2)}$ $q = 0.80639 \text{ kip/ft}^2$ <p>Check bearing capacity ratio:</p> <p>Ratio - Capacity</p> $\text{Ratio} = \frac{q}{q_a}$ $\text{Ratio} = \frac{(0.80639 \text{ kip/ft}^2)}{(2000 \text{ psf})}$ $\text{Ratio} = 0.40319$	<p>Status: PASS Ratio: 0.400</p>
Czerniak	<p>Lateral Soil Pressure (ASD):</p> <p>L/D - Length to least lateral dimension ratio,</p> $L/D = \frac{L}{D}$ $L/D = \frac{(9.5 \text{ ft})}{(36 \text{ in})}$	

$$L/D = 3.1667$$

Since $L/D \leq 10$,

Pile is short.

Considering x-direction:

$H_o = -0.84333$ kip/ft - Lateral force per length of pile,

$M_o = 10.546$ kipft/ft - Overturning moment per length of pile,

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_e) + (3 H_o L_e^2)}{(6 M_o) + (4 H_o L_e)}$$

$$a = \frac{(4 \times (10.546 \text{ kipft/ft}) \times (9.5 \text{ ft})) + (3 \times (-0.84333 \text{ kip/ft}) \times (9.5 \text{ ft})^2)}{(6 \times (10.546 \text{ kipft/ft})) + (4 \times (-0.84333 \text{ kip/ft}) \times (9.5 \text{ ft}))}$$

$$a = 6.5995 \text{ ft}$$

p - Earth pressure against the pile at distance $a/2$ from resting surface,

$$p = \frac{1.178 [(4 M_o) + (3 H_o L_e)]^2}{L_e^2 [(3 M_o) + (2 H_o L_e)]}$$

$$p = \frac{1.178 \times [(4 \times (10.546 \text{ kipft/ft})) + (3 \times (-0.84333 \text{ kip/ft}) \times (9.5 \text{ ft}))]^2}{(9.5 \text{ ft})^2 \times [(3 \times (10.546 \text{ kipft/ft})) + (2 \times (-0.84333 \text{ kip/ft}) \times (9.5 \text{ ft}))]}$$

$$p = 0.27532 \text{ kip/ft}^2$$

s - Earth pressure against the pile at distance L_e ,

$$s = \frac{9.425 [(2 M_o) + (H_o L_e)]}{L_e^2}$$

$$s = \frac{9.425 \times [(2 \times (10.546 \text{ kipft/ft})) + ((-0.84333 \text{ kip/ft}) \times (9.5 \text{ ft}))]}{(9.5 \text{ ft})^2}$$

$$s = 1.3659 \text{ kip/ft}^2$$

Check lateral soil pressure capacity:

p_a - Allowable lateral soil pressure at depth $a/2$,

$$p_a = R \frac{a}{2}$$

$$p_a = (150 \text{ psf/ft}) \times \frac{(6.5995 \text{ ft})}{2}$$

$$p_a = 0.49496 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity

$$\text{Ratio} = \frac{p}{p_a}$$

$$\text{Ratio} = \frac{(0.27532 \text{ kip/ft}^2)}{(0.49496 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.55624$$

p_s - Allowable lateral soil pressure at depth L_e ,

$$p_s = R L_e$$

$$p_s = (150 \text{ psf/ft}) \times (9.5 \text{ ft})$$

$$p_s = 1.425 \text{ kip/ft}^2$$

Ratio - Lateral soil capacity


$$\text{Ratio} = \frac{s}{p_s}$$


$$\text{Ratio} = \frac{(1.3659 \text{ kip/ft}^2)}{(1.425 \text{ kip/ft}^2)}$$

$$\text{Ratio} = 0.95855$$

Status: **PASS**
Ratio: **0.560**

Status: **PASS**
Ratio: **0.960**





Shear force and Bending moment (x-direction, LRFD)

H_o - Lateral force per length of pile,

$$H_o = \frac{V_x}{D}$$

$$H_o = \frac{(-4.217 \text{ kip})}{(36 \text{ in})}$$

$$H_o = -1.4057 \text{ kip/ft}$$

M_o - Moment per length of pile,

$$M_o = \frac{M_x + (V_x H)}{D}$$

$$M_o = \frac{(53.868 \text{ kipft}) + ((-4.217 \text{ kip}) \times (0 \text{ ft}))}{(36 \text{ in})}$$

$$M_o = 17.956 \text{ kipft/ft}$$

E - Distance from lateral load to resisting surface,

$$E = \frac{M_o}{H_o}$$

$$E = \frac{(17.956 \text{ kipft/ft})}{(-1.4057 \text{ kip/ft})}$$

$$E = 12.774 \text{ ft}$$

a - Distance from resting surface to pivot point,

$$a = \frac{(4 M_o L_c) + (3 H_o L_c^2)}{(6 M_o) + (4 H_o L_c)}$$

$$a = \frac{(4 \times (17.956 \text{ kipft/ft}) \times (9.5 \text{ ft})) + (3 \times (-1.4057 \text{ kip/ft}) \times (9.5 \text{ ft})^2)}{(6 \times (17.956 \text{ kipft/ft})) + (4 \times (-1.4057 \text{ kip/ft}) \times (9.5 \text{ ft}))}$$

$$a = 6.5957 \text{ ft}$$

V_{max} - Max shear force located at depth a ,

$$V_{max} = (H_o D) \left[1 - \left[3 \left(\frac{4 E}{L_c} + 3 \right) \left(\frac{a}{L_c} \right)^2 \right] + \left[4 \left(\frac{3 E}{L_c} + 2 \right) \left(\frac{a}{L_c} \right)^3 \right] \right]$$

$$V_{max} = ((-1.4057 \text{ kip/ft}) \times (36 \text{ in})) \times \left[1 - \left[3 \times \left(\frac{4 \times (12.774 \text{ ft})}{(9.5 \text{ ft})} + 3 \right) \times \left(\frac{(6.5957 \text{ ft})}{(9.5 \text{ ft})} \right)^2 \right] + \left[4 \times \left(\frac{3 \times (12.774 \text{ ft})}{(9.5 \text{ ft})} + 2 \right) \times \left(\frac{(6.5957 \text{ ft})}{(9.5 \text{ ft})} \right)^3 \right] \right]$$

$$V_{max} = 12.814 \text{ kip}$$

M_{max} - Max bending moment located at depth $a/2$,

$$M_{max} = (H_o D L_c) \left[\left(\frac{E}{L_c} + \frac{a}{2 L_c} \right) - \left[\left(\frac{4 E}{L_c} + 3 \right) \left(\frac{a}{2 L_c} \right)^3 \right] + \left[\left(\frac{3 E}{L_c} + 2 \right) \left(\frac{a}{2 L_c} \right)^4 \right] \right]$$

$$M_{max} = ((-1.4057 \text{ kip/ft}) \times (36 \text{ in}) \times (9.5 \text{ ft})) \times \left[\left(\frac{(12.774 \text{ ft})}{(9.5 \text{ ft})} + \frac{(6.5957 \text{ ft})}{2 \times (9.5 \text{ ft})} \right) - \left[\left(\frac{4 \times (12.774 \text{ ft})}{(9.5 \text{ ft})} + 3 \right) \times \left(\frac{(6.5957 \text{ ft})}{2 \times (9.5 \text{ ft})} \right)^3 \right] + \left[\left(\frac{3 \times (12.774 \text{ ft})}{(9.5 \text{ ft})} + 2 \right) \times \left(\frac{(6.5957 \text{ ft})}{2 \times (9.5 \text{ ft})} \right)^4 \right] \right]$$

$$M_{max} = 57.244 \text{ kipft}$$

Minimum Reinforcement Check (LRFD)

Parameters:

$f'_{ck} = 3 \text{ ksi}$ - Concrete strength,
 $f_{yk} = 60 \text{ ksi}$ - Longitudinal reinforcement strength,
 $\phi = 0.65$ - Reduction factor for axial strength,
 $\alpha = 0.85$ - Alpha factor for axial strength,
 $A_g = 1017.9 \text{ in}^2$ - Gross area of concrete,

Table 22.4.2.1

Longitudinal reinforcement:

Required reinforcement due to axial load, $A_{st,required}$

22.4.2.2, 10.6.1.1

$A_{st,required}$

$$A_{st,required} = \text{Min} \left[\frac{\frac{P}{\phi \alpha} - (0.85 f'_{ck} A_g)}{f_{yk} - (0.85 f'_{ck})}, (0.08 A_g) \right]$$

$$A_{st,required} = \text{Min} \left[\frac{\frac{(8.811 \text{ kip})}{(0.65) \times (0.85)} - (0.85 \times (3 \text{ ksi}) \times (1017.9 \text{ in}^2))}{(60 \text{ ksi}) - (0.85 \times (3 \text{ ksi}))}, (0.08 \times (1017.9 \text{ in}^2)) \right]$$

$$A_{st,required} = -44.902 \text{ in}^2$$

A_{min} - Governing minimum reinforcement area,

$$A_{min} = \text{Max} [A_{st,required}, (0.0018 A_g)]$$

$$A_{min} = \text{Max} [(-44.902 \text{ in}^2), (0.0018 \times (1017.9 \text{ in}^2))]$$

$$A_{min} = 1.8322 \text{ in}^2$$

n_{rebar} - Required number of reinforcement,

$$n_{rebar} = \frac{A_{min}}{A_{rebar}}$$

$$n_{rebar} = \frac{(1.8322 \text{ in}^2)}{(0.3068 \text{ in}^2)}$$

$$n_{rebar} = 6$$

A_{st} - Actual total reinforcement area,

$$A_{st} = n_{rebar} \frac{\pi d_{bar}^2}{4}$$

$$A_{st} = (6) \times \frac{\pi \times (0.625 \text{ in})^2}{4}$$

$$A_{st} = 1.8408 \text{ in}^2$$

Ratio - Capacity

$$\text{Ratio} = \frac{A_{min}}{A_{st}}$$

$$\text{Ratio} = \frac{(1.8322 \text{ in}^2)}{(1.8408 \text{ in}^2)}$$

$$\text{Ratio} = 0.99533$$

25.2.3

s_{rebar} - Minimum spacing of reinforcement,

$$s_{rebar} = \text{Max} [1.5, (1.5 d_{bar})]$$

$$s_{rebar} = \text{Max} [1.5, (1.5 \times (0.625 \text{ in}))]$$

$$s_{rebar} = 1.5 \text{ in}$$

Ties:

25.7.2.2

Since longitudinal reinforcement is \leq No. 10Ø: Use #3(0.375 in)

25.7.2.1

s_{ties} - Maximum center-to-center spacing of ties,

$$s_{ties} = \text{Min} [(16 d_{bar}), (48 d_{ties}), D]$$

$$s_{ties} = \text{Min} [(16 \times (0.625 \text{ in})), (48 \times (0.375 \text{ in})), (36 \text{ in})]$$

$$s_{ties} = 10 \text{ in}$$

Summary:

Status: **PASS**
Ratio: **1.000**

Main reinforcement: **6 - #5 (0.625 in)**
Ties: **#3(0.375 in) - 10 in**

Axial Compression Strength (ACI 318-19, LRFD)

22.4.2.2 ϕP_N - Allowable axial compressive strength

$$\phi P_N = \phi \cdot 0.85 \left[(0.85 f'_{ck} [A_g - A_{st}]) + (f_{yk} A_{st}) \right]$$

$$\phi P_N = (0.65) \times 0.85 \times \left[(0.85 \times (3 \text{ ksi}) \times [(1017.9 \text{ in}^2) - (1.8408 \text{ in}^2)]) + ((60 \text{ ksi}) \times (1.8408 \text{ in}^2)) \right]$$

$$\phi P_N = 1492.5 \text{ kip}$$

Ratio - Capacity

$$\text{Ratio} = \frac{P}{\phi P_N}$$

$$\text{Ratio} = \frac{(8.811 \text{ kip})}{(1492.5 \text{ kip})}$$

$$\text{Ratio} = 0.0059036$$

Status: **PASS**
Ratio: **0.010**

Shear Strength (ACI 318-19, LRFD)

Parameters:

$b_w = 36 \text{ in}$ - Effective width,
22.5.2.2 d - Effective depth

$$d = 0.80 D$$

$$d = 0.80 \times (36 \text{ in})$$

$$d = 28.8 \text{ in}$$

22.5.5.1.3 λ_s - size effect modification factor

$$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{d}{10}}}, 1 \right]$$

$$\lambda_s = \text{MIN} \left[\sqrt{\frac{2}{1 + \frac{(28.8 \text{ in})}{10}}}, 1 \right]$$

$$\lambda_s = 0.71796$$

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$.

22.5.5.1.1 $V_{c,max}$ - Max shear strength of concrete

$$V_{c,max} = 5 \lambda_s \sqrt{f'_{ck}} b_w d$$

$$V_{c,max} = 5 \times (0.71796) \times \sqrt{(3000 \text{ psi})} \times (36 \text{ in}) \times (28.8 \text{ in})$$

$$V_{c,max} = 203.86 \text{ kip}$$

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$, $P = 8.811 \text{ kip} \rightarrow 8811 \text{ lbf}$.

22.5.5.1.1(a) $V_{c,a}$ - Shear strength of concrete (a)

$$V_{c,a} = \left[2 \lambda_s \sqrt{f'_{ck}} + \frac{P}{6 A_g} \right] b_w d$$

$$V_{c,a} = \left[2 \times (0.71796) \times \sqrt{(3000 \text{ psi})} + \frac{(8811 \text{ lbf})}{6 \times (1017.9 \text{ in}^2)} \right] \times (36 \text{ in}) \times (28.8 \text{ in})$$

$$V_{c,a} = 83.038 \text{ kip}$$

The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$.

22.5.5.1.2 $V_{c,b}$ - Shear strength of concrete (b)

$$V_{c,b} = \left[2 \lambda_s \sqrt{f'_{ck}} + (0.05 f'_{ck}) \right] b_w d$$

$$V_{c,b} = \left[2 \times (0.71796) \times \sqrt{(3000 \text{ psi})} + (0.05 \times (3000 \text{ psi})) \right] \times (36 \text{ in}) \times (28.8 \text{ in})$$

$$V_{c,b} = 237.06 \text{ kip}$$

V_c - Governing shear strength of concrete

$$V_c = \text{Min} [V_{c,max}, V_{c,a}, V_{c,b}]$$

$$V_c = \text{Min} [(203.86 \text{ kip}), (83.038 \text{ kip}), (237.06 \text{ kip})]$$

<p>22.5.1.2</p> <p>22.5.8.5.3</p> <p>22.5.1.1</p>	<p style="text-align: center;">$V_c = 83.038 \text{ kip}$</p> <p>The following variables were converted to be consistent with empirical formula $f'_{ck} = 3 \text{ ksi} \rightarrow 3000 \text{ psi}$.</p> <p>$V_{s,a}$ - Shear strength of steel (a)</p> $V_{s,a} = 8 \sqrt{f'_{ck}} b_w d$ $V_{s,a} = 8 \times \sqrt{(3000 \text{ psi})} \times (36 \text{ in}) \times (28.8 \text{ in})$ $V_{s,a} = 454.3 \text{ kip}$ <p>A_v - Ties rebar area,</p> $A_v = \frac{\pi d_{ties}^2}{4}$ $A_v = \frac{\pi \times (0.375 \text{ in})^2}{4}$ $A_v = 0.11045 \text{ in}^2$ <p>$V_{s,b}$ - Shear strength of steel (b)</p> $V_{s,b} = \frac{2 A_v f_{yw} d}{s_{ties}}$ $V_{s,b} = \frac{2 \times (0.11045 \text{ in}^2) \times (60 \text{ ksi}) \times (28.8 \text{ in})}{(10 \text{ in})}$ $V_{s,b} = 38.17 \text{ kip}$ <p>V_s - Governing shear strength of steel</p> $V_s = MIN[V_{s,a}, V_{s,b}]$ $V_s = MIN[(454.3 \text{ kip}), (38.17 \text{ kip})]$ $V_s = 38.17 \text{ kip}$ <p>ϕV_n - Allowable shear strength</p> $\phi V_n = \phi (V_c + V_s)$ $\phi V_n = (0.65) \times ((83.038 \text{ kip}) + (38.17 \text{ kip}))$ $\phi V_n = 78.786 \text{ kip}$ <p>Considering x-direction:</p> <p>$V_{max} = 12.814 \text{ kip}$ - Maximum shear force in the x-direction, <i>Ratio</i> - Capacity</p> $Ratio = \frac{V_{max}}{\phi V_n}$ $Ratio = \frac{(12.814 \text{ kip})}{(78.786 \text{ kip})}$ $Ratio = 0.16265$	<p>Status: PASS Ratio: 0.160</p>
<p>14.5.2.1b</p>	<p>Flexural Strength (ACI 318-19, LRFD)</p> <p>S_m - Section modulus</p> $S_m = \frac{\pi D^3}{32}$ $S_m = \frac{\pi \times (36 \text{ in})^3}{32}$ $S_m = 4580.4 \text{ in}^3$ <p>$\lambda = 1$ - Concrete modification factor (Normal concrete), Allowable flexural strength: M_n shall be the lesser of:</p> <p>$\phi M_{n,1}$</p> $\phi M_{n,1} = \phi \times 5 \times \lambda \times \sqrt{f'_c} \times S_m$ $\phi M_{n,1} = 0.65 \times 5 \times 1 \times \sqrt{(3 \text{ ksi})} \times 4580.442 \text{ in}^3$ $\phi M_{n,1} = 67.947 \text{ kipft}$ <p>$\phi M_{n,2}$</p>	

$$\phi M_{n,2} = \phi 0.85 f'_{ck} S_m$$

$$\phi M_{n,2} = (0.65) \times 0.85 \times (3 \text{ ksi}) \times (4580.4 \text{ in}^3)$$

$$\phi M_{n,2} = 632.67 \text{ kipft}$$

Therefore,

ϕM_n - Allowable flexural strength,

$$\phi M_n = \text{MIN}[\phi M_{n,1}, \phi M_{n,2}]$$

$$\phi M_n = \text{MIN}[(67.947 \text{ kipft}), (632.67 \text{ kipft})]$$

$$\phi M_n = 67.947 \text{ kipft}$$

Considering x-direction:

$M_{max} = 57.244 \text{ kipft}$ - Maximum moment in the x-direction,

$Ratio$ - Capacity

$$Ratio = \frac{M_{max}}{\phi M_n}$$

$$Ratio = \frac{(57.244 \text{ kipft})}{(67.947 \text{ kipft})}$$

$$Ratio = 0.84248$$

Status: **PASS**
Ratio: **0.840**